

```
# tagman3c
```

```
0.4.2
```

```
## 1.
```

```
**BEDPE -> design_3c_from_bedpe(**
```

```
## 2.
```

```
--- code ---
```

```
install.packages("devtools")
```

```
devtools::load_all(".")
```

```
--- code ---
```

```
## 3.
```

```
### 3.1 sequence
```

- DNA A/C/G/T
- "GATC\n" trim

```
### 3.2 BEDPE
```

```
'chr1 start1 end1 chr2 start2 end2 anchor_flag'
```

```
7
```

```
- 'A'Anchor
```

```
- 'B'Anchor
```

```
## 4.
```

```
--- code ---
```

```
assays <- design_3c_from_bedpe(
```

```
  sequence = "GATC\n",
```

```
  bedpe_path = "pairs.bedpe",
```

```
  sequence_genomic_start = 1,
```

```
  region_padding = 0
```

```
)
```

```
--- code ---
```

```
- 'uniqueness_genome_fasta = "genome.fa"
```

```
- 'uniqueness_max_hits = 1'
```

```
- 'enforce_probe_uniqueness = FALSE'
```

```
## 5. CLI
```

```
--- code ---
```

```
Rscript inst/scripts/design_from_bedpe_cli.R "ACGT..." pairs.bedpe 1 0 genome.fa 1
```

```
--- code ---
```

6.

- 'region_id'
- 'anchor_primer_seq', 'test_primer_seq'
- 'probe_seq_antisense'
- 'pseudo_amplicon_size'
- 'score'

7.

- 'uniqueness_genome_fasta' 'genome.fa'
- 'BEDPE 7 anchor_flag A B'7
- 'sequence' 'sequence_genomic_start' BEDPE