

control 2

2024年10月23日 20:55

break-innermost enclosing loop exit immediately
continue-next iteration of the enclosing loop begins

for loop中continue先执行剩下语句 然后回到for () 执行post processing!!!

for () 中++j和j++一样都是循环体执行完后再执行

++i是先加后用 j++是先用后加

但是对于单独使用时 效果相同

for循环的标准形式:

```
cpp
for (初始化; 条件判断; 更新) {
    循环体
}
```

实际上等价于:

```
cpp
初始化;
while (条件判断) {
    循环体;
    更新;
}
```

单独使用即不立即调用, i++/++i可以单独一个statement的情况

switch->variant of if-else-if

allows multiple choices based on the value of an integral expression (整型类型) ->整数, char, bool, enum! ! ->最终都会被转为整数处理

1. 基本递增规则:

cpp

```
enum Test {
    A = 5,      // 显式指定为5
    B,          // 自动取6 (5+1)
    C = 9,      // 显式指定为9
    D,          // 自动取10 (9+1)
    E           // 自动取11 (10+1)
};
```

2. 中间指定值的情况:

cpp

```
enum Example {
    FIRST,      // 0 (默认从0开始)
    SECOND,     // 1 (0+1)
    THIRD = 5,  // 显式指定为5
}
```

```
SECOND,    // 1 (0+1)
THIRD = 5,  // 显式指定为5
FOURTH,    // 6 (5+1)
FIFTH = 3,  // 显式指定为3
SIXTH      // 4 (3+1)
```

NO 2 cases may have the same value? ?

When a case constant is matched, the statements associated with the case are executed until either
a break statement.
a return statement.
the end of the switch statement.

***enum

enum new-datatype{iden1[=value1],iden2...};

enumeration is a type that can hold finite set of symbolic objects

命名规则和identifier相同

internally represented as integers

*undolved=自己定义非递增怎么办

do-while

However, unlike the the while statement, the is evaluated after at the bottom of do-while statement. 至少会执行一次