From C/A/T to Android

Chubak Bidpaa

Preface

One end of this story is a phototypesetter. The other is a phone. Between them lie minicomputers, university computer rooms, engineering workstations, Internet servers, and machines small enough to disappear inside other products. A system made to provide a congenial place for programming became an infrastructure for people who would never willingly type a shell command. That change is the subject of this book.

The C/A/T in the title is the Graphic Systems phototypesetter used at Bell Labs. It is not the `cat` command, although that small command belongs to the same story. Typesetting made Unix useful beyond the circle of its implementers. Android demonstrates a different kind of reach: a Unix-like kernel can underpin an environment whose everyday interface scarcely resembles a time-sharing terminal. Neither endpoint was inevitable.

This is both a history and an explanation of working machinery. The first part follows the formation and spread of Unix. The second opens the kernel, using John Lions's Sixth Edition commentary and the supplied October 2019 RISC-V edition of xv6 as deliberately different specimens. The third studies programming tools and visual interfaces. The fourth follows Unix ideas into servers, games, and phones. Chapters can be read separately, but earlier distinctions between an interface, an implementation, and an

institution make the later chapters easier to understand.

The intended reader is curious about computing and comfortable encountering small fragments of shell and C. No prior kernel course is assumed. The examples explain a mechanism rather than offer production libraries. Where an example omits error handling or describes pseudocode, the text says so. The practical investigations in the appendices use temporary data and do not require administrative privileges.

The supplied `sources/` collection is the historical and technical foundation. It contains duplicates, empty files, OCR errors, translated editions, and filenames that do not reliably identify their contents. The bibliography and source notes identify the actual works used. Citations prefer section names when extraction has made page numbers unreliable. All narrative, comparisons, and worked examples here are newly written; this book does not reproduce the supplied books or their source listings.

Later developments require additional explanation. The chapters on Wayland, containers, Android, and gaming combine established systems knowledge with the official project documentation identified in the bibliography. This is a structural account, not a release catalogue or a market-share survey. The modern discussion has an editorial cutoff of 6 November 2026; it makes no claim that a particular game, device, or distribution behaves identically across versions.

Several words need care. *Unix* names a historical family and a design tradition. *UNIX* also names a trademark tied to certification. *Linux* strictly names a kernel, although people commonly use it for complete systems assembled around that kernel. *Free software* concerns user freedoms; *open source* concerns an overlapping licensing and development movement. These meanings intersect

without becoming synonyms.

There is no single protagonist. Thompson and Ritchie matter, as do Ossanna, McIlroy, Cherry, Kernighan, the Berkeley groups, Stallman, Torvalds, and many less visible maintainers and users. The recurring actor is the interface: the agreement that lets one person's work become another person's building material. An interface can preserve freedom, conceal complexity, transmit a mistake, or harden into a barrier. Following those agreements helps explain how Unix endured while so much of its original machinery disappeared.

Contents

Preface **iii**

I A System Finds Its Public 1

1 A Fellowship Around a Small Machine **3**
1.1 What was lost when Multics went away 3
1.2 The PDP-7 was a beginning, not the finished design 4
1.3 The PDP-11 and a practical constituency 6
1.4 Why C changed what could travel 7
1.5 A publication becomes an invitation 8

2 Paper, Light, and Little Languages **11**
2.1 The printed page was a computing problem 11
2.2 What the C/A/T actually did 12
2.3 Requests, text, and macro packages 13
2.4 Equations and tables as separate languages 14
2.5 From one device to many 15
2.6 What publishing taught the system 16

3 The Command Line Becomes a Language **19**
3.1 Commands as ordinary programs 19
3.2 The pipeline as a process graph 20

3.3 A convention is a protocol 21
3.4 Expansion is not just string substitution 22
3.5 Editors and the growth of an environment 23
3.6 From improvisation to maintained automation . . 24

4 Berkeley Makes a Larger Unix 27
4.1 A distribution before a separate operating system 27
4.2 The VAX changes the scale of the problem 28
4.3 The disk must keep up 29
4.4 Networking becomes an ordinary programming task 30
4.5 A networked system has different weaknesses . . 31
4.6 BSD as an integration tradition 32

5 The Workstation on the Engineer's Desk 33
5.1 Personal computing without surrendering the network 33
5.2 Why Unix fit the market 34
5.3 Shared files, shared assumptions 35
5.4 Graphics makes the machine a working instrument 36
5.5 RISC, price, and the changing competitive boundary 37
5.6 What survived the workstation era 38

6 Who Gets to Call It Unix? 41
6.1 A successful family becomes a commercial argument 41
6.2 Two kinds of openness compete 42
6.3 What POSIX can promise 43
6.4 A trademark is a different kind of interface 44
6.5 The BSD legal transition 45
6.6 Licenses shape future choices 46

7 GNU, Linux, and the Work of Keeping Software Free 49
7.1 The operating system was larger than the kernel . 49
7.2 A kernel for an inexpensive machine 50

7.3 Distributions turn components into a system . . . 51
7.4 The network becomes a development medium . . 52
7.5 Free software and open source name different arguments 53
7.6 A new center of gravity 54

II The Machinery Beneath the Prompt 57

8 Learning to Read a Kernel 59
8.1 Why a small implementation is a serious subject . 59
8.2 Begin with the machine contract 60
8.3 Tables are the system's memory of itself 61
8.4 Trace a request, then interrupt it 62
8.5 Xv6 is a comparison, not a time machine 63
8.6 History is evidence, not a benchmark competition 64

9 Processes, Traps, and the Illusion of a Private Machine 67
9.1 A program is not a process 67
9.2 Creation and replacement are separate operations 68
9.3 Entering the kernel changes authority 69
9.4 Addresses need an interpreter 70
9.5 Copy-on-write and faults as useful events 71
9.6 Exit must leave an account of what happened . . . 72

10 Who Runs Next? 75
10.1 Concurrency begins before a second processor . . 75
10.2 A context switch preserves a continuation 76
10.3 Runnable is different from running 77
10.4 The lost wakeup is a missing agreement 77
10.5 Locks protect invariants 79
10.6 The hard part is preserving progress 80

11 Files, Blocks, and the Problem of Tomorrow 81
11.1 A name is a route to an object 81
11.2 Three levels of an open file 82
11.3 Bytes become blocks 83
11.4 Locality is a policy decision 84
11.5 A successful write is not the whole durability story 85
11.6 Replacing a file safely takes more than rename . . 86

12 Communication and the Shape of Failure 87
12.1 A pipe is a queue with lifetimes 87
12.2 Signals announce events, not complete work items 88
12.3 Shared memory moves the protocol into the application 89
12.4 Sockets generalize endpoints 90
12.5 A send is not an acknowledgment of application success 91
12.6 Event loops and the cost of waiting 92

III Tools, Screens, and Design 93

13 Building Programs, Building Environments 95
13.1 The toolchain is part of the system 95
13.2 Generators turn descriptions into code 96
13.3 Make records relationships 97
13.4 Debugging depends on observable state 98
13.5 Versions make collaboration historical 99
13.6 Languages beyond C 100
13.7 A development environment is an accumulated promise 101

14 The Art, and the Limits, of Unix Programming 103
14.1 A tradition becomes a set of principles 103

14.2 Composition needs a shared grammar 104
14.3 Clarity includes the invisible state 105
14.4 Policy cannot be eliminated 106
14.5 Critics are part of the evidence 107
14.6 Security tests the boundaries of convenience . . . 108
14.7 A worked design choice: one tool or several? . . . 109

15 The Screen Before Windows 111
15.1 A terminal is a separate participant 111
15.2 The kernel edits some of the input 112
15.3 Cursor addressing creates a new application style 113
15.4 Curses keeps a model of the display 113
15.5 A pseudoterminal preserves the old agreement . . 114
15.6 Characters are not display cells 115
15.7 The terminal's enduring place 116

16 Pixels, Networks, and the X Window System 119
16.1 A bitmap changes what a screen can mean 119
16.2 Why the display is the server 120
16.3 The server does not choose the entire desktop . . . 121
16.4 Rendering moves away from the original model . 122
16.5 Compositing adds another view of the screen . . . 123
16.6 Trust in a shared display connection 124
16.7 What X accomplished 124

17 Wayland and the Ownership of a Frame 127
17.1 A different protocol boundary 127
17.2 Follow a frame from application to display 128
17.3 A buffer is more than a pointer 129
17.4 Security changes useful habits 130
17.5 Extensions carry the rest of the desktop 131
17.6 Xwayland makes migration incremental 132
17.7 A new display system, the same engineering questions 133

IV Unix Beyond the Workstation 135

18 Unix as Infrastructure 137
18.1 The user may never see the machine 137
18.2 Booting is the beginning of a dependency graph . 138
18.3 Permissions are a beginning, not a complete sandbox 139
18.4 Names and resources are different problems . . . 140
18.5 An image is not the running service 141
18.6 Configuration is a program with delayed consequences 142
18.7 Reliability is a maintenance relationship 143
18.8 Infrastructure preserves the old questions at new scale 144

19 Games on a System Built for Other Work 145
19.1 The desktop needs applications people want . . . 145
19.2 Native ports still need an ecosystem 146
19.3 Wine implements a different application contract . 147
19.4 Proton assembles a gaming path 148
19.5 A frame is a deadline, not just an image 149
19.6 Anti-cheat and protected services define another boundary 150
19.7 The Steam Deck turns integration into a product . 150

20 Android and the Many Meanings of Unix 153
20.1 The phone does not need to look like its kernel . . 153
20.2 Bionic marks a different userspace 154
20.3 The runtime and framework define application life 155
20.4 Binder supplies a service vocabulary 156
20.5 The user account becomes an application boundary 157
20.6 Graphics returns to composition 158
20.7 An open project and a commercial product are different objects 158

20.8 BSD and Darwin continue alongside Linux 159
20.9 From a typesetter to an unseen operating system . 160

A A Chronology with Boundaries 163

B Vocabulary and Practical Investigations 169
B.1 A working vocabulary 169
B.2 Investigate a pipeline without large data 172
B.3 Observe an unlinked open file 173
B.4 Compare one shared offset with two independent openings 174
B.5 Read a teaching kernel by invariant 175

C Sources, Editions, and Historical Method 177
C.1 What the source collection can establish 177
C.2 The historical backbone 178
C.3 The implementation backbone 179
C.4 Tools, criticism, and the screen 180
C.5 Modern material and the limits of this account . . 181

Bibliography 183

Index 187

Part I

A System Finds Its Public

Chapter 1

A Fellowship Around a Small Machine

1.1 What was lost when Multics went away

Unix began at Bell Laboratories, not at an institution called "Unix Labs." In 1969, Bell Labs was withdrawing from Multics, the ambitious time-sharing project undertaken with MIT and General Electric. Multics proposed a computing utility: many people would share a powerful installation through interactive terminals, with persistent files and carefully structured protection. Its ambitions were not absurd. Many later systems would adopt ideas it explored. The difficulty for Bell Labs was the expense and slow arrival of a service that met immediate needs.

For Ken Thompson, Dennis Ritchie, Doug McIlroy, and Joe Ossanna, withdrawal also meant losing an appealing way to work. An interactive system was more than a faster replacement for submitting decks of punched cards. It let people keep programs, documents, and unfinished thoughts in a common place. Ritchie's

account emphasizes the wish to preserve a fellowship around computing. That social purpose helps explain why a small operating system could become a large cultural influence. Its users were also its authors, and improvement could begin as a conversation down a corridor (Ritchie 1984, "Origins").

This does not mean that Unix emerged in a vacuum of unlimited freedom. Computers required budgets, management approval, maintenance, and a credible reason to exist. Proposals for a substantial replacement machine failed to produce the desired purchase. The available opportunity was a little-used PDP-7. Thompson's experiments with a space-travel game formed part of the immediate setting, but the game is an inadequate explanation for the operating system. A game could motivate graphics work without explaining directories, process creation, or a community's programming practice.

The useful historical question is therefore not which amusing incident "caused Unix." It is how limited hardware and a particular community encouraged a workable set of compromises. The participants wanted an interactive environment they could understand and alter. They could not build the full computing utility promised by Multics. They could implement an environment that made their own daily work better.

1.2 The PDP-7 was a beginning, not the finished design

The earliest system was written in assembly language. It established parts of the file and process model, but it was not a miniature copy of a modern Linux distribution. Ritchie describes successive experiments in file naming, links, and process control. Features

now presented as a timeless Unix philosophy were often the results of replacing something awkward with something easier to use. Reading the early history as a sequence of revisions gives the designers more credit than imagining they possessed a complete blueprint from the outset.

The file hierarchy gave users a way to organize persistent objects. A process gave a running computation an identity and an environment. A command interpreter let users request work without making each command a special operation inside the kernel. These abstractions reinforced one another. A command could name an ordinary file, become a process, and operate on other files. New commands could be added without redesigning the operating system's central control path.

The division between the kernel and the command environment was especially consequential. Hardware protection and resource arbitration belonged in the kernel. Most choices about useful work could be expressed by ordinary programs. An editor was indispensable to the environment, but it did not need privileged knowledge of how the scheduler worked. This separation made the system expandable by people who were not kernel authors.

Early Unix nevertheless carried constraints that later readers should not romanticize. Memory and disk space were scarce, peripherals were slow, and crashes could destroy work. A terse interface saved typing on slow terminals, but it also made commands hard to discover. Some of the features that feel elegant in retrospect were successful accommodations to severe limitations. Their survival does not prove that every limitation deserved to survive with them.

1.3 The PDP-11 and a practical constituency

The move to a PDP-11 made a larger future possible. The early PDP-11/20 installation was still modest and lacked the memory protection of later machines. Its justification included document preparation for the patent department. An editor and formatter were therefore not optional accessories. They were part of the reason the machine could be acquired and kept useful.

Ritchie recalls supporting three patent typists during the latter half of 1971 while the developers continued experimenting with the system. Their requirements were concrete: mathematical symbols and line-numbered pages for patent applications. A formatter could be adapted quickly to provide a feature that a competing commercial system did not provide. This was a small demonstration of a general advantage: ownership of the implementation could make an unusual local requirement inexpensive to satisfy (Ritchie 1984, discussion of the PDP-11).

The experiment was precarious. A programming mistake could bring down the same machine on which typists were doing productive work. The disk was small enough that material had to be moved to tape frequently. Yet the service worked well enough to win institutional support for a more capable PDP-11/45. Unix's first expansion thus involved evidence of usefulness, not only persuasion about architectural elegance.

The 1974 paper by Ritchie and Thompson describes a system already serving multiple installations and tasks: patent work, telephone-service data, research, programming, and document preparation. It reports the PDP-11 system of its own period. Its hardware figures and limits must not be silently transferred backward to the PDP-7 or forward to Sixth Edition. An edition label is a historical coordinate, not a decorative suffix (Ritchie and Thomp-

son 1974, secs. 1–2).

1.4 Why C changed what could travel

Thompson's B, derived from BCPL, preceded C. B's word-oriented model and implementation did not fit every aspect of the byte-addressed PDP-11 comfortably. Ritchie's work on C added a type system and operations suited to expressing the data structures and machine-level work the kernel required. The important result was not simply a more convenient syntax. It was the ability to describe most of an operating system in a form that could be retargeted to another machine.

The 1973 rewrite of the kernel in C is a major turning point, but "written in C" does not mean independent of hardware. A kernel still needs startup code, trap entry, context switching, access to device registers, and knowledge of memory-management hardware. C also permits assumptions about word sizes, byte order, alignment, and representation that can make a program effectively machine-specific. Portability had to be engineered through interfaces and disciplined assumptions; a language merely made that engineering more tractable.

Later ports, including work on Interdata machines, tested the claim in a way that repeating it on PDP-11s could not. A compiler could absorb many instruction-set differences. Kernel code could retain the organization of processes, files, and devices while selected machine-dependent sections changed. That arrangement would become a template for later operating systems and for the software industries built around them (Kernighan 2020, "Portability").

C and Unix also formed a feedback loop. Unix offered a productive place to implement compilers and tools. C offered a compact way

to extend Unix. Programs written for that environment spread the language, while a growing population of C programmers made new Unix software easier to produce. Neither language popularity nor operating-system adoption has a single cause, but this mutual reinforcement is difficult to miss.

1.5 A publication becomes an invitation

The public presentation in 1973 and the revised paper in 1974 made Unix legible to a wider technical audience. Its claims were unusually tangible: a hierarchical file system, compatible I/O for different objects, separate processes, a replaceable command language, and an extensive collection of programs. A reader could recognize a complete working environment rather than an isolated research mechanism.

Distribution outside Bell Labs depended on licensing. The legal and business setting of AT&T encouraged a form of software circulation very different from selling a fully supported consumer product. Universities could obtain source under license, study it, and exchange knowledge with other authorized users. They did not thereby acquire the unrestricted redistribution rights associated with later free software. Source availability and freedom to redistribute are separate historical facts.

That distinction matters when celebrating Unix as an ancestor of open source. Early participants built a vigorous sharing culture, but its legal boundaries excluded people. The desire to teach from the kernel would later make those boundaries painfully visible in the story of Lions's commentary. The small system was easy enough to explain; permission to circulate the explanation was another matter.

By the middle of the 1970s, Unix had several foundations for expansion: a credible practical workload, a comprehensible kernel, a productive language, and users willing to teach one another. It also had a particular view of composition. The next two chapters follow that view into printed pages and command lines, where some of its most durable inventions became part of ordinary work.

Chapter 2

Paper, Light, and Little Languages

2.1 The printed page was a computing problem

A patent application or mathematical paper is more than a sequence of letters. It contains hierarchy, symbols, alignment, references, and layout constraints. An editor lets an author change the sequence; a formatter interprets that sequence as instructions for a page. Unix's early success in document preparation joined these two activities without pretending they were identical.

This separation had practical consequences. The same source could be revised, searched, compared, stored on tape, and formatted repeatedly. An author could change a paragraph without retyping an entire page. Formatting rules could be improved in a program or macro package rather than enforced through repeated manual correction. The page became the output of a computation whose inputs remained available for further work.

The distinction is familiar in modern publishing, where documents may be built from Markdown, XML, or LaTeX. It was already useful on hardware whose most common output device resembled a typewriter. Unix did not invent every part of this tradition. Its formatters descended through earlier systems, including runoff and roff. What it supplied was a particularly fertile environment for combining editors, formatters, preprocessors, and devices (Ritchie 1984; Roddy 1987).

2.2 What the C/A/T actually did

In 1973 Joe Ossanna arranged for a Graphic Systems CAT phototypesetter at Bell Labs. The machine commonly styled C/A/T exposed character images onto photographic paper. Fonts existed as physical images on film mounted in a rotating mechanism. Selecting a character, positioning it, changing size, and exposing the image involved hardware with mechanical limitations. It was not a laser printer waiting to be driven by a convenient page language.

Kernighan's memoir describes four fonts of 102 characters on the wheel and sixteen available sizes. The photographic output then required chemical processing. These details matter because they explain why typography could shape software structure. A formatter had to know enough about widths and positioning to produce attractive output while respecting what the device could actually do. High quality did not imply easy operation (Kernighan 2020, discussion of the Graphic Systems CAT).

Ossanna's troff turned that device into a publishing resource. Its name identified a typesetter-oriented member of the formatter family; nroff served terminal-like output. The two shared much of their input language, allowing a document to be proofread cheaply and then typeset. The common source was valuable even

when the proof could not reproduce every mathematical symbol or spacing decision exactly.

The C/A/T therefore belongs in a history of Unix for more than picturesque reasons. It connected the operating system to a task whose result could be judged by people who did not care how the kernel was organized. A cleanly printed paper was visible evidence that the tools worked. Better output also raised expectations and motivated better tools.

2.3 Requests, text, and macro packages

A roff-family input file mixes text with requests. A line beginning with a control character can select a font, set spacing, or invoke a macro. The formatter reads an instruction stream, maintains state, and emits positioned material. It is useful to think of this as an interpreter rather than as a typewriter with unusually complicated keys.

Raw formatting requests expose too many details for ordinary authors. A macro package provides a higher-level vocabulary for paragraphs, headings, titles, lists, and notes. Consider this newly written fragment in the traditional `ms` style:

```
.TL
A Small System for a Large Task
.AU
An Example Author
.SH
The document as a program
.PP
The source describes a paragraph.
The formatter chooses the line breaks.
```

The author identifies document roles rather than manually placing every line. A macro package can change the visual treatment of a

heading across an entire document. Cherry and Lesk's account of the `ms` and `mcs` packages shows how this vocabulary also accommodated equations, tables, cover sheets, and institutional styles. Macro naming had to preserve compatibility: a document corpus already depending on old commands was a real constraint on improvement (Cherry and Lesk n.d.).


There is an enduring design tension here. A rich macro language permits local customization, but too much state and too many implicit conventions make documents difficult to reason about. A formatter may accept valid input that nevertheless produces a bad page. Program correctness and editorial correctness are different tests. A build can finish without proving that a table is readable or a heading is useful.

2.4 Equations and tables as separate languages

Mathematics is awkward to express using only primitive position changes. Kernighan and Lorinda Cherry's eqn allowed an author to describe mathematical relationships with words such as "over," "sup," and "sqrt." The preprocessor translated that description into lower-level formatting instructions. The author worked closer to the structure of the expression than to the motion of a typesetter.

Tables present a different problem. They need column descriptions, alignment, rules, and repeating patterns. Michael Lesk's tbl supplied a language for that domain. Later, pic offered a language for diagrams. These programs were not merely collections of shortcuts. Each captured a small body of knowledge and translated it into a form a more general formatter could consume.

A schematic pipeline makes the organization clear:



The ordering of actual preprocessors depends on the document. An equation inside a table can constrain which transformation must happen first. Composition is powerful because the stages communicate through agreed representations; it is fragile when those agreements are misunderstood. A pipeline is not automatically correct simply because every component works separately.

The little-language approach also changes who can contribute. Someone who understands tables can improve tbl without becoming an expert in disk allocation. Someone who understands typography can improve macros without rewriting the shell. The interface between programs becomes an organizational boundary as well as a technical one.

2.5 From one device to many

The original troff was closely associated with the C/A/T. As other output devices became attractive, hardwired assumptions became a cost. Kernighan's device-independent troff separated formatting from a particular machine's final output encoding. A backend could translate intermediate output for a different typesetter or printer. This was a substantial architectural change: it made the boundary between document layout and device operation explicit.

Device independence is always qualified. Font metrics affect line breaking, available glyphs affect notation, and device resolution affects appearance. An intermediate language cannot make these differences disappear. It can localize the knowledge needed to handle them. That is a more useful goal than promising that every printer will produce identical pages.

Later implementations, especially groff, carried the tradition into free software systems and new output formats. Manual pages kept the roff family visible even when most users no longer prepared papers in troff. A command such as `man` appears to present text, but its source tradition includes semantic macros, formatters, pagers, terminal capabilities, and installation conventions. The apparent simplicity is the result of a pipeline of maintained agreements.

TeX and LaTeX belong beside this history without being troff descendants. TeX pursued its own model of mathematical and typographic precision. LaTeX emphasized document structure through a macro layer. Unix provided an accommodating environment for such tools because files, command execution, and redirection did not reserve publishing for one privileged application. The book in the reader's hands uses LaTeX, while the title acknowledges a different publishing lineage.

2.6 What publishing taught the system

Document preparation exercised Unix as a complete environment. It required interactive editing, reliable files, stable tools, reproducible commands, and output whose defects humans could see immediately. It rewarded the ability to combine a specialized preprocessor with a general formatter. It also exposed the cost of poorly defined interfaces: a change in a macro, font table, or backend could alter a document far from the changed code.

That experience complicates the familiar slogan about doing one thing well. Troff itself is a substantial interpreter. Macro packages can be complex programs. A useful tool boundary need not produce a tiny program; it should concentrate a coherent responsibility. Eqn's responsibility was mathematical expression layout,

not an arbitrary limit on source-code size.

Publishing also gave users reasons to preserve source. A photographic page is an artifact; the editable file and its toolchain explain how that artifact was made. Modern reproducible research and documentation builds extend the same concern. When source, tools, fonts, and invocation are recorded, later readers can revise the work instead of merely admiring the output.

The path from patent typists to technical publishing shows how a local need can become a general method. Unix did not become useful because it insisted that every problem was text. It became useful because text was a workable, inspectable representation for many problems, and because the system let users build new interpreters when ordinary text processing was insufficient.

Chapter 3

The Command Line Becomes a Language

3.1 Commands as ordinary programs

A command line looks like a place to type instructions to the operating system. In Unix, most instructions typed there are requests to an ordinary program, the shell. The shell interprets syntax, expands names, arranges input and output, starts programs, and collects their status. Keeping this work outside the kernel made the command language replaceable without changing the machinery that protects files and schedules processes.

That distinction explains why Unix could acquire several shells. Thompson’s early shell, Stephen Bourne’s shell, Bill Joy’s C shell, the Korn shell, and later Bash and others embody different priorities. An interactive user may value history and completion; a script author may value predictable control flow and portability. A shell can serve both audiences, but changes that delight one may surprise the other.

The shell's power rests partly on a modest process interface. It does not need a distinct system call for every external command. It can ask the kernel to create a process, establish file descriptors, and execute a program. A new command installed in a searchable directory becomes part of the user's vocabulary. The kernel need not learn its name.

3.2 The pipeline as a process graph

McIlroy repeatedly pressed the value of connecting programs. Pipes became a kernel and shell facility early in the 1970s, after Unix had already begun to take shape. Their arrival encouraged programs to read standard input and write standard output in forms other programs could use. Ritchie's evolutionary account is especially valuable because it describes a design emerging through use, rather than attributes every later convention to the first version (Ritchie 1984, discussion of pipes).

Consider a deliberately simple analysis of a text file:

```
LC_ALL=C tr -cs 'A-Za-z' '\n' < notes.txt |
    tr 'A-Z' 'a-z' |
    sort |
    uniq -c |
    sort -nr
```

This ASCII-oriented example counts runs of English letters after folding case. It is not a general tokenizer for human languages. The first stage replaces nonletter runs with newlines, the second folds uppercase, the third places equal lines together, and the fourth counts adjacent equal lines. The final sort orders the counts. Explicitly narrowing the problem makes the example useful without disguising its limitations.

The vertical bar does not mean "save the whole output, then run

the next program." The shell arranges a graph of processes connected by finite kernel buffers. The stages may run concurrently. A writer can block when a pipe is full; a reader can block when it is empty and writers remain. This backpressure lets a pipeline process a stream larger than memory without every stage implementing its own queueing protocol.

One consequence is easy to overlook: unused descriptors must be closed. A reader sees end-of-file only when all write references are gone and buffered bytes have been consumed. An accidentally inherited write end can keep a reader waiting forever. The pipeline's attractive notation hides real resource management, explored in chapter 12.

3.3 A convention is a protocol

Standard input, standard output, and standard error are conventions supported by descriptor inheritance. They are not special kinds of files created for each command. The shell usually supplies descriptors 0, 1, and 2 with useful meanings. A process can replace those bindings, and a program that assumes output is always a terminal can break redirection.

Separating diagnostic messages from useful output preserves composition. If a tool inserts progress announcements into a stream of filenames or numbers, a downstream parser may treat them as data. Exit status is another channel. It can distinguish ordinary completion from failure without requiring a program to decode human prose.

The conventions are incomplete. Different tools use different status codes; `grep`, for example, distinguishes no match from an execution error. Historically, a shell pipeline's reported status usually

came from its last command. That can conceal an earlier failure. Some shells provide `pipefail`, but its availability depends on shell and specification version. A portable script must establish its target environment rather than casually assume every useful extension exists everywhere.

Text formats are also protocols. Newline-delimited records are convenient until a field can contain a newline. Filenames on Unix can contain spaces, tabs, and newlines, although not a slash within a component or a NUL byte. Parsing `ls` output is therefore a poor substitute for an interface that passes names unambiguously. On systems that support them, `find -print0` and `xargs -0` use NUL as a delimiter. Their lesson is broader than their syntax: choose a representation in which data cannot be mistaken for structure.

3.4 Expansion is not just string substitution

The shell has a distinctive evaluation model. It recognizes syntax, performs expansions, removes quoting, and finally passes argument arrays to programs. The program does not ordinarily receive the exact command line the user typed. It receives separate strings after the shell has interpreted that line.

Quoting preserves argument boundaries. If a variable contains a pathname, `"$name"` normally passes that value as one argument; an unquoted expansion in traditional shells can undergo field splitting and pathname expansion. A filename containing an asterisk may consequently become an accidental pattern. Such bugs are not merely untidy: they can make scripts operate on the wrong data.

Command substitution has another important property: traditional shell syntax removes trailing newlines from the captured output. That is useful for many textual values but means it is not a transparent transport for arbitrary bytes. The shell is an orchestration language whose data model fits names and commands better than unrestricted binary content.

Greenberg, Kallas, and Vasilakis argue that the shell remains worth improving precisely because its dynamism, power, and ubiquity are hard to replace. Their account of research on semantics and parallel execution shows that apparent informality need not prevent rigorous analysis. A pipeline can sometimes be transformed into a more parallel dataflow graph, but only when the tools' behavior and side effects are sufficiently understood (Greenberg, Kallas, and Vasilakis 2021).

3.5 Editors and the growth of an environment

Editors changed alongside terminals. The line editor ed made sense when printing a screenful of context was expensive. Its compact address and substitution language could operate on a file without repainting a display. Stream-oriented transformations later flourished in sed, while grep made pattern-based selection a reusable command. These tools are related by technique and culture, although their exact behavior and pattern languages should not be treated as identical.

Awk added records, fields, associative arrays, and pattern-action rules. It occupies an instructive middle ground: more structure than a bare filter, less ceremony than a compiled application for many reporting tasks. A task that becomes an unreadable shell

tangle may become a clear awk program because the data model better matches the work.

Vi emerged from Berkeley's screen-editing environment, with ex beneath its visual interface. Emacs came from a different editing and Lisp tradition and became a major part of Unix environments. Both demonstrate that Unix users have always embraced powerful, stateful applications. Their popularity cannot be reconciled with a literal rule that every program must be a tiny stateless filter.

The manual, too, was part of the programming environment. Commands, library functions, system calls, file formats, and administration procedures could be documented in a common framework. A reference manual is not a substitute for a tutorial, but it creates an expectation that interfaces have names and descriptions that can be consulted locally.

3.6 From improvisation to maintained automation

A command typed once can rely on what its author happens to know about the current directory and input. A script handed to someone else cannot. It needs explicit assumptions about arguments, environment, working directory, temporary files, errors, and cleanup. Interactive convenience becomes a maintenance liability when those assumptions remain invisible.

Kernighan and Pike's treatment of the programming environment is valuable because it connects tool use with program construction. Commands become building blocks for experiments; successful experiments can become tools; repeated work can move into scripts or a better-suited language. This is a method of development rather than a claim that all software ought to be written in shell

(Kernighan and Pike 1984).

The environment also changes the cost of asking questions. If a directory of text files can be searched immediately, users can investigate before building a specialized interface. If a transformation can be expressed as four inspectable stages, an intermediate result can be checked. This is one reason the command line survives in graphical environments: it offers a compact language for combinations the interface designer did not predict.

The price is that users inherit responsibility for composition. A misspelled pattern or unchecked status can invalidate a plausible-looking result. The command line is most valuable when its operators treat each connection as an agreement about data and failure. That discipline, more than terseness or nostalgia, is what makes the Unix programming environment durable.

Chapter 4

Berkeley Makes a Larger Unix

4.1 A distribution before a separate operating system

The Berkeley Software Distribution began as additions to an existing Unix environment. Its name describes an activity: collecting useful software and sending it to other sites. Early distributions were not unrestricted, self-contained replacements for AT&T's system. Recipients generally needed an appropriate Unix license. A later BSD identity grew out of this practice rather than appearing fully formed with the first tape.

Universities supplied a distinctive development setting. They had students who could spend intensive periods improving tools, researchers who needed new facilities, and links to other institutions with similar problems. They also had turnover. A successful improvement needed documentation and interfaces that outlived its immediate author. Sharing a distribution made a local change

available for review and reuse elsewhere.

Bill Joy's work on editors and the C shell is part of this story, but BSD was never the work of one programmer alone. Bob Fabry, Chuck Haley, Özalp Babaoglu, Marshall Kirk McKusick, Sam Leffler, Mike Karels, Keith Bostic, and many others contributed at different periods. The Computer Systems Research Group became a center where contributions could be integrated into a coherent system. Integration was a form of engineering, not merely administration (Kernighan 2020, ch. 8).

4.2 The VAX changes the scale of the problem

The PDP-11 was an excellent home for a compact system, but its address-space limits constrained large programs. DEC's VAX offered a 32-bit architecture and hardware support for virtual memory. A port could make Unix run on the new machine without immediately exploiting all those capabilities. That was the situation with Unix/32V, derived from Seventh Edition through work by John Reiser and Tom London at Bell Labs.

Berkeley's virtual-memory work changed the practical possibilities. A process could address more memory than it had resident at a particular moment. The kernel and hardware cooperated to bring pages into physical memory as required. Larger symbolic programs, scientific applications, and development tools became more feasible. The programming model still looked recognizably Unix even though memory management had become much more elaborate.

This is a recurring pattern in the history: retain a useful external abstraction while rebuilding its implementation for a new scale.

A process still executes a program in an address space. A file still presents bytes. Those descriptions conceal increasingly sophisticated policies about page replacement, caching, allocation, and scheduling. Compatibility at the interface buys room for innovation underneath.

Virtual memory also changes the balance of costs. Copying an entire process image at every creation may become expensive. Demand paging and copy-on-write can reduce that expense, but they introduce page faults, shared-state accounting, and new failure paths. A larger address space is not free simply because the processor can express its addresses. It needs an operating system that can manage the resulting work.

4.3 The disk must keep up

A faster processor and a larger memory expose a slow file system more clearly. Workloads such as image processing and VLSI design moved large amounts of data with relatively little computation per byte. A file system using small blocks scattered across a disk could waste most of the device's time seeking rather than transferring useful data.

The Fast File System described by McKusick, Joy, Leffler, and Fabry in 1984 addressed this mismatch. It used larger blocks for transfer efficiency, fragments to avoid excessive waste for small files, and allocation policies that improved locality. Cylinder groups placed related resources in regions of the disk rather than leaving every allocation to an undifferentiated free list (McKusick et al. 1984).

The paper reports performance in its own experimental and hardware setting. Its headline improvements are not a timeless multiplier that can be applied to every disk or application. The enduring

result is the method: measure the actual bottleneck, exploit the physical device's behavior, and preserve a useful programming interface wherever possible.

FFS also included user-visible improvements such as longer filenames and other facilities associated with the 4.2BSD environment. Not all of BSD's contributions were invisible optimizations. The challenge was to introduce new capabilities without forcing every existing program to understand new disk geometry. The boundary between the file API and the allocation algorithm made that possible.

4.4 Networking becomes an ordinary programming task

Networking research and government funding were important to Berkeley's work. The 4.2BSD release in 1983 helped establish TCP/IP and the sockets interface as widely available parts of a Unix programming environment. The Internet was not invented by BSD, and TCP/IP did not originate there. BSD's importance lay in integration, distribution, and the accessibility of a working implementation to a community ready to use it.

A socket is represented by a descriptor, connecting network communication to an existing style of I/O. Yet network setup needs operations with no simple counterpart in opening a local file: choosing an address family, binding a local endpoint, listening, connecting, and accepting a peer. Sockets extended the file-descriptor model without pretending a network was just an ordinary disk file.

That compromise was productive. Programs could use familiar reads and writes once a connection existed, and event mechanisms

could monitor sockets alongside other descriptors. Specialized operations remained available for specialized behavior. The resulting API was not perfectly uniform, but it was usable and expressive enough to spread far beyond BSD (Stevens, Fenner, and Rudoff 2004, ch. 2 and socket overview).

Distribution mattered as much as invention. A networking stack available with a widely studied operating system could be ported, debugged, taught, and adapted. People learned sockets as an ordinary systems skill rather than as a feature of one inaccessible research installation. Code, manuals, and practice reinforced each other.

4.5 A networked system has different weaknesses

A time-sharing host already has concurrency and protection problems. Connecting hosts adds partial failure. A remote machine may disappear while the local one continues running. Delays may reflect congestion, retransmission, a crashed service, or a slow application. A program can remain correct with respect to its local API while making a bad assumption about the state of a peer.

Network services also widen the audience for mistakes. A parser that once handled input from a small group of local users may now receive arbitrary bytes from strangers. Authentication, privilege separation, and resource limits become critical. Convenience mechanisms designed for a trusted laboratory network can become hazards on a hostile network.

The 1988 Internet worm demonstrated how connected environments could magnify vulnerabilities and misplaced trust. It is misleading to infer that networking destroyed a previously secure

Unix. Multiuser protection had limits long before the worm. Networking made those limits visible at a larger scale and increased the cost of ignoring them.

4.6 BSD as an integration tradition

Berkeley's work is sometimes reduced to a branch on a family tree. That image captures inheritance but underplays exchange. Code, techniques, and interfaces moved between research Unix, commercial systems, Berkeley releases, and later independent implementations. A clean tree can make a history of borrowing look like a history of isolation.

The distributions also changed the meaning of a local improvement. An editor fix could influence thousands of users; an API choice could shape applications for decades. This increased the value of consistency, release engineering, and compatibility. A research group that shipped a system was taking responsibility for other people's work.

BSD's later legal separation from AT&T code belongs in chapter 6. Technically, its earlier transformation was already profound. Unix had become a comfortable environment for larger programs, faster disks, and networked applications. Those capabilities made it an attractive base for a new kind of computer: the personal, graphical, network-connected workstation.

Chapter 5

The Workstation on the Engineer's Desk

5.1 Personal computing without surrendering the network

A workstation was not simply a small server with a monitor attached. Its appeal lay in combining local computational power, a high-resolution display, networking, and a serious software environment for one technical user. It changed the relationship between individual and institution. An engineer could control a responsive local machine while still sharing files, printers, mail, and compute resources with colleagues.

The term covers a varied market. Sun systems made Unix and Ethernet a particularly visible combination. Silicon Graphics emphasized advanced graphics and visualization. Hewlett-Packard, IBM, DEC, and others supplied technical systems with their own architectures and Unix variants. Apollo's influential Domain environment was not initially a conventional Unix system, although

later products incorporated Unix compatibility and services. Treating every workstation as an identical Unix box erases the competition that made the category interesting.

Nor did the workstation eliminate time-sharing. A local machine could act as a window onto a remote host, execute some tasks itself, and submit larger work to a shared system. The new pattern distributed responsibility instead of simply replacing central computing. Network transparency became an attractive promise because users wanted resources to feel close even when the hardware was elsewhere.

5.2 Why Unix fit the market

Unix brought compilers, editors, a shell, file tools, and an established body of technical software. C made source-level portability plausible across changing processors. Universities had already trained people who knew the environment. Vendors could offer a machine that felt familiar to these users while differentiating through performance, graphics, peripherals, and support.

This was a favorable division of labor, but not a guarantee of effortless portability. A program could depend on byte order, word size, undocumented library behavior, or a particular window toolkit. Binary compatibility was harder still: an executable built for a Motorola processor could not simply run on a SPARC or MIPS processor. Unix provided a common vocabulary for ports, not a universal executable format for every workstation.

Vendor systems consequently mixed common practice with proprietary investment. SunOS, HP-UX, AIX, IRIX, and other systems supplied distinct administration tools, graphics stacks, drivers, and commercial applications. Their developers were solving real

hardware and customer problems. Fragmentation was partly the result of legitimate specialization, even when it also served commercial lock-in.

Libes and Ressler's *Life with UNIX* captures the variety and enthusiasm of this environment. Its own production note is telling: the book was composed with FrameMaker on a Sun workstation and prepared for a phototypesetter through PostScript. Unix publishing had expanded from a local formatter and device into an ecosystem of commercial applications and interchangeable output paths (Libes and Ressler 1989).

5.3 Shared files, shared assumptions

A networked desktop needs shared state. Sun's Network File System, first released in the mid-1980s, made remote files accessible through familiar filesystem operations. A mounted directory could refer to data on another machine. Existing applications could often use that data without learning a new explicit file-transfer workflow.

The convenience concealed difficult semantics. Local file operations already have failure cases, but remote operations add unavailable servers, network partitions, retransmissions, and inconsistent caches. Early NFS's stateless server design simplified certain aspects of crash recovery, while shifting other responsibilities to clients and auxiliary services. Later NFS versions changed the balance. "NFS is stateless" is therefore an observation about particular versions, not a permanent definition.

A laboratory also needed common user identities and configuration. Directory and naming services could save administrators from maintaining every machine independently. They could also

propagate a mistaken entry or an overly trusting security assumption across a whole site. Shared convenience enlarged the consequences of a shared error.

Diskless workstations made the dependence especially visible. A machine could have a powerful processor and a personal display while relying on network services to boot and obtain its root filesystem. Personal interaction did not imply local autonomy. An outage in an apparently remote administrative layer could stop an entire room of individual desks.

5.4 Graphics makes the machine a working instrument

Computer-aided design, scientific visualization, animation, and engineering analysis needed more than character terminals. A bitmap display could show multiple windows, diagrams, and images. Specialized graphics hardware could accelerate transformations and rendering. Unix processes could produce data that a graphical application interpreted in ways no line printer could represent effectively.

Silicon Graphics illustrates the relationship between applications and system design. Graphics workloads encouraged attention to pipelines, geometry, memory bandwidth, synchronization, and display hardware. IRIX was part of a product whose value depended on the entire machine working well for demanding visual tasks. A kernel benchmark alone could not describe that value.

At the same time, workstation graphics was not one settled architecture. Some environments used proprietary window systems; others adopted X; toolkits and desktop conventions competed. The user could encounter a common operating-system ancestry

through an interface with radically different menus, fonts, and interaction rules. Later chapters explain why X deliberately left many of those choices outside the display server.

The workstation also exposed a persistent distinction between technical and everyday usability. An expert might value remote execution, programmable configuration, and unusual window-management behavior. A new user might find the same environment inconsistent and exhausting. Both reactions could be reasonable. A product designed for one audience can be successful without being a model for every audience.

5.5 RISC, price, and the changing competitive boundary

Many workstation vendors adopted RISC processors to pursue high performance with architectures that suited contemporary compiler and chip-design strategies. SPARC, MIPS, PA-RISC, and POWER belong to this broad setting, although their designs and commercial histories differ. Unix's portability helped vendors move software toward new processors without rebuilding the entire programming environment from nothing.

The surrounding market changed. Commodity personal-computer components became faster and cheaper. Windows NT offered a different technical and commercial platform. Linux and BSD systems brought Unix-like environments to inexpensive machines. Graphics acceleration moved into mass-market products, supported by a much larger gaming and consumer market.

This did not make specialized workstations suddenly useless. Professional certification, applications, drivers, support contracts, and installed workflows remained valuable. It did change which

parts of a machine could justify a premium. A vendor competing through a proprietary processor, operating system, graphics subsystem, and enclosure now faced competitors benefiting from huge production volumes elsewhere.

The decline of the classic Unix workstation market should therefore not be confused with the disappearance of workstation practice. Engineers still use powerful local machines connected to shared services. Many now use Linux, macOS, or Windows with Unix tools. The packaging changed more completely than the pattern of work.

5.6 What survived the workstation era

The workstation helped normalize several expectations: a technical user should have a responsive graphical environment, network access should be ordinary, remote resources should be reachable from local applications, and a development toolchain should be part of the platform. These expectations outlived many of the vendors that established them.

It also created a body of engineering whose later influence was not limited to Unix-branded products. Networking stacks, graphics APIs, compiler work, filesystem techniques, and window-system experience moved between institutions and systems. NeXT's workstation environment would have a particularly consequential afterlife in Apple's software platform. Mach and BSD would survive there in a form very different from a university terminal room.

A familiar historical temptation is to describe the era as the last time computers were coherent and understandable. The contemporary complaints collected in *The UNIX-HATERS Handbook* resist that nostalgia. Users already struggled with window systems,

inconsistent interfaces, network assumptions, and administration (Garfinkel, Weise, and Strassmann 1994). What looks coherent from a distance often felt like a collection of unfinished agreements to the person trying to make it work.

Those agreements were about to become the subject of explicit commercial and standards conflict. If many vendors offered Unix, who could define what Unix meant? Which interfaces should applications rely on, and who controlled the name? The workstation's success made these questions more valuable, and therefore harder to settle.

Chapter 6

Who Gets to Call It Unix?

6.1 A successful family becomes a commercial argument

By the 1980s, Unix was simultaneously a research tradition, licensed source code, a commercial product family, and a valuable name. These meanings could pull in different directions. Researchers wanted to revise a system. Application vendors wanted stable interfaces. Hardware vendors wanted to differentiate their machines while attracting the same software. The owner of the Unix intellectual property wanted a viable business.

The Bell System's divestiture, effective in 1984, changed AT&T's commercial setting. Unix development associated with AT&T's product organization became increasingly important alongside the research editions. System III and System V were not simply new names for the next research manuals. They belonged to a product line that integrated work from several sources and served customers with different expectations.

The familiar contrast between "BSD" and "System V" was conse-

quently both useful and incomplete. Systems differed in terminal interfaces, interprocess communication, administration, libraries, and networking. Yet vendors borrowed features, offered compatibility facilities, and assembled hybrids. A real installed system often resisted classification as one pure branch (Kernighan 2020, ch. 7–8).

For application developers, these differences imposed repeated work. Source could be portable in principle while requiring conditional code, separate build configurations, and extensive testing. Customers could pay the cost indirectly through delayed releases and limited support. The pressure for standardization was therefore practical as well as political.

6.2 Two kinds of openness compete

AT&T and Sun's cooperation on a converged Unix intensified concern among other vendors about who would control the platform. The Open Software Foundation, formed in 1988 by a group of major companies, offered one institutional answer. Unix International supported the AT&T-oriented alternative. "Open" did not yet guarantee the freedoms later associated with an open source license. It could mean vendor independence, standard interfaces, consortium membership, or access under commercial terms.

System V Release 4 combined important elements from System V, BSD, SunOS, and Xenix. The act of integration was technically meaningful even though it did not end the market's disagreements. A converged source base could still produce distinct products, and a common specification could still leave room for incompatible extensions.

The Unix wars were not one battle with a clear end date. They in-

cluded alliances, branding, standards work, desktop competition, procurement, and the positioning of proprietary products. Some efforts reduced incompatibility; others multiplied the institutions claiming to solve it. The desire for a single market sometimes produced more standards before it produced fewer.

It is tempting to declare that the fighting alone caused Unix vendors to lose the desktop. That explanation is too tidy. Hardware economics, application availability, user experience, Microsoft's growth, and the emergence of inexpensive Unix-like systems all mattered. Standards conflict was part of the cost structure, not a sufficient explanation for every commercial outcome.

6.3 What POSIX can promise

A standard can define an interface without prescribing its implementation. POSIX specifies operating-system services and, in its broader body of specifications, a shell and utilities environment. A conforming program can rely on documented behavior within that scope. The first IEEE 1003.1 standard appeared in 1988; later revisions expanded and consolidated the specification.

This is source-level agreement, not an instruction-set translator. A C program using specified interfaces may be recompiled for another conforming system. A binary still depends on processor architecture, calling conventions, executable format, dynamic linking, and other ABI properties. The distinction between API and ABI explains why two systems can both implement POSIX without running each other's executables (Stevens and Rago 2013, ch. 2).

A specification also has boundaries. It may mark a feature optional, leave a value implementation-defined, or permit several

outcomes. A program that accidentally relies on an unspecified behavior can work on one system and fail on another without either system violating the standard. Portability requires reading those qualifications rather than merely recognizing a familiar function name.

Standards do not freeze all development. A system can provide extensions outside the common contract. Those extensions may solve important problems, such as scalable event notification or specialized storage control. The author must decide whether the benefit justifies limiting portability. The useful question is not whether extensions are morally wrong, but whether the dependency is deliberate and documented.

6.4 A trademark is a different kind of interface

The Single UNIX Specification and certification associated with The Open Group give the UNIX name a formal meaning beyond family resemblance. Certification applies to a product and version in a defined environment. It should not be inferred from a kernel's ancestry or from a distributor's claim to be Unix-like.

This makes several apparently contradictory statements compatible. A system can be recognizably Unix in design without being certified. A Linux-based product can pursue or obtain certification without acquiring AT&T kernel code. A system descended from historical Unix does not automatically certify every future release or hardware configuration. Genealogy, interface conformance, and trademark permission are three separate axes.

Keeping those axes separate is especially helpful for Android and macOS. Android uses Linux but does not present a conventional

desktop Unix application environment. Apple's product history includes certified UNIX environments, but that does not make every Apple operating system or every version interchangeable. The contemporary landscape becomes clearer when names are treated as claims with a scope.

6.5 The BSD legal transition

Berkeley developers worked to replace code that required an AT&T license. Keith Bostic's effort to obtain replacement utilities and the work of the CSRG on the kernel made progressively freer distributions possible. Networking Release 1 and Networking Release 2 were milestones in this process. They should not be mistaken for the first day anyone shared BSD software, nor should Net/2 be described as the final legal resolution.

Unix System Laboratories brought litigation involving Berkeley Software Design, Inc., and the University of California in 1992. Claims, counterclaims, and the resulting uncertainty affected the BSD ecosystem. The 1994 settlement and the release of 4.4BSD-Lite provided an important basis for further development without the old AT&T source-license requirement. The legal outcome was more specific than either "all Unix became free" or "Berkeley proved every claim false" (Salus n.d., ch. 13).

The timing overlapped with Linux's early growth, but overlap does not prove a single cause. Linux also benefited from inexpensive PCs, accessible collaboration, existing GNU tools, and a growing distribution ecosystem. The litigation was one influence on people's choices; it was not an experiment that isolated the cause of Linux adoption.

FreeBSD and NetBSD began in 1993, OpenBSD branched from

NetBSD in 1995, and DragonFly BSD later branched from FreeBSD. Their communities established different priorities and release practices. The shared BSD label does not mean that they are editions of one centrally managed product. Their histories show how legal independence can support technical diversity rather than force convergence.

6.6 Licenses shape future choices

A permissive license typically allows redistribution, modification, and incorporation into larger products subject to conditions such as retaining notices. A copyleft license adds conditions designed to preserve specified freedoms when covered work is conveyed. The exact obligations depend on the actual license and circumstances, not on the casual labels “BSD” or “GPL.”

In particular, the GPL does not generally require every private modification to be published to the world. Distribution and corresponding-source obligations must be understood in context. Nor does a permissive license mean that authors have abandoned copyright or attribution. Both approaches use legal permissions to structure collaboration; they select different rules for downstream behavior.

This is why licensing belongs inside a technical history. A kernel may be elegant but unavailable for a needed use. A modest tool with clear redistribution rights can become infrastructure for products its authors never anticipated. An interface tells programmers how components can connect; a license helps determine who may make and share those connections.

The Unix wars showed how much economic value accumulated around such agreements. GNU, Linux, and the freely redis-

tributable BSD systems would change the bargaining position. A user could increasingly choose a Unix-like environment whose right to continue developing did not depend on one proprietor's continued cooperation.

Chapter 7

GNU, Linux, and the Work of Keeping Software Free

7.1 The operating system was larger than the kernel

Richard Stallman announced the GNU project in 1983 and began its work in 1984. Its aim was a free Unix-compatible operating system: an environment users could run, study, modify, and redistribute. Compatibility was a strategic choice. Familiar interfaces made existing software and experience useful, while a new implementation could establish different legal terms. The recursive name "GNU's Not Unix" captured both the relationship and the separation.

An operating system in everyday use needs far more than a kernel. It needs a compiler and linker, libraries, a debugger, a shell, text tools, an editor, installation conventions, and documentation.

GNU's work on Emacs, GCC, GDB, libraries, and utilities supplied many of these elements. Their importance is obscured when the history is told as though a kernel alone suddenly created a complete usable system (Salus n.d., ch. 8, 10–12).

The project also treated legal permission as part of the engineering task. The Free Software Foundation, founded in 1985, supported this goal. The GNU General Public License used copyright to impose conditions on redistribution that preserved defined freedoms for recipients. It was not a rejection of all rules; it was a carefully chosen set of rules intended to prevent a familiar kind of loss of access.

GNU's intended kernel path eventually involved the Hurd, a collection of servers built on a Mach foundation. The schedule and complexity of that work mattered because other components were already useful. A system can be incomplete as a project while contributing essential infrastructure to other systems. That is precisely what made the later combination with Linux possible.

7.2 A kernel for an inexpensive machine

Linus Torvalds began Linux in 1991 while a student in Helsinki, working with a 386-based personal computer. MINIX, Andrew Tanenbaum's teaching system, was part of the surrounding context. Linux was a new kernel implementation, not a rebranding of AT&T Unix source. Its early ambition was much smaller than the eventual range of machines and organizations that would depend on it.

The distinction between inspiration and code descent matters. An interface can be reproduced independently. A programmer can learn from a teaching system without making the new kernel a derivative of that system's implementation. Simplified family

trees often blur these relationships by using the same line to mean shared code, influence, or compatibility.

Linux's original licensing differed from the terms it later adopted. The move to GPL version 2 in 1992 helped make the kernel fit the wider free software ecosystem. Volunteers could combine it with existing tools and share the resulting systems. GNU components were central to many of those systems, though not every Linux-based environment would use the same libraries or utilities.

This history explains the naming debate without resolving it by fiat. "GNU/Linux" emphasizes the construction of a complete system from Linux and GNU components. "Linux" is the common shorter name in much everyday usage. Android demonstrates why neither expression should be applied mechanically: it uses the Linux kernel but a substantially different userspace, including Bionic rather than the GNU C library.

7.3 Distributions turn components into a system

A kernel tarball, compiler, and collection of utilities are not yet an installation experience. Someone must decide versions, build packages, resolve dependencies, arrange a filesystem, provide an installer, configure services, publish updates, and support upgrades. Distributions made these integration tasks repeatable.

Early projects such as SLS, Slackware, and Debian, followed by commercial and community distributions including Red Hat and SUSE, offered different answers. Their importance was not confined to branding. A package database could record which files belonged to which component. A dependency system could express that one package needed another. A release policy could

trade newer versions against predictable behavior.

Dependency management does not eliminate compatibility problems. A package can satisfy a declared version constraint and still expose a behavioral regression. Locally modified configuration complicates upgrades. Security fixes may need to be backported without changing a stable application interface. Distribution engineering therefore involves judgment, testing, and maintenance over time, not just automated compilation.

The work also creates different notions of "current." A server vendor may support an older release with carefully selected fixes. A rolling release may prioritize rapid integration. A developer machine may use new toolchains while a production machine values stable administration. These choices are coherent responses to different workloads rather than evidence that only one distribution has understood Unix correctly.

7.4 The network becomes a development medium

Source availability helped contributors inspect and modify Linux, but collaboration needed channels and decision processes. Mailing lists, patches, maintainers, release candidates, and subsystem ownership created a way to review changes without requiring every developer to understand every driver. Later, Git became a crucial tool for distributed development. The development model evolved with the scale of the work.

Large-scale participation did not mean an absence of authority. Maintainers decide what to accept; reviewers require revisions; release managers choose when a change is ready. The ability to fork limits some forms of control but does not make a successful

fork cheap. A project has accumulated tests, reputation, users, expertise, and relationships that cannot be duplicated by copying a directory alone.

Corporate participation became substantial. Hardware vendors need drivers, cloud companies need scalability, and distributors need maintainable releases. Paid work and volunteer work coexist in the same repositories. The contrast between a purely commercial model and a purely amateur community is a poor description of the resulting system.

There are genuine tensions. A sponsor's priorities may differ from a maintainer's, and a widely used subsystem can still depend on too few reviewers. Public source does not automatically distribute labor fairly. A history of open source should include the economics of maintenance, not merely the excitement of the first public release.

7.5 Free software and open source name different arguments

The term "open source" gained institutional prominence in 1998. It provided a way to argue for collaborative development and acceptable licenses in terms that many businesses found easier to engage with. The free software movement continued to emphasize users' freedoms as an ethical objective. The sets of licenses and projects overlap greatly; the reasons people give for supporting them need not.

Neither movement means software must have a price of zero. A business can sell support, integration, hosted services, or copies while complying with relevant license obligations. Conversely, a free download can remain proprietary. Price, source access, redis-

tribution rights, and governance should be examined separately.

The distinction becomes important in appliances and services. A company may publish covered source while making a device difficult to modify. A network service may use free software internally without giving users the same practical control over the service. Different licenses address these situations differently. A broad slogan about "openness" cannot replace a description of the actual arrangement.

7.6 A new center of gravity

Linux grew across servers, embedded devices, supercomputing, development machines, and phones. Its design and implementation changed substantially: new architectures, multiprocessor scalability, modern filesystems, security frameworks, virtualization, and extensive device support added layers far beyond the early 386 kernel. The continuity lies in maintained interfaces and a development lineage, not in an unchanged small program.

The freely redistributable BSD systems followed their own trajectories. GNU continued independently across many components. Other kernels and research systems explored alternatives. The success of Linux did not collapse these histories into one project, even when they shared tools and contributors.

A useful lesson is that freedom to combine components enlarges the space of possible systems. It can produce a conventional command-line server, a carefully integrated desktop, or a phone that offers no ordinary shell to its owner. The same legal and technical flexibility can support very different user experiences.

To understand what endured through that expansion, it helps to stop the historical clock and examine a smaller specimen. Lions's

Sixth Edition commentary offers an operating system compact enough to follow closely. Xv6 offers a later teaching reconstruction on different hardware. Together they reveal which ideas survived and which implementation assumptions had to be replaced.

Part II

The Machinery Beneath the Prompt

Chapter 8

Learning to Read a Kernel

8.1 Why a small implementation is a serious subject

John Lions's commentary approaches Unix as something a student can read. The subject is Sixth Edition on the PDP-11, not an abstract operating system assembled from unrelated algorithms. A table entry leads to a scheduler; a scheduler leads to a context switch; a context switch leads to machine registers. The explanation gains power from following an actual working system across those boundaries.

Its small size makes this possible, but smallness should not be confused with triviality. A kernel mediates between independent computations and physical devices. It must preserve protection, retain enough state to resume interrupted work, and coordinate activity that happens at inconvenient moments. Even a compact implementation contains subtle interactions whose correctness

depends on assumptions outside the current function (Lions 1977, ch. 1, 4).

The commentary also has a history as a teaching artifact. Source licensing restricted its circulation, and authorized teaching could be difficult to separate from prohibited redistribution. Its later wider publication made visible an educational demand that the earlier licensing structure had frustrated. The famous reputation of the book is therefore partly technical and partly a story about who could study a system.

This chapter uses Lions's method rather than reproducing his annotated source. The reader should learn to ask what must remain true across a transition. Once that habit is established, an unfamiliar kernel becomes less a mass of names and more a set of responsibilities.

8.2 Begin with the machine contract

The processor defines which instructions are privileged, how interrupts arrive, how memory addresses are translated, and what state is saved when execution changes mode. The operating system cannot wish these rules away. An implementation explanation that omits them can make correct code look mysterious or incorrect code look plausible.

On the PDP-11 systems discussed by Lions, memory management uses segments and architecture-specific registers. The familiar modern picture of a large demand-paged virtual address space is the wrong starting point. The kernel also works within tight address-space limits, with arrangements for kernel state and per-process data that exploit the machine's mapping facilities. These details explain code that would otherwise seem needlessly indi-

rect.

A trap is a controlled entry into privileged execution, often used to request a system service. An interrupt usually reports an asynchronous event from a device or timer. Both need entry and return machinery, but they differ in origin and in what the interrupted computation expects. The hardware saves some state; assembly and C code preserve and interpret the rest.

The right reading order is consequently not always the order of files in a directory. Learn the processor's contract, identify the kernel's principal tables, trace one complete operation, then examine its exceptional paths. This is closer to following a transaction through an organization than to reading a novel from the first line to the last.

8.3 Tables are the system's memory of itself

A running kernel contains representations of processes, open files, in-memory inodes, buffers, devices, and pending events. These structures are not incidental bookkeeping. They are how the system remembers the relationships that its interfaces promise.

In Sixth Edition, the process table and the per-process user structure serve different roles. Information needed to manage processes must remain accessible even when a process's larger image is swapped out. Other state can travel with the process. That division makes sense only when read against the memory and swapping model (Lions 1977, ch. 7–8).

Similarly, a descriptor number, an open-file table entry, and an inode represent different things. The descriptor is a process-local reference. The open-file entry holds state associated with an opening, including an offset. The inode represents the underlying

filesystem object. Combining them in one's mental model makes inherited descriptors and unlinking almost impossible to explain correctly.

For each structure, ask four questions: who allocates it, who may refer to it, what protects changes to it, and when it can be reclaimed. These questions expose lifetimes. A reference count is useful only when the code that acquires and releases references obeys a consistent rule. A lock is useful only when all relevant readers and writers agree on what it protects.

8.4 Trace a request, then interrupt it

Suppose a program requests bytes from a file. The request passes through system-call entry, argument handling, descriptor lookup, file and inode state, block mapping, and the buffer cache. If the needed block is absent, a device operation may be started and the process may sleep. A device interrupt later records completion and makes waiting work runnable. Finally the request returns bytes or an error to user space.

This trace is more informative than studying each function independently. It reveals where the operation can block, where an object must remain alive, and where another process can observe state. It also reveals that a system call need not run in one uninterrupted stretch. The logical operation can span several periods of CPU execution.

Now ask what happens at each boundary. What if a signal arrives? What if memory allocation fails? What if another process closes its reference? What if the device reports an error? Historical kernels and modern kernels answer these questions differently, but the questions are stable.

Lions's treatment rewards this style of inquiry. The celebrated difficult context-switch passage is not a license to skip understanding. It is a warning that saved execution state, address mappings, and control flow must be considered together. A local reading of a few C statements can miss the operation's real meaning.

8.5 Xv6 is a comparison, not a time machine

The supplied xv6 text is dated 27 October 2019 and describes a RISC-V implementation. Earlier xv6 material often used x86, and newer revisions can change details and section numbering. This book uses the supplied edition consistently. Its chapters on page tables, traps, locking, scheduling, and the file system provide a second complete specimen (Cox, Kaashoek, and Morris 2019).

Xv6 preserves the teaching value of a small Unix-like interface while making different hardware assumptions. Its Sv39 page tables, supervisor mode, trap machinery, and multicore coordination do not belong to Sixth Edition. Its file-system log is also a teaching design, not a feature that should be retroactively attributed to the original PDP-11 system.

The differences are the point. Both systems support processes and files; the mechanisms maintaining those abstractions have changed. A uniprocessor implementation can rely on facts that fail as soon as two cores execute kernel code simultaneously. An implementation based on segments can organize memory in ways that a page-table implementation would not choose.

Xv6 is also intentionally incomplete as a production system. It omits many policies and facilities required for hostile users, modern devices, large-scale performance, and long-running service. An educational mechanism can expose a principle without being

a recommended implementation for all workloads. The supplied book itself repeatedly distinguishes its model from real-world systems.

8.6 History is evidence, not a benchmark competition

Comparing a modern Linux kernel with Sixth Edition by line count alone explains little. Modern kernels support many processors, devices, filesystems, networking protocols, security mechanisms, and compatibility obligations that the older system did not attempt. Some complexity is avoidable, but some records new responsibilities.

Spinellis's Unix history repository offers another way to study change: follow artifacts and revisions across time. Its reconstruction combines snapshots and repositories, so early commit metadata is not equivalent to a contemporaneous developer log. The paper explicitly discusses its construction and limitations. Historical data must be interpreted as carefully as historical prose (Spinellis 2017).

The practical method is to hold an abstraction steady while comparing the work needed to implement it. How does each system prevent one process from overwriting another? How does each remember a blocked reader? How does each recover a file operation after a crash? Those questions produce a useful account of progress without pretending the later system was simply the earlier one with unnecessary decoration.

The following chapters apply that method. They move from a program's execution, through competition for the processor, to persistent storage and communication. At every stage the visible

interface remains smaller than the machinery required to keep its promise.

Chapter 9

Processes, Traps, and the Illusion of a Private Machine

9.1 A program is not a process

A program is a body of instructions and data in a form that can be loaded. A process is a running environment: an address space, execution state, credentials, open descriptors, and relationships to other processes. Several processes can execute the same program, while one process can replace its program image without becoming a new process.

This distinction makes the Unix process interface unusually flexible. The shell can create a child process and arrange its environment before asking it to execute a particular program. Redirection and pipelines do not have to be implemented separately inside every command. They can be established through the process's inherited resources (Stevens and Rago 2013, ch. 8).

The private-machine illusion is qualified. Processes share the CPU, physical memory, filesystems, devices, and sometimes explicitly shared memory. Their clocks reflect scheduling and contention. Resource limits can stop growth, signals can interrupt work, and administrative action can end execution. The operating system provides isolation and controlled sharing, not an infinitely capable imaginary computer.

9.2 Creation and replacement are separate operations

In the familiar interface, `fork` creates a child with a closely related initial state. Parent and child continue after the call with different return values. Their address spaces are logically separate, although an implementation may initially share physical pages using copy-on-write. That optimization is common in modern systems; it is not a requirement of the interface and should not be assumed for the supplied xv6 implementation.

An `exec` operation replaces the current program image. It does not create a child. A successful exec preserves the process identity while changing the executable code, stack, and much of the memory environment. Selected process properties survive, including descriptors not marked close-on-exec. The exact rules belong to the specified interface and implementation.

The separation lets a shell perform a sequence that can be described schematically as follows:

```
create child
    in child:
        bind chosen input to descriptor 0
        bind chosen output to descriptor 1
        close unused descriptors
        execute requested program
    in parent:
        close no-longer-needed pipe ends
        wait or continue as the command requires
```

This is pseudocode, not a complete C implementation. Real code must handle failures at every stage, avoid leaking descriptors, and choose appropriate behavior if execution fails. After fork in a multithreaded program, the child also faces restrictions before exec because it inherits an address space whose other threads no longer exist in that child. An apparently simple launch can carry difficult library-state assumptions.

Other interfaces, including `posix_spawn`, package common launch operations differently. Their existence does not invalidate the fork/exec model. It shows that an elegant abstraction can acquire performance and concurrency costs in environments unlike the one that first shaped it.

9.3 Entering the kernel changes authority

A user program cannot safely be allowed to program device hardware or rewrite memory mappings at will. Hardware privilege levels constrain those operations. A system call crosses into a controlled entry path where the kernel interprets a request under the caller’s credentials and the system’s resource rules.

A library function and a system call are not the same thing. A function such as a buffered I/O routine may do substantial work in user space and request kernel I/O only occasionally. A thin wrapper may arrange arguments and execute the architecture’s trap

instruction. The boundary that matters for protection is the controlled privilege transition, not whether a function name appears in a familiar header.

On entry, the kernel must preserve enough register state to resume the caller. It needs a valid kernel stack and a known mapping environment. It must also treat user-supplied pointers as untrusted addresses, not as permission to access arbitrary kernel memory. The requested range may cross a page boundary, include an unmapped page, or become invalid under concurrent changes in a more elaborate system.

The xv6 book's trap and page-table chapters make these transitions explicit. Its trampoline arrangement allows carefully controlled code to remain reachable across a page-table change. That is a RISC-V implementation technique in the supplied edition, not a generic synonym for every Unix system-call path (Cox, Kaashoek, and Morris 2019, ch. 3–4).

9.4 Addresses need an interpreter

A virtual address is meaningful within a mapping context. Hardware translates it into a physical address and checks permissions. This lets two processes use the same numerical virtual address for unrelated data. It also lets the kernel map the same physical page into multiple address spaces when sharing is intentional.

In the supplied xv6 Sv39 model, ordinary pages are 4096 bytes and page tables form a three-level tree. The address contains index fields and an offset within a page. Walking the tree locates a page-table entry whose physical page number and permissions determine whether the access can proceed. Real RISC-V also constrains valid address forms; unused upper bits are not a license to

use arbitrary 64-bit values.

The translation lookaside buffer caches recent translations, reducing the cost of repeated walks. Changing a page table may therefore require invalidating cached translations. On multiple cores, the kernel may need to coordinate invalidation across processors that could use the old mapping. A memory-protection decision can become a synchronization problem.

Sixth Edition reaches a related goal through PDP-11 segmentation and swapping arrangements. Its small virtual spaces and hardware-specific mapping rules should be understood on their own terms. Saying that both systems provide protected address spaces is accurate; saying that they use the same virtual-memory implementation is not (Lions 1977, ch. 2, 7, 15).

9.5 Copy-on-write and faults as useful events

A page fault does not always mean a programming error. It means an access could not complete under the current translation and permission state. A kernel can use that event to load data, allocate a page lazily, or perform a copy-on-write operation. An invalid access can instead cause the process to receive a signal or terminate.

For copy-on-write, two address spaces initially refer to the same physical page with writes restricted. A write causes a fault. The kernel allocates and copies when necessary, updates the writer's mapping, and resumes the instruction. The process sees the logical result of independent memory without paying to copy every page at creation time.

Correctness depends on reference counts, permissions, fault clas-

sification, and synchronization. A page cannot be freed while another mapping still uses it. The kernel must not mistake a genuinely read-only executable page for a copy-on-write page. The optimization is therefore a complete lifetime-management mechanism, not a single conditional in the fault handler.

Production virtual-memory systems add file-backed mappings, anonymous memory, shared libraries, reclaim, swapping, huge pages, NUMA placement, and overcommit policies. These mechanisms affect both performance and failure behavior. A successful allocation request does not necessarily mean every future page access will obtain physical memory under all resource policies.

9.6 Exit must leave an account of what happened

When a process exits, most of its resources can be released promptly. Its parent may still need an exit status and identifying information. A zombie is the residual record kept for that purpose, not a secretly executing program. Waiting lets a parent collect the result and permits the remaining record to be reclaimed.

Parent-child relationships also need rules when a parent exits first. Traditional Unix arrangements reparent orphaned children to an appropriate system process; modern systems may have additional subreaper facilities. The exact policy differs, but the underlying requirement remains: termination must not leave an unreclaimable record simply because the original parent disappeared.

This completes one traversal of the private-machine illusion. Creation establishes identity and resources; execution replaces a program; traps request services; mappings enforce isolation; faults support policy; and exit leaves enough evidence for coordination.

The illusion works because the kernel remembers all these relationships even when a program need only think about its next instruction.

Chapter 10

Who Runs Next?

10.1 Concurrency begins before a second processor

A machine with one processor can still have concurrent activity. A process may be suspended while another runs; a device can complete an operation while code is manipulating a related structure. The execution is interleaved rather than physically simultaneous, but the program must still account for more than one possible ordering.

This distinction is essential when reading Lions. Sixth Edition's uniprocessor kernel could rely on the fact that ordinary kernel execution was not preempted by another process at an arbitrary C statement. A process gave up the processor at explicit points, especially when sleeping. Interrupt handlers were a different source of interleaving and required their own discipline (Lions 1977, sec. 8.16).

An algorithm correct under these assumptions can fail immediately on a multiprocessor. Disabling interrupts on one core does

not prevent another core from changing shared memory. Nor does the absence of an explicit sleep guarantee that a second core is not already inside the same function. Historical code must be read with its execution model attached.

10.2 A context switch preserves a continuation

A scheduler chooses runnable work. A context switch makes that choice real by saving one execution context and restoring another. Registers, stack state, address-space state, and bookkeeping all contribute to the ability to continue a suspended computation.

Not every switch saves every piece of state in the same place. A trap may already have saved user registers in a trap frame. A kernel context switch may save only the registers needed to resume a kernel continuation. Confusing these records leads to the false expectation that one structure contains the entire process at every moment.

In xv6, the relationship among a process's kernel context, its trap frame, and the per-CPU scheduler context is explicit. The low-level switch function transfers execution between carefully arranged stacks. A caller eventually returns along a control path that can look surprising if the reader assumes every return corresponds to the immediately preceding chronological call on the same CPU (Cox, Kaashoek, and Morris 2019, ch. 6).

A switch also costs more than the instructions that save registers. Caches may contain another process's working set; translation state may need adjustment; the new process may run on a different core. Scheduling policy therefore interacts with memory locality and processor topology. "Always run the next waiting process

immediately” is not a complete performance policy.

10.3 Runnable is different from running

A process waiting for disk input cannot use the CPU productively merely because its priority is high. It needs an event to make progress. A runnable process has work it can execute; a running process is currently executing; a sleeping process waits for some condition. Real kernels use more detailed states, but this distinction is fundamental.

Scheduling policies balance responsiveness, throughput, fairness, accounting, and sometimes deadlines. These goals can conflict. Giving interactive work prompt service can improve perceived performance while delaying a long computation. Keeping a task on one core can improve locality while leaving another core temporarily less busy.

Historical Unix scheduling used priorities and feedback related to CPU use. Production systems have repeatedly revised these mechanisms as hardware and workloads changed. It is safer to explain the policy’s goals than to treat one version’s formula as the definition of Unix scheduling. The same applies to claims that one scheduler is universally “fair”: fairness requires a stated unit, population, and time scale.

10.4 The lost wakeup is a missing agreement

Suppose a consumer needs an item from an empty queue. It checks the queue, then prepares to sleep. A producer inserts an item and sends a wakeup in between those two actions. If wakeups are not

remembered and the consumer has not yet registered its sleep, the notification reaches nobody. The consumer then sleeps despite work being available.

The problem is not that the producer forgot to send a notification. It is that checking the condition and registering the wait were not coordinated with the producer's update. Thompson's implementation paper explains that event wakeups do not themselves retain a count of past events. The surrounding protocol must close the race (Thompson 1978, sec. 2.3).

The usual conceptual pattern is:

```
lock the condition's lock
while the condition is false:
    sleep, atomically releasing that lock
    resume with that lock held again
perform the protected operation
unlock
```

This is pseudocode. A concrete sleep primitive must define precisely how it transfers protection between the condition lock and the bookkeeping that records the sleeping process. Xv6 demonstrates such a protocol using process locks and a channel associated with the event (Cox, Kaashoek, and Morris 2019, sec. 6.5).

The loop is important. A wakeup means the condition may have changed, not that this particular waiter owns the resource. Another waiter can win the race, several waiters can be awakened, or a more general interface can permit spurious wakeups. The condition is the truth; the notification is an invitation to check it again.

10.5 Locks protect invariants

A lock does not make a variable correct by proximity. It protects an invariant maintained by all code participating in the protocol. For a queue, the invariant might connect a head pointer, tail pointer, item count, and links. Updating only one field under the lock while reading related fields without protection can still expose an impossible state.

Spinlocks wait by repeatedly attempting acquisition. They are appropriate only when the holder will release promptly and the waiting context can afford to spin. A sleeping lock allows the waiter to relinquish the CPU, but cannot be used indiscriminately in interrupt context or while holding resources whose progress requires that same CPU.

Atomic machine instructions make acquisition indivisible, but hardware and compilers can reorder ordinary memory operations. Acquire and release semantics establish the ordering needed for one core to observe changes made under the lock by another. An implementation that works accidentally on one processor's memory model can fail on a weaker one.

Deadlock appears when dependencies form a cycle: one participant holds A while waiting for B, another holds B while waiting for A. A consistent lock order prevents many such cycles. Avoiding sleep while holding certain locks prevents others. Lock ordering must be documented at subsystem boundaries, where a locally reasonable acquisition can complete a global cycle nobody intended.

Xv6 deliberately exposes these issues. Its small size lets the reader follow where a lock is acquired, why interrupts are controlled, and how ownership may be transferred across scheduling. Modern kernels add more specialized mechanisms, including read-copy-

update and lock-free structures, but those techniques still require explicit lifetime and ordering arguments.

10.6 The hard part is preserving progress

Mutual exclusion alone does not guarantee useful behavior. A process can starve if other work repeatedly overtakes it. A low-priority holder can delay high-priority work, producing priority inversion. A wakeup strategy can awaken many processes that mostly return to sleep, creating a thundering herd. Performance failures can arise from a protocol that is technically free of data races.

The best starting point is to state both safety and progress properties. Safety might say that an object is never freed while a user holds a reference. Progress might say that a waiting operation eventually receives a chance to run when its resource becomes available. Each needs different evidence. Stress testing can reveal violations, but a successful run is not a proof that all interleavings are safe.

This is why concurrency occupies so much of kernel engineering. The visible interface often promises a simple result, while the implementation must maintain that result across interruptions, scheduling, and simultaneous execution. The complexity is concentrated around the moments when one computation depends on another. Understanding those moments makes the rest of the kernel much easier to read.

Chapter 11

Files, Blocks, and the Problem of Tomorrow

11.1 A name is a route to an object

A pathname is not the file itself. It is a route through directories to an object. A directory associates names with filesystem identifiers; an inode records metadata and information about where a file's contents can be found. The precise on-disk layout varies, but separating names from objects is a central Unix idea.

A hard link adds another directory entry referring to the same object. A symbolic link stores a path to be interpreted during lookup. Their behavior differs when targets move, disappear, or cross filesystem boundaries. A hard link ordinarily cannot cross the boundary between filesystems because the identifier it stores belongs to one filesystem's namespace. A symbolic link can name a path that resolves elsewhere.

Permission checking also follows the route. Finding a file requires the appropriate search permission on directories along the way,


not merely read permission on the final object. Reading a directory's list of names and searching it for a known name are distinct operations. This is one reason a simple "read/write/execute" summary can mislead when applied to directories (Stevens and Rago 2013, ch. 4).

11.2 Three levels of an open file

A descriptor is an integer in a process's descriptor table. It refers to kernel state for an open file description, which in turn refers to an underlying object. The description contains properties such as the current offset and relevant status flags. Multiple descriptors can share it through duplication or inheritance.

If a parent forks, an inherited descriptor can refer to the same open file description in parent and child. Their reads can consequently affect a shared offset. If they independently open the same pathname, they normally acquire separate descriptions with separate offsets. The underlying file can be identical in both cases; the opening state is what differs.

A compact diagram captures the distinction:



Lions traces the corresponding file and inode tables in Sixth Edition. Modern terminology and structures vary, but the lifetime distinction remains useful. It explains why closing one descriptor need not close all access to the object, and why descriptor leaks are resource leaks rather than merely unused integers (Lions 1977, ch. 18).

Unlinking removes a name. A file can continue to exist while an open reference remains after its last directory link is removed. Reclamation follows the relevant link and reference lifetimes. This makes temporary-file patterns possible, but secure temporary-file creation requires more than inventing a name from a process ID. The historical practice described by Lions should not be copied as modern security guidance.

11.3 Bytes become blocks

The file interface lets a program read a range of bytes. The storage device transfers blocks or sectors under different constraints. The kernel maps logical file positions to storage locations and keeps partial transfers and metadata out of the application's ordinary logic. The abstraction is convenient because applications need not know the disk's physical geometry.

Sixth Edition uses its own inode addressing scheme, including the historical distinction between small and large files. Thompson's later implementation paper describes another layout with ten direct addresses and indirect levels. These are different snapshots. The commonly taught modern diagram of direct, single-indirect, double-indirect, and triple-indirect pointers must not be pasted over every historical inode (Lions 1977, ch. 19)(Thompson 1978, sec. 4).

Indirect addressing trades metadata work against maximum size and compactness for small files. A small file can avoid traversing several levels of mapping. A large file can acquire more blocks without requiring an enormous fixed-size inode. Modern extent-based designs instead describe ranges of contiguous storage. Each representation encodes assumptions about allocation, fragmentation, and common workloads.

The buffer cache keeps recently used blocks in memory and coordinates access to blocks already being read or modified. A cache entry is not just a bag of bytes. It has identity, state, ownership rules, and a relationship to outstanding I/O. Two callers must not independently modify unrelated cached copies of what is supposed to be one authoritative block.

11.4 Locality is a policy decision

FFS improved performance by recognizing that the filesystem's allocation policy affects the physical work required from the disk. Nearby metadata and file blocks can reduce seeks; larger transfers can make better use of bandwidth. Fragments reduce the internal waste that larger blocks would otherwise impose on small files (McKusick et al. 1984).

Those choices reveal a limit of purely interface-oriented reasoning. Two filesystems can present the same read and write calls while differing dramatically in latency and throughput. An abstraction hides physical layout from applications; it does not make physical layout irrelevant to the implementation.

Solid-state storage changes the cost model. There is no mechanical seek, but erase blocks, write amplification, controller behavior, queue depth, and durability guarantees still matter. A policy optimized for one device can become unnecessary or counterproductive on another. The enduring Unix interface is compatible with repeated changes to the assumptions beneath it.

11.5 A successful write is not the whole durability story

A program may write data that remains in a kernel cache. The call's success can mean that the kernel accepted the bytes, not that all relevant storage has survived a sudden power loss. Buffered libraries add another layer: flushing a user-space buffer is different from requesting that the kernel synchronize data to durable storage.

A file operation often modifies several blocks. Creating a file can require an inode allocation, directory entry, allocation bitmap or free list, and timestamps. If a crash preserves only some modifications, the filesystem can contain contradictory claims about ownership. A checker can repair certain inconsistencies after restart, but repair may lose information or require expensive scanning.

Journaling records enough intent or changed state to make recovery controlled. Copy-on-write filesystems use a different family of techniques, writing new structures before switching references. Neither label alone specifies every application-level durability guarantee. Metadata consistency, data persistence, and the atomicity of a multi-file application update are different properties.

The supplied xv6 filesystem uses a simple physical redo log. Changed blocks are recorded in the log; a committed header marks a transaction as recoverable; installation copies logged blocks to their home locations. Recovery replays a committed transaction after restart. Large writes are split to fit the log, so one application write is not necessarily one indivisible persistent transaction (Cox, Kaashoek, and Morris 2019, sec. 7.5–7.6).

This is an excellent teaching mechanism because the commit point is visible. It is not evidence that hardware can never tear a write

or reorder I/O. Real systems must match their protocol to the storage contract, including flushes, barriers, checksums, or other mechanisms as required. A recovery proof depends on what the device promises to preserve.

11.6 Replacing a file safely takes more than rename

Applications often write a new temporary file and rename it into place. Within the specified same-filesystem conditions, rename can provide an atomic namespace replacement to concurrent readers. That is a valuable property: readers need not observe a half-written new file through the final name.

Crash durability is a separate question. Depending on the filesystem and platform, an application may need to synchronize the temporary file, perform the rename, and synchronize the containing directory to preserve the intended result across a crash. Cross-filesystem moves and updates involving several names require different reasoning. The correct sequence must be checked against the target system's guarantees.

This distinction between visibility and persistence is the filesystem's version of a broader theme. A clean interface can make ordinary operation simple while leaving exceptional guarantees explicit. Unix made files easy to manipulate; reliable storage engineering still requires asking what happens when the machine stops between two steps.

Chapter 12

Communication and the Shape of Failure

12.1 A pipe is a queue with lifetimes

The shell pipeline works because the kernel provides a communication object whose endpoints can be inherited and rebound. One endpoint is used for reading, the other for writing. The bytes travel through a finite buffer. The object also records whether readers and writers remain, which is essential to deciding whether an empty buffer means “wait” or “end of input.”

For a two-stage pipeline, the shell creates the pipe and children, gives the producer the write end as standard output, and gives the consumer the read end as standard input. Each participant closes the ends it does not need. The parent also closes its copies after arranging the children. Those closes are part of the communication protocol, not optional tidying.

If the parent accidentally retains a write reference, the consumer may never see end-of-file. If all readers disappear, a writer en-

counters the broken-pipe behavior defined by the interface, commonly involving `SIGPIPE` and an error. This lets a downstream command stop early without requiring the producer to know the downstream command's purpose (Stevens and Rago 2013, ch. 15).

A pipe is a byte stream rather than a sequence of arbitrary application messages. The interface provides particular atomicity guarantees for writes up to `PIPE_BUF`; it does not promise that every read returns one original write. Applications needing records must supply framing, respect the specified limits, and handle short transfers.

12.2 Signals announce events, not complete work items

Signals provide asynchronous notification of selected events. A user can interrupt foreground work; a timer can expire; a child can change state. A process may accept a default action, ignore an allowed signal, or install a handler. Some signals cannot be caught or ignored.

The difficulty is that a handler can run while ordinary code is in a sensitive state. A library may hold internal locks or be halfway through updating a data structure. Calling a convenient function from the handler can reenter code that is not safe to reenter. The set of async-signal-safe operations is therefore deliberately constrained.

A common strategy is to make the handler do minimal work and arrange for ordinary control flow to respond. Even setting a flag requires an appropriate type and protocol. More elaborate designs can route notifications into an event loop through platform-supported mechanisms. The aim is to separate notification from

work whose context requirements are stronger.

Ordinary non-real-time signals can coalesce: multiple occurrences do not necessarily produce an equal number of pending notifications. An application must not treat them as an unbounded reliable message queue. This resembles the sleep/wakeup lesson. An event mechanism tells a process to reexamine state; it does not always preserve every historical occurrence.

12.3 Shared memory moves the protocol into the application

Two processes can communicate by mapping shared storage into their address spaces. This can avoid repeated copying through a stream interface and support efficient data structures. It also removes some of the natural boundaries that make a pipe easy to understand.

The participants must agree on layout, synchronization, ownership, and recovery if one dies while modifying shared state. A pointer valid in one address space may not be valid in another unless mappings are arranged accordingly. Offsets or handles can be safer representations. A language-level object containing hidden pointers may be unsuitable for unqualified placement in shared memory.

Memory visibility is another concern. A writer updating fields and then setting a readiness flag needs ordering that ensures the reader sees consistent data. Merely observing the same bytes through two mappings does not supply a complete concurrency protocol. The locks, atomics, and memory-order rules of chapter 10 return here.

The performance advantage consequently comes with a transfer of responsibility. The kernel supplies the shared mapping; applications must supply more of the agreement about meaning. Shared memory is not a faster drop-in replacement for every pipe or socket.

12.4 Sockets generalize endpoints

A socket has an address family, communication type, and protocol context. A local Unix-domain socket can connect processes on one host; an Internet socket can connect through a network. A server commonly binds a name or address, listens, and accepts connections. Accepting returns a connected endpoint distinct from the listening endpoint, allowing the server to continue receiving new clients.

The descriptor representation makes established connections fit familiar I/O operations. Setup and control remain explicit because networks need semantics ordinary files do not have. A socket can have a peer, a shutdown direction, address information, and protocol-specific options. This is a pragmatic extension of the file interface rather than a proof that all objects should have identical operations (Stevens, Fenner, and Rudoff 2004).

TCP supplies an ordered reliable byte stream while the connection remains usable. It does not preserve application message boundaries. A write of a hundred bytes followed by another write of a hundred bytes can be read in different-sized pieces. A receiver must accumulate data according to a framing rule, such as a fixed header containing a length.

Lengths themselves are untrusted data. Before allocating a buffer, the receiver must check bounds and arithmetic overflow. A peer

that declares a giant message and then sends slowly can consume resources even without violating the framing syntax. Protocol design therefore includes limits, timeouts, and cancellation, not merely a diagram of packet fields.

12.5 A send is not an acknowledgment of application success

A successful local send often means bytes were accepted into the local networking path. It does not prove the remote application parsed them, committed a transaction, or even remained alive afterward. Transport acknowledgments and application acknowledgments answer different questions.

Suppose a client asks a server to charge an account. The server performs the operation, then the connection fails before the reply reaches the client. Retrying can duplicate the effect; refusing to retry can leave the user unable to determine what happened. TCP cannot settle this ambiguity because the missing fact concerns the application’s persistent state, not just delivery of bytes.

Application protocols can use operation identifiers, deduplication, idempotent actions, and durable records to make retries meaningful. Each mechanism has a scope. An identifier remembered only until a process restarts does not provide the same guarantee as one recorded with the transaction. “Exactly once” requires a precise model of failures and storage rather than confidence in the network library.

This is where distributed systems depart most sharply from the experience of a local command pipeline. A local kernel can often know that a process has exited. Across a network, silence is ambiguous. A timeout is a policy decision about waiting, not proof

that a peer no longer exists.

12.6 Event loops and the cost of waiting

A server handling many clients cannot always dedicate an expensive thread to each idle connection. Readiness interfaces such as select and poll, and platform-specific mechanisms such as epoll and kqueue, allow it to wait for activity across many descriptors. Their semantics differ; readiness and completion are not interchangeable concepts.

Readiness means an operation is likely to make progress under defined conditions. Another actor can change the state before the operation runs, so nonblocking code must still handle a result that says to try again later. A readable descriptor can also indicate end-of-file or an error. An event loop needs state for partial messages, pending writes, and connection cleanup.

A design can become difficult to maintain when that state is scattered among callbacks with unclear ownership. Threads do not automatically solve the problem; they move the state into stacks and synchronization. The right choice depends on workload, language facilities, and how clearly the program can express lifetimes and cancellation.

Unix's communication history is therefore a history of expanding contracts. Pipes coordinate nearby processes, signals notify, shared memory exposes common data, and sockets connect endpoints whose failures may be only partially observable. The interfaces remain compact because they leave application meaning to the application. Good engineering begins by recognizing exactly where that responsibility starts.

Part III

Tools, Screens, and Design

Chapter 13

Building Programs, Building Environments

13.1 The toolchain is part of the system

Unix offered a place to write programs, not merely a place to execute finished applications. An editor, compiler, assembler, linker, debugger, and manual formed a practical sequence from idea to running code. Their boundaries made it possible to replace one stage or inspect an intermediate result. A compiler error and a linker error could be located in different parts of the construction process.

This environment also sustained itself. The system's programs were built on the system, and its documentation was prepared with its document tools. The 1974 paper calls attention to this self-supporting quality. It mattered institutionally: improvements to the tools immediately improved the developers' ability to improve the system (Ritchie and Thompson 1974, sec. 1).

C benefited from that environment, but Unix was never exclusively

a C-language world. Fortran supported numerical work; assemblers remained necessary; interpreters and little languages served specialized tasks. Later Lisp, ML-family languages, scripting languages, and managed runtimes found homes there. A process interface based on arguments, descriptors, and status does not require all participants to share a source language.

13.2 Generators turn descriptions into code

Stephen Johnson's yacc generated parsers from a grammar and associated actions. Lex, associated with Michael Lesk and Eric Schmidt, generated lexical analyzers from pattern descriptions. The pairing made language implementation more accessible by expressing recurring machinery as specifications rather than rewriting every state transition by hand.

A lexical analyzer recognizes tokens; a parser relates those tokens to a grammar. The distinction helps authors separate character-level details from structural rules. It does not eliminate ambiguity or semantic analysis. A grammar can be ambiguous, an action can have a bug, and a perfectly parsed program can still be meaningless.

Generators also create a maintenance obligation. The generated file may be difficult to review directly; the grammar and generator version become essential inputs. Checking in generated output can make bootstrapping easier while introducing the risk that source and output diverge. A build needs a declared rule for which representation is authoritative.

These tools belong to the same family of ideas as eqn and tbl. Each lets an author work in a representation closer to the problem, then translates it into a lower-level mechanism. The common

principle is not that every problem needs a new language. It is that a suitable representation can remove repetitive reasoning from ordinary code.

13.3 Make records relationships

Stuart Feldman's make addressed the repeated work of rebuilding programs. A project contains targets and prerequisites. If an input has changed, the relevant target and its dependents need rebuilding. Encoding these relationships lets the tool decide what work is necessary.

A small original example is enough to show the model:

```
report: report.o parse.o
        cc -o report report.o parse.o

report.o: report.c parse.h
        cc -c report.c

parse.o: parse.c parse.h
        cc -c parse.c
```

In an actual makefile, each recipe begins with a tab. The example's important content is the dependency graph, including the header. If the header is omitted, the build may succeed while leaving an object file compiled against an obsolete declaration. Incremental correctness depends on complete inputs, not only on convenient command notation.

Traditional timestamp-based decisions are economical, but they have limits. Generated inputs, clock differences, hidden environment changes, and tools whose versions are not recorded can produce stale or nonreproducible output. Modern build systems use techniques such as content hashing, declared toolchains, sandboxed actions, and remote caches. These are extensions of the

desire to make the construction process explicit.

A document build has the same structure. Citations require bibliography processing; references may require reruns; an index has its own processor. A single successful typesetting pass is not necessarily a finished book. The build system in this repository delegates that dependency work to latexmk rather than expecting the reader to remember an invocation sequence.

13.4 Debugging depends on observable state

A debugger connects machine behavior to source-level expectations. It can stop execution, inspect variables, examine a stack, and report where a failure occurred. Optimized code complicates that relationship: a variable can disappear, instructions can move, and the stack may not resemble a simple sequence of source calls.

Tracing offers a complementary view. A system-call trace can show which files a program opens, where it blocks, and what the kernel reports. It can reveal a missing configuration file or a permission error without understanding every internal function. It cannot by itself explain all user-space computation or prove that a program's result is correct.

Profiling asks yet another question: where does time or another resource go? Sampling, counters, and instrumented events expose different aspects of behavior. Measurement overhead and attribution rules matter. A program waiting for a remote service may consume little CPU while remaining painfully slow for its user.

Unix's preference for inspectable files and separate processes often makes such tools convenient, but observability is not automatic.

A program must preserve useful error context, avoid corrupting data streams with diagnostics, and give administrators enough information to connect a failure with its cause. Silence on ordinary success is compatible with detailed evidence when something goes wrong.

13.5 Versions make collaboration historical

SCCS and RCS supported source history before the distributed systems now familiar to many programmers. Later systems expanded collaboration across repositories and institutions. Git, developed in 2005 in the setting of Linux kernel development, made content-addressed objects and distributed history central to a widely adopted workflow.

A version-control system preserves relationships among states. It can show what changed, associate a change with an explanation, and support branching and merging. It cannot supply a good explanation if the author records only “fix.” Nor can a clean merge prove semantic compatibility: two edits can apply without conflict and still violate a shared invariant.

History also supports investigation. A regression can be narrowed by searching for the change that introduced it. An old implementation can be compared with a later one. Spinellis’s reconstruction extends this practice to periods before the relevant systems used a continuous modern repository, while warning readers not to mistake reconstructed metadata for an untouched contemporaneous record (Spinellis 2017).

The repository is thus both a collaboration mechanism and an argument about provenance. Source history is especially valuable when accompanied by build instructions and tests that make older

states interpretable. Without those, preservation can become a collection of files whose behavior nobody can reproduce.

13.6 Languages beyond C

The supplied collection includes Unix programming treatments in Standard ML and OCaml. Their presence is a useful corrective to histories that identify Unix programming with a single syntax. File descriptors, processes, and sockets can be exposed through different type systems and runtime models. The operating-system contract survives translation into a language’s abstractions.

A managed language may wrap a descriptor in an object with buffering, exceptions, or automatic cleanup. Those features can make programs safer, but they do not repeal the underlying semantics. Garbage collection does not guarantee timely release of a scarce descriptor. A buffered channel can retain data the kernel has not yet seen. An exception can interrupt a multi-step protocol before cleanup finishes.

Type systems can express distinctions that C convention leaves implicit. They may help separate bytes from text, optional values from present ones, and valid states from invalid combinations. At foreign-function boundaries, those guarantees need careful preservation. An unchecked C interface can reintroduce lifetime and representation errors beneath a safe wrapper.

The larger lesson is that Unix supplies useful primitive agreements, while languages can improve how programmers handle them. The right abstraction can expose an important failure rather than hide it. A function returning a result that must be checked is often more helpful than a convenient wrapper that silently discards the distinction.

13.7 A development environment is an accumulated promise

Over decades, Unix environments grew from a small local toolkit into platforms hosting enormous language ecosystems. Package registries, generated code, native libraries, compiler versions, and deployment runtimes added dependencies far beyond a handful of C files. The task of understanding a build became correspondingly harder.

The original strengths remain useful when applied deliberately. Record inputs. Keep stages inspectable. Distinguish generated artifacts from their sources. Make failure visible. Preserve enough history to explain why a choice was made. These practices do not depend on a particular shell or compiler.

They also connect programming with the subject of the next chapter. Raymond's account of the Unix tradition turns many such practices into explicit design advice. The advice is most useful when tested against concrete programs and against the objections of users who have paid for its failures.

Chapter 14

The Art, and the Limits, of Unix Programming

14.1 A tradition becomes a set of principles

Eric S. Raymond's *The Art of UNIX Programming* gathers a design tradition that had previously been carried through tools, books, conversations, and example programs. Its rules concern modularity, clarity, composition, separation, simplicity, transparency, representation, and other habits. The value is not that every Unix program follows them. It is that the rules make intentions available for examination (Raymond 2004, ch. 1).

Ritchie had already offered a less celebratory view in his 1977 retrospective, discussing reliability, security, and areas where Unix had invested little effort. The designers' willingness to name those limits is part of the tradition too. Criticism is most useful when it states a workload, a failure, and an assumption that can be examined, rather than treating either admiration or irritation as sufficient evidence (Ritchie 1977).

They are best read as engineering pressures rather than universal laws. A small interface can conceal an enormous implementation. A larger program can offer a clearer conceptual model than five fragile adapters. A text format can improve inspection or become an ambiguous private language that nobody has documented. The desired property must be identified before the slogan can help.

Raymond's account is also historically situated. Published in the early 2000s, it reflects experience accumulated before today's mobile and cloud environments took their current shape. Its observations remain useful, but later systems provide new tests. A camera application, a compositor, and a kernel driver do not divide naturally into the same pieces as a line-oriented report generator.

14.2 Composition needs a shared grammar

A program becomes composable when another program can use its behavior without relying on accidental details. Standard input and output help, but they are only transport. The real agreement includes record boundaries, encoding, ordering, errors, and versioning.

Imagine a tool that reports storage usage. Human-readable output might contain aligned columns, abbreviated units, and translated headings. That is pleasant for a person but awkward for a parser. A machine-readable mode can provide explicit fields and stable units. Both views can be useful; forcing one to serve both audiences often produces a brittle compromise.

JSON, CSV, and other structured formats address some problems while introducing their own contracts. CSV needs an agreed dialect and escaping rules. JSON distinguishes some value types but does not automatically supply a schema or preserve every numeric

representation. Newline-delimited text remains excellent for many simple tasks. The right choice depends on what ambiguities the application can tolerate.

Composition also needs failure semantics. If a producer stops halfway through a dataset, can the consumer distinguish incomplete output from a complete shorter dataset? Does the pipeline preserve the failing status? Can a retry duplicate effects? A clean data format without a clean failure protocol is only half an interface.

14.3 Clarity includes the invisible state

Raymond's preference for clarity over cleverness is especially valuable when examining state. A compact function can still depend on a large implicit machine: environment variables, global settings, current directory, cached credentials, or a sequence of prior calls. Line count is a poor measure of how much a maintainer must remember.

A clearer design makes legal transitions visible. A connection may be uninitialized, connected, closing, or closed. If unrelated booleans encode those states, impossible combinations can appear. An explicit representation can reduce the number of questions every caller must ask. The lesson applies to ordinary applications as much as to kernels.

Transparency means making relevant behavior observable. It does not mean dumping every internal detail into the user's interface. A person submitting a form needs a useful explanation of failure, while an operator may need a trace identifier and diagnostic record. Different audiences need different views of the same event.

This is a productive extension of the Unix tradition. Files, logs, trac-

ing tools, and stable interfaces can expose enough state to diagnose problems without requiring every user to become an administrator. Visibility should serve an actual decision or investigation.

14.4 Policy cannot be eliminated

Separating policy from mechanism can preserve flexibility. A display server can provide operations while a window manager chooses placement and decoration. A scheduler can provide accounting and priorities while an administrator assigns limits. Such boundaries allow one component to evolve without rebuilding everything around it.

Yet a mechanism still embodies choices. Which objects exist, which operations are possible, and what defaults apply all constrain policy. If an interface allows only one global clipboard or assumes every input device has the same coordinate model, later policy cannot easily repair the limitation.

Raymond acknowledges a practical cost: when users can choose policy, they may also have to choose it. Experts may welcome the freedom; newcomers may experience a burden. An operating system that offers ten ways to solve an ordinary problem has not automatically made that problem easy (Raymond 2004, discussion of mechanism and policy).

Good defaults are therefore compatible with modularity. A well-integrated environment can offer a standard policy while retaining an interface for replacement. The challenge is to make customization possible without making customization mandatory for basic competence.

14.5 Critics are part of the evidence

The UNIX-HATERS Handbook is polemical, frequently funny, and often unfair in its rhetoric. It is nevertheless valuable evidence of frustration with shells, terminals, mail, networking, graphics, and tools that experts had learned to tolerate. Its existence prevents a comfortable history in which every inconvenience was an intentional virtue (Garfinkel, Weise, and Strassmann 1994).

A complaint about cryptic names can point to discoverability. A complaint about inconsistent options can point to interface debt. A complaint about editing configuration files can point to missing validation and poor recovery. The author's tone does not determine whether the underlying problem is real.

The empirical reliability work of Miller, Fredriksen, and So provides a different form of criticism. Their 1990 study tested almost ninety utilities across seven Unix versions with random input and reported crashes in more than 24 percent of the programs tested. These were results for that sample and method, not a current failure rate for all Unix software (Miller, Fredriksen, and So 1990).

The finding matters because the utilities were familiar and frequently used. Repetition in ordinary operation had not exposed every malformed input path. A reputation for maturity did not substitute for deliberate adversarial testing. The broader lesson is that simple interfaces and long service can coexist with serious implementation defects.

14.6 Security tests the boundaries of convenience

Text-oriented tools are easy to combine, but accepting arbitrary text as commands can create injection vulnerabilities. A program that constructs a shell command by concatenating untrusted values grants those values access to the shell's syntax. Passing an explicit argument array to a program avoids that particular interpretation step, though the target program's own option and input semantics still require care.

Environment variables and search paths are convenient forms of implicit configuration. They can also redirect execution toward an unintended program or library. Privileged code must establish a trustworthy context rather than inherit every convenience of an interactive session. A boundary that is harmless among cooperating local users may be unsafe when an attacker controls one side.

Minimalism does not guarantee security either. A small parser written in unsafe code can still have a memory error. A large service may use privilege separation and carefully constrained interfaces to limit the effect of a bug. The relevant questions concern attack surface, authority, validation, lifetime, and recoverability.

The Unix tradition contributes useful tools to that analysis, especially process boundaries and explicit interfaces. It also leaves historical baggage, including broad ambient authority within a user account. Later systems have had to add stronger confinement mechanisms when the original trust assumptions no longer fit.

14.7 A worked design choice: one tool or several?

Suppose a team needs to import measurements, validate them, compute a summary, and produce a chart. Separate tools make intermediate data easy to inspect and permit replacement of the chart renderer. A single program can preserve typed values, perform shared validation once, and report errors in one consistent vocabulary.

The decision depends on the boundaries. If the stages already have stable, useful representations, separate tools can work well. If every stage requires access to the same complex mutable structure, forcing the data through lossy text adapters can make the system worse. The right module may be a library rather than a process.

A useful compromise is to separate an engine from its interfaces. A library can implement the core operations; a command-line frontend can support automation; a graphical frontend can support exploration. The shared engine prevents inconsistent calculations, while explicit external formats preserve interoperability.

This design follows the spirit of Unix without mechanically reproducing its earliest packaging. It concentrates responsibility, keeps important interfaces inspectable, and lets users work in the mode suited to them. The tradition remains valuable when it provides questions to ask, rather than a verdict announced before the program’s requirements are known.

Chapter 15

The Screen Before Windows

15.1 A terminal is a separate participant

Early Unix users often interacted through a terminal whose behavior was partly independent of the host. A printing terminal turned characters into marks on paper. A video terminal maintained a display and interpreted control sequences. Neither was merely a modern graphical text box with its decoration removed.

The connection carried a stream of bytes. Some represented printable characters; others changed terminal state or controlled the communication. The host also maintained terminal settings that affected how input and output were processed. The result was a protocol among application, kernel terminal subsystem, communication link, and device.

Slow output made brevity valuable. A line editor could operate without redrawing a page. Short command names and compact diagnostics reduced transmission and typing. These choices later

became cultural expectations, but their original economics were concrete. A convention optimized for paper and low bandwidth need not be the ideal convention for a new user on a fast display.

15.2 The kernel edits some of the input

In canonical terminal input, the terminal subsystem can collect a line, interpret editing characters, and deliver input to the application after a delimiter. Echoing can make typed characters visible before the application reads them. Control characters can trigger signals or other special behavior according to the settings.

This explains a common surprise: pressing a key does not always deliver one byte immediately to the application. Some work happens before the application's read completes. Conversely, a full-screen editor or game may configure a more direct input mode so it can interpret individual keystrokes itself.

"Raw" is often used informally for such behavior, but terminal settings contain several independent choices. Input translation, signal generation, echo, output processing, minimum byte counts, and timing can be configured separately. Modern portable code uses the specified termios interface; historical systems had different controls and structures (Stevens and Rago 2013, ch. 18).

A program that changes terminal state must restore it when appropriate. If it crashes or exits incorrectly, the next shell can inherit a confusing environment: no echo, unexpected line endings, or a display left in an alternate mode. The terminal remembers state beyond one process's lifetime. That is why cleanup is part of interface correctness.

15.3 Cursor addressing creates a new application style

A video terminal that can move its cursor and erase selected regions supports an entirely different interaction model from a printing terminal. An editor can show nearby text and change only the affected lines. A monitor can update a table of values. A menu can highlight a selection instead of printing another prompt below the previous one.

The difficulty was diversity. Terminals differed in control sequences, available operations, dimensions, and the cost of an update. Hardcoding one device’s behavior into every application would have reproduced the portability problem at the display boundary.

Termcap described capabilities so applications could ask how a terminal performed a particular operation. Terminfo later provided a different compiled database and associated interfaces. The environment’s terminal type identifies the expected description. A wrong value can produce nonsense even when the application and emulator are individually working.

Capabilities are more informative than a list of brand names. An application usually wants to know how to move the cursor, clear a region, or select an attribute. It need not care which vendor supplied the device. This is another instance of replacing a concrete identity with an operational contract.

15.4 Curses keeps a model of the display

Ken Arnold’s curses work at Berkeley helped applications use terminals without handcrafting every update. A curses library

can maintain a virtual screen, compare it with its model of the actual screen, and emit a suitable sequence of terminal operations. Applications describe the desired result at a higher level than individual cursor-motion bytes.

The distinction between a virtual window and the physical screen is useful. An application can update several logical regions, then request a refresh. The library can combine changes instead of transmitting each intermediate state. On a slow connection, avoiding redundant output can matter more than the cost of computing the difference.

Curses is therefore not a graphical window system in the later X sense. Its windows are regions in a character-cell model within a terminal connection. They do not automatically correspond to independently managed client surfaces, graphics buffers, or desktop windows. The same word names different abstractions at different layers.

Ncurses carried and extended this tradition in free software environments. Text interfaces remained useful for installers, remote administration, editors, and monitoring. Their persistence was not simply resistance to graphics. A character interface can be economical, script-friendly in some respects, and effective over remote links, provided the user's needs fit the model.

15.5 A pseudoterminal preserves the old agreement

A graphical terminal emulator displays a character-oriented session inside a modern desktop. On the host side, a pseudoterminal supplies the terminal interface expected by programs. One end belongs to the application-facing terminal subsystem; the other

can be driven by an emulator or remote-login service.

This arrangement preserves behavior that a plain pipe does not provide: terminal settings, job control, foreground process groups, and appropriate signal interactions. A program can test whether its output is a terminal and choose color or formatting accordingly. That choice is a convention, not proof that the output is human-readable in every setting.

SSH can connect a remote session to a pseudoterminal while encrypting and authenticating the transport. The bytes sent through the session still include terminal control sequences. Secure transport does not remove the need to interpret those sequences carefully or sanitize untrusted material when the application requires it.

The emulator also has its own policies: font selection, scrollback, clipboard interaction, colors, key mappings, and supported extensions. A terminal application and its emulator therefore negotiate a living protocol, even though the visual result resembles an old text screen. The apparent timelessness conceals decades of implementation change.

15.6 Characters are not display cells

ASCII made some early assumptions unusually convenient: many ordinary printable characters occupied one byte and one cell. International text breaks the equivalence. An encoding can use several bytes for a code point; a displayed grapheme can contain several code points; a glyph can occupy zero, one, or more terminal cells under the terminal's width rules.

Combining marks, East Asian width, bidirectional scripts, and emoji sequences complicate cursor placement and selection. A

program that cuts a byte string at an arbitrary offset can split an encoded character. A program that counts code points can still misjudge visual width. Terminal libraries and emulators must agree closely enough for the display to remain coherent, and agreement is not universal for every sequence.

Accessibility presents another challenge. A text interface is not automatically accessible merely because it uses characters. Repeated screen repainting can obscure meaning for assistive technology. Color-only distinctions and position-dependent status can hide information. A line-oriented mode or a clear textual summary may be more usable than an elaborate full-screen dashboard.

These issues do not make terminal applications obsolete. They show that an interface optimized for expert local use needs additional design when its audience and writing systems expand. The same pattern appears later in graphical desktops and phones.

15.7 The terminal's enduring place

The terminal preserves a compact boundary between a program and a wide range of display environments. A shell running remotely can remain useful without knowing the local GPU, monitor resolution, or desktop toolkit. That separation is extraordinarily valuable for administration and software development.

Its limits are equally real. Precise typography, rich accessibility semantics, fluid images, touch input, and complex spatial interaction do not fit naturally into a character-cell protocol. Extensions can address some needs, but each extension adds negotiation and compatibility work. The terminal is a successful specialized interface, not a universal endpoint for all human interaction.

Bitmap displays made it possible to redraw the interface boundary

itself. Instead of asking which escape sequence moves a cursor, a system could manage arbitrary pixels, windows, input devices, and independent graphical clients. Unix's existing separation of processes and networks would shape how that next environment was built.

Chapter 16

Pixels, Networks, and the X Window System

16.1 A bitmap changes what a screen can mean

A character terminal begins with a grid whose cells have predefined roles. A bitmap display begins with addressable picture elements. Text becomes one kind of image among many. Windows can overlap, proportional fonts can appear beside diagrams, and a pointer can select objects that are not conveniently described by a line number.

Experiments at Bell Labs, including the Blit terminal associated with Rob Pike and colleagues, explored programmable bitmap terminals and layers of interaction. Computation could be divided between host and terminal in ways that did not fit the old picture of a passive display. A terminal could become a small computing environment in its own right.

These experiments should not be turned into a single chain in which curses necessarily evolved into Blit and then into X. Different groups pursued related problems with different hardware and assumptions. The relationship is a change in the available design space, not always a direct code lineage (Kernighan 2020; Raymond 2004).

16.2 Why the display is the server

X emerged at MIT in the 1980s, with Bob Scheifler and Jim Gettys among its central figures. It offered a network-capable protocol between graphical applications and a display service. The application is the X client; the component managing the display and input is the X server. This terminology follows the service being provided, not the physical size or location of the machine.

An application running on a distant host can connect to a server on the user's workstation. The user sees a local window while the application executes elsewhere. This fits the workstation era's mixture of personal interaction and shared computation. It also explains why the server is not necessarily the large remote machine in everyday language.

X11, introduced in 1987, established a protocol whose longevity became remarkable. Implementations and extensions changed, but the protocol boundary allowed a huge body of clients and tools to accumulate. A stable protocol can preserve investments across hardware generations in much the same way that a stable file interface can preserve applications.

Network transparency was valuable, but it did not make distance free. Round trips add latency. A program that repeatedly asks the server for information and waits before issuing the next re-

quest can perform poorly over a long link. A protocol permitting remote execution does not guarantee that every application uses it efficiently.

16.3 The server does not choose the entire desktop

X provides mechanisms for windows, events, drawing, and related resources. A window manager can decide placement, decoration, stacking, and focus policy. Toolkits provide widgets and application conventions. Desktop environments assemble still more services, including file management, settings, session behavior, and integration among applications.

This division creates flexibility. A user can change the window manager without replacing every client. A toolkit can offer a new visual style without requiring the server to implement every button’s behavior. Different institutions can choose interaction policies suited to their users and hardware.

It also creates integration costs. Selection and clipboard conventions, keyboard focus, drag and drop, fonts, settings, and session management need agreements across components that were designed independently. A protocol that permits many policies does not supply a shared policy by itself. Users can experience that absence as inconsistency (Raymond 2004, discussion of X and mechanism versus policy).

Desktop projects such as KDE and GNOME addressed some of these needs by building more coherent environments on top of the display system. Their importance extends beyond visual decoration. Common libraries, accessibility interfaces, settings mechanisms, and application conventions make the platform easier to

use and develop for.

16.4 Rendering moves away from the original model

Early X offered drawing requests suited to the hardware and applications of its time. Later graphics workloads demanded accelerated 3D rendering, complex compositing, modern font rasterization, and efficient image transfer. Asking the server to perform every rendering operation through the original protocol was no longer the best path.

Direct-rendering infrastructure let applications use graphics hardware through controlled interfaces while the display system retained coordination responsibilities. OpenGL and later APIs supplied rendering models very different from drawing a rectangle through core X requests. Mesa became a major collection of open graphics implementations and userspace drivers on Linux and other systems.

The resulting stack contains several distinct roles. A kernel driver manages hardware access and resources. A userspace driver translates rendering operations into device commands. Libraries expose APIs to applications. A display server and compositor coordinate visible surfaces. The same vendor name can appear in several layers, but those layers are not interchangeable.

This is why a report that “X renders everything” can be misleading for a modern desktop. Many applications already render their own content using local libraries and acceleration, then arrange for the result to be displayed. The protocol’s historical identity and the actual route of a frame can differ substantially.

16.5 Compositing adds another view of the screen

A compositing window manager can combine off-screen window contents into a final image. This enables effects such as shadows, translucency, transforms, and smoother transitions. It also provides a place to manage presentation timing and the relationship between application updates and the display's refresh.

The extra stage can be useful, but it raises questions about copying, latency, and synchronization. A buffer must not be displayed before rendering finishes, and an application must not overwrite storage still being used for presentation. Graphics correctness includes ownership and timing agreements as much as pixel calculations.

Full-screen applications can sometimes avoid unnecessary composition through direct-scanout or related paths, subject to hardware and policy. There is no universal rule that compositing always adds the same amount of latency or that bypassing it is always possible. The implementation must consider format, scaling, overlays, multiple monitors, and other clients.

The growing complexity motivated a reconsideration of where the display boundary should sit. If clients render their own content and a compositor already decides what reaches the screen, why retain all the historical coordination paths between client, X server, window manager, and compositor? Wayland would make that question central.

16.6 Trust in a shared display connection

The traditional X model assumes considerable trust among clients connected to a server. Depending on extensions and controls, clients can obtain information or influence input in ways inappropriate for mutually hostile applications. A desktop running every application under one user's broad authority inherits that assumption.

Authentication to the server is therefore critical. Opening access broadly to solve a connection problem can grant far more power than the user intended. Remote forwarding through SSH protects a transport and can apply trust distinctions, but it does not turn the whole application environment into a capability system automatically.

This security model is historically understandable. A workstation user's programs were often treated as collaborators in one personal environment. Modern desktops install applications from many sources, process hostile web content, and offer sandboxing. A display protocol that assumes all clients are equally trusted can undermine those boundaries.

The criticism is not that X developers failed to predict every later threat. It is that a once-useful trust model became an architectural constraint. Long-lived interfaces preserve assumptions along with features. Replacing those assumptions requires migration work that can be as hard as designing the new protocol.

16.7 What X accomplished

X gave Unix a broadly shared graphical substrate across vendors and architectures. It supported local and remote applications, a

wide variety of window managers, and decades of software. That achievement is not cancelled by the difficulty of adapting it to new rendering and security models.

The complaints in the supplied *UNIX-HATERS Handbook* remain useful as evidence of costs users felt while the system was still relatively young. They should be read beside, rather than in place of, an account of what the architecture enabled (Garfinkel, Weise, and Strassmann 1994, ch. 7). A history that records only triumph or only irritation misses the reason such systems both succeed and become candidates for replacement.

Wayland did not arise because Unix suddenly discovered graphics. It arose after decades of graphical practice had shifted rendering, compositing, hardware access, and application trust. Understanding X's success makes the reasons for that shift more precise.

Chapter 17

Wayland and the Ownership of a Frame

17.1 A different protocol boundary

Wayland, begun by Kristian Høgsberg in 2008, defines communication between clients and a compositor. The project's own overview emphasizes input handling and buffer management. Clients render their content; the compositor receives buffers, arranges surfaces, routes input, and controls presentation. Wayland is a protocol and supporting libraries, not one mandatory desktop implementation (Wayland contributors 2026).

That last distinction matters in practical discussion. GNOME's Mutter, KDE's KWin, and compositors built with libraries such as wlroots can implement Wayland while differing in policy, extensions, integration, and behavior. A problem observed on one compositor is not automatically a property of every Wayland environment.

The compositor can run on the hardware, inside another window

system, or as a client of another compositor. The protocol does not require that every compositor directly owns a physical monitor. This flexibility also makes testing and nested sessions possible without redefining the basic client relationship.

The new boundary reflects work already done by modern clients and compositors. It removes the need to treat historical server-side drawing operations as the center of the architecture. It does not remove the underlying difficulty of graphics hardware, input devices, or desktop integration.

17.2 Follow a frame from application to display

An application decides that part of its content has changed. Its toolkit and rendering libraries produce pixels in a buffer. The client associates that content with a surface and commits an update through the Wayland protocol. The compositor then considers the surface alongside other surfaces and the current output configuration.

If composition is needed, the compositor combines content into an output image, often using the GPU. If conditions permit, it may present a client buffer more directly. Kernel modesetting facilities control display configuration and presentation at the hardware boundary. The exact path depends on drivers, formats, scaling, monitors, and policy.

The frame therefore passes through several agreements:

Participant	Principal responsibility
Client and toolkit	Content, layout, rendering, application interaction
Compositor	Surface arrangement, input routing, presentation policy
Userspace driver	Rendering API implementation and device commands
Kernel graphics driver	Hardware resource management and display control
Display hardware	Scanout and physical output

This is a responsibility map, not a claim that each row is a separate process or that every frame takes an identical route. The map prevents one common confusion: a rendering API, display protocol, and graphics driver solve related but different problems.

17.3 A buffer is more than a pointer

A software-rendered client can use shared memory for pixel storage. Accelerated rendering commonly uses mechanisms that let participants refer to graphics buffers without copying every pixel through the protocol connection. Linux dma-buf is important in sharing such resources across components.

Sharing requires agreement on dimensions, pixel format, layout modifiers, and access. A buffer whose bytes are meaningful to one driver may not be usable by another participant without a compatible import path. A handle transfers a reference to storage; it does not automatically transfer a complete understanding of its representation.

Timing is equally important. Rendering may still be in progress when the client submits the buffer. The compositor must know when it is safe to read, and the client must know when storage can be reused. Implicit and explicit synchronization provide different ways to express these dependencies. Support varies with the complete driver and compositor stack, not merely with the name of the protocol.

This is the graphics version of the lifetime problems already encountered in files and processes. Reusing a buffer too early can corrupt a frame; retaining it forever leaks resources. A smooth desktop depends on these agreements being maintained many times per second.

17.4 Security changes useful habits

Wayland's core model does not grant an ordinary client a general right to inspect every other surface or capture every keystroke. Input is routed by the compositor, and access to wider desktop information requires additional mechanisms and policy. This supports stronger separation among applications than the traditional shared-trust X model.

The change affects legitimate software as well as attackers. Screen capture, remote control, global shortcuts, automation, input methods, and accessibility tools need carefully designed interfaces. A feature that once worked by observing the whole display cannot simply reuse that route when the route is deliberately absent.

Desktop portals and services such as PipeWire provide important pieces of modern Linux capture and sharing workflows. A portal can mediate a request and obtain user consent; a media service can carry selected streams. The details depend on desktop and portal

implementation. Saying “Wayland supports screen sharing” is less informative than naming the complete path and the versions that supply it.

Security is therefore an integration project, not only a restriction. If an architecture removes a broad authority, it needs usable replacements for legitimate tasks. Otherwise users and developers will seek workarounds that restore the old authority through less visible channels.

17.5 Extensions carry the rest of the desktop

A minimal core protocol cannot describe every need of a complete desktop. Extensions cover matters such as toplevel window roles, decorations, output information, presentation timing, and other specialized behavior. Some protocols are widely standardized; others are experimental or tied to particular compositor communities.

This creates a familiar balance. Keeping the core small makes it easier to understand and preserve. Leaving too much outside a common agreement can produce inconsistent capabilities across environments. Protocol development consequently requires coordination among toolkits, compositors, application authors, and sometimes driver developers.

Fractional scaling illustrates the issue. A logical application coordinate and a physical output pixel need not have a one-to-one relationship. Applications, toolkits, and compositors must agree on buffer scale, resampling, and appropriate sizes. Mixed-density monitors make the problem more demanding. A feature cannot be reduced to a single checkbox in the core protocol.

Color management, high-dynamic-range presentation, and variable refresh introduce further contracts. Their development changes rapidly, so this book avoids a blanket claim that every Wayland desktop offers the same capabilities. The stable historical point is that presentation policy has moved toward a compositor-centered architecture while detailed agreements continue to evolve.

17.6 Xwayland makes migration incremental

A display transition cannot require every application to be rewritten at once. Xwayland runs an X server as a Wayland client, allowing many existing X applications to appear within a Wayland session. It preserves the older application protocol while adapting presentation to the newer environment.

Compatibility has limits. An application relying on global X behavior may not receive equivalent authority over the whole Wayland desktop. Input, scaling, capture, and window-management details can differ. The compatibility layer is a bridge between contracts with different assumptions, not a promise that those assumptions have become identical.

The arrangement resembles other successful transitions in Unix history. A stable interface protects existing software while a lower layer changes. The bridge lets institutions migrate in stages, but it also adds a component whose bugs and performance must be understood. Compatibility reduces the cost of change without making change costless.

17.7 A new display system, the same engineering questions

Wayland is often discussed as a contest between desktop preferences. The more useful technical questions concern ownership and authority. Who renders? Who may inspect a surface? Who routes a key? Who owns a buffer at a given instant? Which component can prove the GPU has finished writing it?

Those questions connect the graphics stack to the rest of the book. A buffer needs a lifetime, a protocol needs versioning, an extension needs adoption, and a security boundary needs a practical user experience. The replacement of one display protocol is therefore both a technical and an institutional history.

Unix graphics has moved from printing characters to composing GPU-rendered surfaces without reaching a final arrangement. Each stage made a different set of assumptions economical. The enduring work is to identify those assumptions clearly enough that the next stage can change them.

Part IV

Unix Beyond the Workstation

Chapter 18

Unix as Infrastructure

18.1 The user may never see the machine

A person browsing a website may depend on Unix-like systems without interacting with a terminal, desktop, or recognizable operating-system interface. Servers perform computation behind a network protocol. The user's experience is shaped by latency, availability, and correctness, while the operating system recedes into an infrastructure layer.

This is not a complete break with the original system. Time-sharing also mediated access to shared resources. The difference is scale, distance, automation, and the division of responsibility. A server may be operated by one organization, hosted by another, built from hundreds of projects, and used by people who cannot inspect its configuration or choose when it is upgraded.

Unix's process model, networking, toolchain, and scriptable environment made it well suited to this setting. Free software made extensive adaptation and redistribution possible. Commodity hardware improved the economics. None of these advantages

eliminates the work of keeping a service dependable.

18.2 Booting is the beginning of a dependency graph

After firmware and a bootloader arrange initial execution, the kernel initializes essential facilities and starts user-space work. The first user-space process in the traditional model has special responsibilities for the rest of the environment. Historical init arrangements and scripts established services in a largely sequential style, with system-specific conventions.

Modern service managers can express dependencies, monitor processes, restart failed services, collect logs, and coordinate sockets and other resources. Systemd is a prominent Linux example; other systems and communities use different supervisors. It is not a universal component of Unix, nor is its presence a definition of Linux.

Supervision addresses a real gap between launching a process and maintaining a service. A process may start successfully but fail to become ready. A service may need a network mount, credentials, or a local database before it can do useful work. Restarting it blindly can amplify a failure or destroy diagnostic evidence.

Dependencies also contain cycles and ambiguous readiness conditions. “The network is up” can mean a configured interface, a route, successful name resolution, or access to a particular service. A useful service contract states the condition it actually needs. Administration becomes more reliable when vague global milestones are replaced with specific observable requirements.

18.3 Permissions are a beginning, not a complete sandbox

Traditional Unix permissions attach owner, group, and other access rules to filesystem objects. Credentials determine which class applies. The superuser model historically provided broad administrative authority. These mechanisms support multiuser isolation, but they are not a complete answer to mutually hostile applications sharing one user's account.

An ordinary desktop application may be able to read many of that user's files, connect to local services, and access inherited credentials. If it is compromised, the damage can extend well beyond its intended task. The principle of least privilege asks that a component receive only the authority it actually needs.

Privilege separation can divide a service into a small component that performs restricted privileged operations and larger components running with less authority. Linux capabilities split some traditional root powers; mandatory-access-control systems such as SELinux and AppArmor impose additional policies; seccomp can restrict system-call behavior. Each mechanism has a defined scope and can be undermined by mistakes in the surrounding configuration.

Chroot changes a process's apparent filesystem root, but it is not by itself a complete isolation boundary. Filesystem views are only one part of a process's authority. Open descriptors, credentials, kernel attack surface, and other interfaces remain relevant. A historical convenience must not be promoted into a security guarantee it was not designed to make.

18.4 Names and resources are different problems

Linux namespaces can give processes different views of selected system resources: process identifiers, mounts, networking, and other domains. A process inside a container can see a filesystem layout and PID space that differ from the host's ordinary view. The kernel is still shared.

Control groups organize processes for resource control and accounting. They can constrain or weight use of CPU, memory, I/O, and other resources, depending on controllers and configuration. A namespace can hide a name; a cgroup can constrain consumption. Confusing these functions makes it hard to explain why a container can look isolated while still exhausting a shared resource.

The cgroup v2 documentation describes a unified hierarchy and explicit rules for controller behavior and delegation. It is a reminder that a resource-control interface is itself a substantial system, with constraints that administrators and runtimes must respect (Heo and Linux kernel contributors 2026). A value written to a control file is meaningful only within that model.

Containers assemble these and other mechanisms with filesystem images, credentials, security policy, and runtime setup. They do not create a second independent kernel. A virtual machine normally adds a guest kernel behind a virtualized hardware boundary. The two approaches can coexist; a cloud deployment may run containers inside virtual machines.

The distinction has practical consequences. A kernel vulnerability can affect containers sharing that kernel. A virtual machine has its own attack surface in the hypervisor and device model. The

right boundary depends on the threat model and operational requirements, not on a universal claim that one packaging format is always safe.

18.5 An image is not the running service

A container image can record a filesystem and execution metadata. It does not necessarily include external data, secrets, network policy, host kernel behavior, or the service's complete deployment configuration. Reproducing an image is therefore not the same as reproducing the service.

Persistent data requires a separate lifecycle. Replacing an application container should not accidentally discard the database, and rolling back an executable may not roll back a schema change. Versioned artifacts help, but applications must define compatibility across transitions. The most expensive failures often occur between versions rather than within a single version.

Orchestrators such as Kubernetes coordinate desired state across many machines. They can place work, restart it, expose services, and manage rollouts. Their control loops add another layer of asynchronous behavior. The fact that a configuration has been accepted does not mean every machine has already reached the requested state.

This resembles the old distinction between runnable and running. A declaration of intent and an observed condition are different facts. Good operators measure the latter, while keeping enough history to understand why the control system has not achieved the former.

18.6 Configuration is a program with delayed consequences

Shell scripts remain common in infrastructure because they can orchestrate existing tools with little ceremony. Greenberg and colleagues observe that cloud environments have not displaced the shell; they have supplied more places for it to appear (Greenberg, Kallas, and Vasilakis 2021). The danger is treating a script as disposable after it becomes essential.

Configuration languages have their own semantics. Defaults, inheritance, includes, variable expansion, and merge rules can create behavior no individual file states plainly. A system can contain a hidden state machine in the interaction among scripts, service managers, and remote controllers even when no source file calls it one.

Declarative configuration helps when the desired state is well specified and convergence is controlled. It does not guarantee harmless repetition. An operation described as a resource may still trigger irreversible work. A migration, credential rotation, or storage deletion needs its own transition rules and recovery plan.

The Unix tradition offers a useful discipline here: make inputs explicit, check status, keep diagnostic output distinct from machine data, and preserve observable intermediate state. These practices are valuable whether the final controller is a shell script or a large service.

18.7 Reliability is a maintenance relationship

A reliable service needs monitoring, logs, updates, tested restoration, and people who understand its failure modes. A backup that has never been restored is evidence that data was copied, not proof that service can be recovered. A health check that merely confirms a process exists can miss a service unable to answer useful requests.

Metrics, logs, and traces provide different evidence. A metric can reveal a rising error rate; a log can explain an individual failure; a trace can connect work across services. None should require exposing secrets or collecting irrelevant personal data to be useful. Observability is the design of evidence, not an invitation to record everything indiscriminately.

Updates have a similar dual role. They repair defects while introducing change. Long-term maintenance may preserve an interface while backporting security fixes. A version string alone may not tell whether a known defect is present. Operators need the distributor's actual patch and support information.

The supplied random-input reliability study remains relevant as a method, not as a current statistic. Frequently used components can contain unexplored failure paths. Fuzzing, fault injection, and recovery exercises supply evidence ordinary successful operation cannot provide (Miller, Fredriksen, and So 1990).

18.8 Infrastructure preserves the old questions at new scale

The server and cloud eras did not abolish Unix's fundamental concerns. Processes still need lifetimes, names still need interpretation, communication still has partial failures, and persistent state still needs crash semantics. Automation multiplies the speed and reach of both good decisions and mistakes.

The major change is that the person affected by a failure may be far from the person who can diagnose it. Clear contracts and useful evidence become more valuable as that distance grows. The system's success is measured less by how elegantly it can be configured than by how predictably it serves people who never see the configuration.

Chapter 19

Games on a System Built for Other Work

19.1 The desktop needs applications people want

An operating system can have excellent process isolation and networking while remaining unattractive to someone whose important application does not run. Games make this truth unusually visible. Their requirements span graphics, sound, input, timing, content delivery, copy protection, and social services. A missing piece can prevent play even when the kernel and compiler work perfectly.

Unix had games from its earliest years, including the activities around the PDP-7. Later Unix and Linux systems supported many native games and ports. That continuity should not be confused with broad compatibility with the commercial Windows game market. The latter required a much larger body of APIs, middleware, drivers, and tested behavior.

Linux gaming therefore provides a useful test of the book's central argument. A shared interface can make independently developed software usable in a new environment, but the interface includes far more than function names. Timing, undocumented assumptions, packaging, and failure behavior can all become part of what compatibility must reproduce.

19.2 Native ports still need an ecosystem

A native port adapts a game's code and dependencies to the target platform. Libraries such as SDL can abstract input, windows, and other services. Cross-platform engines can reduce the work further. Yet an engine's support does not guarantee that every plugin, codec, launcher, or online service used by a particular game also supports the platform.

Developers must test different graphics drivers, audio configurations, window systems, controllers, and library environments. Distributing a binary raises questions about compatible runtime libraries and supported distributions. A game that works on the developer's machine may fail on a user's installation with a different loader or dependency.

Runtime containers and bundled libraries can reduce variation, but they must cooperate with host components such as graphics drivers. A program cannot always bundle its way out of the hardware boundary. The installation environment and the machine's active driver stack still form part of the effective platform.

The economics matter as well. A publisher compares expected audience, support burden, testing cost, and opportunity cost. Technical feasibility alone does not guarantee a port. A platform can consequently face a cycle: fewer games reduce adoption, while a

smaller audience reduces incentives to support it.

19.3 Wine implements a different application contract

Wine provides a compatibility implementation for Windows applications on Unix-like systems. It does not normally boot a full Windows guest operating system for each application. It implements and translates the interfaces applications expect, coordinating with the host's processes, files, windowing, and other facilities.

That description needs a qualification. Running code for one processor architecture on a different architecture can require additional translation or emulation mechanisms. The claim that Wine is not a conventional whole-machine emulator does not mean instruction-set differences vanish. The application API and CPU execution model are separate layers.

Compatibility work includes observable behavior that a clean specification may not capture. An application can depend on an undocumented return value, a particular synchronization pattern, or a bug in a widely deployed implementation. Reproducing that behavior can be necessary even when a more elegant design would avoid it.

This makes compatibility engineering both empirical and historical. Developers compare behavior, isolate regressions, and add targeted fixes. The result can look inelegant locally while serving a coherent goal: preserve an existing application's assumptions without requiring its author to rewrite it.

19.4 Proton assembles a gaming path

Valve introduced Proton as part of its Steam Play work in 2018. The official project overview describes it as a tool for running Windows-exclusive games on Linux using Wine. Proton integrates and coordinates additional components and fixes for the gaming environment; it is not simply a new name for the Linux kernel or for all of Wine (Valve and Proton contributors 2026).

DXVK translates major Direct3D 9, 10, and 11 interfaces toward Vulkan; vkd3d-proton addresses Direct3D 12. These components are important because modern games often express graphics work through Direct3D rather than a native Linux API. Their translation path relies on capable Vulkan drivers and appropriate hardware features.

Vulkan supplies a lower-level explicit graphics and compute API. It does not automatically make translation perfect or costless. Resource binding, synchronization, shader compilation, and feature support must be mapped carefully. A game can be CPU-limited, GPU-limited, or affected by synchronization overhead in ways that make simple performance comparisons misleading.

Proton versions can change a game's behavior, and individual titles can need specific fixes. The official README exposes configuration and logging facilities, which themselves evolve. This book therefore explains the architecture rather than promising that a particular title works under every release. Compatibility is a tested relationship among a game, a runtime, drivers, and hardware.

19.5 A frame is a deadline, not just an image

A game must present useful frames at an acceptable cadence. Average frame rate alone can hide stutter. A brief stall during shader compilation or asset loading may be more noticeable than a modest reduction in steady throughput. Frame pacing asks how evenly the work arrives at the display.

The pipeline crosses many boundaries: input sampling, simulation, command generation, driver processing, GPU execution, compositor policy, and display scanout. Queueing can improve throughput while increasing latency. Reducing a queue can improve responsiveness while making missed deadlines more visible. The best configuration depends on hardware, refresh behavior, and the application's goals.

Shader caches and precompilation can reduce repeated work, but cached results depend on relevant versions and device properties. A driver update can invalidate assumptions. A downloaded cache is not a universal substitute for every shader a game might generate dynamically. The practical success of gaming requires maintenance of these details, not merely a functioning translation layer.

Audio and input have similar timing concerns. A controller must be identified and mapped sensibly; focus changes and device reconnection must behave predictably; suspend and resume must preserve a coherent session. These are integration qualities that ordinary kernel benchmarks rarely measure.

19.6 Anti-cheat and protected services define another boundary

Some multiplayer games depend on anti-cheat systems and other protected services. A compatibility layer may implement the game's ordinary APIs while failing the service's requirements or authorization policy. Some systems offer Linux or Proton support under particular conditions; others depend on Windows-specific kernel mechanisms or publisher choices.

The obstacle is therefore not always a missing graphics function. A server can refuse a client environment even when the game would otherwise run. A publisher may need to enable a supported mode, validate it, and accept its security tradeoffs. A universal statement that anti-cheat "works" or "does not work" on Linux conceals these distinctions.

This is another lesson about interfaces and institutions. Compatibility includes permission to participate in a service. Implementing a local behavior cannot compel a remote operator to accept it. The effective platform boundary is partly technical and partly organizational.

19.7 The Steam Deck turns integration into a product

The Steam Deck, released in 2022, made Linux gaming visible as a coherent consumer device rather than solely a configurable desktop arrangement. Its SteamOS environment combines a Linux base, graphics drivers, compatibility tools, a controller-oriented interface, power management, and a selected hardware platform.

The fixed hardware target reduces some variation without removing the need for testing. A useful handheld experience requires readable text, appropriate control prompts, workable launchers, acceptable performance, and sensible suspend behavior. A game can render correctly yet remain awkward on a small screen or require an unsupported input path.

The product illustrates how much value comes from curation and defaults. The underlying components retain their separate identities, but users benefit from an organization testing the combination. This is related to distribution engineering and to the classic workstation vendor's integration role, even though the market and licensing structure are different.

Linux gaming's recent history thus returns to an old Unix problem: how can independently developed parts form an environment people can actually use? The answer includes stable interfaces, translation, measurement, and extensive integration work. The same answer helps explain how a Unix-like kernel reached an even larger audience through phones.

Chapter 20

Android and the Many Meanings of Unix

20.1 The phone does not need to look like its kernel

Android's first commercial phones appeared in 2008. A user encountered applications, touch interaction, a lifecycle managed by the platform, and services designed around a mobile device. Underneath, the Linux kernel supplied process isolation, memory management, scheduling, networking, drivers, and other essential mechanisms. The application experience did not have to resemble a Linux workstation to benefit from that machinery.

This distinction is the reason the title ends with Android. The continuity is substantial, but it is not the survival of an unchanged user interface. A phone owner may never see a shell or a pathname. The abstractions that made Unix useful to programmers can operate behind interfaces designed for entirely different habits and constraints.

Mobile devices also change the operating environment. Energy, thermal limits, radios, cameras, sensors, and intermittent connectivity are central concerns. A background computation can reduce battery life or interfere with an immediate interaction. An application may need to stop and restart under platform control rather than assume it owns an uninterrupted session.

The kernel is therefore a foundation, not a complete explanation of the product. Understanding Android requires following the layers above it and the institutions that decide how those layers are assembled.

20.2 Bionic marks a different userspace

Conventional GNU/Linux distributions commonly use the GNU C library and many GNU utilities. Android uses Bionic as its C library, math library, and dynamic-linker implementation. The official maintainer overview identifies these components explicitly and describes the loader's role in starting ELF programs (Android Open Source Project 2026).

The choice affects binary compatibility. A native executable built for one Linux userspace may expect a different dynamic loader, library ABI, filesystem layout, or set of interfaces. Sharing a kernel family does not make that executable automatically usable on Android. The kernel system-call boundary is only one part of the environment an application expects.

Bionic also shows why "Linux" and "GNU/Linux" cannot always be treated as interchangeable labels. GNU's contributions are foundational to many Linux systems, but Android's system composition differs. The most informative description names the actual kernel, libraries, runtime, and application model rather than

forcing every product into one familiar desktop category.

A shell and command tools can exist on Android devices, especially for development and debugging, without defining the ordinary application experience. The presence of a command interpreter is not evidence that a phone offers the same permissions, packages, or workflow as a desktop distribution. Context determines what the familiar tools can do.

20.3 The runtime and framework define application life

Early Android used the Dalvik runtime; later releases adopted ART. The platform's Java and Kotlin application ecosystem operates through framework services and a managed runtime, with native code available through the NDK and other system components. This is a different contract from launching an arbitrary desktop ELF executable in a login session.

Applications are made of components whose lifetimes are managed by the system. A visible activity, background work, and a service have different expectations and restrictions. The platform can reclaim a process, change an application's execution opportunities, or recreate user interface state. Exact rules evolve with Android releases and target SDK levels.

This model reflects resource and user-experience goals. A phone should remain responsive and conserve energy even when many applications have been installed. It cannot assume every application will voluntarily stop work at the ideal moment. Policy is enforced through framework rules as well as kernel mechanisms.

The lifecycle creates application-design obligations. Important

state cannot live only in a transient screen object. Work must distinguish what can be repeated, what must survive restart, and what should be cancelled when the user leaves. These are variations of the same lifetime and failure questions already seen in servers and kernels.

20.4 Binder supplies a service vocabulary

Android uses Binder for important communication among processes and system services. Its object-oriented transaction model provides a way to invoke operations across process boundaries, transfer references and certain resources, and associate requests with caller identity. Generated interfaces can make an interaction resemble a local method call, but the boundary remains real.

A remote operation can block, fail because a process dies, or trigger reentrant work. Arguments need serialization and validation. The service must check whether the caller is authorized to perform the requested action. A convenient stub does not turn a remote transaction into an ordinary in-process function call.

Binder's prominence is instructive because it departs from the simplest "everything is a byte stream" caricature of Unix. Android keeps Unix-like processes and descriptors while using a richer IPC mechanism suited to a service framework. The system did not have to choose between retaining every historical interface and abandoning the kernel tradition entirely.

The broader platform also includes facilities such as Zygote for process startup and shared runtime initialization. These mechanisms exploit process and memory behavior for a workload very different from the original shell launching a small command. A stable set of primitive abstractions can support specialized higher-level

launch policies.

20.5 The user account becomes an application boundary

Traditional multiuser Unix often assumed that programs belonging to one user were mutually trusted. Android ordinarily assigns applications separate Linux identities and storage boundaries, with exceptions and shared relationships governed by platform rules. The identity mechanism is reused to separate applications rather than only human login accounts.

Permissions and framework checks then mediate access to sensitive capabilities. Modern Android also uses SELinux policy, seccomp and other hardening, and restrictions on background execution and storage. The details vary by version and device, but the architectural trend is clear: a phone's installed applications are not assumed to deserve the same broad ambient authority.

A permission prompt is not the whole security model. An application can delegate access, receive a resource through another component, or interact with a privileged service that validates a request. Correctness depends on the entire path of authority. A service that forgets to validate its caller can bypass the intended boundary even when the application sandbox itself is functioning.

Updates are part of the model too. Kernel, vendor drivers, firmware, framework components, and applications may have different maintenance paths. A device's security depends on which components can be updated, for how long, and by whom. Public source for one layer does not guarantee that every deployed device receives timely fixes.

20.6 Graphics returns to composition

Android applications render into surfaces that are coordinated by the system's graphics stack. SurfaceFlinger and hardware-composer integration help assemble what appears on the display. GPU APIs and device drivers perform work beneath application toolkits. This is a compositor-centered environment, but it is not simply a Wayland desktop placed on a phone.

The similarity lies in the engineering problems: buffer ownership, synchronization, composition, scaling, presentation deadlines, and hardware capabilities. The protocols and framework arrangements differ. A family resemblance should not be mistaken for interchangeability.

Touch input also changes policy. Focus, gesture interpretation, orientation, software keyboards, and application transitions require coordination across layers. A desktop window-manager convention cannot be imported unchanged and expected to feel natural. The user interface embodies the physical form of the device.

Energy makes the frame pipeline a resource policy as well as a visual one. Rendering unnecessary frames consumes power and generates heat. The platform must coordinate application demand with refresh behavior, hardware acceleration, and background limits. Smooth interaction is an agreement about timing across a whole system.

20.7 An open project and a commercial product are different objects

The Android Open Source Project supplies a large body of platform source. Commercial devices can combine it with proprietary

applications, services, drivers, firmware, branding, and distribution arrangements. AOSP and a particular retail phone are therefore not identical artifacts.

The Linux kernel's GPL obligations and the licenses of userspace components apply to their respective covered material. They do not make every application and remote service on a phone open source automatically. A complete account must name which component and which permission is being discussed.

Control over modification is also practical. A device may have published source yet restrict bootloader unlocking, require signed firmware, or depend on unavailable hardware support. A technically skilled owner may be able to install another system on some models and not others. The general availability of Android source does not settle every device's future.

This tension reaches back to the beginning of the book. Source access, permission to redistribute, ability to replace a component, and support for a working product have always been separate questions. Modern devices combine them in new ways rather than making the distinction obsolete.

20.8 BSD and Darwin continue alongside Linux

The contemporary Unix landscape remains plural. FreeBSD integrates a base system with a strong operating-system identity; NetBSD has emphasized portability; OpenBSD is associated with security, code review, and related engineering priorities. These descriptions are emphases, not exhaustive feature lists or guarantees that every component of a project has one property.

Apple's Darwin foundation follows another path. XNU combines Mach-derived facilities with BSD components and other subsystems, including its driver framework. The shipping macOS experience adds substantial frameworks, graphics, applications, and product policy above that foundation. Calling macOS "just BSD" or "just Mach" misses the integrated architecture.

The supplied 1986 Mach paper describes an early stage with tasks, threads, ports, and virtual-memory innovations alongside Unix compatibility. It should not be used as a literal blueprint for every later Mach-derived system. In particular, the fact that Mach research explored moving services into separate servers does not imply that XNU is a pure user-space-server microkernel (Accetta et al. 1986).

These systems can share tools and standards while preserving distinct implementation and licensing histories. A shell script may work across several of them; a binary or kernel module may not. The book's recurring distinction among API, ABI, ancestry, and certification is most useful here, where familiar names invite overgeneralization.

20.9 From a typesetter to an unseen operating system

The C/A/T made Unix useful by turning editable source into a printed artifact people wanted. Android makes a Unix-like kernel useful behind an interface people do not experience as Unix at all. The endpoints differ in hardware, audience, scale, and policy, yet both show the importance of an environment that can be adapted around a concrete task.

What persisted was not a fixed list of commands or a promise that

every service would become a file. It was a collection of productive boundaries: processes with identities, named persistent objects, explicit communication, replaceable tools, and implementations that could travel across machines. Some boundaries had to be strengthened; others were replaced when their assumptions no longer fit.

The history also shows that interfaces do not maintain themselves. People write drivers, review patches, document behavior, resolve licensing questions, test combinations, and keep old applications alive through transitions. Their work is easiest to overlook when the result feels ordinary. A phone that wakes promptly or a game that launches correctly can conceal decades of such labor.

Unix's future cannot be read from its first edition. New languages, hardware, security requirements, and forms of interaction will continue to change what counts as a useful system. Its history offers something more durable than a prediction: a way to examine which agreements make a system understandable, which make it adaptable, and which have become obstacles to the people it serves.

Appendix A

A Chronology with Boundaries

Dates identify particular events, not the moment an entire community changed direction. A publication can follow an implementation; a release can take years to become common. This chronology separates those kinds of milestones. The early history follows Ritchie and Kernighan; the BSD and free software sequence also uses Salus. Later entries supply context for the modern chapters (Ritchie 1984; Kernighan 2020; Salus n.d.).

1969 Bell Labs withdraws from Multics. Thompson begins the work on the PDP-7 that becomes Unix. This precedes the first published manual.

1971 Unix is operating on the PDP-11. Patent-document work provides an early practical constituency. The First Edition manual appears in November; edition numbering originally follows manuals, not a modern release-management scheme.

1973 The kernel is rewritten substantially in C. Pipes become part of the developing environment early in this period. Bell Labs

acquires the Graphic Systems phototypesetter. Ritchie and Thompson present their system publicly at the Symposium on Operating Systems Principles.

1974 The revised time-sharing-system paper appears in *Communications of the ACM*. Its description is a snapshot, not a complete account of every earlier Unix version.

1975 Sixth Edition becomes a widely studied and distributed Unix. It is the system examined by Lions.

1977 Lions's commentary bears this copyright year. Ritchie's retrospective discusses both strengths and deficiencies. These accounts should not be read as documentation for modern Linux.

1978 The early Berkeley distributions establish a continuing practice of collecting and distributing additions. The Bell System Technical Journal publishes an extensive Unix issue.

1979 Seventh Edition is released. Ritchie presents the historical account later reprinted as "The Evolution of the Unix Time-sharing System." Unix/32V and Berkeley's VAX work belong to the transition toward larger address spaces.

1982 Sun Microsystems is founded. Networked technical workstations become a major setting for Unix development and use.

1983 4.2BSD integrates influential filesystem and networking work. Stallman announces GNU. These are separate developments with later intersections.

1984 Bell System divestiture takes effect. The FFS paper is published. GNU work begins. X development starts at MIT.

1985 The Free Software Foundation is established. NeXT is

founded.

1986 The supplied Mach paper describes its then-current Unix compatibility, memory, IPC, and multiprocessor work. Bach publishes *The Design of the UNIX Operating System*.

1987 X11 establishes the long-lived X protocol generation. MINIX provides a separately implemented teaching system.

1988 The Open Software Foundation is formed amid vendor conflict. The first IEEE POSIX.1 standard appears. The Internet worm exposes risks in connected systems and their software.

1991 Linux development becomes public. BSD Networking Release 2 is made available. Neither event means all historical Unix source has become freely redistributable.

1992 Linux adopts GPLv2 terms. USL litigation involving BSD begins.

1993 FreeBSD and NetBSD begin. Distributions such as Slackware and Debian help make Linux-based systems repeatable installations.

1994 The BSD settlement and 4.4BSD-Lite provide a clearer base for independent BSD development. Linux 1.0 is released. The *UNIX-HATERS Handbook* records contemporary criticism.

1995 OpenBSD branches from NetBSD.

1996–1997 KDE and GNOME begin in successive years, contributing to more integrated free software desktop environments.

1998 "Open source" becomes an organized public framing for licenses and collaborative development.

2001 Mac OS X establishes a new shipping Apple platform built

on Darwin and extensive higher-level frameworks. POSIX and the Single UNIX Specification are consolidated in the 2001 standards generation.

2003–2004 Raymond's book is first published in 2003; the supplied printing bears a 2004 copyright date. DragonFly BSD begins as another independent BSD development path in 2003.

2005 Git is developed in the context of Linux kernel collaboration.

2008 Commercial Android phones appear. Wayland development begins. These are different responses to changing device and graphics requirements.

2018 Valve introduces Proton for Steam Play, combining Wine-based compatibility with a gaming-focused integration effort.

2019 The supplied RISC-V xv6 text is dated 27 October. Its section numbers and implementation details are the xv6 baseline in this book.

2021 Greenberg, Kallas, and Vasilakis publish "Unix Shell Programming: The Next 50 Years," arguing that the shell remains worthy of research and improvement.

2022 Steam Deck shipments make a curated Linux gaming environment available as a prominent handheld consumer product.

2026 The editorial cutoff for this manuscript is 6 November. Descriptions of contemporary architecture do not assert a universal compatibility result for every release, device, or game.

A family tree can complement these dates, but its lines need labels. A line may mean copied code, a rewritten compatible interface, institutional succession, or influence. Linux's relationship to Unix

is not the same kind of relationship as a BSD branch's relationship to its parent. A diagram that uses one unlabeled arrow for both relationships can be more memorable than accurate.

Appendix B

Vocabulary and Practical Investigations

B.1 A working vocabulary

ABI An application binary interface: calling conventions, representations, executable and linking expectations, and related agreements needed by compiled programs.

API An application programming interface. Shared API behavior can support source portability without providing binary compatibility.

Buffer Storage whose contents have a temporary role in a transfer or computation. Correctness includes ownership and reuse timing.

Capability An authority-bearing reference or, in Linux's specific usage, one of the powers split from traditional superuser authority. The meanings should be distinguished in context.

Compositor A component that arranges and presents surfaces,

often combining them into an output image. Its other responsibilities depend on the display architecture.

Context switch A transition between execution contexts that preserves enough state to resume suspended work.

Copy-on-write Sharing storage until a modification requires a private copy, with protection and lifetime rules enforcing the illusion.

Descriptor A process-local integer reference to an open kernel object or description. It is not a pathname.

Directory A namespace object associating component names with filesystem objects or identifiers.

Distribution An integrated, maintained assembly of a kernel, libraries, packages, configuration, and release policies.

Driver Code implementing a hardware or device interface. Graphics stacks often contain both kernel and userspace driver components.

End-of-file A result defined by the object being read. For a pipe, an empty buffer becomes EOF when no writers remain.

Exec Replacement of a process's program image. A successful exec is not creation of a new process identity.

Fork Creation of a child process with defined inheritance from its parent. Physical copying strategy is an implementation choice.

Free software Software licensed to preserve specified user freedoms, including studying, modifying, and redistributing it.

Inode A filesystem representation of an object's metadata and

content mapping. A directory name and an inode are different entities.

Interrupt An event that redirects execution under hardware rules, commonly to report a device or timer event.

Kernel The privileged core managing protected access to resources and implementing essential system mechanisms.

Namespace A context in which names are interpreted. Linux namespaces virtualize selected views of system resources.

Open file description Kernel state associated with an opening, including properties such as offset, potentially shared by descriptors.

Page fault An access that cannot complete under current mapping rules; it may invoke a useful allocation policy or report an invalid access.

Pipe A byte-stream communication object with finite buffering and defined endpoint lifetimes.

POSIX A family of specifications for portable operating-system interfaces and associated environments, with versioned scope.

Process An execution environment containing identity, memory, resources, and execution state; distinct from the program it executes.

Pseudoterminal A kernel-provided terminal pair enabling emulators and remote services to supply terminal semantics to applications.

Race Behavior dependent on an ordering not adequately controlled by the program's protocol. Not every race is a language-level data race.

Signal A notification mechanism with defined default actions, handling rules, masking, and pending-state behavior.

Socket A communication endpoint whose operations depend on its address family, type, protocol, and state.

System call A controlled request for kernel service through an architecture-specific entry mechanism.

Terminal emulator A program interpreting terminal protocols and presenting their character-oriented interaction in another environment.

Transaction A unit of work with explicitly defined atomicity and recovery properties. The word alone does not establish those properties.

Virtual memory The mapping and management mechanisms separating program-visible addresses from physical storage and enforcing access rules.

Zombie A terminated process's retained status record awaiting collection, rather than a process still executing instructions.

B.2 Investigate a pipeline without large data

The following shell fragment creates an isolated temporary directory, counts a tiny ASCII dataset, and removes its own files on exit. It assumes a Unix-like environment with `mktemp -d` and a POSIX-style shell. The mktemp invocation is common but should be checked on unusual systems. No administrative privileges are needed.

```
#!/bin/sh
set -eu
scratch_dir=$(mktemp -d)
trap 'rm -rf "$scratch_dir"' EXIT
printf '%s\n' 'red blue red' 'blue green' \
    > "$scratch_dir/words"
LC_ALL=C tr -cs 'a-z' '\n' < "$scratch_dir/words" |
    sort | uniq -c | sort -nr
```

The counts should be two red, two blue, and one green. The order of the tied entries follows the final sort's rules; it is not an additional semantic property of word counting. The sample begins with a letter, avoiding an initial empty token. Its letter-only definition is intentional, not a recommendation for processing arbitrary natural language.

Now run each stage separately and inspect the intermediate stream. Ask where records begin and end, which stage assumes equal values are adjacent, and why the final order differs from alphabetical order. This turns a pipeline from a memorized spell into an inspectable algorithm.

The trap's variable is assigned before use and quoted during cleanup. The shell's error mode still does not establish complete pipeline-error handling for every shell version. For maintained automation, specify the shell and failure policy deliberately rather than generalizing from this small controlled input.

B.3 Observe an unlinked open file

This Python 3 example uses the Unix ability to keep an open file after its name is removed. It creates and removes only its own temporary file. It is intended for Unix-like systems; other operating systems can use different deletion semantics.

```
import os
import tempfile

with tempfile.TemporaryDirectory() as directory:
    path = os.path.join(directory, "example")
    with open(path, "w+b") as stream:
        stream.write(b"still available\n")
        stream.flush()
        os.unlink(path)
        assert not os.path.exists(path)
        stream.seek(0)
        assert stream.read() == b"still available\n"
```

The assertions distinguish namespace state from open-object state. The name is gone, but the descriptor still refers to the object. After the final close, the filesystem can reclaim storage under its normal lifetime rules. This is not a crash-durability experiment and should not be described as one.

B.4 Compare one shared offset with two independent openings

The next example demonstrates an open file description directly. Python’s unbuffered descriptor operations avoid adding a language-level read buffer that could obscure the offset being examined.

```
import os
import tempfile

with tempfile.TemporaryDirectory() as directory:
    path = os.path.join(directory, "letters")
    with open(path, "wb") as stream:
        stream.write(b"abcd")
    first = os.open(path, os.O_RDONLY)
    duplicate = os.dup(first)
    independent = os.open(path, os.O_RDONLY)
    try:
        assert os.read(first, 1) == b"a"
        assert os.read(duplicate, 1) == b"b"
        assert os.read(independent, 1) == b"a"
    finally:
        for descriptor in (first, duplicate, independent):
            os.close(descriptor)
```

The duplicate shares an offset with the first descriptor. The independent opening starts from its own offset. The same underlying bytes participate in both relationships. Fork inheritance can produce a related sharing effect across processes, but duplication lets this investigation isolate the essential distinction without adding scheduling.

B.5 Read a teaching kernel by invariant

With an authorized copy of Sixth Edition source or an xv6 source tree matching the supplied book, select one operation rather than reading random functions. For a pipe read, identify the condition that means data is available, the state that records writers, and the lock or interrupt protocol protecting both.

Write down what must remain true while the reader sleeps. Then trace what the writer changes before it wakes the reader. Ask whether an intervening notification can be lost and which exact operation closes that window. Finally inspect how the last writer’s

close changes the condition for EOF.

For a filesystem operation, make the same exercise about persistence. List every block changed by a file creation, identify the commit point in the supplied xv6 log, and consider a crash before and after it. The exercise should end with a statement of assumptions, especially what a disk write is assumed to preserve.

These investigations are deliberately small. Their purpose is to train distinctions that survive changes of hardware, language, and user interface. A reader who can explain the observations has learned more than the syntax of a particular command.

Appendix C

Sources, Editions, and Historical Method

C.1 What the source collection can establish

The supplied collection is rich but uneven. It includes historical papers, textbooks, manuals, memoirs, OCR transcriptions, translated editions, duplicate files, empty files, and short fragments. Its filenames are useful locators but not reliable bibliographic descriptions. This manuscript uses contents and internal title pages to identify works.

The bibliography's local-file notes provide an audit trail. A companion `SOURCE-GUIDE.md` in the repository maps citation keys to exact files and records limitations. The guide also distinguishes supplementary official project documentation from the local collection. The sources themselves have been left unchanged.

Different kinds of evidence answer different questions. A contem-

poraneous design paper can establish what its authors described at that date. A memoir can explain motivations and social context, while being subject to retrospective selection. A textbook can provide a coherent technical model that is intentionally simpler than every shipping implementation. A source tree can establish what code does only when interpreted with its build, hardware, and version context.

C.2 The historical backbone

Ritchie's "Evolution" is the main account of the early development sequence. It explicitly dates Unix's birth to 1969, distinguishes earlier experiments from the published 1974 description, and gives concrete context for patent work, pipes, and C. The version in the collection identifies an original 1979 presentation and a 1984 journal reprint. The bibliography cites the latter while preserving that distinction (Ritchie 1984).

Ritchie and Thompson's time-sharing-system paper provides the public technical snapshot. It is used for its file and process model and for what the authors said about the system's applications at that moment. Thompson's 1978 implementation paper provides a later architectural account, including a filesystem layout that should not be projected backward onto every earlier edition (Ritchie and Thompson 1974; Thompson 1978).

Kernighan's memoir supplies context about Bell Labs, the C/A/T, tools, commercialization, and descendants. The supplied copy's copyright page says 2020, so the bibliography uses that year rather than silently substituting another edition's date. Salus supplies a complementary history of users, licensing, GNU, BSD, and Linux. The supplied Salus compilation has no securely established publication date, so none has been invented (Kernighan 2020; Salus

n.d.).

The short file named as a quarter-century Unix history is not treated as a complete copy of Salus's separate book. Similarly, the file named `ken-thompson-history-of-unix.txt` contains Markus Kuhn's 2003 Unix Tools lectures. It is not cited as a first-person Thompson history. Correct attribution takes precedence over a convenient filename.

C.3 The implementation backbone

Lions's supplied commentary is the 1977 teaching text about Sixth Edition. The explanations in this book use its chapter and section structure, especially processes, switching, critical sections, file tables, and inodes. They do not reproduce its source listing or claim that its techniques constitute modern production guidance (Lions 1977).

The supplied xv6 text is the RISC-V edition dated 27 October 2019. Its page tables, trap entry, locking, scheduling, and log are treated as a coherent comparison implementation. Section numbers refer to that edition. Online xv6 revisions can differ, so readers using another version should locate the corresponding topic rather than assume a line number will match (Cox, Kaashoek, and Morris 2019).

Bach supplies a broader Unix-kernel account. Stevens and Rago's third edition supplies the application-facing distinction between standardized interfaces and implementation behavior. Stevens, Fenner, and Rudoff supply the sockets and stream-programming background. These works cover different layers and periods; their examples are not interchangeable snapshots of a single operating system (Bach 1986; Stevens and Rago 2013; Stevens, Fenner, and

Rudoff 2004).

The FFS paper is used both historically and technically. Its measured results belong to its tested machines and workloads. Its general lesson about locality and abstraction is a synthesis here, not a claim that the same performance ratio applies to modern storage (McKusick et al. 1984).

C.4 Tools, criticism, and the screen

Roddy's guide and Cherry and Lesk's macro documentation explain the roff family and the boundary between primitive requests and document structure. The supplied Cherry–Lesk text identifies the Research Tenth Edition context but does not establish a precise date; the bibliography retains that uncertainty (Roddy 1987; Cherry and Lesk n.d.).

The Kernighan–Pike file used here is a Russian translation with an original English publication date of 1984 and a translation date of 2003. It supports the account of an integrated programming environment. The shell examples in this manuscript are original and are not presented as quotations or translations from that file (Kernighan and Pike 1984).

Raymond's supplied printing bears a 2004 copyright although the work was first published in 2003. Its design rules are discussed as advice to be tested, not as a binding definition of Unix. The *UNIX-HATERS Handbook* supplies counterevidence about usability and integration. The 1990 random-input study supplies measured criticism with an explicitly limited sample. None of those sources licenses an unsupported claim about the reliability of every current system (Raymond 2004; Garfinkel, Weise, and Strassmann 1994; Miller, Fredriksen, and So 1990).

The Mach paper describes a 1986 implementation and research direction. Later microkernel developments and Apple's XNU are not collapsed into that early design. The distinction is essential because a project's name can survive substantial architectural change (Accetta et al. 1986).

C.5 Modern material and the limits of this account

The supplied historical collection does not fully cover contemporary Wayland, Android, containers, or Proton. The modern chapters therefore add established systems knowledge and explicitly identified official project documentation. The Wayland project overview establishes the protocol's compositor, input, and buffer model. Bionic's maintainer guide establishes its library and loader roles. Proton's documentation establishes its Wine-based purpose and the existence of version-specific configuration and component integration (Wayland contributors 2026; Android Open Source Project 2026; Valve and Proton contributors 2026).

The cgroup v2 documentation supplies the resource-control model. These online references were consulted on 6 November 2026. Where available, the bibliography records the fetched document's Git blob identifier. A blob identifies file content; it is not a claim to have pinned an entire project release. URLs may later show newer content (Heo and Linux kernel contributors 2026).

Detailed explanations of graphics synchronization, Android lifecycle, and distributed failure are the author's technical synthesis. They should not be mistaken for measurements conducted for this book or quotations from the historical collection. The account de-

liberately avoids current market-share figures, a list of supported phone models, and universal game-compatibility promises.

Historical precision includes knowing when evidence is incomplete. Rather than smoothing every ambiguity into a confident date or claiming all branches developed in isolation, this book preserves distinctions that affect the explanation. The aim is a history readers can question, trace, and extend, not a legend that depends on never opening its sources.

Bibliography

Accetta, Mike et al. (1986). "Mach: A New Kernel Foundation for UNIX Development". In: *USENIX Summer Conference*. Describes the April 1986 implementation, not every later Mach architecture; `sources/mach-new-kernel-for-unix.txt`.

Android Open Source Project (2026). *Bionic Maintainer Overview*. Consulted README blob `4b7e42d06d4f81895df49947d0f5d6d089d53201`. URL: `https://github.com/aosp-mirror/platform_bionic/blob/main/README.md` (visited on 11/06/2026).

Bach, Maurice J. (1986). *The Design of the UNIX Operating System*. Local transcription: `sources/the-design-of-the-unix-operating-system-maurice-j.-bach-.txt`. Prentice-Hall.

Cherry, Lorinda L. and Michael E. Lesk (n.d.). *Typing Documents on the UNIX System: Using the -ms and -mcs Macros with Troff*. Research Tenth Edition text; `sources/cherry-typing-docs-in-unix.txt`; supplied transcription does not establish a publication date. AT&T Bell Laboratories.

Cox, Russ, Frans Kaashoek, and Robert Morris (Oct. 27, 2019). *xv6: A Simple, Unix-like Teaching Operating System*. RISC-V edition supplied in `sources/xv6-unix-like-osdev.txt`; section numbers refer to this edition.

Garfinkel, Simson, Daniel Weise, and Steven Strassmann, eds. (1994). *The UNIX-HATERS Handbook*. Local transcription: `sources/unix-haters-handbook.txt`. IDG Books.

Greenberg, Michael, Konstantinos Kallas, and Nikos Vasilakis (2021). "Unix Shell Programming: The Next 50 Years". In: *Workshop on Hot Topics in Operating Systems*. Local transcription: `sources/unix-shellprog-the-next-50yr.txt`. DOI: `10.1145/3458336.3465294`.

Heo, Tejun and Linux kernel contributors (2026). *Control Group v2*. Kernel documentation, maintained since 2015. URL: `https://github.com/torv`

alds/linux/blob/master/Documentation/admin-guide/cgroup-v2.rst (visited on 11/06/2026).

Kernighan, Brian W. (2020). *UNIX: A History and a Memoir*. Date follows the supplied copy's copyright page; sources/kernighan-unix-history-and-memoir.txt. Kindle Direct Publishing. ISBN: 9781695978553.

Kernighan, Brian W. and Rob Pike (1984). *The UNIX Programming Environment*. Consulted through the 2003 Russian translation in sources/kernighan-pike-unix-programming-env.txt; examples here are newly written. Prentice-Hall.

Libes, Don and Sandy Ressler (1989). *Life with UNIX: A Guide for Everyone*. Local transcription: sources/unix-hist-life-with-unix.txt. Prentice-Hall.

Lions, John (1977). *A Commentary on the Sixth Edition UNIX Operating System*. Original teaching commentary; sources/lions-commentary-on-unix-6th-edition-with-source-code-john-lions-.txt.

McKusick, Marshall K. et al. (Aug. 1984). "A Fast File System for UNIX". In: *ACM Transactions on Computer Systems* 2.3. Local transcription: sources/fast-filesys-for-unix.txt, pp. 181–197.

Miller, Barton P., Lars Fredriksen, and Bryan So (Dec. 1990). "An Empirical Study of the Reliability of UNIX Utilities". In: *Communications of the ACM* 33.12. Local transcription: sources/empiricial-study-of-unix-utils.txt, pp. 32–44.

Raymond, Eric S. (2004). *The Art of UNIX Programming*. Copyright year of the supplied third printing; first published in 2003. Local transcription: sources/art-of-unix-prog.txt. Addison-Wesley. ISBN: 0131429019.

Ritchie, Dennis M. (1977). "The UNIX Time-Sharing System: A Retrospective". In: Conference version identified in the supplied text; sources/ritchie-unix-retroprespective.txt.

– (1984). "The Evolution of the Unix Time-Sharing System". In: *AT&T Bell Laboratories Technical Journal* 63.6. First presented in 1979; local transcription: sources/unix-evolution.txt, pp. 1577–1593.

Ritchie, Dennis M. and Ken Thompson (1974). "The UNIX Time-Sharing System". In: *Communications of the ACM* 17.7. Local transcription: sources/unix-paper.txt, pp. 365–375.

Roddy, Kevin P. (1987). *UNIX NROFF/TROFF: A User's Guide*. Local transcription: sources/unix-troff-guide.txt. Holt, Rinehart and Winston.

Salus, Peter H. (n.d.). *The Daemon, the GNU, and the Penguin: A History of Free and Open Source*. Undated supplied serial compilation; sources/unix-hist-daemon-gnu-penguin.txt.

Spinellis, Diomidis (2017). "A Repository of Unix History and Evolution". In: *Empirical Software Engineering*. Supplied working-paper transcription: `sources/unix-history-repo-spinellis.txt`; DOI identifies the publication. DOI: `10.1007/s10664-016-9445-5`.

Stevens, W. Richard, Bill Fenner, and Andrew M. Rudoff (2004). *UNIX Network Programming, Volume 1: The Sockets Networking API*. 3rd ed. Local transcription: `sources/unix-netprog-network-vol1.txt`. Addison-Wesley.

Stevens, W. Richard and Stephen A. Rago (2013). *Advanced Programming in the UNIX Environment*. 3rd ed. Local transcription: `sources/advanced-programming-in-the-unix-environment-w.-richard-stevens-stephen-a.-rago-.txt`. Addison-Wesley.

Thompson, Ken (1978). "UNIX Implementation". In: *Bell System Technical Journal* 57.6. Local transcription: `sources/unix-impl.txt`, pp. 1931–1946.

Valve and Proton contributors (2026). *Proton: Introduction and Runtime Configuration*. Consulted README blob `5d4d2e9aa6a325954dea7962a81c409c21ef2057`; compatibility remains title and version dependent. URL: `https://github.com/ValveSoftware/Proton/blob/proton_11.0/README.md` (visited on 11/06/2026).

Wayland contributors (2026). *Wayland: Project Overview*. Upstream mirror; consulted README blob `75c1ba4353672ae54b2f2820a7f011122e2d2e3c`. URL: `https://github.com/wayland-mirror/wayland/blob/main/README.md` (visited on 11/06/2026).

Index

4.4BSD-Lite, 45

A
accessibility, 115
Android, 153
    sandbox, 157
anti-cheat, 150
AOSP, 158
Apollo, 33
application lifecycle, 155
ART, 155
awk, 23

B
backups, 143
Bell Laboratories, 3
Berkeley Software
        Distribution, 27
Binder, 153
Bionic, 153
bitmap terminals, 119
Blit, 119
Bostic, Keith, 45
BSD, 27
buffer cache, 81
buffers
    graphics, 127

C
C language, 7
C/A/T phototypesetter, 11
canonical mode, 112
cgroups, 140
Cherry, Lorinda, 14
compilers, 95
compositors, 123
concurrency, 75
containers, 137
context switching, 76
copy-on-write, 71
crash recovery, 85
curses, 111
cylinder groups, 29

D
Dalvik, 155
DARPA, 30
Darwin, 153

deadlock, 79
debuggers, 98
development tools, 95
direct rendering, 122
distributions, 51
dma-buf, 129
document preparation, 11
DRM/KMS, 127

E
ed, 23
Emacs, 23
eqn, 14
event loops, 92
exec, 67

F
Fast File System, 29
file descriptors, 82
filesystems, 81
fork, 67
frame pacing, 149
free software, 49
FreeBSD, 159
fsync, 85

G
gaming on Linux, 145
Git, 99
GNU, 49
GPU, 127
grep, 23

I
init, 138
inodes, 81
interprocess communication, 87
interrupts, 75

J
journaling, 85
Joy, Bill, 27

L
lex, 95
licensing, 41
line discipline, 112
Linux, 49
Lions, John, 59
locking, 75
lost wakeups, 77

M
Mach, 159
macOS, 153
macros
  troff, 13
make, 95
McIlroy, Douglas, 19
memory ordering, 79
Mesa, 122
MINIX, 50
ML, 100
modularity, 103
Multics, 3

N
namespaces, 140

NetBSD, 159
NFS, 35
NIS, 35
nonblocking I/O, 92

O
observability, 143
OCaml, 100
open file descriptions, 82
Open Software Foundation, 42
open source, 49
OpenBSD, 159
OpenGL, 122
Ossanna, Joseph, 11

P
package management, 51
page faults, 71
patent applications, 6
PDP-11, 6
  memory management, 60
permissions, 139
  Android, 157
persistence, 81
pic, 14
pipes, 19
policy and mechanism, 103
portability, 7
POSIX, 41
privilege separation, 139
processes, 67
Proton, 145
pseudoterminals, 114

R
Raymond, Eric S., 103
RCS, 99
RISC, 37
RISC-V, 63
Ritchie, Dennis, 3

S
SCCS, 99
scheduling, 75
seccomp, 139
security, 137
sed, 23
SELinux, 139, 157
servers, 137
service supervision, 138
shader compilation, 149
shared memory, 89
shell, 19
signals, 87
Silicon Graphics, 33
Single UNIX Specification, 41
Sixth Edition Unix, 59
sleep and wakeup, 77
sockets, 30, 87
spinlocks, 79
SSH, 114
Stallman, Richard, 49
standard error, 21
standard input, 21
Standard ML, 100

Steam Deck, 145
Sun Microsystems, 33
supervisor mode, 69
SurfaceFlinger, 158
Sv39, 63
synchronization
    graphics, 129
system administration, 137
system calls, 69
System V Release 4, 42
systemd, 138

T
tbl, 14
TCP, 87
TCP/IP, 30
Teletype, 111
termcap, 111
terminal emulators, 114
terminals, 111
terminfo, 111
termios, 112
The Open Group, 44
Thompson, Ken, 3
Torvalds, Linus, 49
tracing, 98
traps, 60
troff, 11

U
Unicode, 115
UNIX certification, 44
Unix International, 42
Unix philosophy, 103
Unix wars, 41
UNIX-HATERS Handbook, 107
updates, 143
user mode, 69
USL litigation, 45

V
VAX, 27
version control, 99
vi, 23
virtual memory, 67
Vulkan, 145

W
wait, 72
Wayland, 127
window managers, 119
Wine, 145
workstations, 33

X
X Window System, 119
    security, 124
XNU, 159
xv6, 59
Xwayland, 132

Y
yacc, 95

Z
zombie processes, 72