

2009 Volkswagen Touareg 2 (7L6) V8-4.2L (BAR)

Vehículo > Dirección y suspensión > Dirección > Servicio y reparación > Extracción y sustitución > Índice

Especificaciones de apriete de los sujetadores ♦ 1. Reemplace siempre los sujetadores después de retirarlos. ♦ 2. Observe la secuencia de apriete. Consulte => [Secuencia de apriete] . Ver: Columna de dirección > Componentes > Descripción general del conjunto de la columna de dirección .

Component	Fastener Size	Nm
Belt Pulley to Power Steering Pump Bolt		
- 6-Cylinder Diesel, from MY 2009	-	22
- Gasoline Engine	-	25
Control Line Backing Plate Bolt	-	12
Control Line to Steering Gear	-	7
Drive Flange and Hard Rubber Disc Bolt, 10-Cylinder Diesel	-	14 + 45° turn
Handle to Steering Column Bolt	M5 x 8	4.5
Oil Cooler to Radiator	-	9
Power Steering Line Union Fitting	-	30
Power Steering Line to Steering Gear Retaining Bolt	M6 x 12	9
Power Steering Pump to Bracket Bolt		
- 6-Cylinder Diesel, from MY 2009	-	22
- Gasoline Engine	-	25
Power Steering Pump Mounting Bolt, 10-Cylinder Diesel	-	20
Pressure Line to Power Steering Pump Bolt, 6-Cylinder Diesel, from MY 2009	-	9
Pressure Line to Power Steering Pump Banjo Fitting		
- Gasoline Engine	-	40
- 10-Cylinder Diesel	-	35
Shield to Steering Gear Bolt	M6 x 16	10
Steering Column Protective Boot Nut	M6	4
Steering Column to Lateral Control Arm Bolt 2	M8 x 28	20
Steering Column to Lateral Control Arm Nut 1	M8	20
Steering Column U-Joint to Steering Gear Bolt 1	M10 x 35	40 + 90° turn
Steering Gear to Subframe Bolt 1	M12 x 1.5 x 80	90 + 90° turn
Suction Line to Cylinder Block Mounting Bolt, 10-Cylinder Diesel	-	9
Suction Line to Power Steering Pump Bolt, 10-Cylinder Diesel	-	10
Tie Rod to Steering Gear	-	100
Tie Rod End to Tie Rod Nut	-	70
Tie Rod End to Wheel Bearing Housing Nut 1	M14 x 1.5	90