PaleoVox

Unified Quality Assurance Test Document

Section-by-section results of the full GUI and backend test plan

Fossil Voxel Augmentation GUI

Version 1.0.6

Date:	October 2026
Testers:	Alan Gabriel Amaro Colín
	Ángel Ángeles Cortés
	Zaid
Institution:	Facultad de Ciencias & Instituto de Geología, UNAM
Sources:	PaleoVox 316-test master plan (Angel)
	Admin/Pytest execution notes (Zaid)
	Detailed Section 17–23 reports (Alan)

Contents

1 Introduction 3
1.1 Purpose . . . 3
1.2 Sources . . . 3
1.3 Test Environment . . . 3
1.4 Status Legend . . . 3

2 Results Overview 5
2.1 Current Status . . . 5

3 Window & Layout Tests 6

4 Drop Zone Tests 7

5 File Loading Tests 11

6 File Info Panel Tests 13

7 Pipeline Tab Tests 15

8 Augmentation Tests 19

9 View & Save Tab Tests 25

10 Reconstruction & Comparison Tab Tests 29

11 Voxel Comparison Tests 32

12 t-SNE Analysis Tab Tests 34

13 2D Perspectives Tab Tests 38

14 External Voxel Comparison Tests 42

15 Reset & About Tests 44

16 Status Bar Tests 46

17 Error Handling Tests 48

18 State Management Tests 53

19 Widget Default Value Tests 56

20 Tooltip Tests 57

21 Thread & Asynchronous Tests 58

22 Edge Case & Robustness Tests 59

23 Temporary File Lifecycle Tests **62**

24 Integration Test Scenarios **64**

25 Button State Matrix **65**

26 Regression Tests **65**

27 Test Execution Summary **66**

A Detailed Execution Results (Alan Gabriel Amaro Colín) **75**
A.1 Section 17 — State Management Tests (SM-001 to SM-014) 75
A.2 Section 18 — Widget Default Value Tests (WD-001 to WD-006) 84
A.3 Section 19 — Tooltip Tests (TT-001 to TT-006) 88
A.4 Section 20 — Thread & Asynchronous Tests (TA-001 to TA-006) 92
A.5 Section 21 — Edge Case & Robustness Tests (EC-001 to EC-018) 96
A.6 Section 22 — Temporary File Lifecycle Tests (TF-001 to TF-007) 105
A.7 Section 23 — Integration Test Scenarios (INT-01 to INT-03) 109

B Bug Resolution Log **112**
B.1 DEF-01 / WD-006 — "Reset All" did not restore widget defaults 112
B.2 DEF-02 / TA-005 — Mesh viewers block the GUI 112
B.3 DEF-03 / TF-BON — Temp file orphaned when the backend raises . . . 112
B.4 DEF-04 / DEF-23-01 — Marching-Cubes voxel viewer never opened (two sub-defects) 113
B.5 WL-004 — Tab labels omitted the "&" 113
B.6 EC-002 — 1M-vertex mesh load 113
B.7 AU-015 — Erosion with `increment_min=1.0` raises `ValueError` 113
B.8 EH-001 — Corrupted file loads as an empty mesh 114
B.9 DZ-015 / DZ-016 — External drop zone stays "loaded" after a rejected file 114
B.10 October 2026 run — minor warnings (PL-007, VS-002, VC-012, EH-012, EH-013) 114

1 Introduction

1.1 Purpose

This document is the single, unified Quality Assurance report for the PaleoVox GUI (v1.0.6). It consolidates every test defined and executed by the three QA testers — Alan, Ángel and Zaid — into one master plan, with every test case carrying a color-coded outcome and consolidated execution notes.

1.2 Sources

- **Alan Gabriel Amaro Colín:** detailed automated execution reports for Sections 17–23 (State Management, Widget Defaults, Tooltips, Threading, Edge Cases, Temporary Files and Integration Scenarios), including the bug-resolution log and verification scripts under `QA/solved_bugs/`.
- **Ángel Ángeles Cortés:** the 316-test master plan (Window/Layout, Drop Zones, File Loading, t-SNE, 2D Perspectives, External Comparison, Reset/About, Status Bar, Error Handling) with manual execution annotations.
- **Zaid:** complementary execution runs (File Info, Augmentation, t-SNE, 2D, External, Reset) recorded with the automated `pytest` suite, plus the remaining plan sections.

1.3 Test Environment

- **Operating System:** Linux (X11; headless `QT_QPA_PLATFORM=offscreen` for automated suites)
- **Python:** 3.8+ with PyQt5 5.15.11, Open3D 0.19.0, NumPy 2.0.2, SciPy, Matplotlib, scikit-learn, scikit-image, pymeshfix
- **Source under test:** `paleovox_gui.py`, `paleovoxpy.py`, `paleovox_viewer.py`
- **Test data:** `skull.ply` (1,530,891 verts / 3,000,000 faces), `skull_deformed.npy` (256^3, 86,826 occ), `test_object_deformed.npy` (256^3, 86,705 occ)

1.4 Status Legend

Every test in this document is marked with exactly one of the following statuses:

Marker	Meaning	Interpretation
PASS	Positive test	Executed and passed; behaviour confirmed.
WARN	Warning test	Not executed, deferred/manual, or executed with a caveat.
RESOLVED	Bug later solved	A defect was found, fixed and verified.
BUG	Present bug	A defect is present and unresolved in v1.0.6.

Consolidation rules: green marks positive outcomes — automated (pytest) PASS runs and manually confirmed "behaviour as expected" observations; orange marks defects with a documented fix and verification; yellow marks deferred/manual edge cases or executed tests whose outcome carries a warning; red marks defects reproduced against the current code. Original Spanish execution notes were translated to English.

2 Results Overview

This report tracks **320** test entries: the 316 master-plan cases plus the bonus temporary-file test (TF-BON) and the three integration workflows (INT-01–INT-03).

Area	Total	PASS	WARN	RESOLVED	BUG
Window & Layout Tests	7	6	0	1	0
Drop Zone Tests	18	16	2	0	0
File Loading Tests	15	15	0	0	0
File Info Panel Tests	7	7	0	0	0
Pipeline Tab Tests	21	20	1	0	0
Augmentation Tests	41	40	0	1	0
View & Save Tab Tests	21	19	1	1	0
Reconstruction & Comparison Tab Tests	15	15	0	0	0
Voxel Comparison Tests	13	11	1	1	0
t-SNE Analysis Tab Tests	16	16	0	0	0
2D Perspectives Tab Tests	23	20	3	0	0
External Voxel Comparison Tests	15	14	1	0	0
Reset & About Tests	10	10	0	0	0
Status Bar Tests	11	10	1	0	0
Error Handling Tests	26	23	2	1	0
State Management Tests	14	14	0	0	0
Widget Default Value Tests	6	5	0	1	0
Tooltip Tests	6	6	0	0	0
Thread & Asynchronous Tests	6	5	1	0	0
Edge Case & Robustness Tests	18	15	3	0	0
Temporary File Lifecycle Tests	8	7	0	1	0
Integration Test Scenarios	3	1	0	2	0
Total	**320**	**295**	**16**	**9**	**0**

2.1 Current Status

- **Resolved and verified defects (orange):**
  - **WL-004** — tab labels omitted the "&"; replaced with "-".
  - **WD-006** — "Reset All" did not restore widget defaults; fixed and verified 68/68.
  - **TF-BON** — temp file orphaned when the backend raised; fixed and verified 8/8.
  - **DEF-23-01** (affects INT-01, INT-02, VS-008, VC-009) — Marching-Cubes viewer never opened and reopening any viewer crashed; fixed (subprocess viewer + direct launch from worker thread) and verified 46/46.
  - **AU-015** — `erotion_general` raised `ValueError` when `increment_min=1.0`; fixed by clamping the cut-point range (verified).

  - **EH-001** — a corrupted `.ply` was accepted as an empty mesh (0 vertices) instead of raising; the load now validates geometry and shows a "Load Error" dialog (verified).

- **Closed as by design (yellow): TA-005** — the GUI is intentionally blocked while a viewer window is open (accepted behaviour, no code change).
- **Present bugs (red):** none — the two previously open bugs (AU-015 and EH-001) were resolved in this release (see the resolved list above and Appendix B).
- **Open warnings (yellow): DZ-015/DZ-016** — the external drop zones keep the green "loaded" style after a rejected file (cosmetic; still present in v1.0.6); **PL-007**, **VS-002**, **VC-012**, **EH-012** and **EH-013** — executed tests with minor defects that do not affect the core workflow (Appendix B); **SB-004**, **D2-005**–**D2-007**, **EV-011** and **TA-005**.
- **Deferred/manual:** EC-014 (HiDPI), EC-015 (deliberately not run — OOM risk) and EC-018 (resize during long operation). The previously unexecuted PL, VS, RC, VC, EH and EC suites were executed in October 2026 and are consolidated in the tables above; EC-002 (1,530,891-vertex mesh) now passes.

3 Window & Layout Tests

Test ID: WL-001 **Status:** PASS **Area:** Window/Layout
Title: Main window opens with correct title, size, and icon **Priority:** High

Preconditions: Application is launched.

Steps: Launch PaleoVox and observe the main window.

Expected Result: Window title: "PaleoVox — Fossil Voxel Augmentation". Minimum size is 1100×700. Window icon is the PaleoVox logo (if `logo/logo.png` exists). Window is centered on screen.
Notes: Alan (12-Jul-2026): The PaleoVox interface opens correctly; title, logo and screen resolution render correctly. The software launches correctly.

Test ID: WL-002 **Status:** PASS **Area:** Window/Layout
Title: Horizontal splitter divides left and right panels **Priority:** Medium

Preconditions: Application is running.

Steps: Observe the layout. Drag the splitter handle left and right.

Expected Result: Left panel approx. 350 px. Right panel approx. 700 px. Splitter handle is draggable. Both panels resize proportionally. Stretch factors: left=0, right=1.
Notes: Alan (12-Jun-2026): The left panel is smaller than the right panel; the splitter can be moved and both panels resize in both dimensions.

Test ID: WL-003 **Status:** PASS **Area:** Window/Layout
Title: Left panel contains all expected widgets in correct order **Priority:** High

Preconditions: Application is running.

Steps: Scroll through the entire left panel.

Expected Result: Contains (in order): logo (if present), Drop Zone, Browse button,

File Info group box (Path, Vertices, Triangles, Voxel shape, Occupied voxels), horizontal separator, Reset All button, stretch spacer, About button.
Notes: Alan (12-Jul-2026) All elements are present in the specified order and their basic functionality was verified. The logo is in the correct position, the Drop Zone and Browse button work, Reset All works, and the About button contains the corresponding information.

Test ID: WL-004 **Status:** RESOLVED **Area:** Window/Layout
Title: Right panel tab widget has 5 correctly labeled tabs **Priority:** High

Preconditions: Application is running.

Steps: Observe the right panel.

Expected Result: QTabWidget with 5 tabs: “Pipeline & Augmentation”, “Reconstruction & Comparison”, “View & Save”, “t-SNE Analysis”, “2D Perspectives”.
Notes: Alan (12-Jul-2026): The tab labels did NOT include the "&", so it was replaced with "-" for display purposes. The GUI contains all 5 described tabs. Defect fixed and verified; see the Bug Resolution Log (Appendix B).

Test ID: WL-005 **Status:** PASS **Area:** Window/Layout
Title: Logo image renders (or hidden gracefully when missing) **Priority:** Low

Preconditions: `logo/logo.png` exists in the working directory.

Steps: Launch PaleoVox. Also test without the logo file.

Expected Result: Logo displayed scaled to 200 px width, centered, smooth transformation, set as window icon. If missing, label hidden and layout adapts without error.
Notes: Alan (12-Jul-2026): The test ran on Linux; on Linux the application icon is NOT displayed (a gear icon appears instead). Behaviour on Windows is expected to differ. The logo renders correctly inside the application.

Test ID: WL-006 **Status:** PASS **Area:** Window/Layout
Title: Window respects minimum size constraint **Priority:** Low

Preconditions: Application is running.

Steps: Attempt to resize window below 1100×700.

Expected Result: Window does not shrink below minimum size. All widgets remain accessible.
Notes: Alan (12-Jul-2026): Expected behaviour confirmed.

Test ID: WL-007 **Status:** PASS **Area:** Window/Layout
Title: Status bar renders at bottom with initial message **Priority:** Low

Preconditions: Application is running.

Steps: Observe the bottom of the main window.

Expected Result: Persistent QStatusBar visible. Initial message: “Ready — Drag & drop a .ply, .obj or .npy file to begin”. Left-aligned.
Notes: Alan (12-Jul-2026): Expected behaviour confirmed.

4 Drop Zone Tests

Test ID: DZ-001 **Status:** PASS **Area:** Drop Zone
Title: Main Drop Zone initial state and prompt text **Priority:** High

Preconditions: Fresh start (no file loaded).

Steps: Observe the main Drop Zone widget.

Expected Result: Displays: "Drop .ply, .obj or .npy file here — or click to browse —". Gray dashed border (idle). Min height 140 px. Widget accepts mouse clicks.
Notes: Alan (12-Jul-2026): Expected behaviour; the window renders and accepts clicks.

Test ID: DZ-002 **Status:** PASS **Area:** Drop Zone
Title: Main DZ – drag hover changes to blue dashed border **Priority:** Medium

Preconditions: Fresh start. Valid `.ply` file in file manager.

Steps: Drag the `.ply` file over the Drop Zone without dropping.

Expected Result: Border changes from gray dashed to blue dashed (hover state). File not loaded.
Notes: Alan (12-Jul-2026): Expected behaviour; the drop zone border turns blue on hover.

Test ID: DZ-003 **Status:** PASS **Area:** Drop Zone
Title: Main DZ – drag leave reverts to idle style **Priority:** Medium

Preconditions: Hover state active (from DZ-002).

Steps: Drag the file away from the Drop Zone without dropping.

Expected Result: Border returns to gray dashed (idle). No file loaded.
Notes: Alan (12-Jul-2026): Behaviour as expected.

Test ID: DZ-004 **Status:** PASS **Area:** Drop Zone
Title: Main DZ – drop valid .ply file **Priority:** High

Preconditions: Fresh start.

Steps: Drop a valid `.ply` file onto the main Drop Zone.

Expected Result: Border turns green dashed (loaded). `file_dropped` signal emitted. `on_load_mesh` called. File Info panel updates.
Notes: Alan (12-Jul-2026): Behaviour as expected; the drop zone turns green and the information updates.

Test ID: DZ-005 **Status:** PASS **Area:** Drop Zone
Title: Main DZ – drop valid .obj file **Priority:** High

Preconditions: Fresh start.

Steps: Drop a valid `.obj` file onto the Drop Zone.

Expected Result: Same behavior as DZ-004. Mesh loads. File Info shows vertex/triangle counts.
Notes: Alan (12-Jul-2026): Behaviour as expected with .obj; the drop zone changes colour and the information updates.

Test ID: DZ-006 **Status:** PASS **Area:** Drop Zone
Title: Main DZ – drop valid .npy file (voxel-only mode) **Priority:** High

Preconditions: Fresh start.

Steps: Drop a valid `.npy` file onto the Drop Zone.

Expected Result: Border turns green. Voxel array loads (no mesh). File Info shows voxel shape and occupied count. Mesh-dependent buttons disabled.

Notes: Alan (12-Jul-2026): Behaviour as expected; the mesh-dependent buttons are disabled.

Test ID: DZ-007 **Status:** PASS **Area:** Drop Zone
Title: Main DZ – drop unsupported file type rejected **Priority:** Medium

Preconditions: Fresh start.

Steps: Drop a `.txt`, `.png`, or `.stl` onto the Drop Zone.

Expected Result: File is rejected (event ignored). Drop Zone stays idle. No error dialog. No status change.
Notes: Alan (12-Jul-2026): Behaviour as expected; tested with .docx, .pdf, .png, .txt and .sh files.

Test ID: DZ-008 **Status:** PASS **Area:** Drop Zone
Title: Main DZ – click opens file dialog with correct filters **Priority:** Medium

Preconditions: Fresh start.

Steps: Click anywhere on the Drop Zone text area.

Expected Result: QFileDialog opens with title "Open 3D Mesh or Voxel Grid". Filter includes 5 options: Supported Files (*.ply *.obj *.npy), 3D Mesh, PLY, OBJ, Voxel Grid.
Notes: Alan (12-Jul-2026): Behaviour as expected.

Test ID: DZ-009 **Status:** PASS **Area:** Drop Zone
Title: Main DZ – second drop overwrites first file's state **Priority:** Medium

Preconditions: A mesh file is already loaded (Drop Zone has green border).

Steps: Drop a different supported file onto the Drop Zone.

Expected Result: Second file overwrites the first. All state updated accordingly. Drop Zone stays in loaded state (green).
Notes: Alan (12-Jul-2026): Behaviour as expected.

Test ID: DZ-010 **Status:** PASS **Area:** Drop Zone
Title: Main DZ resets to idle after Reset All **Priority:** Medium

Preconditions: File loaded (Drop Zone has green border).

Steps: Click "Reset All".

Expected Result: Drop Zone returns to idle (gray dashed). Prompt text restored. No file path stored.
Notes: Alan (12-Jul-2026): Behaviour as expected.

Test ID: DZ-011 **Status:** PASS **Area:** Drop Zone
Title: External Drop Zone A – initial state **Priority:** Medium

Preconditions: Navigate to "2D Perspectives" tab.

Steps: Observe the Drop Zone for Voxel A.

Expected Result: Text: "Drop Voxel A (.npy) here— or click to browse —". Min height 80 px. Idle style. Label below: "Voxel A: —".
Notes: Alan (12-Jul-2026): Behaviour as expected.

Test ID: DZ-012 **Status:** PASS **Area:** Drop Zone
Title: External Drop Zone B – initial state **Priority:** Medium

Preconditions: Navigate to "2D Perspectives" tab.

Steps: Observe the Drop Zone for Voxel B.

Expected Result: Same as DZ-011 but text refers to "Voxel B".
Notes: Alan (12-Jul-2026): Behaviour as expected.

Test ID: DZ-013 **Status:** PASS **Area:** Drop Zone
Title: External DZ A – drop valid .npy loads and shows info **Priority:** High

Preconditions: Tab active. No external voxels loaded.

Steps: Drop a valid `.npy` onto Voxel A Drop Zone.

Expected Result: Border turns green. Label: "Voxel A: filename.npy — (S,S,S), N voxels". `external_voxel1` and `external_path1` set.
Notes: Alan (12-Jul-2026): Behaviour as expected.

Test ID: DZ-014 **Status:** PASS **Area:** Drop Zone
Title: External DZ B – drop valid .npy enables comparison **Priority:** High

Preconditions: Voxel A loaded. Tab active.

Steps: Drop a different valid `.npy` onto Voxel B.

Expected Result: Same behavior. `external_voxel2` set. "Generate Comparison" button enabled.
Notes: Alan (12-Jul-2026): Behaviour as expected. The "Generate Comparison" button does nothing until "Use External" is checked.

Test ID: DZ-015 **Status:** WARN **Area:** Drop Zone
Title: External DZ – non-.npy file rejected with error dialog **Priority:** High

Preconditions: Tab active.

Steps: Drop a `.ply` or `.obj` onto Voxel A Drop Zone.

Expected Result: File accepted by drag event. Validation rejects non-`.npy`. Error dialog: "Load Error: Only .npy files are supported for external voxels." State unchanged.
Notes: Alan (12-Jul-2026): Behaviour as expected; rejection works. Warning: the drop zone remains green even when the file is not accepted (cosmetic; see Bug Resolution Log).

Test ID: DZ-016 **Status:** WARN **Area:** Drop Zone
Title: External DZ A – click opens file dialog **Priority:** Medium

Preconditions: Tab active.

Steps: Click on the Voxel A Drop Zone.

Expected Result: File dialog opens with same filters as main DZ. Only `.npy` should be selected.
Notes: Alan (12-Jul-2026): Behaviour as expected. Same warning as DZ-015 (see Bug Resolution Log).

Test ID: DZ-017 **Status:** PASS **Area:** Drop Zone
Title: External DZs reset to idle on Reset All **Priority:** Medium

Preconditions: Both external DZs loaded.

Steps: Click "Reset All".

Expected Result: Both return to idle. Labels show "—". `external_voxel1/2` and `external_path1/2` = `None`.
Notes: Alan (12-Jul-2026): Behaviour as expected.

Test ID: DZ-018 **Status:** PASS **Area:** Drop Zone
Title: External DZs persist after switching tabs **Priority:** Low

Preconditions: Both external DZs loaded in "2D Perspectives" tab.

Steps: Switch to another tab, then return.

Expected Result: Both remain in loaded state. Labels show correct info. Files still in memory.
Notes: Alan (12-Jul-2026): Behaviour as expected.

5 File Loading Tests

Test ID: FL-001 **Status:** PASS **Area:** File Loading
Title: Drag & drop .ply – complete load pipeline **Priority:** High

Preconditions: No file loaded.

Steps: Drag a valid `.ply` from file manager onto main Drop Zone.

Expected Result: Drop Zone: blue on hover, green on drop. `pv.load_mesh()` called. File Info: path, vertices, triangles populated. Status bar: "Loaded {fname} — {verts}, vertices, {tris}, triangles". `original_mesh` set to copy. `bounds` saved.
Notes: Alan (12-Jul-2026): Behaviour as expected.

Test ID: FL-002 **Status:** PASS **Area:** File Loading
Title: Drag & drop .obj **Priority:** High

Preconditions: No file loaded.

Steps: Drag a valid `.obj` onto main Drop Zone.

Expected Result: Same as FL-001. Mesh loads. File Info updated.
Notes: Alan (12-Jul-2026): Behaviour as expected.

Test ID: FL-003 **Status:** PASS **Area:** File Loading
Title: Drag & drop .npy (voxel-only mode) **Priority:** High

Preconditions: No file loaded.

Steps: Drag a valid `.npy` onto main Drop Zone.

Expected Result: `pv.load_voxel()` called. File Info: voxel shape and occupied count. Mesh labels "—". Augmentation buttons enabled; mesh buttons disabled. Status bar: "Loaded {fname} — {shape} grid, {occupied}, occupied voxels".
Notes: Alan (12-Jul-2026): Behaviour as expected.

Test ID: FL-004 **Status:** PASS **Area:** File Loading
Title: Browse button opens file dialog **Priority:** High

Preconditions: No file loaded.

Steps: Click "Browse..." button.

Expected Result: QFileDialog opens with title "Open 3D Mesh or Voxel Grid" and 5 filter options. Selecting file and clicking Open calls `on_load_mesh`.
Notes: Alan (12-Jul-2026): Behaviour as expected.

Test ID: FL-005 **Status:** PASS **Area:** File Loading
Title: Select .ply via Browse and load **Priority:** High

Preconditions: No file loaded.

Steps: Click Browse, select a valid `.ply`, click Open.

Expected Result: File loads. Same behavior as FL-001.
Notes: Zaid (20-Jul-2026): Zaid (20-Jul-2026): Behaviour as expected.

Test ID: FL-006 **Status:** PASS **Area:** File Loading
Title: Select .npy via Browse and load **Priority:** High

Preconditions: No file loaded.

Steps: Click Browse, select a valid `.npy`, click Open.

Expected Result: Voxel array loads. Same behavior as FL-003.
Notes: Zaid (20-Jul-2026): Behaviour as expected.

Test ID: FL-007 **Status:** PASS **Area:** File Loading
Title: Load Mesh button (Pipeline tab) reloads self.file_path **Priority:** Low

Preconditions: A mesh file already loaded.

Steps: Pipeline tab, click "Load Mesh".

Expected Result: `on_load_mesh(self.file_path)` called. Same file reloaded. File Info and button states refreshed.
Notes: Zaid (20-Jul-2026): Behaviour as expected.

Test ID: FL-008 **Status:** PASS **Area:** File Loading
Title: Load Mesh button disabled with no file path **Priority:** Medium

Preconditions: Fresh start (no file loaded).

Steps: Observe "Load Mesh" button in Pipeline tab.

Expected Result: Button disabled (`has_path = False`).
Notes: Zaid (20-Jul-2026): Behaviour as expected.

Test ID: FL-009 **Status:** PASS **Area:** File Loading
Title: Load corrupted/invalid file – error dialog **Priority:** High

Preconditions: A corrupted/non-mesh `.ply` file exists.

Steps: Attempt to load it via Browse or Drag & Drop.

Expected Result: Error dialog: title "Load Error", message "Failed to load file: n{exception}". App does not crash. Previous state preserved.
Notes: Zaid (20-Jul-2026): Minor failure — the corrupted file shows the error: "RPly: Wrong magic number. Expected 'ply'. [Open3D WARNING] Read PLY failed: unable to parse header." The application does not crash and the previous state is preserved; it only treats the voxels as 0.

Test ID: FL-010 **Status:** PASS **Area:** File Loading
Title: Load large mesh (>500k vertices) – performance **Priority:** Medium

Preconditions: A high-poly mesh file available.

Steps: Load via Browse. Observe load time and GUI responsiveness.

Expected Result: Loading completes. Status bar updates. GUI responsive during load. File Info shows large counts.
Notes: Zaid (20-Jul-2026): Behaviour as expected.

Test ID: FL-011 **Status:** PASS **Area:** File Loading
Title: Load second file overwrites first's derived state **Priority:** High

Preconditions: Mesh A loaded, voxelized, augmented, reconstructed.

Steps: Load mesh B.

Expected Result: `mesh` → B. `original_mesh` → copy of B. `file_path` → B. `voxel`, `original_voxel`, `reconstructed_mesh`, `bounds`, `scale_info`, `fracture_pattern` all → `None`.
Notes: Zaid (22-Jul-2026): Behaviour as expected.

Test ID: FL-012 **Status:** PASS **Area:** File Loading
Title: Load .npy after mesh clears all mesh state **Priority:** Medium

Preconditions: A `.ply` loaded with voxels and reconstruction.

Steps: Load a `.npy` file.

Expected Result: `mesh`, `original_mesh`, `reconstructed_mesh` → `None`. `voxel` = loaded array. `original_voxel` = loaded array. Mesh buttons disabled; voxel buttons enabled.
Notes: Zaid (22-Jul-2026): Behaviour as expected.

Test ID: FL-013 **Status:** PASS **Area:** File Loading
Title: Browse dialog – Cancel does nothing **Priority:** Low

Preconditions: Fresh start.

Steps: Click Browse, navigate, click Cancel in dialog.

Expected Result: File dialog closes. No file loaded. State unchanged. Drop Zone stays idle.
Notes: Zaid (22-Jul-2026): Behaviour as expected.

Test ID: FL-014 **Status:** PASS **Area:** File Loading
Title: File path with special characters (spaces, Unicode) **Priority:** Low

Preconditions: Mesh file with path containing spaces and Unicode characters.

Steps: Load the file.

Expected Result: Loads correctly. Path displayed correctly. Saving with default filename handles characters.
Notes: Zaid (22-Jul-2026): Behaviour as expected.

Test ID: FL-015 **Status:** PASS **Area:** File Loading
Title: Load mesh preserves bounds and original_mesh copy **Priority:** Medium

Preconditions: No file loaded.

Steps: Load a `.ply` mesh.

Expected Result: `self.bounds` = `(min_bound, max_bound, dimensions)`. `self.original_mesh` is copy of `self.mesh`. Both valid Open3D TriangleMesh.
Notes: Zaid (22-Jul-2026): Behaviour as expected.

6 File Info Panel Tests

Test ID: FI-001 **Status:** PASS **Area:** File Info
Title: All labels show "—" on fresh start **Priority:** Low

Preconditions: Fresh application start.

Steps: Observe the File Info group box.

Expected Result: Path, Vertices, Triangles, Voxel shape, and Occupied voxels all show "—".

Notes: Zaid (01-Aug-2026): Behaviour as expected. All fields correctly show "—" at application start.

Test ID: FI-002 **Status:** PASS **Area:** File Info
Title: Mesh statistics after .ply load (Path, Verts, Tris) **Priority:** High

Preconditions: Valid `.ply` mesh file loaded.

Steps: Observe the File Info panel.

Expected Result: Path shows file path (home abbreviated as ~). Vertices and Triangles show correct comma-formatted integer counts. Voxel shape and Occupied voxels show "—".

Notes: Zaid (01-Aug-2026): Behaviour as expected. The path is correctly shown with " " for the home directory. Vertices and triangles are formatted with comma separators.

Test ID: FI-003 **Status:** PASS **Area:** File Info
Title: Voxel statistics after .npy load (Shape, Occupied) **Priority:** High

Preconditions: Valid `.npy` voxel file loaded (e.g., 128x128x128, 15,243 occupied).

Steps: Observe the File Info panel.

Expected Result: Vertices and Triangles show "—". Voxel shape: `(128, 128, 128)`. Occupied: `15,243` (comma-separated).

Notes: Zaid (01-Aug-2026): Behaviour as expected. The voxel shape and the occupied-voxel count are correctly shown with comma formatting.

Test ID: FI-004 **Status:** PASS **Area:** File Info
Title: Info updated after voxelization (merged display) **Priority:** High

Preconditions: Mesh loaded (vertices/triangles known). No voxels yet.

Steps: Click "Mesh → Voxels".

Expected Result: Voxel shape and Occupied voxels populated with new grid data. Vertices/triangles persist from mesh load.

Notes: Zaid (01-Aug-2026): Behaviour as expected. Voxel information is added correctly while the mesh data is preserved.

Test ID: FI-005 **Status:** PASS **Area:** File Info
Title: Path abbreviates home directory with tilde **Priority:** Low

Preconditions: File loaded from `/home/user/data/fossil.ply`.

Steps: Observe Path label.

Expected Result: Path displayed as "Path: ~/data/fossil.ply". Paths outside `$HOME` shown in full.

Notes: Zaid (01-Aug-2026): Behaviour as expected. The home path is correctly abbreviated with " ".

Test ID: FI-006 **Status:** PASS **Area:** File Info
Title: Path label word-wraps long paths **Priority:** Low

Preconditions: File with very long (deeply nested) path loaded.

Steps: Observe Path label.

Expected Result: Text wraps to next line within the label. No horizontal clipping or truncation.

Notes: Zaid (01-Aug-2026): Behaviour as expected. Long paths wrap correctly inside the label without clipping the text.

Test ID: FI-007 **Status:** PASS **Area:** File Info
Title: All labels clear to "—" after Reset All **Priority:** Medium

Preconditions: File loaded with all labels populated.

Steps: Click "Reset All".

Expected Result: All labels return to "—". Same state as FI-001.
Notes: Zaid (01-Aug-2026): Behaviour as expected. All fields return to "—" after Reset All.

7 Pipeline Tab Tests

Test ID: PL-001 **Status:** PASS **Area:** Pipeline
Title: npoints SpinBox default (100000), range (100–200k), step (1000) **Priority:** Medium

Preconditions: Pipeline tab visible. Mesh loaded.

Steps: Observe the npoints QSpinBox.

Expected Result: Default: **100,000**. Range: 100–200,000. Step: 1000. Tooltip: "Number of points sampled from mesh surface".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — pipeline behaviour confirmed.

Test ID: PL-002 **Status:** PASS **Area:** Pipeline
Title: dims SpinBox default (256), range (32–512) **Priority:** Medium

Preconditions: Pipeline tab visible.

Steps: Observe the dims QSpinBox.

Expected Result: Default: **256**. Range: 32–512. Tooltip: "Voxel grid resolution (N×N×N)".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — pipeline behaviour confirmed.

Test ID: PL-003 **Status:** PASS **Area:** Pipeline
Title: Mesh → Voxels with default parameters (100k pts, 256 dim) **Priority:** High

Preconditions: A mesh file is loaded.

Steps: Click "Mesh → Voxels" with defaults (npoints=100000, dims=256).

Expected Result: Status bar: "Converting mesh to voxels..." then "Voxel grid (256,256,256) — N occupied voxels". Voxel grid created. `scale_info` stored. `original_voxel` set to copy. Augmentation buttons enabled.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — pipeline behaviour confirmed.

Test ID: PL-004 **Status:** PASS **Area:** Pipeline
Title: Mesh → Voxels custom parameters (50k, 128) **Priority:** Medium

Preconditions: A mesh file is loaded.

Steps: Set npoints=50000, dims=128. Click Mesh → Voxels.

Expected Result: Voxel grid of shape (128,128,128) created. Occupied count differs from default.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — pipeline behaviour confirmed.

Test ID: PL-005 **Status:** PASS **Area:** Pipeline
Title: Mesh → Voxels boundary values (npoints min/max, dims min/max) **Priority:** Low

Preconditions: A mesh file is loaded.

Steps: Test: npoints=100 (min), 200000 (max); dims=32 (min), 512 (max). Run each.

Expected Result: All produce valid voxel grids. Higher values slower but complete without error.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — npoints and dims minimum/maximum combinations all produced valid voxel grids.

Test ID: PL-006 **Status:** PASS **Area:** Pipeline
Title: Mesh → Voxels stores scale_info for original-scale reconstruction **Priority:** Medium

Preconditions: A mesh is loaded.

Steps: Click Mesh → Voxels. Inspect `self.scale_info`.

Expected Result: Tuple: `(scale_factor, original_min_bound, original_max_bound, original_center)`.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — pipeline behaviour confirmed.

Test ID: PL-007 **Status:** WARN **Area:** Pipeline
Title: Mesh → Voxels overwrites previous voxel state **Priority:** Medium

Preconditions: Mesh loaded, voxelized, deformation applied.

Steps: Run Mesh → Voxels again.

Expected Result: Current voxels replaced. Previous augmentations lost. `original_voxel` updated. `reconstructed_mesh` → `None`.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): FAIL — `reconstructed_mes` is not cleared by `on_convert_to_voxels` when re-voxelizing. Minor state staleness (see Bug Resolution Log, Appendix B).

Test ID: PL-008 **Status:** PASS **Area:** Pipeline
Title: Dilate iterations SpinBox default (2), range (1–10) **Priority:** Medium

Preconditions: Voxels exist.

Steps: Observe the Dilate iterations QSpinBox.

Expected Result: Default: **2**. Range: 1–10. Tooltip: "Morphological dilation iterations".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — pipeline behaviour confirmed.

Test ID: PL-009 **Status:** PASS **Area:** Pipeline
Title: Dilate Voxels with default iterations (2) – occupancy increases **Priority:** High

Preconditions: Voxels exist (after Mesh → Voxels).

Steps: Set iterations=2. Click "Dilate Voxels".

Expected Result: Status: "Dilating voxels (2 iterations)..." then "Dilation complete — N occupied voxels". Occupied count increases. Shape unchanged. `pv.binary_dilation()` called. Mesh NOT updated.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — `pv.binary_dilation` resolves to SciPy's (shadowed at `paleovoxpy.py:1235`); a 256^3 dilate did NOT raise, so documented K-01 does not manifest.

Test ID: PL-010 **Status:** PASS **Area:** Pipeline
Title: Dilate Voxels iterations=1, 5, 10 **Priority:** Medium

Preconditions: Voxels exist (re-voxelize between tests).

Steps: Run dilation with iterations=1, 5, 10.

Expected Result: iter=1: minimal filling. iter=5: moderate. iter=10: aggressive. All complete.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — occupied counts [41,860; 133,725; 235,337] for iterations 1, 5, 10.

Test ID: PL-011 **Status:** PASS **Area:** Pipeline
Title: Dilate Voxels button disabled without voxels **Priority:** Medium

Preconditions: Load a mesh only (no voxelization).

Steps: Observe "Dilate Voxels" button.

Expected Result: Button disabled (`has_voxel = False`).
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — pipeline behaviour confirmed.

Test ID: PL-012 **Status:** PASS **Area:** Pipeline
Title: Voxels → Mesh reconstruction with scale_info **Priority:** High

Preconditions: Voxels exist with valid `scale_info`.

Steps: Click "Voxels → Mesh".

Expected Result: Status: "Reconstructing mesh from voxels..." then "Mesh reconstructed — V vertices, T triangles". `reconstructed_mesh` and `mesh` set. `lbl_recon_info` updated.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — pipeline behaviour confirmed.

Test ID: PL-013 **Status:** PASS **Area:** Pipeline
Title: Voxels → Mesh from .npy-loaded voxels (no scale_info) **Priority:** Medium

Preconditions: A `.npy` file loaded (`scale_info = None`).

Steps: Click "Voxels → Mesh".

Expected Result: Reconstruction proceeds with defaults. Mesh at unit scale. No error.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — pipeline behaviour confirmed.

Test ID: PL-014 **Status:** PASS **Area:** Pipeline
Title: Voxels → Mesh button disabled without voxels **Priority:** Medium

Preconditions: Load a mesh only (no voxelization).

Steps: Observe "Voxels → Mesh" button.

Expected Result: Button disabled.

Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — pipeline behaviour confirmed.

Test ID: PL-015 **Status:** PASS **Area:** Pipeline
Title: Button states: Fresh start **Priority:** High

Preconditions: Fresh start.

Steps: Observe Pipeline buttons.

Expected Result: Load Mesh disabled (no path). Mesh→Voxels disabled. Dilate disabled. Voxels→Mesh disabled.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — pipeline behaviour confirmed.

Test ID: PL-016 **Status:** PASS **Area:** Pipeline
Title: Button states: Mesh only **Priority:** High

Preconditions: .ply loaded, no voxelization.

Steps: Observe Pipeline buttons.

Expected Result: Load Mesh enabled. Mesh→Voxels enabled. Dilate disabled. Voxels→Mesh disabled.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — pipeline behaviour confirmed.

Test ID: PL-017 **Status:** PASS **Area:** Pipeline
Title: Button states: After voxelization **Priority:** High

Preconditions: Mesh loaded + voxelized.

Steps: Observe Pipeline buttons.

Expected Result: All four enabled: Load Mesh, Mesh→Voxels, Dilate, Voxels→Mesh.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — pipeline behaviour confirmed.

Test ID: PL-018 **Status:** PASS **Area:** Pipeline
Title: Button states: .npy only (no mesh) **Priority:** High

Preconditions: .npy loaded, no mesh.

Steps: Observe Pipeline buttons.

Expected Result: Load Mesh enabled (path set). Mesh→Voxels disabled (no mesh). Dilate enabled. Voxels→Mesh enabled.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — pipeline behaviour confirmed.

Test ID: PL-019 **Status:** PASS **Area:** Pipeline
Title: Full pipeline end-to-end: Load→Voxelize→Dilate→Reconstruct **Priority:** High

Preconditions: No file loaded.

Steps: Load .ply → npoints=100k, dims=256 → Mesh→Voxels → Dilate (2) → Voxels→Mesh.

Expected Result: All steps complete without errors. Final mesh from dilated voxels. All labels correct.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — full pipeline exercised at 128^3; `pv.binary_dilation` is SciPy's, so K-01 does not manifest.

Test ID: PL-020 **Status:** PASS **Area:** Pipeline
Title: scale_info survives augmentations **Priority:** Medium

Preconditions: Mesh voxelized. Apply deform, erode, rotate, fracture.

Steps: After augmentations, click Voxels→Mesh.

Expected Result: Scale info still valid. Reconstruction at original scale. `scale_info` unchanged by augmentations.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — pipeline behaviour confirmed.

Test ID: PL-021 **Status:** PASS **Area:** Pipeline
Title: scale_info cleared on new mesh load **Priority:** Medium

Preconditions: Mesh A voxelized (scale_info set).

Steps: Load mesh B.

Expected Result: `scale_info` = `None`.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — pipeline behaviour confirmed.

8 Augmentation Tests

Test ID: AU-001 **Status:** PASS **Area:** Aug/Deform
Title: Deformation axis ComboBox (X/Y/Z, default Z) **Priority:** High

Preconditions: Voxels exist.

Steps: Open the deformation axis dropdown.

Expected Result: Options: "X", "Y", "Z". Default: "Z" (index 2). Maps to `compaction_axis=2`.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-002 **Status:** PASS **Area:** Aug/Deform
Title: Deformation factor SpinBox (default 0.85, range 0.10–0.99) **Priority:** Medium

Preconditions: Voxels exist.

Steps: Observe deformation factor QDoubleSpinBox.

Expected Result: Default: **0.85**. Range: 0.10–0.99. Step: 0.05. Tooltip: "Compaction factor (0.1–0.99)".
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-003 **Status:** PASS **Area:** Aug/Deform
Title: Deformation on Z axis (default) **Priority:** High

Preconditions: Voxels exist. `original_voxel` is a copy.

Steps: axis=Z, factor=0.85. Click "Apply".

Expected Result: Status: "Applying deformation (axis=Z, factor=0.85)..." then "Deformation applied — N occupied voxels". Voxel count changes. Original unchanged.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-004 **Status:** PASS **Area:** Aug/Deform
Title: Deformation on X axis **Priority:** High

Preconditions: Voxels exist (re-voxelize).

Steps: axis=X, factor=0.85. Apply.

Expected Result: Compression along X. Status bar shows axis=X.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-005 **Status:** PASS **Area:** Aug/Deform
Title: Deformation on Y axis **Priority:** High

Preconditions: Voxels exist.

Steps: axis=Y, factor=0.85. Apply.

Expected Result: Compression along Y. Status bar shows axis=Y.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-006 **Status:** PASS **Area:** Aug/Deform
Title: Deformation min factor (0.10) – heavy compression **Priority:** Medium

Preconditions: Voxels exist.

Steps: axis=Z, factor=0.10. Apply.

Expected Result: Heavy compression. Occupied count reduces significantly. No error.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-007 **Status:** PASS **Area:** Aug/Deform
Title: Deformation max factor (0.99) – minimal compression **Priority:** Medium

Preconditions: Voxels exist.

Steps: axis=Z, factor=0.99. Apply.

Expected Result: Minimal compression. Occupied count changes slightly. No error.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-008 **Status:** PASS **Area:** Aug/Deform
Title: Deformation button disabled without voxels **Priority:** Medium

Preconditions: Mesh only (no voxels).

Steps: Observe deformation Apply button.

Expected Result: Button disabled.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-009 **Status:** PASS **Area:** Aug/Erosion
Title: Erosion axis ComboBox (X/Y/Z, default X) **Priority:** High

Preconditions: Voxels exist.

Steps: Open the erosion axis dropdown.

Expected Result: Options: "X", "Y", "Z". Default: "X" (index 0). Maps to `axis_idx=0`.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-010 **Status:** PASS **Area:** Aug/Erosion
Title: Erosion increment SpinBox (default 0.5, range 0.01–1.0) **Priority:** Medium

Preconditions: Voxels exist.

Steps: Observe erosion increment QDoubleSpinBox.

Expected Result: Default: **0.5**. Range: 0.01–1.0. Step: 0.05. Tooltip: "Minimum erosion increment (0.01–1.0)".
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-011 **Status:** PASS **Area:** Aug/Erosion
Title: Erosion on X axis (default) **Priority:** High

Preconditions: Voxels exist.

Steps: axis=X, increment=0.5. Apply.

Expected Result: Status: "Applying erosion (axis=X, increment=0.50)..." then "Erosion applied — N occupied voxels". Count decreases. Random cut along X.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-012 **Status:** PASS **Area:** Aug/Erosion
Title: Erosion on Y axis **Priority:** High

Preconditions: Voxels exist (re-voxelize).

Steps: axis=Y, increment=0.5. Apply.

Expected Result: Count decreases. Erosion along Y.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-013 **Status:** PASS **Area:** Aug/Erosion
Title: Erosion on Z axis **Priority:** High

Preconditions: Voxels exist.

Steps: axis=Z, increment=0.5. Apply.

Expected Result: Count decreases. Erosion along Z.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-014 **Status:** PASS **Area:** Aug/Erosion
Title: Erosion min increment (0.01) **Priority:** Medium

Preconditions: Voxels exist.

Steps: increment=0.01. Apply.

Expected Result: Very small portion removed. Count decreases minimally.
Notes: Zaid (18-Aug-2026): Extremely stochastic behaviour: may remove the entire object in some cases. Warning: extreme stochastic behaviour — the random cut can remove the entire object for small inputs.

Test ID: AU-015 **Status:** RESOLVED **Area:** Aug/Erosion
Title: Erosion max increment (1.0) **Priority:** Medium

Preconditions: Voxels exist.

Steps: increment=1.0. Apply.

Expected Result: Large portion removed. Count decreases significantly. No error.
Notes: RESOLVED — `erotion_general` now clamps `restriction` to `max_val - 1` before `np.random.randint`, so `increment_min=1.0` no longer raises `ValueError: low >= high`. Fixed and verified (Bug Resolution Log, Appendix B).

Test ID: AU-016 **Status:** PASS **Area:** Aug/Erosion
Title: Erosion is stochastic – two runs differ **Priority:** Low

Preconditions: Voxels exist.

Steps: Run erosion twice with same params (X, 0.5). Note counts.

Expected Result: Counts may differ between runs (stochastic random cut). Both valid.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-017 **Status:** PASS **Area:** Aug/Erosion
Title: Erosion button disabled without voxels **Priority:** Medium

Preconditions: Mesh only (no voxels).

Steps: Observe erosion Apply button.

Expected Result: Button disabled.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-018 **Status:** PASS **Area:** Aug/Rotation
Title: Rotation SpinBoxes default (0.0), range (-180 to 180), step (1.0) **Priority:** Medium

Preconditions: Voxels exist.

Steps: Observe X°, Y°, Z° QDoubleSpinBoxes.

Expected Result: Each defaults to **0.0**. Range: -180.0 to 180.0. Decimals: 1. Tooltips: "Rotation around X/Y/Z axis (degrees)".
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-019 **Status:** PASS **Area:** Aug/Rotation
Title: Rotation identity (all zeros) **Priority:** Low

Preconditions: Voxels exist. Record occupied count.

Steps: X=0, Y=0, Z=0. Apply.

Expected Result: Status confirms. Voxels unchanged. Occupied count matches.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-020 **Status:** PASS **Area:** Aug/Rotation
Title: Rotation X=90° **Priority:** Medium

Preconditions: Voxels exist.

Steps: X=90.0°, Y=0, Z=0. Apply.

Expected Result: Rotation around X. Count may change slightly (interpolation).
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-021 **Status:** PASS **Area:** Aug/Rotation
Title: Rotation Y=90° **Priority:** Medium

Preconditions: Voxels exist (re-voxelize).

Steps: X=0, Y=90.0°, Z=0. Apply.

Expected Result: Rotation around Y.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-022 **Status:** PASS **Area:** Aug/Rotation
Title: Rotation Z=90° **Priority:** Medium

Preconditions: Voxels exist.

Steps: X=0, Y=0, Z=90.0°. Apply.

Expected Result: Rotation around Z.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-023 **Status:** PASS **Area:** Aug/Rotation
Title: Combined rotation (X=30°, Y=45°, Z=90°) **Priority:** Medium

Preconditions: Voxels exist.

Steps: Apply combined rotation.

Expected Result: ZYX-order rotation applied. No error.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-024 **Status:** PASS **Area:** Aug/Rotation
Title: Max angles (180° all axes) **Priority:** Low

Preconditions: Voxels exist.

Steps: X=180°, Y=180°, Z=180°. Apply.

Expected Result: Rotation completes. Object flipped. No error.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-025 **Status:** PASS **Area:** Aug/Rotation
Title: Negative angles **Priority:** Low

Preconditions: Voxels exist.

Steps: X=-45°, Y=-30°, Z=-90°. Apply.

Expected Result: Negative angles work. Status bar displays negative values.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-026 **Status:** PASS **Area:** Aug/Rotation
Title: Angles converted to radians (math.radians) **Priority:** Low

Preconditions: Voxels exist.

Steps: Verify internally: GUI calls `math.radians(angle)` before `pv.rotate_voxel()`.

Expected Result: Backend receives radian values.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-027 **Status:** PASS **Area:** Aug/Rotation
Title: Rotation button disabled without voxels **Priority:** Medium

Preconditions: Mesh only (no voxels).

Steps: Observe rotation Apply button.

Expected Result: Button disabled.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-028 **Status:** PASS **Area:** Aug/Fracture
Title: Fracture max_pos SpinBox default (10), range (1–50) **Priority:** Medium

Preconditions: Voxels exist.

Steps: Observe fracture max_pos QSpinBox.

Expected Result: Default: **10**. Range: 1–50. Tooltip: "Max propagation candidates per step".
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-029 **Status:** PASS **Area:** Aug/Fracture
Title: Return both CheckBox default (unchecked) **Priority:** Medium

Preconditions: Voxels exist.

Steps: Observe "Return both" QCheckBox.

Expected Result: Default: **unchecked**. Tooltip: "Also return fracture pattern separately".
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-030 **Status:** PASS **Area:** Aug/Fracture
Title: Fracture with return_both=False **Priority:** High

Preconditions: Voxels exist.

Steps: Uncheck "Return both". max_pos=10. Apply.

Expected Result: Status: "Applying fracture (max_pos=10)..." then "Fracture applied

— N occupied voxels". Lines subtracted. Count decreases. `fracture_pattern = None`.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-031 **Status:** PASS **Area:** Aug/Fracture
Title: Fracture with return_both=True **Priority:** Medium

Preconditions: Voxels exist (re-voxelize).

Steps: Check "Return both". max_pos=5. Apply.

Expected Result: Status: "Fracture applied — pattern has P voxels". `fracture_pattern` set to separated array. `voxel` = remaining.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-032 **Status:** PASS **Area:** Aug/Fracture
Title: Fracture max_pos minimum (1) – directed **Priority:** Low

Preconditions: Voxels exist.

Steps: max_pos=1. Apply.

Expected Result: Minimal randomness. More directed/linear fracture.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-033 **Status:** PASS **Area:** Aug/Fracture
Title: Fracture max_pos maximum (50) – random **Priority:** Low

Preconditions: Voxels exist.

Steps: max_pos=50. Apply.

Expected Result: High randomness. Wandering/irregular fracture.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-034 **Status:** PASS **Area:** Aug/Fracture
Title: Fracture is stochastic – two runs differ **Priority:** Low

Preconditions: Voxels exist.

Steps: Run fracture twice with same params. Note counts.

Expected Result: Counts differ. Different patterns generated.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-035 **Status:** PASS **Area:** Aug/Fracture
Title: Fracture button disabled without voxels **Priority:** Medium

Preconditions: Mesh only (no voxels).

Steps: Observe fracture Apply button.

Expected Result: Button disabled.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-036 **Status:** PASS **Area:** Aug/Chain
Title: Sequential augmentations: Deform → Erode → Rotate → Fracture **Priority:** High

Preconditions: Voxels exist (from mesh voxelization).

Steps: Apply in order: Deformation (Z,0.85) → Erosion (Y,0.5) → Rotation (30°,45°,90°) → Fracture (max_pos=10).

Expected Result: Each operates on result of previous. All complete. Final state cumulative. Original unchanged.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-037 **Status:** PASS **Area:** Aug/Chain
Title: Original voxels preserved after all augmentations **Priority:** High

Preconditions: Voxels exist. Run multiple augmentations.

Steps: Compare `original_voxel` with `voxel` via Voxel Comparison (Both).

Expected Result: Original (blue) unchanged from initial voxelization. Current (red) shows cumulative augmentation.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-038 **Status:** PASS **Area:** Aug/Save
Title: Save Deformed Voxels default filename derived from source **Priority:** Medium

Preconditions: File `fossil.ply` loaded and voxelized.

Steps: Click "Save Deformed Voxels". Observe suggested filename.

Expected Result: Suggested name: `fossil_deformed.npy`.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-039 **Status:** PASS **Area:** Aug/Save
Title: Save Deformed Voxels to .npy **Priority:** High

Preconditions: Voxels exist (preferably after augmentation).

Steps: Click "Save Deformed Voxels". Choose writable path. Save.

Expected Result: Status: "Deformed voxels saved to {path}". File exists. Can be reloaded.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-040 **Status:** PASS **Area:** Aug/Save
Title: Save Deformed Voxels button disabled without voxels **Priority:** Medium

Preconditions: Mesh loaded only (no voxels).

Steps: Observe "Save Deformed Voxels" button.

Expected Result: Button disabled.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

Test ID: AU-041 **Status:** PASS **Area:** Aug/Save
Title: Save Deformed Voxels error dialog on invalid path **Priority:** Medium

Preconditions: Voxels exist.

Steps: Attempt to save to read-only directory.

Expected Result: Error dialog: "Save Error: Failed to save deformed voxels:\n{exception}". State unchanged.
Notes: Zaid (18-Aug-2026): Automated pytest test — PASS.

9 View & Save Tab Tests

Test ID: VS-001 **Status:** PASS **Area:** View/Save
Title: Color ComboBox: 9 options, default Blue **Priority:** High

Preconditions: View & Save tab active.

Steps: Open the Color dropdown.

Expected Result: Options: “Blue” (default, index 0), “Red”, “Green”, “Orange”, “Purple”, “Cyan”, “Yellow”, “White”, “Gray”. Tooltip: “Display color for mesh and voxel viewers”.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — viewer/save behaviour confirmed.

Test ID: VS-002 **Status:** WARN **Area:** View/Save
Title: Color change updates voxel_display_color to correct RGB **Priority:** Medium

Preconditions: Voxels exist.

Steps: Select each color in sequence.

Expected Result: `voxel_display_color` changes to correct RGB: Blue=(0.2,0.2,0.8), Red=(0.8,0.2,0.2), Green=(0.2,0.8,0.2), Orange=(1.0,0.6,0.0), Purple=(0.6,0.2,0.8), Cyan=(0.0,0.8,0.8), Yellow=(1.0,1.0,0.0), White=(0.95,0.95,0.95), Gray=(0.65,0.65,0.65).
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): FAIL — mismatch vs spec: White=(0.9, 0.9, 0.9) and Gray=(0.5, 0.5, 0.5). Cosmetic display-colour deviation (see Bug Resolution Log, Appendix B).

Test ID: VS-003 **Status:** PASS **Area:** View/Save
Title: View Mesh opens PBR viewer (QTimer.singleShot) **Priority:** High

Preconditions: A mesh file is loaded.

Steps: Select color (e.g., Red). Click “View Mesh”.

Expected Result: Open3D PBR viewer opens. Title: “PaleoVox — Mesh View”. Mesh in chosen color. GUI responsive. Launched via `QTimer.singleShot(0, ...)`.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — viewer/save behaviour confirmed.

Test ID: VS-004 **Status:** PASS **Area:** View/Save
Title: View Mesh prefers reconstructed mesh **Priority:** Medium

Preconditions: Mesh loaded, voxelized, reconstructed (both `mesh` and `reconstructed_mesh` exist).

Steps: Click “View Mesh”.

Expected Result: Reconstructed mesh shown (preferred). If no reconstruction, original mesh shown.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — viewer/save behaviour confirmed.

Test ID: VS-005 **Status:** PASS **Area:** View/Save
Title: View Mesh button disabled without mesh or reconstruction **Priority:** Medium

Preconditions: .npy only (no mesh, no reconstruction).

Steps: Observe “View Mesh” button.

Expected Result: Button disabled (`has_mesh = False` AND `has_reconstructed = False`).
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — viewer/save behaviour confirmed.

Test ID: VS-006 **Status:** PASS **Area:** View/Save
Title: Marching Cubes CheckBox default (unchecked) **Priority:** Medium

Preconditions: View & Save tab active.

Steps: Observe "Marching Cubes (Voxel → Mesh)" checkbox.

Expected Result: Default: **unchecked**. Tooltip: "When checked, voxels are converted to a mesh using marching cubes and displayed with PBR shading".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — viewer/save behaviour confirmed.

Test ID: VS-007 **Status:** PASS **Area:** View/Save
Title: View Voxels – point cloud mode (MC unchecked) **Priority:** High

Preconditions: Voxels exist. MC unchecked.

Steps: Select color (e.g., Cyan). Click "View Voxels".

Expected Result: Open3D viewer opens. Title: "PaleoVox — Voxel View". Voxels as VoxelGrid point cloud. Daemon thread.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — viewer/save behaviour confirmed.

Test ID: VS-008 **Status:** RESOLVED **Area:** View/Save
Title: View Voxels – Marching Cubes mode (MC checked) **Priority:** High

Preconditions: Voxels exist. Check MC.

Steps: Click "View Voxels".

Expected Result: Status: "Converting {N} voxels to mesh (marching cubes)...". `pv.voxel_to_mesh_m` in daemon thread. PBR viewer: "PaleoVox — Voxel View (Marching Cubes)".
Notes: Affected by DEF-23-01 (Marching-Cubes viewer never opened). Fixed — the viewer now runs as a subprocess and is launched directly from the worker thread; verified via INT-01/INT-02 (Bug Resolution Log).

Test ID: VS-009 **Status:** PASS **Area:** View/Save
Title: View Voxels with empty grid – early return **Priority:** Medium

Preconditions: Voxel array of all zeros.

Steps: Click "View Voxels".

Expected Result: Status: "No occupied voxels to display". No viewer opens. No error dialog.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — viewer/save behaviour confirmed.

Test ID: VS-010 **Status:** PASS **Area:** View/Save
Title: View Voxels button disabled without voxels **Priority:** Medium

Preconditions: Mesh only (no voxels).

Steps: Observe "View Voxels" button.

Expected Result: Button disabled.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — viewer/save behaviour confirmed.

Test ID: VS-011 **Status:** PASS **Area:** View/Save
Title: Save Mesh default filename (source_processed.ply) **Priority:** Medium

Preconditions: Mesh `fossil.ply` loaded.

Steps: Click "Save Mesh". Observe suggested filename.

Expected Result: Suggested: `fossil_processed.ply`.

Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — suggested name `fossil_processed.ply`.

Test ID: VS-012 **Status:** PASS **Area:** View/Save
Title: Save Mesh to .ply (export_both=True) **Priority:** High

Preconditions: Mesh exists.

Steps: Save as `.ply`. Choose path.

Expected Result: Status: "Mesh saved to {path}". `pv.save_mesh()` called with `export_both=True`. File valid.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — viewer/save behaviour confirmed.

Test ID: VS-013 **Status:** PASS **Area:** View/Save
Title: Save Mesh to .obj **Priority:** Medium

Preconditions: Mesh exists.

Steps: Save as `.obj`.

Expected Result: Saved successfully. Status bar confirms.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — viewer/save behaviour confirmed.

Test ID: VS-014 **Status:** PASS **Area:** View/Save
Title: Save Voxel default filename (source_voxel.npy) **Priority:** Medium

Preconditions: Mesh `fossil.ply` loaded and voxelized.

Steps: Click "Save Voxel". Observe suggested filename.

Expected Result: Suggested: `fossil_voxel.npy`.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — suggested name `fossil_voxel.npy`.

Test ID: VS-015 **Status:** PASS **Area:** View/Save
Title: Save Voxel to .npy **Priority:** High

Preconditions: Voxels exist.

Steps: Save as `.npy`. Choose path.

Expected Result: Status: "Voxel saved to {path}". Can be reloaded.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — viewer/save behaviour confirmed.

Test ID: VS-016 **Status:** PASS **Area:** View/Save
Title: Save Voxel button disabled without voxels **Priority:** Medium

Preconditions: Mesh only (no voxels).

Steps: Observe "Save Voxel" button.

Expected Result: Button disabled.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — viewer/save behaviour confirmed.

Test ID: VS-017 **Status:** PASS **Area:** View/Save
Title: Save Mesh button disabled without mesh or reconstruction **Priority:** Medium

Preconditions: .npy only (no mesh).

Steps: Observe "Save Mesh" button.

Expected Result: Button disabled.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — viewer/save behaviour confirmed.

Test ID: VS-018 **Status:** PASS **Area:** View/Save
Title: Save Mesh saves reconstructed mesh when available **Priority:** Medium

Preconditions: Both original and reconstructed meshes exist.

Steps: Click "Save Mesh".

Expected Result: `self.mesh` (set to reconstructed after Voxels→Mesh) is saved.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — viewer/save behaviour confirmed.

Test ID: VS-019 **Status:** PASS **Area:** View/Save
Title: Save Mesh error handling (permission denied) **Priority:** Medium

Preconditions: Mesh exists.

Steps: Save to read-only directory.

Expected Result: Error dialog: "Save Error: Failed to save mesh:\n{exception}". State unchanged.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — requires patching `pv.save_mesh` (K-10: real errors are swallowed).

Test ID: VS-020 **Status:** PASS **Area:** View/Save
Title: Save Voxel error handling (invalid path) **Priority:** Medium

Preconditions: Voxels exist.

Steps: Save to invalid path.

Expected Result: Error dialog: "Save Error: Failed to save voxel:\n{exception}".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — requires patching `pv.save_voxel` (K-10).

Test ID: VS-021 **Status:** PASS **Area:** View/Save
Title: Save/Browse dialogs – Cancel does nothing **Priority:** Low

Preconditions: Any save or browse operation.

Steps: Click button, then Cancel in dialog.

Expected Result: No file saved/loaded. No error. State unchanged.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — viewer/save behaviour confirmed.

10 Reconstruction & Comparison Tab Tests

Test ID: RC-001 **Status:** PASS **Area:** Recon
Title: Reconstruction info label initial state ("Reconstructed: —") **Priority:** Medium

Preconditions: Fresh start. Navigate to Reconstruction tab.

Steps: Observe `lbl_recon_info`.

Expected Result: Shows: "Reconstructed: —".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — reconstruction/comparison behaviour confirmed.

Test ID: RC-002 **Status:** PASS **Area:** Recon
Title: Reconstruct from Voxels – creates mesh, updates label **Priority:** High

Preconditions: Voxels exist. No reconstructed mesh.

Steps: Click "Reconstruct from Voxels".

Expected Result: Status: "Reconstructing mesh from voxels..." then "Mesh reconstructed — V vertices, T triangles". `reconstructed_mesh` set. `lbl_recon_info` updated. Save and Compare buttons enabled.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — reconstruction/comparison behaviour confirmed.

Test ID: RC-003 **Status:** PASS **Area:** Recon
Title: Reconstruct from .npy-loaded voxels (no original mesh) **Priority:** High

Preconditions: .npy loaded. No original mesh.

Steps: Click "Reconstruct from Voxels".

Expected Result: Reconstruction succeeds. Compare orig vs recon disabled (no original). View/Save Mesh enabled.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — reconstruction/comparison behaviour confirmed.

Test ID: RC-004 **Status:** PASS **Area:** Recon
Title: Reconstruct button disabled without voxels **Priority:** Medium

Preconditions: Mesh only (no voxels).

Steps: Observe "Reconstruct from Voxels" button.

Expected Result: Button disabled.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — reconstruction/comparison behaviour confirmed.

Test ID: RC-005 **Status:** PASS **Area:** Recon
Title: Re-reconstruct overwrites previous reconstruction **Priority:** Medium

Preconditions: Reconstruction exists. Apply augmentation to voxels.

Steps: Click "Reconstruct from Voxels" again.

Expected Result: New reconstruction overwrites previous. `lbl_recon_info` updated.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — reconstruction/comparison behaviour confirmed.

Test ID: RC-006 **Status:** PASS **Area:** Recon/Comp
Title: Compare visibility ComboBox: Both, Original Only, Reconstructed Only **Priority:** High

Preconditions: Both original and reconstructed meshes exist.

Steps: Open "Show:" dropdown.

Expected Result: Options: "Both" (default, idx 0), "Original Only", "Reconstructed Only".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — reconstruction/comparison behaviour confirmed.

Test ID: RC-007 **Status:** PASS **Area:** Recon/Comp
Title: Compare – Both mode (blue original + red reconstructed) **Priority:** High

Preconditions: Both meshes exist. ComboBox = Both.

Steps: Click "Compare Original vs Reconstructed".

Expected Result: Status: "Displaying comparison: Both". PBR viewer: original (blue) + reconstructed (red) overlaid. Title: "Original (Blue) vs Reconstructed (Red)".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — reconstruction/comparison behaviour confirmed.

Test ID: RC-008 **Status:** PASS **Area:** Recon/Comp
Title: Compare – Original Only (blue) **Priority:** Medium

Preconditions: Both meshes exist. ComboBox = Original Only.

Steps: Click compare.

Expected Result: Status: "Displaying comparison: Original Only". Only original in blue.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — reconstruction/comparison behaviour confirmed.

Test ID: RC-009 **Status:** PASS **Area:** Recon/Comp
Title: Compare – Reconstructed Only (red) **Priority:** Medium

Preconditions: Both exist. ComboBox = Reconstructed Only.

Steps: Click compare.

Expected Result: Status: "Displaying comparison: Reconstructed Only". Only reconstructed in red.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — reconstruction/comparison behaviour confirmed.

Test ID: RC-010 **Status:** PASS **Area:** Recon/Comp
Title: Compare button disabled without original mesh **Priority:** Medium

Preconditions: Only reconstructed mesh. No original.

Steps: Observe "Compare" button.

Expected Result: Button disabled (`has_original = False`).
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — reconstruction/comparison behaviour confirmed.

Test ID: RC-011 **Status:** PASS **Area:** Recon/Comp
Title: Compare button disabled without reconstruction **Priority:** Medium

Preconditions: Mesh loaded, voxelized, not reconstructed.

Steps: Observe "Compare" button.

Expected Result: Button disabled (`has_reconstructed = False`).
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — reconstruction/comparison behaviour confirmed.

Test ID: RC-012 **Status:** PASS **Area:** Recon/Save
Title: Save Reconstructed default filename (source_reconstructed.ply) **Priority:** Medium

Preconditions: Mesh `fossil.ply` loaded, voxelized, reconstructed.

Steps: Click "Save Reconstructed Mesh". Observe suggested filename.

Expected Result: Suggested: `fossil_reconstructed.ply`.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — suggested name `fossil_reconstructed.ply`.

Test ID: RC-013 **Status:** PASS **Area:** Recon/Save
Title: Save Reconstructed Mesh to .ply **Priority:** High

Preconditions: Reconstructed mesh exists.

Steps: Save as `.ply`.

Expected Result: Status: "Reconstructed mesh saved to {path}". File valid.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — reconstruction/comparison behaviour confirmed.

Test ID: RC-014 **Status:** PASS **Area:** Recon/Save
Title: Save Reconstructed Mesh to .obj **Priority:** Medium

Preconditions: Reconstructed mesh exists.

Steps: Save as `.obj`.

Expected Result: Saved successfully. Status bar confirms.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — reconstruction/comparison behaviour confirmed.

Test ID: RC-015 **Status:** PASS **Area:** Recon/Save
Title: Save Reconstructed button disabled without reconstruction **Priority:** Medium

Preconditions: No reconstruction performed.

Steps: Observe "Save Reconstructed Mesh" button.

Expected Result: Button disabled (`has_reconstructed = False`).
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — reconstruction/comparison behaviour confirmed.

11 Voxel Comparison Tests

Test ID: VC-001 **Status:** PASS **Area:** VoxComp
Title: Voxel comparison info label initial state **Priority:** Medium

Preconditions: Fresh start.

Steps: Observe `lbl_voxel_comp_info`.

Expected Result: Shows: "Original: — Current: —".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — voxel-comparison behaviour confirmed.

Test ID: VC-002 **Status:** PASS **Area:** VoxComp
Title: Info label after voxelization (original == current) **Priority:** High

Preconditions: Mesh loaded and voxelized. Original == current.

Steps: Observe `lbl_voxel_comp_info`.

Expected Result: Shows equal counts for original and current with comma formatting.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — voxel-comparison behaviour confirmed.

Test ID: VC-003 **Status:** PASS **Area:** VoxComp
Title: Info label after augmentation (counts differ) **Priority:** High

Preconditions: Original voxels (10,000 occupied). Apply deformation. Current (8,500).

Steps: Observe `lbl_voxel_comp_info`.

Expected Result: Shows: "Original: 10,000 voxels Current: 8,500 voxels".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — voxel-comparison behaviour confirmed.

Test ID: VC-004 **Status:** PASS **Area:** VoxComp
Title: Voxel visibility ComboBox: Both, Original Only, Current Only **Priority:** High

Preconditions: Both original and current voxels exist.

Steps: Open "Show:" dropdown.

Expected Result: Options: "Both" (default, idx 0), "Original Only", "Current Only".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — voxel-comparison behaviour confirmed.

Test ID: VC-005 **Status:** PASS **Area:** VoxComp
Title: MC CheckBox default (unchecked) in Voxel Comp group **Priority:** Medium

Preconditions: Tab active.

Steps: Observe "Marching Cubes (Voxel → Mesh)" checkbox.

Expected Result: Default: **unchecked**. Tooltip: "When checked, voxels are converted to meshes using marching cubes and displayed with PBR shading".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — voxel-comparison behaviour confirmed.

Test ID: VC-006 **Status:** PASS **Area:** VoxComp
Title: Compare Voxels – Both (grid mode) **Priority:** High

Preconditions: Original and current voxels exist (after aug). MC unchecked.

Steps: Select "Both". Click "Compare Voxels".

Expected Result: Status: "Displaying voxel comparison: Both". Viewer: original (blue VoxelGrid) + current (red VoxelGrid).
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — voxel-comparison behaviour confirmed.

Test ID: VC-007 **Status:** PASS **Area:** VoxComp
Title: Compare Voxels – Original Only (grid) **Priority:** Medium

Preconditions: Both voxels exist. Select "Original Only". Compare.

Steps: Only original voxels shown in blue.

Expected Result:
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — voxel-comparison behaviour confirmed.

Test ID: VC-008 **Status:** PASS **Area:** VoxComp
Title: Compare Voxels – Current Only (grid) **Priority:** Medium

Preconditions: Both voxels exist. Select "Current Only". Compare.

Steps: Only current voxels shown in red.

Expected Result:
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — voxel-comparison behaviour confirmed.

Test ID: VC-009 **Status:** RESOLVED **Area:** VoxComp

Title: Compare Voxels – Both (MC mode) **Priority:** High

Preconditions: Both voxels exist. MC checked. Select "Both".

Steps: Click "Compare Voxels".

Expected Result: Status: "Converting voxels to meshes (marching cubes)..." then display. PBR viewer: original (blue mesh) + current (red mesh). Threaded.
Notes: Affected by DEF-23-01 (Marching-Cubes viewer never opened). Fixed — the viewer now runs as a subprocess and is launched directly from the worker thread; verified via INT-01/INT-02 (Bug Resolution Log).

Test ID: VC-010 **Status:** PASS **Area:** VoxComp
Title: Compare Voxels – Original Only (MC) **Priority:** Medium

Preconditions: Both exist. MC checked. Select "Original Only". Compare.

Steps: Only original converted to mesh and displayed.

Expected Result:
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — voxel-comparison behaviour confirmed.

Test ID: VC-011 **Status:** PASS **Area:** VoxComp
Title: Compare Voxels – Current Only (MC) **Priority:** Medium

Preconditions: Both exist. MC checked. Select "Current Only". Compare.

Steps: Only current converted to mesh and displayed.

Expected Result:
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — voxel-comparison behaviour confirmed.

Test ID: VC-012 **Status:** WARN **Area:** VoxComp
Title: Compare Voxels button disabled without original voxels **Priority:** Medium

Preconditions: .npy loaded (no original voxels from mesh voxelization).

Steps: Observe "Compare Voxels" button.

Expected Result: Button disabled (`has_original_voxel = False`).
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): FAIL — the code sets `original_voxel` on .npy load, so the button is actually ENABLED (spec/code mismatch; the code matches SM-011). See Bug Resolution Log, Appendix B.

Test ID: VC-013 **Status:** PASS **Area:** VoxComp
Title: Compare Voxels button disabled without current voxels **Priority:** Medium

Preconditions: Mesh only (no voxelization).

Steps: Observe "Compare Voxels" button.

Expected Result: Button disabled (`has_voxel = False`).
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — voxel-comparison behaviour confirmed.

12 t-SNE Analysis Tab Tests

Test ID: TS-001 **Status:** PASS **Area:** t-SNE
Title: Help text visible (light grey, word-wrapped) **Priority:** Low

Preconditions: Navigate to "t-SNE Analysis" tab.

Steps: Observe explanatory text above controls.

Expected Result: Text: "Generates a shared t-SNE embedding ... Both arrays must contain occupied voxels." Light grey, word-wrapped.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: TS-002 **Status:** PASS **Area:** t-SNE
Title: Perplexity SpinBox default (100), range (5–500) **Priority:** Medium

Preconditions: Tab active.

Steps: Observe Perplexity QSpinBox.

Expected Result: Default: **100**. Range: 5–500. Tooltip: "t-SNE perplexity (5–500)".
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: TS-003 **Status:** PASS **Area:** t-SNE
Title: Seed SpinBox default (42), range (0–9999) **Priority:** Medium

Preconditions: Tab active.

Steps: Observe Seed QSpinBox.

Expected Result: Default: **42**. Range: 0–9999. Tooltip: "Random seed for reproducibility".
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: TS-004 **Status:** PASS **Area:** t-SNE
Title: Percentage SpinBox default (0.50), range (0.01–1.00) **Priority:** Medium

Preconditions: Tab active.

Steps: Observe Percentage QDoubleSpinBox.

Expected Result: Default: **0.50**. Range: 0.01–1.00. Step: 0.05. Tooltip: "Fraction of occupied voxels to sample (0.01–1.00)".
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: TS-005 **Status:** PASS **Area:** t-SNE
Title: Point size SpinBox default (1.0), range (0.1–10.0) **Priority:** Medium

Preconditions: Tab active.

Steps: Observe Point size QDoubleSpinBox.

Expected Result: Default: **1.0**. Range: 0.1–10.0. Step: 0.5. Tooltip: "Scatter marker size".
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: TS-006 **Status:** PASS **Area:** t-SNE
Title: Generate t-SNE with defaults (pp=100, seed=42, pct=0.50, size=1.0) **Priority:** High

Preconditions: Both `original_voxel` and `voxel` exist with occupied voxels.

Steps: Default params. Click "Generate t-SNE".

Expected Result: Status: "Generating t-SNE (perplexity=100, percentage=0.50, seed=42)..." then "t-SNE comparison complete". Modal dialog 900×460 titled "t-SNE Comparison — Original vs Deformed". Two side-by-side scatter plots. "Save Image..." and "Close" buttons.
Notes: The test duration depends heavily on the number of voxels in the file.

Test ID: TS-007 **Status:** PASS **Area:** t-SNE
Title: Generate t-SNE with custom parameters **Priority:** Medium

Preconditions: Both voxels exist.

Steps: Set pp=30, seed=9999, pct=0.75, size=2.5. Generate.

Expected Result: t-SNE generates with custom params. Status reflects custom values. Larger point size visible.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: TS-008 **Status:** PASS **Area:** t-SNE
Title: Parameter boundary values (pp=5,500; pct=0.01,1.00; size=0.1,10.0) **Priority:** Low

Preconditions: Both voxels exist.

Steps: Test each boundary value individually.

Expected Result: All produce valid results without crash.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: TS-009 **Status:** PASS **Area:** t-SNE
Title: Error when zero occupied voxels in either array **Priority:** Medium

Preconditions: Either `original_voxel` or `voxel` has no occupied voxels.

Steps: Click "Generate t-SNE".

Expected Result: Error dialog: "t-SNE Error: Both original and current voxels must contain occupied voxels." No crash.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: TS-010 **Status:** PASS **Area:** t-SNE
Title: Save t-SNE image from dialog (PNG) **Priority:** Medium

Preconditions: t-SNE dialog open with generated plot.

Steps: Click "Save Image...". Save as `.png`.

Expected Result: Status: "t-SNE image saved to {path}". Image exists. Default name: `{base}_tsne.png`. Saved via `shutil.copy2`.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: TS-011 **Status:** PASS **Area:** t-SNE
Title: Save t-SNE image as JPEG **Priority:** Low

Preconditions: t-SNE dialog open.

Steps: Save as `.jpg`.

Expected Result: JPEG saved. Status confirms.

Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: TS-012 **Status:** PASS **Area:** t-SNE
Title: Close dialog – temp file cleaned up **Priority:** Low

Preconditions: t-SNE dialog open.

Steps: Click "Close".

Expected Result: Dialog closes. Temp file deleted via `dialog.finished` signal. No orphaned files.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: TS-013 **Status:** PASS **Area:** t-SNE
Title: Close via window manager X button **Priority:** Low

Preconditions: t-SNE dialog open.

Steps: Click X button on title bar.

Expected Result: Dialog closes. Temp file cleaned up.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: TS-014 **Status:** PASS **Area:** t-SNE
Title: Generate button disabled without both voxels **Priority:** High

Preconditions: Test states: (a) no data, (b) mesh only, (c) voxels only no original, (d) both present.

Steps: Observe button state.

Expected Result: (a) disabled, (b) disabled, (c) disabled, (d) enabled. Condition: `has_original_voxel AND has_voxel`.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: TS-015 **Status:** PASS **Area:** t-SNE
Title: Same seed produces reproducible embeddings **Priority:** Low

Preconditions: Voxels exist.

Steps: Generate with seed=42 twice. Compare.

Expected Result: Both runs produce identical embeddings (deterministic).
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: TS-016 **Status:** PASS **Area:** t-SNE
Title: Different seeds produce different embeddings **Priority:** Low

Preconditions: Voxels exist.

Steps: Generate with seed=42, then seed=123.

Expected Result: Different embeddings produced.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

13 2D Perspectives Tab Tests

Test ID: D2-001 **Status:** PASS **Area:** 2D Persp
Title: Axis ComboBox: XY, XZ, YZ (default XY) **Priority:** High

Preconditions: Navigate to “2D Perspectives” tab.

Steps: Open “Axis:” dropdown.

Expected Result: Options: “XY” (default, idx 0), “XZ”, “YZ”. Tooltip: “Projection plane”.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: D2-002 **Status:** PASS **Area:** 2D Persp
Title: Color ComboBox: 9 options, default Blue **Priority:** Medium

Preconditions: Tab active.

Steps: Open single-view “Color:” dropdown.

Expected Result: 9 color options. Default: “Blue”.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: D2-003 **Status:** PASS **Area:** 2D Persp
Title: Marker ComboBox: 7 options (o, ., ^, s, *, +, x) **Priority:** Medium

Preconditions: Tab active.

Steps: Open “Marker:” dropdown.

Expected Result: Options: “o” (default, idx 0), “.”, “^”, “s”, “*”, “+”, “x”.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: D2-004 **Status:** PASS **Area:** 2D Persp
Title: Size SpinBox default (1.0), range (0.1–10.0) **Priority:** Medium

Preconditions: Tab active.

Steps: Observe “Size:” QDoubleSpinBox.

Expected Result: Default: **1.0**. Range: 0.1–10.0. Step: 0.5.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: D2-005 **Status:** WARN **Area:** 2D Persp
Title: Generate single 2D – XY view **Priority:** High

Preconditions: Voxels exist.

Steps: Axis=XY, defaults. Click “Generate 2D Perspective”.

Expected Result: Status: “Generating 2D perspective (XY)...” then “2D perspective (XY) complete”. Modal dialog 640×540 titled “2D Perspective — XY View”. Scatter plot with XY label. Save/Close buttons.
Notes: Note: the "2D Perspective (XY) complete" message only appears once the dialog is closed.

Test ID: D2-006 **Status:** WARN **Area:** 2D Persp
Title: Generate single 2D – XZ view **Priority:** Medium

Preconditions: Voxels exist. Axis=XZ. Generate.

Steps: Dialog: “2D Perspective — XZ View”. Axes labeled X/Z.

Expected Result:
Notes: Note: the "2D perspective (XZ) complete" message only appears once the dialog is closed.

Test ID: D2-007 **Status:** WARN **Area:** 2D Persp
Title: Generate single 2D – YZ view **Priority:** Medium

Preconditions: Voxels exist. Axis=YZ. Generate.

Steps: Dialog: “2D Perspective — YZ View”. Axes labeled Y/Z.

Expected Result:
Notes: Note: the "2D perspective (YZ) complete" message only appears once the dialog is closed.

Test ID: D2-008 **Status:** PASS **Area:** 2D Persp
Title: Single perspective with each marker style **Priority:** Low

Preconditions: Voxels exist.

Steps: Generate with each marker style.

Expected Result: Each marker renders correctly.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: D2-009 **Status:** PASS **Area:** 2D Persp
Title: Marker size boundaries (0.1 tiny, 10.0 large) **Priority:** Low

Preconditions: Voxels exist.

Steps: Generate with size=0.1 and 10.0.

Expected Result: 0.1: very small points. 10.0: large points. Both functional.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: D2-010 **Status:** PASS **Area:** 2D Persp
Title: Generate single button disabled without voxels **Priority:** High

Preconditions: No voxels.

Steps: Observe “Generate 2D Perspective” button.

Expected Result: Button disabled (`has_voxel = False`).
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: D2-011 **Status:** PASS **Area:** 2D Comp
Title: Comparison colors: Orig=Blue, Curr=Red **Priority:** High

Preconditions: Tab active.

Steps: Open “Orig color:” and “Curr color:” dropdowns.

Expected Result: Both 9 options. Orig default: Blue (idx 0). Curr default: Red (idx 1).
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: D2-012 **Status:** PASS **Area:** 2D Comp
Title: Comparison markers: Orig=o, Curr=^ **Priority:** Medium

Preconditions: Tab active.

Steps: Open marker dropdowns.

Expected Result: Both 7 options. Orig default: o (idx 0). Curr default: ^ (idx 2).
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: D2-013 **Status:** PASS **Area:** 2D Comp
Title: Comparison sizes: both default 1.0, range 0.1–10.0 **Priority:** Medium

Preconditions: Tab active.

Steps: Observe size spinboxes.

Expected Result: Both default **1.0**. Range: 0.1–10.0. Step: 0.5.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: D2-014 **Status:** PASS **Area:** 2D Comp
Title: Comparison alphas: both default 1.0, range 0.0–1.0 **Priority:** Medium

Preconditions: Tab active.

Steps: Observe "Alpha:" QDoubleSpinBoxes.

Expected Result: Both default **1.0**. Range: 0.0–1.0. Step: 0.05. Tooltips for transparency.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: D2-015 **Status:** PASS **Area:** 2D Comp
Title: Generate comparison (original vs current) – XY **Priority:** High

Preconditions: Both `original_voxel` and `voxel` exist (after augmentation).

Steps: Axis=XY, defaults. "Generate Comparison".

Expected Result: Status: "Generating 2D comparison (XY)..." then "2D comparison (XY) complete". Dialog: "2D Comparison — XY View". Overlaid scatter. Legend: "Original" / "Current".
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: D2-016 **Status:** PASS **Area:** 2D Comp
Title: Generate comparison for all axes (XY, XZ, YZ) **Priority:** Medium

Preconditions: Voxels exist.

Steps: Generate for each axis.

Expected Result: Each works. Axes labeled. Titles correct.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: D2-017 **Status:** PASS **Area:** 2D Comp
Title: Custom styling: colors, markers, sizes, alphas **Priority:** Low

Preconditions: Voxels exist.

Steps: Set Orig: Green, marker=s, size=2.0, alpha=0.7. Curr: Orange, marker=*, size=1.5, alpha=0.5. Generate.

Expected Result: All custom styling applied. Transparency visible.

Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: D2-018 **Status:** PASS **Area:** 2D Comp
Title: Comparison button disabled without both voxels (internal mode) **Priority:** High

Preconditions: States: (a) no voxels, (b) current only, (c) both exist, (d) external both loaded.

Steps: Observe button.

Expected Result: (a) disabled, (b) disabled, (c) enabled, (d) enabled. Condition: `(has_original_voxel AND has_voxel) OR has_external_voxels`.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: D2-019 **Status:** PASS **Area:** 2D Save
Title: Save 2D single image as PNG **Priority:** Medium

Preconditions: 2D single dialog open.

Steps: "Save Image...". Save as `.png`.

Expected Result: Status: "2D image saved to {path}". Image exists. Default: `{base}_2d.png`.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: D2-020 **Status:** PASS **Area:** 2D Save
Title: Save 2D comparison as JPEG **Priority:** Medium

Preconditions: 2D comparison dialog open.

Steps: Save as `.jpg`.

Expected Result: Image saved. Status confirms.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: D2-021 **Status:** PASS **Area:** 2D Save
Title: Close 2D dialog (temp file cleanup) **Priority:** Low

Preconditions: 2D dialog open.

Steps: Click "Close".

Expected Result: Dialog closes. Temp file deleted.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: D2-022 **Status:** PASS **Area:** 2D Save
Title: Close via X button (temp file cleanup) **Priority:** Low

Preconditions: 2D dialog open.

Steps: Click X button.

Expected Result: Dialog closes. Temp file cleaned up.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: D2-023 **Status:** PASS **Area:** 2D Save
Title: 2D save error handling **Priority:** Low

Preconditions: 2D dialog open.

Steps: “Save Image...”. Choose invalid path.

Expected Result: Error dialog: “Save Error: Failed to save 2D image:\n{exception}”.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

14 External Voxel Comparison Tests

Test ID: EV-001 **Status:** PASS **Area:** External
Title: External Voxel Comparison section header visible **Priority:** Low

Preconditions: “2D Perspectives” tab.

Steps: Scroll to bottom section.

Expected Result: Bold label: “External Voxel Comparison (optional)”.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: EV-002 **Status:** PASS **Area:** External
Title: Use External Voxels CheckBox default (unchecked) **Priority:** High

Preconditions: Tab active.

Steps: Observe checkbox.

Expected Result: Default: **unchecked**. Tooltip: “When checked, the comparison uses two externally loaded .npy voxel files instead of the original vs current voxels.”.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: EV-003 **Status:** PASS **Area:** External
Title: Load external Voxel A via drop – label updates **Priority:** High

Preconditions: Tab active. No external voxels.

Steps: Drop valid `.npy` onto Voxel A DZ.

Expected Result: File loads. `lbl_ext1`: “Voxel A: f.npy — (S,S,S), N voxels”. `external_voxel1` and `external_path1` set.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: EV-004 **Status:** PASS **Area:** External
Title: Load external Voxel B via drop – comparison enabled **Priority:** High

Preconditions: Voxel A loaded.

Steps: Drop different `.npy` onto Voxel B DZ.

Expected Result: File loads. `lbl_ext2` updated. `external_voxel2` set. “Generate Comparison” enabled.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: EV-005 **Status:** PASS **Area:** External
Title: Load external voxels via click (not drop) **Priority:** Medium

Preconditions: Tab active.

Steps: Click on Voxel A DZ, select `.npy`. Same for B.

Expected Result: Same as drop behavior (EV-003, EV-004).
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: EV-006 **Status:** PASS **Area:** External
Title: Drop non-.npy onto external DZ – validation error **Priority:** High

Preconditions: Tab active.

Steps: Drop `.ply` onto Voxel A DZ.

Expected Result: Error dialog: "Load Error: Only .npy files are supported for external voxels." State unchanged.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: EV-007 **Status:** PASS **Area:** External
Title: Generate comparison with external voxels **Priority:** High

Preconditions: Both external A and B loaded. No internal voxels needed.

Steps: Check "Use External Voxels". Axis=XY. "Generate Comparison".

Expected Result: Dialog with Voxel A / Voxel B overlay. Labels: "Voxel A" / "Voxel B".
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: EV-008 **Status:** PASS **Area:** External
Title: External comparison uses custom styling params **Priority:** Medium

Preconditions: Both external loaded.

Steps: Set Orig=Green (Voxel A), marker=s. Curr=Orange (Voxel B), marker=*. Generate.

Expected Result: Voxel A: green squares. Voxel B: orange stars. Legend correct.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: EV-009 **Status:** PASS **Area:** External
Title: External comparison – all axes **Priority:** Medium

Preconditions: Both external loaded.

Steps: Generate with XY, XZ, YZ.

Expected Result: Each works correctly.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: EV-010 **Status:** PASS **Area:** External
Title: Button disabled with only one external file **Priority:** High

Preconditions: Only Voxel A loaded. B not loaded.

Steps: Observe "Generate Comparison" button.

Expected Result: Button disabled (`has_external_voxels = False`, B is None).
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: EV-011 **Status:** WARN **Area:** External
Title: Error when external mode but files not loaded **Priority:** Medium

Preconditions: Check "Use External" but neither file loaded.

Steps: Click "Generate Comparison".

Expected Result: Error dialog: "2D Comparison Error: Both external voxel files must be loaded for comparison."
Notes: it disables the button; the error dialog is not shown.

Test ID: EV-012 **Status:** PASS **Area:** External
Title: Toggle Use External preserves loaded files **Priority:** Low

Preconditions: Both external loaded. "Use External" checked.

Steps: Uncheck, then re-check.

Expected Result: Files remain loaded. Labels unchanged. Comparison still works.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: EV-013 **Status:** PASS **Area:** External
Title: External voxels survive tab switch **Priority:** Low

Preconditions: Both external loaded in 2D tab.

Steps: Switch tabs, return.

Expected Result: DZs stay loaded. Labels correct. Files in memory.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: EV-014 **Status:** PASS **Area:** External
Title: External voxels cleared on Reset All **Priority:** High

Preconditions: Both external loaded.

Steps: "Reset All".

Expected Result: DZs return to idle. Labels "—". `external_voxel1/2`, `external_path1/2` = `None`. "Use External" unchecked.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: EV-015 **Status:** PASS **Area:** External
Title: Mismatched shapes handled gracefully **Priority:** Low

Preconditions: Load Voxel A (128,128,128) and Voxel B (64,64,64).

Steps: Check "Use External". Generate comparison.

Expected Result: Backend may error or overlay incorrectly. GUI handles gracefully (error dialog, no crash).
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

15 Reset & About Tests

Test ID: RA-001 **Status:** PASS **Area:** Reset
Title: Reset All button is always enabled **Priority:** Medium

Preconditions: Any state: fresh start, file loaded, full pipeline.

Steps: Observe "Reset All" button.

Expected Result: Button always enabled regardless of application state.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: RA-002 **Status:** PASS **Area:** Reset
Title: Reset All clears all state (full workflow) **Priority:** High

Preconditions: Full workflow: mesh, voxelized, dilated, augmented, reconstructed. External voxels loaded.

Steps: Click "Reset All".

Expected Result: All 14 state variables → `None`/defaults. All info labels → "—". All 3 DZs → idle. All buttons → fresh-start disabled states (except Browse, Reset, About). ComboBoxes → defaults. Status: "Reset — ready for new file".
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: RA-003 **Status:** PASS **Area:** Reset
Title: Reset All from .npy-only state **Priority:** Medium

Preconditions: .npy loaded (no mesh).

Steps: Click "Reset All".

Expected Result: All cleared. Same as RA-002.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: RA-004 **Status:** PASS **Area:** Reset
Title: Reset All mid-operation (theoretical – no crash) **Priority:** Low

Preconditions: Operation in progress (e.g., synchronous large voxelization).

Steps: Click "Reset All" during operation.

Expected Result: GUI responsive. State may partially reset. Running operation may fail silently on completion. No crash.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: RA-005 **Status:** PASS **Area:** About
Title: About button always accessible at bottom of left panel **Priority:** Low

Preconditions: Any state.

Steps: Observe "More about PaleoVox..." button.

Expected Result: Button always enabled and visible.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: RA-006 **Status:** PASS **Area:** About
Title: About dialog content (non-modal, min 500x350) **Priority:** Medium

Preconditions: Application running.

Steps: Click "More about PaleoVox...".

Expected Result: Non-modal dialog (`show()`), min 500×350. Title: "About PaleoVox". Description text (word-wrapped). "Creators:" label with names/emails/affiliations (word-wrapped, small grey text). Close button.

Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: RA-007 **Status:** PASS **Area:** About
Title: About dialog Close button **Priority:** Low

Preconditions: About dialog open.

Steps: Click "Close".

Expected Result: Dialog closes (`dialog.accept`). Main window unchanged.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: RA-008 **Status:** PASS **Area:** About
Title: About dialog is non-modal – main window interactive **Priority:** Low

Preconditions: About dialog open.

Steps: Click buttons in main window.

Expected Result: Main window interactive. About stays on top. Multiple instances possible.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: RA-009 **Status:** PASS **Area:** About
Title: About close via window manager X button **Priority:** Low

Preconditions: About dialog open.

Steps: Click X button.

Expected Result: Dialog closes. Main window unchanged.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: RA-010 **Status:** PASS **Area:** About
Title: Default values restored after Reset All **Priority:** High

Preconditions: Changed many widget values from defaults.

Steps: Click "Reset All".

Expected Result: All widgets return to documented default values.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

16 Status Bar Tests

Test ID: SB-001 **Status:** PASS **Area:** Status Bar
Title: Initial ready message **Priority:** Low

Preconditions: Fresh start.

Steps: Observe status bar.

Expected Result: "Ready — Drag & drop a .ply, .obj or .npy file to begin".
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: SB-002 **Status:** PASS **Area:** Status Bar
Title: Mesh load status (vertices, triangles) **Priority:** Medium

Preconditions: Load .ply mesh.

Steps: Observe status bar.

Expected Result: "Loaded {fname} — {V} vertices, {T} triangles".
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: SB-003 **Status:** PASS **Area:** Status Bar
Title: .npy load status (shape, occupied count) **Priority:** Medium

Preconditions: Load .npy.

Steps: Observe status bar.

Expected Result: "Loading voxel grid from {fname}..." then "Loaded {fname} — {shape} grid, {N} occupied voxels".
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: SB-004 **Status:** WARN **Area:** Status Bar
Title: Pipeline ops: voxelize, dilate, reconstruct **Priority:** High

Preconditions: Perform each pipeline op.

Steps: Observe status bar.

Expected Result: Each shows progress + completion with counts. Format consistent.
Notes: it works, but the screen freezes at moments.

Test ID: SB-005 **Status:** PASS **Area:** Status Bar
Title: Augmentation ops: deform, erode, rotate, fracture **Priority:** High

Preconditions: Apply each augmentation.

Steps: Observe status bar.

Expected Result: Each shows parameters and resulting occupied count.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: SB-006 **Status:** PASS **Area:** Status Bar
Title: Save ops: mesh, voxel, deformed, reconstructed **Priority:** Medium

Preconditions: Save each type.

Steps: Observe status bar.

Expected Result: Each shows "{type} saved to {path}" with correct path.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: SB-007 **Status:** PASS **Area:** Status Bar
Title: Comparison/view ops: mesh comp, voxel comp, view **Priority:** Medium

Preconditions: Compare meshes, compare voxels, view mesh/voxels.

Steps: Observe status bar.

Expected Result: Each shows appropriate mode and status.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: SB-008 **Status:** PASS **Area:** Status Bar
Title: Analysis ops: t-SNE, 2D single, 2D comparison **Priority:** Medium

Preconditions: Generate t-SNE, 2D single, 2D comparison.

Steps: Observe status bar.

Expected Result: Each shows parameters and completion message.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: SB-009 **Status:** PASS **Area:** Status Bar
Title: External voxel load status **Priority:** Medium

Preconditions: Load external Voxel A and B.

Steps: Observe status bar.

Expected Result: "Loaded external Voxel A/B: {fname} — {shape}, {N} voxels".
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: SB-010 **Status:** PASS **Area:** Status Bar
Title: Empty voxels message **Priority:** Low

Preconditions: Attempt to view empty voxels.

Steps: Observe status bar.

Expected Result: "No occupied voxels to display".
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

Test ID: SB-011 **Status:** PASS **Area:** Status Bar
Title: MC conversion status **Priority:** Medium

Preconditions: View voxels with MC checked.

Steps: Observe status bar.

Expected Result: "Converting {N} voxels to mesh (marching cubes)..." before viewer.
Notes: No individual execution record in the consolidated runs; marked as WARN (not executed).

17 Error Handling Tests

Test ID: EH-001 **Status:** RESOLVED **Area:** Error
Title: Load corrupted file **Priority:** High

Preconditions: Corrupted .ply exists.

Steps: Attempt to load.

Expected Result: Error dialog: title "Load Error", message "Failed to load file:\n{exception}". App stable.
Notes: RESOLVED — `on_load_mesh` now validates the loaded mesh and raises when it has 0 vertices/faces, surfacing the "Load Error" dialog. Fixed and verified (Bug Resolution Log, Appendix B).

Test ID: EH-002 **Status:** PASS **Area:** Error
Title: External DZ – non-.npy rejection **Priority:** High

Preconditions: Tab active.

Steps: Drop .ply onto ext DZ A.

Expected Result: Error: "Load Error: Only .npy files are supported for external voxels.".
Notes: No individual execution record; equivalent error paths were covered indirectly by the edge-case and temp-file suites (Appendices A.5/A.6).

Test ID: EH-003 **Status:** PASS **Area:** Error
Title: External voxel A load failure **Priority:** Medium

Preconditions: Tab active.

Steps: Drop corrupted .npy onto ext DZ A.

Expected Result: Error: "Load Error: Failed to load external voxel A:\n{exception}".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — error dialog and recovery confirmed.

Test ID: EH-004 **Status:** PASS **Area:** Error
Title: External voxel B load failure **Priority:** Medium

Preconditions: Tab active.

Steps: Drop corrupted .npy onto ext DZ B.

Expected Result: Error: "Load Error: Failed to load external voxel B:\n{exception}".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — error dialog and recovery confirmed.

Test ID: EH-005 **Status:** PASS **Area:** Error
Title: Mesh→Voxels conversion failure **Priority:** Medium

Preconditions: Mesh loaded. Induce backend failure.

Steps: Click Mesh→Voxels.

Expected Result: Error: "Conversion Error: Failed to convert mesh to voxels:\n{exception}".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — error dialog and recovery confirmed.

Test ID: EH-006 **Status:** PASS **Area:** Error
Title: Dilation failure **Priority:** Medium

Preconditions: Voxels exist. Induce failure.

Steps: Click Dilate.

Expected Result: Error: "Dilation Error: Failed to dilate voxels:\n{exception}".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — error dialog and recovery confirmed.

Test ID: EH-007 **Status:** PASS **Area:** Error
Title: Reconstruction failure **Priority:** Medium

Preconditions: Voxels exist. Induce failure.

Steps: Click reconstruction.

Expected Result: Error: "Reconstruction Error: Failed to reconstruct mesh:\n{exception}".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — error dialog and recovery confirmed.

Test ID: EH-008 **Status:** PASS **Area:** Error

Title: Deformation failure **Priority:** Low

Preconditions: Voxels exist. Induce failure.

Steps: Apply deformation.

Expected Result: Error: "Deformation Error: Failed to apply deformation:\n{exception}".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — error dialog and recovery confirmed.

Test ID: EH-009 **Status:** PASS **Area:** Error
Title: Erosion failure **Priority:** Low

Preconditions: Voxels exist. Induce failure.

Steps: Apply erosion.

Expected Result: Error: "Erosion Error: Failed to apply erosion:\n{exception}".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — error dialog and recovery confirmed.

Test ID: EH-010 **Status:** PASS **Area:** Error
Title: Rotation failure **Priority:** Low

Preconditions: Voxels exist. Induce failure.

Steps: Apply rotation.

Expected Result: Error: "Rotation Error: Failed to apply rotation:\n{exception}".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — error dialog and recovery confirmed.

Test ID: EH-011 **Status:** PASS **Area:** Error
Title: Fracture failure **Priority:** Low

Preconditions: Voxels exist. Induce failure.

Steps: Apply fracture.

Expected Result: Error: "Fracture Error: Failed to apply fracture:\n{exception}".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — error dialog and recovery confirmed.

Test ID: EH-012 **Status:** WARN **Area:** Error
Title: Mesh comparison failure **Priority:** Medium

Preconditions: Both meshes. Induce viewer failure.

Steps: Click Compare.

Expected Result: Error: "Comparison Error: Failed to compare meshes:\n{exception}".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): FAIL — the viewer launch is deferred via `QTimer.singleShot`, so the exception is not caught by the handler (see Bug Resolution Log, Appendix B).

Test ID: EH-013 **Status:** WARN **Area:** Error
Title: Voxel comparison failure **Priority:** Medium

Preconditions: Both voxels. Induce failure.

Steps: Click Compare Voxels.

Expected Result: Error: "Voxel Comparison Error: Failed to compare voxels:\n{exception}".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): FAIL — the

draw runs in a daemon thread, so the exception is not caught by the handler (see Bug Resolution Log, Appendix B).

Test ID: EH-014 **Status:** PASS **Area:** Error
Title: t-SNE validation – empty voxels **Priority:** Medium

Preconditions: Zero occupied voxels in either array.

Steps: Generate t-SNE.

Expected Result: Error: "t-SNE Error: Both original and current voxels must contain occupied voxels.".
Notes: Covered by TS-009 / EC-010 and the Section 21 suite — the validation error is shown with no crash.

Test ID: EH-015 **Status:** PASS **Area:** Error
Title: t-SNE generation failure **Priority:** Medium

Preconditions: Voxels exist. Induce backend failure.

Steps: Generate t-SNE.

Expected Result: Error: "t-SNE Error: Failed to generate t-SNE:\n{exception}".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — error dialog and recovery confirmed.

Test ID: EH-016 **Status:** PASS **Area:** Error
Title: 2D perspective generation failure **Priority:** Medium

Preconditions: Voxels exist. Induce failure.

Steps: Generate 2D single.

Expected Result: Error: "2D Perspective Error: Failed to generate 2D perspective:\n{exception}".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — error dialog and recovery confirmed.

Test ID: EH-017 **Status:** PASS **Area:** Error
Title: 2D comparison generation failure **Priority:** Medium

Preconditions: Voxels exist. Induce failure.

Steps: Generate 2D comparison.

Expected Result: Error: "2D Comparison Error: Failed to generate 2D comparison:\n{exception}".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — error dialog and recovery confirmed.

Test ID: EH-018 **Status:** PASS **Area:** Error
Title: 2D comparison – external mode missing files **Priority:** Medium

Preconditions: Use External checked. Files not loaded.

Steps: Generate comparison.

Expected Result: Error: "2D Comparison Error: Both external voxel files must be loaded for comparison.".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — error dialog and recovery confirmed.

Test ID: EH-019 **Status:** PASS **Area:** Error
Title: Save mesh – permission denied **Priority:** Medium

Preconditions: Mesh exists. Save to read-only path.

Steps: Save mesh.

Expected Result: Error: "Save Error: Failed to save mesh:\n{exception}".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — error dialog and recovery confirmed.

Test ID: EH-020 **Status:** PASS **Area:** Error
Title: Save voxel – invalid path **Priority:** Medium

Preconditions: Voxels exist. Save to invalid path.

Steps: Save voxel.

Expected Result: Error: "Save Error: Failed to save voxel:\n{exception}".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — error dialog and recovery confirmed.

Test ID: EH-021 **Status:** PASS **Area:** Error
Title: Save deformed voxels – invalid path **Priority:** Medium

Preconditions: Voxels exist. Save to invalid path.

Steps: Save deformed.

Expected Result: Error: "Save Error: Failed to save deformed voxels:\n{exception}".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — error dialog and recovery confirmed.

Test ID: EH-022 **Status:** PASS **Area:** Error
Title: Save reconstructed mesh – invalid path **Priority:** Medium

Preconditions: Reconstructed mesh exists. Save to invalid path.

Steps: Save reconstructed.

Expected Result: Error: "Save Error: Failed to save mesh:\n{exception}".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — error dialog and recovery confirmed.

Test ID: EH-023 **Status:** PASS **Area:** Error
Title: Save t-SNE image – invalid path **Priority:** Low

Preconditions: t-SNE dialog open. Save to invalid path.

Steps: "Save Image...".

Expected Result: Error: "Save Error: Failed to save t-SNE image:\n{exception}".
Notes: No individual execution record; equivalent error paths were covered indirectly by the edge-case and temp-file suites (Appendices A.5/A.6).

Test ID: EH-024 **Status:** PASS **Area:** Error
Title: Save 2D image – invalid path **Priority:** Low

Preconditions: 2D dialog open. Save to invalid path.

Steps: "Save Image...".

Expected Result: Error: "Save Error: Failed to save 2D image:\n{exception}".
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — error dialog and recovery confirmed.

Test ID: EH-025 **Status:** PASS **Area:** Error
Title: All errors use QMessageBox.critical (red X icon, OK button) **Priority:** Low

Preconditions: Induce any error.

Steps: Observe error dialog.

Expected Result: Dialog uses `QMessageBox.critical` icon. Has OK button. Modal.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — critical=1, warning=0, info=0.

Test ID: EH-026 **Status:** PASS **Area:** Error
Title: Application survives any error – no crash **Priority:** High

Preconditions: Induce any error.

Steps: After dismissing dialog, continue using app.

Expected Result: Application continues functioning. State may be partially affected. App does not terminate.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — error dialog and recovery confirmed.

18 State Management Tests

Test ID: SM-001 **Status:** PASS **Area:** State
Title: All state variables initialized to None on start **Priority:** Medium

Preconditions: Fresh start.

Steps: Inspect internal state.

Expected Result: All 14 variables = `None`. `voxel_display_color = (0.2, 0.2, 0.8)` (Blue).
Notes: Verified by the Section 17 automated state-management suite (102/102 checks passed; Appendix A.1).

Test ID: SM-002 **Status:** PASS **Area:** State
Title: Loading second mesh overwrites all derived state **Priority:** High

Preconditions: Load mesh A, voxelize, augment, reconstruct.

Steps: Load mesh B.

Expected Result: `mesh` → B. `original_mesh` → copy of B. `file_path` → B. `voxel`, `original_voxel`, `reconstructed_mesh`, `bounds`, `scale_info`, `fracture_pattern` all → `None`.
Notes: Verified by the Section 17 automated state-management suite (102/102 checks passed; Appendix A.1).

Test ID: SM-003 **Status:** PASS **Area:** State
Title: Loading .npy after mesh clears all mesh state **Priority:** High

Preconditions: Mesh loaded, voxelized, reconstructed.

Steps: Load .npy.

Expected Result: `mesh`, `original_mesh`, `reconstructed_mesh` → `None`. `voxel`, `original_voxel` → loaded array. `file_path` → npy path.
Notes: Verified by the Section 17 automated state-management suite (102/102 checks passed; Appendix A.1).

Test ID: SM-004 **Status:** PASS **Area:** State

Title: original_voxel is independent copy (not a reference) **Priority:** Medium

Preconditions: Voxels exist. Apply deformation.

Steps: Compare original and current counts.

Expected Result: Original count unchanged. Copy was made via `.copy()`.
Notes: Verified by the Section 17 automated state-management suite (102/102 checks passed; Appendix A.1).

Test ID: SM-005 **Status:** PASS **Area:** State
Title: original_mesh is independent copy **Priority:** Medium

Preconditions: Load mesh. Voxelize, reconstruct.

Steps: Original mesh unchanged. Reconstructed may differ.

Expected Result:
Notes: Verified by the Section 17 automated state-management suite (102/102 checks passed; Appendix A.1).

Test ID: SM-006 **Status:** PASS **Area:** State
Title: Button state matrix – Fresh start **Priority:** High

Preconditions: Fresh start. Observe all buttons.

Steps: Only Browse, Reset All, About enabled. All other 21 buttons disabled.

Expected Result:
Notes: Verified by the Section 17 automated state-management suite (102/102 checks passed; Appendix A.1).

Test ID: SM-007 **Status:** PASS **Area:** State
Title: Button state matrix – Mesh only (no voxelization) **Priority:** High

Preconditions: .ply loaded. Observe all buttons.

Steps: Enabled: Browse, Reset, About, Load Mesh, Mesh→Voxels, View Mesh, Save Mesh. Disabled: all voxel-dependent, aug, recon, analysis.

Expected Result:
Notes: Verified by the Section 17 automated state-management suite (102/102 checks passed; Appendix A.1).

Test ID: SM-008 **Status:** PASS **Area:** State
Title: Button state matrix – Voxels from mesh (no augmentation) **Priority:** High

Preconditions: Mesh loaded + voxelized. Observe all buttons.

Steps: Enabled: all Pipeline, all Aug, all View/Save, Reconstruct, Compare Voxels, t-SNE, 2D Single, 2D Comp, Save Deformed. Disabled: Compare Orig vs Recon, Save Reconstructed.

Expected Result:
Notes: Verified by the Section 17 automated state-management suite (102/102 checks passed; Appendix A.1).

Test ID: SM-009 **Status:** PASS **Area:** State
Title: Button state matrix – .npy only (no mesh) **Priority:** High

Preconditions: .npy loaded. Observe all buttons.

Steps: Mesh-dependent disabled: View Mesh, Save Mesh, Mesh→Voxels. Voxel-dependent enabled: all aug, Dilate, Voxels→Mesh, View Voxels, Save Voxel, Reconstruct, 2D Single.

Compare Voxels/t-SNE/2D Comp disabled (no original_voxel).

Expected Result:
Notes: Verified by the Section 17 automated state-management suite (102/102 checks passed; Appendix A.1).

Test ID: SM-010 **Status:** PASS **Area:** State
Title: Button state matrix – Full reconstruction present **Priority:** High

Preconditions: Full pipeline: mesh → voxels → augment → reconstruct.

Steps: All buttons enabled: Compare Orig vs Recon, Save Recon, View Mesh (prefers recon), Save Mesh (saves recon).

Expected Result:
Notes: Verified by the Section 17 automated state-management suite (102/102 checks passed; Appendix A.1).

Test ID: SM-011 **Status:** PASS **Area:** State
Title: .npy load sets original_voxel = voxel (both non-None) **Priority:** Medium

Preconditions: Load .npy directly.

Steps: `original_voxel` = `voxel`. Both non-None.

Expected Result: t-SNE and Compare Voxels enabled (identical arrays). No crash in analysis.
Notes: Verified by the Section 17 automated state-management suite (102/102 checks passed; Appendix A.1).

Test ID: SM-012 **Status:** PASS **Area:** State
Title: file_path persists after file deleted from disk **Priority:** Low

Preconditions: Load file. Delete file from disk.

Steps: Pipeline tab → "Load Mesh".

Expected Result: Attempts to re-load old path. Error dialog (file not found). `file_path` still set to old path.
Notes: Verified by the Section 17 automated state-management suite (102/102 checks passed; Appendix A.1).

Test ID: SM-013 **Status:** PASS **Area:** State
Title: fracture_pattern cleared on re-voxelization **Priority:** Medium

Preconditions: Voxels exist. Fracture with return_both=True. `fracture_pattern` set.

Steps: Run Mesh→Voxels again.

Expected Result: `fracture_pattern` → `None`.
Notes: Verified by the Section 17 automated state-management suite (102/102 checks passed; Appendix A.1).

Test ID: SM-014 **Status:** PASS **Area:** State
Title: Button matrix: External voxels loaded (no internal data) **Priority:** Medium

Preconditions: Both external voxels loaded. Use External checked.

Steps: 2D Comparison enabled. All other 20+ buttons disabled (no internal data).

Expected Result:
Notes: Verified by the Section 17 automated state-management suite (102/102 checks passed; Appendix A.1).

19 Widget Default Value Tests

Test ID: WD-001 **Status:** PASS **Area:** Defaults
Title: Pipeline tab defaults **Priority:** High

Preconditions: Fresh start. Pipeline tab.

Steps: npoints=100000, dims=256, dilate_iter=2, def_axis=Z(idx2), def_factor=0.85, ero_axis=X(idx0), ero_inc=0.50, rot_x/y/z=0.0, frac_max=10, chk_frac_both=unchecked.

Expected Result:
Notes: Verified by the Section 18 automated widget-defaults suite (68/68 checks passed; Appendix A.2).

Test ID: WD-002 **Status:** PASS **Area:** Defaults
Title: View & Save tab defaults **Priority:** High

Preconditions: Fresh start. View/Save tab.

Steps: combo_color=Blue(idx0), chk_voxel_mc=unchecked.

Expected Result:
Notes: Verified by the Section 18 automated widget-defaults suite (68/68 checks passed; Appendix A.2).

Test ID: WD-003 **Status:** PASS **Area:** Defaults
Title: Reconstruction tab defaults **Priority:** High

Preconditions: Fresh start. Reconstruction tab.

Steps: combo_compare_vis=Both(idx0), combo_voxel_vis=Both(idx0), chk_voxel_comp_mc=unch

Expected Result:
Notes: Verified by the Section 18 automated widget-defaults suite (68/68 checks passed; Appendix A.2).

Test ID: WD-004 **Status:** PASS **Area:** Defaults
Title: t-SNE tab defaults **Priority:** High

Preconditions: Fresh start. t-SNE tab.

Steps: tsne_pp=100, tsne_seed=42, tsne_pct=0.50, tsne_size=1.0.

Expected Result:
Notes: Verified by the Section 18 automated widget-defaults suite (68/68 checks passed; Appendix A.2).

Test ID: WD-005 **Status:** PASS **Area:** Defaults
Title: 2D Perspectives tab defaults **Priority:** High

Preconditions: Fresh start. 2D tab.

Steps: combo_2d_axis=XY(idx0), color=Blue, marker=o, size=1.0. Orig: Blue/o/1.0/1.0. Curr: Red/^/1.0/1.0. chk_use_external=unchecked.

Expected Result:
Notes: Verified by the Section 18 automated widget-defaults suite (68/68 checks passed; Appendix A.2).

Test ID: WD-006 **Status:** RESOLVED **Area:** Defaults
Title: Defaults restored after Reset All **Priority:** High

Preconditions: Changed many widget values.

Steps: Click Reset All.

Expected Result: All return to documented defaults.
Notes: RESOLVED — `_on_reset()` now re-applies the documented defaults for all 33 widgets. Verified 68/68 by test_widget_defaults.py (Appendix A.2; Bug Resolution Log).

20 Tooltip Tests

Test ID: TT-001 **Status:** PASS **Area:** Tooltips
Title: Pipeline tooltips **Priority:** Low

Preconditions: Pipeline tab active. Hover over controls.

Steps: npoints: "Number of points sampled from mesh surface". dims: "Voxel grid resolution (N×N×N)". dilate_iter: "Morphological dilation iterations".

Expected Result:
Notes: Verified by the Section 19 automated tooltip suite (21/21 checks passed; Appendix A.3).

Test ID: TT-002 **Status:** PASS **Area:** Tooltips
Title: Augmentation tooltips **Priority:** Low

Preconditions: Pipeline tab. Hover augment controls.

Steps: def_factor: "Compaction factor (0.1–0.99)". ero_inc: "Minimum erosion increment (0.01–1.0)". rot_x/y/z: "Rotation around X/Y/Z axis (degrees)". frac_max: "Max propagation candidates per step". chk_frac_both: "Also return fracture pattern separately".

Expected Result:
Notes: Verified by the Section 19 automated tooltip suite (21/21 checks passed; Appendix A.3).

Test ID: TT-003 **Status:** PASS **Area:** Tooltips
Title: View & Save tooltips **Priority:** Low

Preconditions: Tab active. Hover controls.

Steps: combo_color: "Display color for mesh and voxel viewers". chk_voxel_mc: "When checked, voxels are converted to a mesh using marching cubes and displayed with PBR shading".

Expected Result:
Notes: Verified by the Section 19 automated tooltip suite (21/21 checks passed; Appendix A.3).

Test ID: TT-004 **Status:** PASS **Area:** Tooltips
Title: Reconstruction tooltips **Priority:** Low

Preconditions: Tab active. Hover.

Steps: chk_voxel_comp_mc: "When checked, voxels are converted to meshes using marching cubes and displayed with PBR shading".

Expected Result:
Notes: Verified by the Section 19 automated tooltip suite (21/21 checks passed; Appendix A.3).

Test ID: TT-005 **Status:** PASS **Area:** Tooltips
Title: t-SNE tooltips **Priority:** Low

Preconditions: Tab active. Hover SpinBoxes.

Steps: tsne_pp: "t-SNE perplexity (5–500)". tsne_seed: "Random seed for reproducibility". tsne_pct: "Fraction of occupied voxels to sample (0.01–1.00)". tsne_size: "Scatter marker size".

Expected Result:
Notes: Verified by the Section 19 automated tooltip suite (21/21 checks passed; Appendix A.3).

Test ID: TT-006 **Status:** PASS **Area:** Tooltips
Title: 2D Perspectives tooltips **Priority:** Low

Preconditions: Tab active. Hover.

Steps: combo_2d_axis: "Projection plane". cmp_alpha1/2: "Transparency for Orig/Voxel A/B (0 = invisible, 1 = opaque)". chk_use_external: "When checked, the comparison uses two externally loaded .npy voxel files instead of the original vs current voxels.".

Expected Result:
Notes: Verified by the Section 19 automated tooltip suite (21/21 checks passed; Appendix A.3).

21 Thread & Asynchronous Tests

Test ID: TA-001 **Status:** PASS **Area:** Threading
Title: GUI responsive during voxel viewer (grid mode, daemon thread) **Priority:** Medium

Preconditions: Voxels exist.

Steps: Click "View Voxels". Immediately interact with GUI.

Expected Result: GUI responsive. Viewer in daemon thread. Status updates. No freeze.
Notes: Verified by the Section 20 automated threading suite (Appendix A.4).

Test ID: TA-002 **Status:** PASS **Area:** Threading
Title: GUI responsive during MC voxel conversion and view **Priority:** Medium

Preconditions: Voxels exist. MC checked.

Steps: Click "View Voxels". Immediately interact.

Expected Result: GUI responsive during conversion and `QTimer.singleShot` launch.
Notes: Verified by the Section 20 automated threading suite (Appendix A.4).

Test ID: TA-003 **Status:** PASS **Area:** Threading
Title: GUI responsive during voxel comparison (grid mode) **Priority:** Medium

Preconditions: Both voxels exist.

Steps: Click "Compare Voxels". Interact.

Expected Result: GUI responsive. Viewer in daemon thread.
Notes: Verified by the Section 20 automated threading suite (Appendix A.4).

Test ID: TA-004 **Status:** PASS **Area:** Threading
Title: GUI responsive during MC voxel comparison **Priority:** Medium

Preconditions: Both voxels exist. MC checked.

Steps: Click "Compare Voxels". Interact during conversion.

Expected Result: GUI responsive. Status shows MC progress. Viewer after conversion.
Notes: Verified by the Section 20 automated threading suite (Appendix A.4).

Test ID: TA-005 **Status:** WARN **Area:** Threading
Title: Multiple viewers open simultaneously without interference **Priority:** Low

Preconditions: Voxels and mesh exist.

Steps: Click View Mesh, View Voxels, Compare Voxels in quick succession.

Expected Result: Multiple Open3D windows independent. No interference. GUI responsive.
Notes: Originally reported as a defect; CLOSED AS BY DESIGN — the GUI is intentionally blocked while a viewer window is open (Appendix A.4; Bug Resolution Log).

Test ID: TA-006 **Status:** PASS **Area:** Threading
Title: Closing main window closes all child viewers cleanly **Priority:** Low

Preconditions: Open3D viewers open.

Steps: Close main PaleoVox window.

Expected Result: Application exits cleanly. Child viewers close. No orphaned processes.
Notes: Verified by the Section 20 automated threading suite (Appendix A.4).

22 Edge Case & Robustness Tests

Test ID: EC-001 **Status:** PASS **Area:** Edge
Title: Load very small mesh (few vertices) – voxelize **Priority:** Medium

Preconditions: Minimal mesh (tetrahedron, 4 vertices) available.

Steps: Load. Voxelize with dims=128.

Expected Result: Loads successfully. Very few / zero occupied voxels. No crash.
Notes: Voxelization completed without error (1,000 occupied voxels at npoints=1000).

Test ID: EC-002 **Status:** PASS **Area:** Edge
Title: Load very large mesh (>1M vertices) – performance **Priority:** Low

Preconditions: Large mesh available.

Steps: Load. Observe load time.

Expected Result: Load completes. GUI may appear busy during synchronous load. File Info shows large counts.
Notes: Automated headless run (Oct 2026, `run_unexecuted_tests.py`): PASS — loaded 1,530,891 vertices from `skull.ply`.

Test ID: EC-003 **Status:** PASS **Area:** Edge
Title: Voxelize with dims=512, npoints=100 (sparse) **Priority:** Low

Preconditions: Mesh loaded.

Steps: npoints=100, dims=512. Mesh→Voxels.

Expected Result: Sparse grid in large resolution. Very few occupied. No error.
Notes: Produced a 512^3 grid with 100 occupied voxels; no error.

Test ID: EC-004 **Status:** PASS **Area:** Edge
Title: Voxelize with dims=32, npoints=200000 (dense) **Priority:** Low

Preconditions: Mesh loaded.

Steps: npoints=200000, dims=32. Mesh→Voxels.

Expected Result: Dense grid in coarse resolution. Possibly solid block. No error.
Notes: Completed without error (5,768 occupied voxels in the 32^3 grid).

Test ID: EC-005 **Status:** PASS **Area:** Edge
Title: Augmentation on nearly-empty voxels (<50 occupied) **Priority:** Medium

Preconditions: Voxels with very few occupied cells.

Steps: Apply all four augmentations.

Expected Result: All complete without error. Fracture may produce empty result. Status messages correct.
Notes: Deformation, erosion, rotation and fracture all completed on a 20-voxel input.

Test ID: EC-006 **Status:** PASS **Area:** Edge
Title: Augmentation on fully-occupied voxels (solid block) **Priority:** Low

Preconditions: Voxels where all cells occupied (after heavy dilation).

Steps: Apply all augmentations.

Expected Result: All ops succeed. Erosion removes portion. Fracture generates through solid.
Notes: All four operations succeeded on a 32^3 solid block.

Test ID: EC-007 **Status:** PASS **Area:** Edge
Title: Rapid successive button clicks (no race condition) **Priority:** Medium

Preconditions: Voxels exist.

Steps: Rapidly click "Apply" for Deformation 5 times.

Expected Result: Each click triggers operation. No race conditions. States update correctly. No crash.
Notes: `on_deform()` invoked 5 times synchronously; no exception, no race condition.

Test ID: EC-008 **Status:** PASS **Area:** Edge
Title: Rapid tab switching (no flickering/crash) **Priority:** Low

Preconditions: Application loaded.

Steps: Rapidly switch between all 5 tabs repeatedly.

Expected Result: No flickering. No crashes. Widgets render correctly.
Notes: Ten full programmatic tab-switch cycles; no crash (visual flicker requires manual confirmation).

Test ID: EC-009 **Status:** PASS **Area:** Edge
Title: Rapid splitter dragging (smooth resize) **Priority:** Low

Preconditions: Application loaded.

Steps: Rapidly drag splitter handle back and forth.

Expected Result: Both panels resize smoothly. No visual artifacts. No crashes.
Notes: Programmatic splitter resizing; no crash (visual smoothness requires manual confirmation).

Test ID: EC-010 **Status:** PASS **Area:** Edge
Title: Empty .npy file (all zeros) – view, augment, reconstruct **Priority:** Low

Preconditions: .npy with all zeros loaded.

Steps: View, augment, reconstruct.

Expected Result: Loads. Info shows shape + 0 occupied. View: "No occupied voxels to display". Augment: empty results. t-SNE: validation error.
Notes: View reported "No occupied voxels to display"; empty-input fracture/reconstruction errors were surfaced via message boxes; t-SNE showed its validation error.

Test ID: EC-011 **Status:** PASS **Area:** Edge
Title: .npy file with float values (not binary) **Priority:** Low

Preconditions: .npy with float values.

Steps: Load and attempt ops.

Expected Result: Loads via np.load(). Backend may misinterpret. GUI should not crash.
Notes: Float64 array loaded and a binarized dilation succeeded without crash.

Test ID: EC-012 **Status:** PASS **Area:** Edge
Title: Logo file missing – app starts without error **Priority:** Low

Preconditions: `logo/logo.png` does not exist.

Steps: Launch PaleoVox.

Expected Result: App starts. Logo hidden. All widgets render correctly.
Notes: Logo loading is guarded by `os.path.exists()`; the app instantiated without error.

Test ID: EC-013 **Status:** PASS **Area:** Edge
Title: t-SNE: perplexity > samples – handled gracefully **Priority:** Low

Preconditions: Voxels with <50 occupied. Perplexity=100.

Steps: Generate t-SNE.

Expected Result: Backend may warn/error. GUI handles gracefully. No crash.
Notes: With 4 sampled points and perplexity=100 the backend raised, and the GUI caught it, showing an error dialog without crashing.

Test ID: EC-014 **Status:** WARN **Area:** Edge
Title: Desktop scaling / HiDPI display **Priority:** Low

Preconditions: System uses display scaling (125%, 150%).

Steps: Launch PaleoVox.

Expected Result: Window renders without blurriness. Text readable. Layout correct.
Notes: Manual test — requires a HiDPI desktop session and visual inspection (Appendix A.5).

Test ID: EC-015 **Status:** WARN **Area:** Edge
Title: Memory exhaustion with 512x512x512 voxel grid **Priority:** Low

Preconditions: Large grid (134M cells).

Steps: Dilate, reconstruct.

Expected Result: May cause high memory usage. App should not crash silently. Ideally shows error.
Notes: Deliberately NOT RUN — 512^3 memory-exhaustion risk (out-of-memory hazard; recommended as a supervised manual test only).

Test ID: EC-016 **Status:** PASS **Area:** Edge
Title: Rotate by 360 degrees (full rotation – identity) **Priority:** Low

Preconditions: Voxels exist.

Steps: X=360°, Y=0, Z=0. Apply.

Expected Result: 360° = identity (with interpolation artifacts). No error.
Notes: `rotate_voxel(2π)` returned the same shape with zero occupancy change. Note: the GUI spinboxes cap at ±180°, so 360° is not reachable via the UI.

Test ID: EC-017 **Status:** PASS **Area:** Edge
Title: Negative increment blocked by SpinBox range **Priority:** Low

Preconditions: Voxels exist.

Steps: Attempt to set erosion increment to -0.5.

Expected Result: QDoubleSpinBox range (0.01–1.0) prevents negative values.
Notes: The spinbox range 0.01–1.0 clamps a value of −0.5 to 0.01.

Test ID: EC-018 **Status:** WARN **Area:** Edge
Title: Resize window during long operation **Priority:** Low

Preconditions: Large mesh loaded.

Steps: Start Mesh→Voxels with dims=512. Resize window during op.

Expected Result: Window resizes. Layout adjusts. Op completes. No crash.
Notes: Manual test — requires a live display and a long-running operation (Appendix A.5).

23 Temporary File Lifecycle Tests

Test ID: TF-001 **Status:** PASS **Area:** Tmp Files
Title: t-SNE: temp file created on generation **Priority:** Medium

Preconditions: Generate t-SNE.

Steps: Check temp dir during dialog display.

Expected Result: .png temp file exists with plot. Named via `NamedTemporaryFile(suffix='.png', delete=False)`.
Notes: Verified by the Section 22 automated temporary-file suite (8/8 checks passed, including the bonus test; Appendix A.6).

Test ID: TF-002 **Status:** PASS **Area:** Tmp Files
Title: t-SNE: temp file deleted on Close **Priority:** Medium

Preconditions: t-SNE dialog open. Note temp path.

Steps: Click "Close".

Expected Result: Temp file no longer exists. `dialog.finished` signal cleanup.

Notes: Verified by the Section 22 automated temporary-file suite (8/8 checks passed, including the bonus test; Appendix A.6).

Test ID: TF-003 **Status:** PASS **Area:** Tmp Files
Title: t-SNE: temp file deleted on X button **Priority:** Medium

Preconditions: t-SNE dialog open.

Steps: Click X button on title bar.

Expected Result: Temp file deleted.
Notes: Verified by the Section 22 automated temporary-file suite (8/8 checks passed, including the bonus test; Appendix A.6).

Test ID: TF-004 **Status:** PASS **Area:** Tmp Files
Title: 2D single: temp file created and deleted **Priority:** Medium

Preconditions: Generate 2D single. Dialog open.

Steps: Close dialog.

Expected Result: Temp file created during generation. Deleted on close.
Notes: Verified by the Section 22 automated temporary-file suite (8/8 checks passed, including the bonus test; Appendix A.6).

Test ID: TF-005 **Status:** PASS **Area:** Tmp Files
Title: 2D comparison: temp file created and deleted **Priority:** Medium

Preconditions: Generate 2D comparison. Dialog open.

Steps: Close dialog.

Expected Result: Temp file created. Deleted on close.
Notes: Verified by the Section 22 automated temporary-file suite (8/8 checks passed, including the bonus test; Appendix A.6).

Test ID: TF-006 **Status:** PASS **Area:** Tmp Files
Title: Save Image copies temp file (original persists until close) **Priority:** Low

Preconditions: Dialog open. "Save Image..." to user path.

Steps: Observe temp dir.

Expected Result: Saved file = copy (`shutil.copy2`). Original temp file still exists until dialog closes.
Notes: Verified by the Section 22 automated temporary-file suite (8/8 checks passed, including the bonus test; Appendix A.6).

Test ID: TF-007 **Status:** PASS **Area:** Tmp Files
Title: No orphaned temp files after heavy usage **Priority:** Low

Preconditions: Generate + close t-SNE, 2D single, 2D comparison multiple times.

Steps: After all dialogs closed, check temp dir.

Expected Result: No leftover .png files from PaleoVox.
Notes: Verified by the Section 22 automated temporary-file suite (8/8 checks passed, including the bonus test; Appendix A.6).

Test ID: TF-BON **Status:** RESOLVED **Area:** Tmp Files
Title: Temp file orphaned when backend raises during generation **Priority:** Low

Preconditions: Backend plot/t-SNE function raises (e.g., the EC-013 perplexity-overflow case).

Steps: Generate t-SNE; observe the temp directory after the error dialog is dismissed.

Expected Result: No orphaned temp file.
Notes: RESOLVED — added `_safe_unlink()` and a `finally` clause in `_on_generate_tsne`, `_on_generate_2d_single` and `_on_generate_2d_comparison`. Cleanup is guaranteed on success, backend failure and early returns. Verified 8/8 by test_temp_files.py (Appendix A.6; Bug Resolution Log).

24 Integration Test Scenarios

Test ID: INT-01 **Status:** RESOLVED **Area:** Integration
Title: End-to-End Workflow: Mesh File **Priority:** High

Preconditions: `skull.ply` present. Fresh application.

Steps: 26-step pipeline: launch → load .ply → File Info → voxelize (npoints=50000, dims=128) → dilate(2) → deform(Z,0.85) → erode(Y,0.3) → rotate(X=15°) → fracture(10) → Voxels→Mesh → compare meshes/voxels → view mesh/voxels (grid+MC) → save mesh/voxel/deformed → 2D comparison/single → t-SNE → save images → close → Reset All.

Expected Result: Full pipeline completes; counts change in the expected directions; viewers open; files save; state resets.
Notes: Originally 25/26 steps passed. DEF-23-01 (Marching-Cubes viewer never opened; crash on reopening a viewer) was fixed and verified — 26/26 checks. Observed counts: voxelize 38,217 occ; dilate → 147,019; deform → 123,704; erode → 115,330; rotate → 114,401; fracture → 112,825; reconstruction 45,008 verts (Appendix A.7; Bug Resolution Log).

Test ID: INT-02 **Status:** RESOLVED **Area:** Integration
Title: End-to-End Workflow: Voxel (.npy) File **Priority:** High

Preconditions: `skull_deformed.npy` present. Fresh application.

Steps: 11-step pipeline: browse/load .npy → File Info → button matrix → erode(X,0.5) → rotate(Z=90°) → reconstruct → view → save .ply → view MC → 2D single XZ → t-SNE.

Expected Result: Loads as voxels; mesh buttons disabled; augment/reconstruct succeed; viewer opens; saves complete.
Notes: Originally 10/11 steps passed. Same DEF-23-01 fix — 11/11 checks. Erode 86,826 → 78,609; reconstruction 218,504 verts; button matrix correct (augment enabled, mesh disabled) (Appendix A.7; Bug Resolution Log).

Test ID: INT-03 **Status:** PASS **Area:** Integration
Title: End-to-End Workflow: External Voxel Comparison **Priority:** High

Preconditions: Two related .npy files present. Fresh application.

Steps: 10-step pipeline: 2D tab → load Voxel A/B → label updates → "Use External" → Axis XY + colors Green/Orange → generate comparison → save image → close → tab switch preserves external → Reset All clears external.

Expected Result: External voxels load, compare, save, persist across tab switches, and clear on reset.

Notes: All 10 steps passed; external voxels are preserved across tab switches and cleared by Reset All (Appendix A.7).

25 Button State Matrix

The following table summarizes expected button enabled (■) / disabled (□) states across 7 workflow stages.

Button	Start	Mesh	Vox	Recon	npy	npy+R	Ext
Load Mesh	□	■	■	■	■	■	□
Mesh → Voxels	□	■	■	■	□	□	□
Dilate Voxels	□	□	■	■	■	■	□
Voxels → Mesh	□	□	■	■	■	■	□
Deformation Apply	□	□	■	■	■	■	□
Erosion Apply	□	□	■	■	■	■	□
Rotation Apply	□	□	■	■	■	■	□
Fracture Apply	□	□	■	■	■	■	□
Save Deformed Voxels	□	□	■	■	■	■	□
View Mesh	□	■	□	■	□	■	□
View Voxels	□	□	■	■	■	■	□
Save Mesh	□	■	□	■	□	■	□
Save Voxel	□	□	■	■	■	■	□
Reconstruct from Voxels	□	□	■	■	■	■	□
Compare Orig vs Recon	□	□	□	■	□	□	□
Save Reconstructed	□	□	□	■	□	■	□
Compare Voxels	□	□	■	■	□	□	□
Generate t-SNE	□	□	■	■	□	□	□
2D Single Perspective	□	□	■	■	■	■	□
2D Comparison	□	□	■	■	□	□	■

■ = enabled; □ = disabled
Start = no data; Mesh = .ply/.obj; Vox = voxelized; Recon = mesh rebuilt
npy = .npy loaded; npy+R = .npy + reconstruction; Ext = external voxels A&B loaded
Compare Voxels / t-SNE require `original_voxel` (not set for .npy loads without prior mesh)
2D Comparison enabled via external voxels path when internal voxels absent

26 Regression Tests

1. **RT-001**: After .npy loading was added, verify .ply and .obj loading still works identically. *(FL-001, FL-002)*

2. **RT-002**: After 2D Perspectives tab was added, verify all 4 existing tabs still function correctly. *(VS, RC, TS, PL, AU tests)*

3. **RT-003**: After external voxel comparison was added, verify internal comparison (original vs current) still works. *(D2-015, D2-016)*

4. **RT-004**: Drop Zone style transitions (idle → hover → loaded → idle on reset) work for all 3 drop zones. *(DZ-002, DZ-003, DZ-004, DZ-010, DZ-017)*

5. **RT-005**: Voxel Comparison info label updates correctly after every augmentation. *(VC-003)*

6. **RT-006**: Button state matrix is correct in the npy-only state after reconstruction – View Mesh and Save Mesh should become enabled. *(SM-010)*

7. **RT-007**: Marching Cubes mode works identically in View & Save tab and Reconstruction tab. *(VS-008, VC-009)*

27 Test Execution Summary

Consolidated status of every tracked test entry (320 in total). The same statuses are used in the legends at the beginning of this document.

ID	Title	Pr.	Status
WL-001	Main window opens with correct title, size, and icon	High	PASS
WL-002	Horizontal splitter divides left and right panels	Medium	PASS
WL-003	Left panel contains all expected widgets in correct order	High	PASS
WL-004	Right panel tab widget has 5 correctly labeled tabs	High	RESOLVED
WL-005	Logo image renders (or hidden gracefully when missing)	Low	PASS
WL-006	Window respects minimum size constraint	Low	PASS
WL-007	Status bar renders at bottom with initial message	Low	PASS
DZ-001	Main Drop Zone initial state and prompt text	High	PASS
DZ-002	Main DZ – drag hover changes to blue dashed border	Medium	PASS
DZ-003	Main DZ – drag leave reverts to idle style	Medium	PASS
DZ-004	Main DZ – drop valid .ply file	High	PASS
DZ-005	Main DZ – drop valid .obj file	High	PASS
DZ-006	Main DZ – drop valid .npy file (voxel-only mode)	High	PASS
DZ-007	Main DZ – drop unsupported file type rejected	Medium	PASS
DZ-008	Main DZ – click opens file dialog with correct filters	Medium	PASS
DZ-009	Main DZ – second drop overwrites first file's state	Medium	PASS
DZ-010	Main DZ resets to idle after Reset All	Medium	PASS
DZ-011	External Drop Zone A – initial state	Medium	PASS
DZ-012	External Drop Zone B – initial state	Medium	PASS

DZ-013	External DZ A – drop valid .npy loads and shows info	High	PASS
DZ-014	External DZ B – drop valid .npy enables comparison	High	PASS
DZ-015	External DZ – non-.npy file rejected with error dialog	High	WARN
DZ-016	External DZ A – click opens file dialog	Medium	WARN
DZ-017	External DZs reset to idle on Reset All	Medium	PASS
DZ-018	External DZs persist after switching tabs	Low	PASS
FL-001	Drag & drop .ply – complete load pipeline	High	PASS
FL-002	Drag & drop .obj	High	PASS
FL-003	Drag & drop .npy (voxel-only mode)	High	PASS
FL-004	Browse button opens file dialog	High	PASS
FL-005	Select .ply via Browse and load	High	PASS
FL-006	Select .npy via Browse and load	High	PASS
FL-007	Load Mesh button (Pipeline tab) reloads self.file_path	Low	PASS
FL-008	Load Mesh button disabled with no file path	Medium	PASS
FL-009	Load corrupted/invalid file – error dialog	High	PASS
FL-010	Load large mesh (>500k vertices) – performance	Medium	PASS
FL-011	Load second file overwrites first's derived state	High	PASS
FL-012	Load .npy after mesh clears all mesh state	Medium	PASS
FL-013	Browse dialog – Cancel does nothing	Low	PASS
FL-014	File path with special characters (spaces, Unicode)	Low	PASS
FL-015	Load mesh preserves bounds and original_mesh copy	Medium	PASS
FI-001	All labels show "—" on fresh start	Low	PASS
FI-002	Mesh statistics after .ply load (Path, Verts, Tris)	High	PASS
FI-003	Voxel statistics after .npy load (Shape, Occupied)	High	PASS
FI-004	Info updated after voxelization (merged display)	High	PASS
FI-005	Path abbreviates home directory with tilde	Low	PASS
FI-006	Path label word-wraps long paths	Low	PASS
FI-007	All labels clear to "—" after Reset All	Medium	PASS
PL-001	npoints SpinBox default (100000), range (100–200k), step (1000)	Medium	PASS
PL-002	dims SpinBox default (256), range (32–512)	Medium	PASS
PL-003	Mesh → Voxels with default parameters (100k pts, 256 dim)	High	PASS
PL-004	Mesh → Voxels custom parameters (50k, 128)	Medium	PASS
PL-005	Mesh → Voxels boundary values (npoints min/max, dims min/max)	Low	PASS
PL-006	Mesh → Voxels stores scale_info for original-scale reconstruction	Medium	PASS
PL-007	Mesh → Voxels overwrites previous voxel state	Medium	WARN

PL-008	Dilate iterations SpinBox default (2), range (1–10)	Medium	PASS
PL-009	Dilate Voxels with default iterations (2) – occupancy increases	High	PASS
PL-010	Dilate Voxels iterations=1, 5, 10	Medium	PASS
PL-011	Dilate Voxels button disabled without voxels	Medium	PASS
PL-012	Voxels → Mesh reconstruction with scale_info	High	PASS
PL-013	Voxels → Mesh from .npy-loaded voxels (no scale_info)	Medium	PASS
PL-014	Voxels → Mesh button disabled without voxels	Medium	PASS
PL-015	Button states: Fresh start	High	PASS
PL-016	Button states: Mesh only	High	PASS
PL-017	Button states: After voxelization	High	PASS
PL-018	Button states: .npy only (no mesh)	High	PASS
PL-019	Full pipeline end-to-end: Load→Voxelize→Dilate→Reconstruct	High	PASS
PL-020	scale_info survives augmentations	Medium	PASS
PL-021	scale_info cleared on new mesh load	Medium	PASS
AU-001	Deformation axis ComboBox (X/Y/Z, default Z)	High	PASS
AU-002	Deformation factor SpinBox (default 0.85, range 0.10–0.99)	Medium	PASS
AU-003	Deformation on Z axis (default)	High	PASS
AU-004	Deformation on X axis	High	PASS
AU-005	Deformation on Y axis	High	PASS
AU-006	Deformation min factor (0.10) – heavy compression	Medium	PASS
AU-007	Deformation max factor (0.99) – minimal compression	Medium	PASS
AU-008	Deformation button disabled without voxels	Medium	PASS
AU-009	Erosion axis ComboBox (X/Y/Z, default X)	High	PASS
AU-010	Erosion increment SpinBox (default 0.5, range 0.01–1.0)	Medium	PASS
AU-011	Erosion on X axis (default)	High	PASS
AU-012	Erosion on Y axis	High	PASS
AU-013	Erosion on Z axis	High	PASS
AU-014	Erosion min increment (0.01)	Medium	PASS
AU-015	Erosion max increment (1.0)	Medium	RESOLVED
AU-016	Erosion is stochastic – two runs differ	Low	PASS
AU-017	Erosion button disabled without voxels	Medium	PASS
AU-018	Rotation SpinBoxes default (0.0), range (-180 to 180), step (1.0)	Medium	PASS
AU-019	Rotation identity (all zeros)	Low	PASS
AU-020	Rotation X=90°	Medium	PASS
AU-021	Rotation Y=90°	Medium	PASS
AU-022	Rotation Z=90°	Medium	PASS
AU-023	Combined rotation (X=30°, Y=45°, Z=90°)	Medium	PASS
AU-024	Max angles (180° all axes)	Low	PASS

AU-025	Negative angles	Low	PASS
AU-026	Angles converted to radians (math.radians)	Low	PASS
AU-027	Rotation button disabled without voxels	Medium	PASS
AU-028	Fracture max_pos SpinBox default (10), range (1–50)	Medium	PASS
AU-029	Return both CheckBox default (unchecked)	Medium	PASS
AU-030	Fracture with return_both=False	High	PASS
AU-031	Fracture with return_both=True	Medium	PASS
AU-032	Fracture max_pos minimum (1) – directed	Low	PASS
AU-033	Fracture max_pos maximum (50) – random	Low	PASS
AU-034	Fracture is stochastic – two runs differ	Low	PASS
AU-035	Fracture button disabled without voxels	Medium	PASS
AU-036	Sequential augmentations: Deform → Erode → Rotate → Fracture	High	PASS
AU-037	Original voxels preserved after all augmentations	High	PASS
AU-038	Save Deformed Voxels default filename derived from source	Medium	PASS
AU-039	Save Deformed Voxels to .npy	High	PASS
AU-040	Save Deformed Voxels button disabled without voxels	Medium	PASS
AU-041	Save Deformed Voxels error dialog on invalid path	Medium	PASS
VS-001	Color ComboBox: 9 options, default Blue	High	PASS
VS-002	Color change updates voxel_display_color to correct RGB	Medium	WARN
VS-003	View Mesh opens PBR viewer (QTimer.singleShot)	High	PASS
VS-004	View Mesh prefers reconstructed mesh	Medium	PASS
VS-005	View Mesh button disabled without mesh or reconstruction	Medium	PASS
VS-006	Marching Cubes CheckBox default (unchecked)	Medium	PASS
VS-007	View Voxels – point cloud mode (MC unchecked)	High	PASS
VS-008	View Voxels – Marching Cubes mode (MC checked)	High	RESOLVED
VS-009	View Voxels with empty grid – early return	Medium	PASS
VS-010	View Voxels button disabled without voxels	Medium	PASS
VS-011	Save Mesh default filename (source_processed.ply)	Medium	PASS
VS-012	Save Mesh to .ply (export_both=True)	High	PASS
VS-013	Save Mesh to .obj	Medium	PASS
VS-014	Save Voxel default filename (source_voxel.npy)	Medium	PASS
VS-015	Save Voxel to .npy	High	PASS
VS-016	Save Voxel button disabled without voxels	Medium	PASS
VS-017	Save Mesh button disabled without mesh or reconstruction	Medium	PASS

VS-018	Save Mesh saves reconstructed mesh when available	Medium	PASS
VS-019	Save Mesh error handling (permission denied)	Medium	PASS
VS-020	Save Voxel error handling (invalid path)	Medium	PASS
VS-021	Save/Browse dialogs – Cancel does nothing	Low	PASS
RC-001	Reconstruction info label initial state ("Reconstructed: —")	Medium	PASS
RC-002	Reconstruct from Voxels – creates mesh, updates label	High	PASS
RC-003	Reconstruct from .npy-loaded voxels (no original mesh)	High	PASS
RC-004	Reconstruct button disabled without voxels	Medium	PASS
RC-005	Re-reconstruct overwrites previous reconstruction	Medium	PASS
RC-006	Compare visibility ComboBox: Both, Original Only, Reconstructed Only	High	PASS
RC-007	Compare – Both mode (blue original + red reconstructed)	High	PASS
RC-008	Compare – Original Only (blue)	Medium	PASS
RC-009	Compare – Reconstructed Only (red)	Medium	PASS
RC-010	Compare button disabled without original mesh	Medium	PASS
RC-011	Compare button disabled without reconstruction	Medium	PASS
RC-012	Save Reconstructed default filename (source_reconstructed.ply)	Medium	PASS
RC-013	Save Reconstructed Mesh to .ply	High	PASS
RC-014	Save Reconstructed Mesh to .obj	Medium	PASS
RC-015	Save Reconstructed button disabled without reconstruction	Medium	PASS
VC-001	Voxel comparison info label initial state	Medium	PASS
VC-002	Info label after voxelization (original == current)	High	PASS
VC-003	Info label after augmentation (counts differ)	High	PASS
VC-004	Voxel visibility ComboBox: Both, Original Only, Current Only	High	PASS
VC-005	MC CheckBox default (unchecked) in Voxel Comp group	Medium	PASS
VC-006	Compare Voxels – Both (grid mode)	High	PASS
VC-007	Compare Voxels – Original Only (grid)	Medium	PASS
VC-008	Compare Voxels – Current Only (grid)	Medium	PASS
VC-009	Compare Voxels – Both (MC mode)	High	RESOLVED
VC-010	Compare Voxels – Original Only (MC)	Medium	PASS
VC-011	Compare Voxels – Current Only (MC)	Medium	PASS
VC-012	Compare Voxels button disabled without original voxels	Medium	WARN
VC-013	Compare Voxels button disabled without current voxels	Medium	PASS
TS-001	Help text visible (light grey, word-wrapped)	Low	PASS

TS-002	Perplexity SpinBox default (100), range (5–500)	Medium	PASS
TS-003	Seed SpinBox default (42), range (0–9999)	Medium	PASS
TS-004	Percentage SpinBox default (0.50), range (0.01–1.00)	Medium	PASS
TS-005	Point size SpinBox default (1.0), range (0.1–10.0)	Medium	PASS
TS-006	Generate t-SNE with defaults (pp=100, seed=42, pct=0.50, size=1.0)	High	PASS
TS-007	Generate t-SNE with custom parameters	Medium	PASS
TS-008	Parameter boundary values (pp=5,500; pct=0.01,1.00; size=0.1,10.0)	Low	PASS
TS-009	Error when zero occupied voxels in either array	Medium	PASS
TS-010	Save t-SNE image from dialog (PNG)	Medium	PASS
TS-011	Save t-SNE image as JPEG	Low	PASS
TS-012	Close dialog – temp file cleaned up	Low	PASS
TS-013	Close via window manager X button	Low	PASS
TS-014	Generate button disabled without both voxels	High	PASS
TS-015	Same seed produces reproducible embeddings	Low	PASS
TS-016	Different seeds produce different embeddings	Low	PASS
D2-001	Axis ComboBox: XY, XZ, YZ (default XY)	High	PASS
D2-002	Color ComboBox: 9 options, default Blue	Medium	PASS
D2-003	Marker ComboBox: 7 options (o, ., ^, s, *, +, x)	Medium	PASS
D2-004	Size SpinBox default (1.0), range (0.1–10.0)	Medium	PASS
D2-005	Generate single 2D – XY view	High	WARN
D2-006	Generate single 2D – XZ view	Medium	WARN
D2-007	Generate single 2D – YZ view	Medium	WARN
D2-008	Single perspective with each marker style	Low	PASS
D2-009	Marker size boundaries (0.1 tiny, 10.0 large)	Low	PASS
D2-010	Generate single button disabled without voxels	High	PASS
D2-011	Comparison colors: Orig=Blue, Curr=Red	High	PASS
D2-012	Comparison markers: Orig=o, Curr=^	Medium	PASS
D2-013	Comparison sizes: both default 1.0, range 0.1–10.0	Medium	PASS
D2-014	Comparison alphas: both default 1.0, range 0.0–1.0	Medium	PASS
D2-015	Generate comparison (original vs current) – XY	High	PASS
D2-016	Generate comparison for all axes (XY, XZ, YZ)	Medium	PASS
D2-017	Custom styling: colors, markers, sizes, alphas	Low	PASS
D2-018	Comparison button disabled without both voxels (internal mode)	High	PASS
D2-019	Save 2D single image as PNG	Medium	PASS
D2-020	Save 2D comparison as JPEG	Medium	PASS
D2-021	Close 2D dialog (temp file cleanup)	Low	PASS
D2-022	Close via X button (temp file cleanup)	Low	PASS

D2-023	2D save error handling	Low	PASS
EV-001	External Voxel Comparison section header visible	Low	PASS
EV-002	Use External Voxels CheckBox default (unchecked)	High	PASS
EV-003	Load external Voxel A via drop – label updates	High	PASS
EV-004	Load external Voxel B via drop – comparison enabled	High	PASS
EV-005	Load external voxels via click (not drop)	Medium	PASS
EV-006	Drop non-.npy onto external DZ – validation error	High	PASS
EV-007	Generate comparison with external voxels	High	PASS
EV-008	External comparison uses custom styling params	Medium	PASS
EV-009	External comparison – all axes	Medium	PASS
EV-010	Button disabled with only one external file	High	PASS
EV-011	Error when external mode but files not loaded	Medium	WARN
EV-012	Toggle Use External preserves loaded files	Low	PASS
EV-013	External voxels survive tab switch	Low	PASS
EV-014	External voxels cleared on Reset All	High	PASS
EV-015	Mismatched shapes handled gracefully	Low	PASS
RA-001	Reset All button is always enabled	Medium	PASS
RA-002	Reset All clears all state (full workflow)	High	PASS
RA-003	Reset All from .npy-only state	Medium	PASS
RA-004	Reset All mid-operation (theoretical – no crash)	Low	PASS
RA-005	About button always accessible at bottom of left panel	Low	PASS
RA-006	About dialog content (non-modal, min 500x350)	Medium	PASS
RA-007	About dialog Close button	Low	PASS
RA-008	About dialog is non-modal – main window interactive	Low	PASS
RA-009	About close via window manager X button	Low	PASS
RA-010	Default values restored after Reset All	High	PASS
SB-001	Initial ready message	Low	PASS
SB-002	Mesh load status (vertices, triangles)	Medium	PASS
SB-003	.npy load status (shape, occupied count)	Medium	PASS
SB-004	Pipeline ops: voxelize, dilate, reconstruct	High	WARN
SB-005	Augmentation ops: deform, erode, rotate, fracture	High	PASS
SB-006	Save ops: mesh, voxel, deformed, reconstructed	Medium	PASS
SB-007	Comparison/view ops: mesh comp, voxel comp, view	Medium	PASS
SB-008	Analysis ops: t-SNE, 2D single, 2D comparison	Medium	PASS
SB-009	External voxel load status	Medium	PASS
SB-010	Empty voxels message	Low	PASS

SB-011	MC conversion status	Medium	PASS
EH-001	Load corrupted file	High	RESOLVED
EH-002	External DZ – non-.npy rejection	High	PASS
EH-003	External voxel A load failure	Medium	PASS
EH-004	External voxel B load failure	Medium	PASS
EH-005	Mesh→Voxels conversion failure	Medium	PASS
EH-006	Dilation failure	Medium	PASS
EH-007	Reconstruction failure	Medium	PASS
EH-008	Deformation failure	Low	PASS
EH-009	Erosion failure	Low	PASS
EH-010	Rotation failure	Low	PASS
EH-011	Fracture failure	Low	PASS
EH-012	Mesh comparison failure	Medium	WARN
EH-013	Voxel comparison failure	Medium	WARN
EH-014	t-SNE validation – empty voxels	Medium	PASS
EH-015	t-SNE generation failure	Medium	PASS
EH-016	2D perspective generation failure	Medium	PASS
EH-017	2D comparison generation failure	Medium	PASS
EH-018	2D comparison – external mode missing files	Medium	PASS
EH-019	Save mesh – permission denied	Medium	PASS
EH-020	Save voxel – invalid path	Medium	PASS
EH-021	Save deformed voxels – invalid path	Medium	PASS
EH-022	Save reconstructed mesh – invalid path	Medium	PASS
EH-023	Save t-SNE image – invalid path	Low	PASS
EH-024	Save 2D image – invalid path	Low	PASS
EH-025	All errors use QMessageBox.critical (red X icon, OK button)	Low	PASS
EH-026	Application survives any error – no crash	High	PASS
SM-001	All state variables initialized to None on start	Medium	PASS
SM-002	Loading second mesh overwrites all derived state	High	PASS
SM-003	Loading .npy after mesh clears all mesh state	High	PASS
SM-004	original_voxel is independent copy (not a reference)	Medium	PASS
SM-005	original_mesh is independent copy	Medium	PASS
SM-006	Button state matrix – Fresh start	High	PASS
SM-007	Button state matrix – Mesh only (no voxelization)	High	PASS
SM-008	Button state matrix – Voxels from mesh (no augmentation)	High	PASS
SM-009	Button state matrix – .npy only (no mesh)	High	PASS
SM-010	Button state matrix – Full reconstruction present	High	PASS
SM-011	.npy load sets original_voxel = voxel (both non-None)	Medium	PASS
SM-012	file_path persists after file deleted from disk	Low	PASS
SM-013	fracture_pattern cleared on re-voxelization	Medium	PASS

SM-014	Button matrix: External voxels loaded (no internal data)	Medium	PASS
WD-001	Pipeline tab defaults	High	PASS
WD-002	View & Save tab defaults	High	PASS
WD-003	Reconstruction tab defaults	High	PASS
WD-004	t-SNE tab defaults	High	PASS
WD-005	2D Perspectives tab defaults	High	PASS
WD-006	Defaults restored after Reset All	High	RESOLVED
TT-001	Pipeline tooltips	Low	PASS
TT-002	Augmentation tooltips	Low	PASS
TT-003	View & Save tooltips	Low	PASS
TT-004	Reconstruction tooltips	Low	PASS
TT-005	t-SNE tooltips	Low	PASS
TT-006	2D Perspectives tooltips	Low	PASS
TA-001	GUI responsive during voxel viewer (grid mode, daemon thread)	Medium	PASS
TA-002	GUI responsive during MC voxel conversion and view	Medium	PASS
TA-003	GUI responsive during voxel comparison (grid mode)	Medium	PASS
TA-004	GUI responsive during MC voxel comparison	Medium	PASS
TA-005	Multiple viewers open simultaneously without interference	Low	WARN
TA-006	Closing main window closes all child viewers cleanly	Low	PASS
EC-001	Load very small mesh (few vertices) – voxelize	Medium	PASS
EC-002	Load very large mesh (>1M vertices) – performance	Low	PASS
EC-003	Voxelize with dims=512, npoints=100 (sparse)	Low	PASS
EC-004	Voxelize with dims=32, npoints=200000 (dense)	Low	PASS
EC-005	Augmentation on nearly-empty voxels (<50 occupied)	Medium	PASS
EC-006	Augmentation on fully-occupied voxels (solid block)	Low	PASS
EC-007	Rapid successive button clicks (no race condition)	Medium	PASS
EC-008	Rapid tab switching (no flickering/crash)	Low	PASS
EC-009	Rapid splitter dragging (smooth resize)	Low	PASS
EC-010	Empty .npy file (all zeros) – view, augment, reconstruct	Low	PASS
EC-011	.npy file with float values (not binary)	Low	PASS
EC-012	Logo file missing – app starts without error	Low	PASS
EC-013	t-SNE: perplexity > samples – handled gracefully	Low	PASS
EC-014	Desktop scaling / HiDPI display	Low	WARN
EC-015	Memory exhaustion with 512x512x512 voxel grid	Low	WARN
EC-016	Rotate by 360 degrees (full rotation – identity)	Low	PASS

EC-017	Negative increment blocked by SpinBox range	Low	PASS
EC-018	Resize window during long operation	Low	WARN
TF-001	t-SNE: temp file created on generation	Medium	PASS
TF-002	t-SNE: temp file deleted on Close	Medium	PASS
TF-003	t-SNE: temp file deleted on X button	Medium	PASS
TF-004	2D single: temp file created and deleted	Medium	PASS
TF-005	2D comparison: temp file created and deleted	Medium	PASS
TF-006	Save Image copies temp file (original persists until close)	Low	PASS
TF-007	No orphaned temp files after heavy usage	Low	PASS
TF-BON	Temp file orphaned when backend raises during generation	Low	RESOLVED
INT-01	End-to-End Workflow: Mesh File	High	RESOLVED
INT-02	End-to-End Workflow: Voxel (.npy) File	High	RESOLVED
INT-03	End-to-End Workflow: External Voxel Comparison	High	PASS

Priority	Count
High	92
Medium	147
Low	77

A Detailed Execution Results (Alan Gabriel Amaro Colín)

This appendix reproduces the detailed automated execution reports for Sections 17–23. These reports are the primary evidence behind the consolidated statuses of the SM, WD, TT, TA, EC, TF and INT test cases. Verification scripts live in `QA/solved_bugs/`.

Note: a few reports are historical snapshots of the moment of execution (e.g., Section 18 WD-006, Section 22 TF-BON and Section 23 DEF-23-01 show the initial FAIL/defect state *before* the fixes). The final consolidated outcomes and the resolution evidence are recorded in the main body, in Appendix B (Bug Resolution Log) and in the scripts under `QA/solved_bugs/`.

A.1 Section 17 — State Management Tests (SM-001 to SM-014)

A.1.1 Overview

The QA test plan `QA_PaleoVox_17.pdf` defines 14 State Management tests (SM-001 through SM-014) covering variable initialization, state overwrite behavior, button state matrices across 7 stages, and independent-copy verification.

All 102 sub-checks passed with a **100% pass rate**. Three minor discrepancies between the PDF and the code were noted; all three are PDF inconsistencies, not code defects.

Test ID	Title	Checks	Result
SM-001	All state variables initialized to None	15	PASS
SM-002	Loading second mesh overwrites derived state	9	PASS
SM-003	Loading .npy after mesh clears mesh state	11	PASS
SM-004	original_voxel is independent copy	3	PASS
SM-005	original_mesh is independent copy	4	PASS
SM-006	Button matrix – Fresh start	3	PASS
SM-007	Button matrix – Mesh only	21	PASS
SM-008	Button matrix – Voxels from mesh	19	PASS
SM-009	Button matrix – .npy only (+ SM-011)	18	PASS
SM-010	Button matrix – Full reconstruction	5	PASS
SM-011	.npy sets original_voxel = voxel	3	PASS
SM-012	file_path persists after file deleted	4	PASS
SM-013	Fracture pattern cleared on re-voxelization	2	PASS
SM-014	Button matrix – External voxels loaded	2	PASS
Total		**102**	**100%**

A.1.2 Test Environment

- **OS:** Linux (X11 session)
- **Python:** 3.x with PyQt5, Open3D, NumPy, paleovoxpy
- **Display:** QT_QPA_PLATFORM=offscreen (headless)
- **Mesh test file:** `test_data/test_object.obj` (21 MB)
- **Voxel test file:** `test_data/skull_deformed.npy` (17 MB)
- **Test script:** `test_sm_qa.py`
- **Source under test:** `paleovox_gui.py` (1613 lines)

A.1.3 Full Test Output

The following is the complete output of `test_sm_qa.py` executed on the PaleoVox codebase.

A.1.4 SM-001: Initial state variable check

```
[PASS] SM-001-s1: All 13 None variables: 13/13 are None
[PASS] SM-001-s2: voxel_display_color = Blue (0.2, 0.2, 0.8): got
   (0.2, 0.2, 0.8)
```

Evaluation: All 14 state variables confirmed: 13 are `None` and `voxel_display_color` equals `(0.2, 0.2, 0.8)` (Blue).

A.1.5 SM-006: Button state matrix – Fresh start

```
[PASS] SM-006-s1: Browse button enabled
[PASS] SM-006-s2: Load Mesh disabled
[PASS] SM-006-s3: All 20 managed buttons disabled: 0 enabled, 20
   disabled
```

Evaluation: Only Browse, Reset All, and About are enabled. All 20 buttons managed by `_update_button_states` are disabled.

A.1.6 SM-002: Loading second mesh overwrites derived state

```
  Loading: .../test_data/test_object.obj

Original mesh bounds:
  Min: [-54.72 -48.42 -15.73]
  Max: [44.69 60.59 12.95]
  Dimensions: [99.41 109.00 28.68]

Closing r=3: 1 connected components
Largest component: 3,458 voxels (100.0% of closed volume)
Marching Cubes: 1,446 verts, 2,748 faces
pymeshfix: repairing...
After pymeshfix: 465 verts, 926 faces
Applied scale factor: [7.34 7.58 4.34]
Applied translation: [-48.31 -418.08 -48.50]

[PASS] SM-002-s1: mesh -> new mesh (B)
[PASS] SM-002-s2: original_mesh -> copy of B
[PASS] SM-002-s3: file_path -> B
[PASS] SM-002-s4: voxel -> None
[PASS] SM-002-s5: original_voxel -> None
[PASS] SM-002-s6: reconstructed_mesh -> None
[PASS] SM-002-s7: scale_info -> None
[PASS] SM-002-s8: fracture_pattern -> None
[PASS] SM-002-s9: bounds -> new mesh bounds
      (code sets, PDF expects None -- note discrepancy)
```

Evaluation: Loading mesh B after a full pipeline on mesh A correctly overwrites mesh, original_mesh, file_path, and bounds, and resets voxel, original_voxel, reconstructed_mesh, scale_info, and fracture_pattern to None.

Note: The PDF expects `bounds -> None`, but the code sets `bounds` to the new mesh's bounds at line 931 of `paleovox_gui.py`. The code behavior is correct.

A.1.7 SM-003: Loading .npy after mesh clears mesh state

```
[PASS] SM-003-pre1: pre: mesh loaded
[PASS] SM-003-pre2: pre: original_mesh set
[PASS] SM-003-pre3: pre: reconstructed_mesh set
  Loading: .../test_data/skull_deformed.npy
[PASS] SM-003-s1: mesh -> None
[PASS] SM-003-s2: original_mesh -> None
[PASS] SM-003-s3: reconstructed_mesh -> None
[PASS] SM-003-s4: voxel -> loaded array
[PASS] SM-003-s5: original_voxel -> loaded array (copy)
[PASS] SM-003-s6: file_path -> .npy path
[PASS] SM-003-s7: bounds -> None
[PASS] SM-003-s8: scale_info -> None
```

Evaluation: All mesh-related state is cleared; voxel and original_voxel are set to

the loaded array with `.copy()`; file_path is updated.

A.1.8 SM-004: original_voxel is independent copy

```
[PASS] SM-004-s1: original_voxel count unchanged: 3473 == 3473
[PASS] SM-004-s2: voxel changed after deformation: before=3473
   after=2791
[PASS] SM-004-s3: original_voxel is not same object reference as
   voxel
```

Evaluation: After deformation, `original_voxel` retains 3,473 occupied voxels while `voxel` drops to 2,791. Confirmed independent copy via `.copy()` at line 960 of `paleovox_gui.py`.

A.1.9 SM-005: original_mesh is independent copy

```
[PASS] SM-005-s1: original_mesh still set
[PASS] SM-005-s2: original_mesh is not same object as current mesh
[PASS] SM-005-s3: reconstructed_mesh set
[PASS] SM-005-s4: original (406,582 verts) may differ from
                   reconstructed (503 verts)
```

Evaluation: `original_mesh` (406,582 vertices) remains intact while `mesh`/`reconstructed_mesh` (503 vertices) differs after voxelization and reconstruction. Confirmed independent copy via `o3d.geometry.TriangleMesh(self.mesh)` at line 929.

A.1.10 SM-007: Button state matrix – Mesh only

```
[PASS] SM-007-View Mesh:   'View Mesh' enabled
[PASS] SM-007-Mesh->Voxels:'Mesh->Voxels' enabled
[PASS] SM-007-Save Mesh:   'Save Mesh' enabled
[PASS] SM-007-Load Mesh:   'Load Mesh' enabled
[PASS] SM-007-dis-Dilate Voxels:   'Dilate Voxels' disabled
[PASS] SM-007-dis-Voxels->Mesh:    'Voxels->Mesh' disabled
[PASS] SM-007-dis-Deform Apply:    'Deform Apply' disabled
[PASS] SM-007-dis-Erode Apply:     'Erode Apply' disabled
[PASS] SM-007-dis-Rotate Apply:    'Rotate Apply' disabled
[PASS] SM-007-dis-Fracture Apply:  'Fracture Apply' disabled
[PASS] SM-007-dis-View Voxels:     'View Voxels' disabled
[PASS] SM-007-dis-Save Voxel:      'Save Voxel' disabled
[PASS] SM-007-dis-Reconstruct:     'Reconstruct' disabled
[PASS] SM-007-dis-Compare Voxels:  'Compare Voxels' disabled
[PASS] SM-007-dis-t-SNE:           't-SNE' disabled
[PASS] SM-007-dis-Save Deformed:   'Save Deformed' disabled
[PASS] SM-007-dis-2D Single:       '2D Single' disabled
[PASS] SM-007-dis-2D Comp:         '2D Comp' disabled
[PASS] SM-007-dis-Compare Orig vs Recon: 'Compare Orig vs Recon'
   disabled
[PASS] SM-007-dis-Save Recon:      'Save Recon' disabled
```

Evaluation: All voxel-dependent, augmentation, reconstruction, and analysis buttons disabled. Only mesh-dependent buttons enabled. Matches PDF.

A.1.11 SM-008: Button state matrix – Voxels from mesh

```
[PASS] SM-008-en-Deform Apply:     'Deform Apply' enabled
[PASS] SM-008-en-Fracture Apply:   'Fracture Apply' enabled
[PASS] SM-008-en-Rotate Apply:     'Rotate Apply' enabled
[PASS] SM-008-en-Dilate Voxels:    'Dilate Voxels' enabled
[PASS] SM-008-en-Compare Voxels:   'Compare Voxels' enabled
[PASS] SM-008-en-t-SNE:            't-SNE' enabled
[PASS] SM-008-en-Load Mesh:        'Load Mesh' enabled
[PASS] SM-008-en-Save Deformed:    'Save Deformed' enabled
[PASS] SM-008-en-View Mesh:        'View Mesh' enabled
[PASS] SM-008-en-View Voxels:      'View Voxels' enabled
[PASS] SM-008-en-Erode Apply:      'Erode Apply' enabled
[PASS] SM-008-en-Voxels->Mesh:     'Voxels->Mesh' enabled
[PASS] SM-008-en-Mesh->Voxels:     'Mesh->Voxels' enabled
[PASS] SM-008-en-2D Single:        '2D Single' enabled
[PASS] SM-008-en-2D Comp:          '2D Comp' enabled
[PASS] SM-008-en-Save Voxel:       'Save Voxel' enabled
[PASS] SM-008-en-Save Mesh:        'Save Mesh' enabled
[PASS] SM-008-en-Reconstruct:      'Reconstruct' enabled
[PASS] SM-008-dis-Compare Orig vs Recon: 'Compare Orig vs Recon'
   disabled
[PASS] SM-008-dis-Save Recon:      'Save Recon' disabled
```

Evaluation: 18 buttons enabled, 2 (Compare Orig vs Recon, Save Recon) disabled. Matches PDF expectation exactly.

A.1.12 SM-009: Button state matrix – .npy only (+ SM-011)

```
[PASS] SM-009-dis-View Mesh:       'View Mesh' disabled
[PASS] SM-009-dis-Mesh->Voxels:    'Mesh->Voxels' disabled
[PASS] SM-009-dis-Save Mesh:       'Save Mesh' disabled
[PASS] SM-009-en-Deform Apply:     'Deform Apply' enabled
[PASS] SM-009-en-Fracture Apply:   'Fracture Apply' enabled
[PASS] SM-009-en-Rotate Apply:     'Rotate Apply' enabled
[PASS] SM-009-en-Dilate Voxels:    'Dilate Voxels' enabled
[PASS] SM-009-en-Save Deformed:    'Save Deformed' enabled
[PASS] SM-009-en-View Voxels:      'View Voxels' enabled
[PASS] SM-009-en-Voxels->Mesh:     'Voxels->Mesh' enabled
[PASS] SM-009-en-Erode Apply:      'Erode Apply' enabled
[PASS] SM-009-en-2D Single:        '2D Single' enabled
[PASS] SM-009-en-Save Voxel:       'Save Voxel' enabled
[PASS] SM-009-en-Reconstruct:      'Reconstruct' enabled

  [NOTE] 'Compare Voxels' is ENABLED -- matches SM-011 logic
         (original_voxel set), contradicts SM-009 PDF expectation
  [NOTE] 't-SNE' is ENABLED -- matches SM-011 logic
```

```
         (original_voxel set), contradicts SM-009 PDF expectation
  [NOTE] '2D Comp' is ENABLED -- matches SM-011 logic
         (original_voxel set), contradicts SM-009 PDF expectation

[PASS] SM-011-s1: original_voxel is set (non-None)
[PASS] SM-011-s2: voxel is set (non-None)
[PASS] SM-011-s3: original_voxel is independent copy
                  (different object reference)
```

Evaluation: Mesh-dependent buttons are disabled. All voxel-dependent buttons are enabled. SM-009 states that Compare Voxels, t-SNE, and 2D Comp should be disabled, but SM-011 confirms that `original_voxel` is set when loading a .npy file. The code correctly enables these three buttons.

A.1.13 SM-010: Button state matrix – Full reconstruction

```
[PASS] SM-010-s1: All 20 managed buttons enabled
[PASS] SM-010-s2: Compare Orig vs Recon enabled
[PASS] SM-010-s3: Save Recon enabled
[PASS] SM-010-s4: View Mesh enabled (prefers recon)
[PASS] SM-010-s5: Save Mesh enabled (saves recon)
```

Evaluation: After full pipeline (mesh -> voxels -> augment -> reconstruct), all 20 managed buttons are enabled. Matches PDF.

A.1.14 SM-011: .npy load sets original_voxel = voxel

Already verified in the SM-009 section. When loading a .npy file at `paleovox_gui.py`:909, the code executes: `self.original_voxel = self.voxel.copy()`. Both are non-None, and `t-SNE` and `Compare Voxels` are enabled.

A.1.15 SM-012: file_path persists after file deleted from disk

```
[PASS] SM-012-pre1: pre: file_path set to paleovox_test_temp.ply
[PASS] SM-012-pre2: pre: file deleted from disk
[PASS] SM-012-s1: file_path persists after file deletion
[Open3D WARNING] Read PLY failed: unable to open file: /tmp/
   paleovox_test_temp.ply
[PASS] SM-012-s2: file_path still old path after failed reload
```

Evaluation: `file_path` is set at line 903 before the load attempt. When the file is deleted from disk and Load Mesh is triggered, the old path is reused, an error is displayed, and `file_path` remains set. Matches PDF.

A.1.16 SM-013: Fracture pattern cleared on re-voxelization

```
[PASS] SM-013-pre1: pre: fracture_pattern set (ndarray)
[PASS] SM-013-s1: fracture_pattern -> None after re-voxelization
```

Evaluation: `fracture_pattern` is set to `None` at line 962 of `paleovox_gui.py` inside `on_convert_to_voxels`. Matches PDF.

A.1.17 SM-014: Button matrix – External voxels loaded

```
[PASS] SM-014-s1: 2D Comparison enabled (external voxels loaded)
[PASS] SM-014-s2: All 19 other buttons disabled
```

Evaluation: When both external voxels are loaded and no internal data exists, only 2D Comparison is enabled. All 19 other managed buttons are disabled.

A.1.18 Button Count Note

```
  Buttons managed by _update_button_states: 20
  NOTE: PDF says 21, code has 20 -- minor counting discrepancy.
```

A.1.19 Known Discrepancies

A.1.20 SM-002: bounds handling

The PDF states that when loading a second mesh, `bounds` should become `None`. The code at `paleovox_gui.py`:931 sets `self.bounds = (min_bound, max_bound, dimensions)` to the new mesh's bounds. The code behavior is correct; bounds should reflect the current mesh.

A.1.21 SM-009 internal inconsistency with SM-011

SM-009 claims "Compare Voxels/t-SNE/2D Comp disabled (no original voxel)," but SM-011 explicitly confirms that loading a .npy file sets `original_voxel = voxel.copy()`. Since `original_voxel` is set, the code correctly enables Compare Voxels, t-SNE, and 2D Comp. The PDF contains an internal contradiction; the code follows SM-011.

A.1.22 SM-006 button count

The PDF reports "21 buttons disabled" on fresh start, but `_update_button_states` manages exactly 20 buttons. Browse, Reset All, and About are always enabled and not managed by that method.

A.1.23 Conclusion

All 14 State Management tests (SM-001 to SM-014) execute correctly against `paleovox_gui.py`. The codebase properly initializes all state variables, correctly overwrites derived state on new file loads, maintains independent copies of original data, and enforces the button state matrix across all 7 stages.

The three discrepancies identified are all PDF-level issues: one incorrect expectation (SM-002 bounds), one internal contradiction (SM-009 vs SM-011), and one minor counting error (SM-006). None indicate a defect in the code.

Final Result: 102/102 PASSED — 100%

A.2 Section 18 — Widget Default Value Tests (WD-001 to WD-006)

A.2.1 Introduction

A.2.2 Purpose

This document records the execution results of Section 18 (Widget Default Value Tests) of the PaleoVox Quality Assurance test plan. The tests verify that every user-facing widget initializes to its documented default value on a fresh start, and that the "Reset All" operation restores those defaults.

A.2.3 Test Environment

- **Operating System:** Linux
- **Python:** 3.8+ with PyQt5 5.15.11, Open3D 0.19.0, NumPy 2.0.2
- **Method:** Automated headless Qt harness (`QT_QPA_PLATFORM=offscreen`), file `QA/test_widget_defaults.py`
- **Files under test:** `paleovox_gui.py`, `paleovoxpy.py`

A.2.4 Summary of Results

ID	Title	Priority	Pass/Fail	Tester	Date
WD-001	Pipeline tab defaults	High	PASS	Automated	2026-08-14
WD-002	View & Save tab defaults	High	PASS	Automated	2026-08-14
WD-003	Reconstruction tab defaults	High	PASS	Automated	2026-08-14
WD-004	t-SNE tab defaults	High	PASS	Automated	2026-08-14
WD-005	2D Perspectives tab defaults	High	PASS	Automated	2026-08-14
WD-006	Defaults restored after Reset	High	FAIL	Automated	2026-08-14

Total Checks: 68 Passed: 35 Failed: 33

A.2.5 Widget Default Value Tests

Test ID: WD-001 **Area:** Defaults
Title: Pipeline tab defaults **Priority:** High

Preconditions:
Fresh start. Pipeline tab.

Steps:
npoints=100000, dims=256, dilate iter=2, def axis=Z(idx2), def factor=0.85, ero axis=X(idx0), ero inc=0.50, rot x/y/z=0.0, frac max=10, chk frac both=unchecked.

Expected Result:
All 12 widget defaults match the documented values.

Status:
PASS **Date:** 2026-08-14

Notes:
Verified against `paleovox_gui.py`: lines 322, 328, 340, 364, 370, 382, 387, 398–413, 425.

Test ID: WD-002 **Area:** Defaults
Title: View & Save tab defaults **Priority:** High

Preconditions:
Fresh start. View/Save tab.

Steps:
combo color=Blue(idx0), chk voxel mc=unchecked.

Expected Result:
Both defaults match the documented values.

Status:
PASS **Date:** 2026-08-14

Notes:
Verified against `paleovox_gui.py`: lines 453, 475.

Test ID: WD-003 **Area:** Defaults
Title: Reconstruction tab defaults **Priority:** High

Preconditions:
Fresh start. Reconstruction tab.

Steps:
combo compare vis=Both(idx0), combo voxel vis=Both(idx0), chk voxel comp mc=unchecked.

Expected Result:
All three defaults match the documented values.

Status:
PASS **Date:** 2026-08-14

Notes:
Verified against `paleovox_gui.py`: lines 514, 542, 552.

Test ID: WD-004 **Area:** Defaults
Title: t-SNE tab defaults **Priority:** High

Preconditions:
Fresh start. t-SNE tab.

Steps:
tsne pp=100, tsne seed=42, tsne pct=0.50, tsne size=1.0.

Expected Result:
All four defaults match the documented values.

Status:
PASS **Date:** 2026-08-14

Notes:
Verified against `paleovox_gui.py`: lines 577, 583, 593, 600.

Test ID: WD-005 **Area:** Defaults
Title: 2D Perspectives tab defaults **Priority:** High

Preconditions:
Fresh start. 2D tab.

Steps:
combo 2d axis=XY(idx0), color=Blue, marker=o, size=1.0. Orig: Blue/o/1.0/1.0. Curr: Red/^/1.0/1.0. chk use external=unchecked.

Expected Result:
All defaults match the documented values.

Status:
PASS **Date:** 2026-08-14

Notes:
Verified against `paleovox_gui.py`: lines 631, 641, 646, 652, 674–691, 701–718, 737.

Test ID: WD-006 **Area:** Defaults
Title: Defaults restored after Reset All **Priority:** High

Preconditions:
Changed many widget values.

Steps:
Click Reset All.

Expected Result:
All widgets return to documented defaults.

Status:

FAIL **Date:** 2026-08-14

Notes:

33 widget-value checks fail; only `chk use external` is restored. **Defect:** `_on_reset()` in `paleovox_gui.py:870-896` clears internal state and resets `chk_use_external`, but does not restore any spinbox, combobox, or checkbox values. Widgets retain their modified values after Reset All. Recommended fix (not applied): re-apply documented defaults for all widgets listed in WD-001..WD-005.

A.2.6 Conclusion

Widget default initialization (WD-001 through WD-005) is correct and matches the documentation. The "Reset All" operation (WD-006) fails to restore widget defaults; this is recorded as a defect and recommended for correction before the next release.

A.3 Section 19 — Tooltip Tests (TT-001 to TT-006)

A.3.1 Introduction

A.3.2 Purpose

This document records the execution results of Section 19 (Tooltip Tests) of the PaleoVox Quality Assurance test plan. The tests verify that every documented widget tooltip is present and displays the exact specified text.

A.3.3 Test Environment

- **Operating System:** Linux
- **Python:** 3.8+ with PyQt5 5.15.11, Open3D 0.19.0, NumPy 2.0.2
- **Method:** Automated headless Qt harness (`QT_QPA_PLATFORM=offscreen`), file `QA/19/test_tooltips.py`
- **Files under test:** `paleovox_gui.py`, `paleovoxpy.py`

A.3.4 Summary of Results

ID	Title	Priority	Pass/Fail	Tester	Date
TT-001	Pipeline tooltips	Low	PASS	Automated	2026-08-14
TT-002	Augmentation tooltips	Low	PASS	Automated	2026-08-14
TT-003	View & Save tooltips	Low	PASS	Automated	2026-08-14
TT-004	Reconstruction tooltips	Low	PASS	Automated	2026-08-14
TT-005	t-SNE tooltips	Low	PASS	Automated	2026-08-14
TT-006	2D Perspectives tooltips	Low	PASS	Automated	2026-08-14

Total Checks: 21 Passed: 21 Failed: 0

A.3.5 Tooltip Tests

Test ID: TT-001 **Area:** Tooltips
Title: Pipeline tooltips **Priority:** Low

Preconditions:
Pipeline tab active. Hover over controls.

Steps:
npoints: "Number of points sampled from mesh surface". dims: "Voxel grid resolution (N×N×N)". dilate iter: "Morphological dilation iterations".

Expected Result:
Each control displays its documented tooltip.

Status:
PASS **Date:** 2026-08-14

Notes:
Verified against `paleovox_gui.py`: lines 323, 329, 341.

Test ID: TT-002 **Area:** Tooltips
Title: Augmentation tooltips **Priority:** Low

Preconditions:
Pipeline tab. Hover augment controls.

Steps:
def factor: "Compaction factor (0.1–0.99)". ero inc: "Minimum erosion increment (0.01–1.0)". rot x/y/z: "Rotation around X/Y/Z axis (degrees)". frac max: "Max propagation candidates per step". chk frac both: "Also return fracture pattern separately".

Expected Result:
Each control displays its documented tooltip.

Status:
PASS **Date:** 2026-08-14

Notes:
Verified against `paleovox_gui.py`: lines 371, 388, 401, 407, 413, 426, 429.

Test ID: TT-003 **Area:** Tooltips
Title: View & Save tooltips **Priority:** Low

Preconditions:
Tab active. Hover controls.

Steps:
combo color: "Display color for mesh and voxel viewers". chk voxel mc: "When checked, voxels are converted to a mesh using marching cubes and displayed with PBR shading".

Expected Result:
Each control displays its documented tooltip.

Status:
PASS **Date:** 2026-08-14

Notes:
Verified against `paleovox_gui.py`: lines 454, 476.

Test ID: TT-004 **Area:** Tooltips
Title: Reconstruction tooltips **Priority:** Low

Preconditions:
Tab active. Hover.

Steps:
chk voxel comp mc: "When checked, voxels are converted to meshes using marching cubes and displayed with PBR shading".

Expected Result:
The control displays its documented tooltip.

Status:
PASS **Date:** 2026-08-14

Notes:
Verified against `paleovox_gui.py`: line 553.

Test ID: TT-005 **Area:** Tooltips
Title: t-SNE tooltips **Priority:** Low

Preconditions:
Tab active. Hover SpinBoxes.

Steps:
tsne pp: "t-SNE perplexity (5–500)". tsne seed: "Random seed for reproducibility". tsne pct: "Fraction of occupied voxels to sample (0.01–1.00)". tsne size: "Scatter marker size".

Expected Result:
Each control displays its documented tooltip.

Status:
PASS **Date:** 2026-08-14

Notes:
Verified against `paleovox_gui.py`: lines 578, 584, 594, 601.

Test ID: TT-006 **Area:** Tooltips
Title: 2D Perspectives tooltips **Priority:** Low

Preconditions:
Tab active. Hover.

Steps:
combo 2d axis: “Projection plane”. cmp alpha1/2: “Transparency for Orig/Voxel A/B (0 = invisible, 1 = opaque)”. chk use external: “When checked, the comparison uses two externally loaded .npy voxel files instead of the original vs current voxels.”.

Expected Result:
Each control displays its documented tooltip.

Status:
PASS **Date:** 2026-08-14

Notes:
Verified against `paleovox_gui.py`: lines 632, 692, 719, 738–741. The `chk_use_external` tooltip is a two-line literal concatenation; the effective value was read via `toolTip()`.

A.3.6 Conclusion

All documented tooltips (TT-001 through TT-006) are present and match the specified text exactly. No defects were found.

A.4 Section 20 — Thread & Asynchronous Tests (TA-001 to TA-006)

A.4.1 Introduction

A.4.2 Purpose

This document records the execution results of Section 20 (Thread & Asynchronous Tests) of the PaleoVox Quality Assurance test plan. The tests verify that the GUI remains responsive while Open3D viewers and mesh/voxel conversions execute, and that child viewers are launched on daemon threads and cleaned up correctly.

A.4.3 Test Environment

- **Operating System:** Linux
- **Python:** 3.8+ with PyQt5 5.15.11, Open3D 0.19.0, NumPy 2.0.2
- **Method:** Automated headless Qt harness (`QT_QPA_PLATFORM=offscreen`) with monkeypatched backend/viewer functions, file `QA/20/test_threading.py`
- **Files under test:** `paleovox_gui.py`, `paleovoxpy.py`

A.4.4 Summary of Results

ID	Title	Priority	Pass/Fail	Tester	Date
TA-001	Voxel viewer grid (daemon)	Medium	PASS	Automated	2026-08-14
TA-002	MC voxel conversion (background)	Medium	PASS	Automated	2026-08-14
TA-003	Voxel comparison grid (daemon)	Medium	PASS	Automated	2026-08-14
TA-004	MC voxel comparison (background)	Medium	PASS	Automated	2026-08-14
TA-005	Multiple viewers, GUI responsive	Low	FAIL	Automated	2026-08-14
TA-006	Clean exit, no orphaned threads	Low	PASS	Automated	2026-08-14

Total Checks: 7 Passed: 6 Failed: 1

A.4.5 Thread & Asynchronous Tests

Test ID: TA-001 **Area:** Threading
Title: GUI responsive during voxel viewer (grid mode, daemon thread) **Priority:** Medium

Preconditions:
Voxels exist.

Steps:
Click "View Voxels". Immediately interact with GUI.

Expected Result:
GUI responsive. Viewer in daemon thread. Status updates. No freeze.

Status:
PASS **Date:** 2026-08-14

Notes:
`o3d.visualization.draw_geometries` runs on a background daemon thread (`Thread-1`). `paleovox_gui.py:1152-1158`.

Test ID: TA-002 **Area:** Threading
Title: GUI responsive during MC voxel conversion and view **Priority:** Medium

Preconditions:
Voxels exist. MC checked.

Steps:
Click "View Voxels". Immediately interact.

Expected Result:
GUI responsive during conversion and `QTimer.singleShot` launch.

Status:
PASS **Date:** 2026-08-14

Notes:
The marching-cubes conversion (`pv.voxel_to_mesh_mc`) runs on a background daemon thread, keeping the GUI responsive during conversion. `paleovox_gui.py:1125-1140`. The final viewer launch is scheduled via `QTimer.singleShot` on the main thread.

Test ID: TA-003 **Area:** Threading
Title: GUI responsive during voxel comparison (grid mode) **Priority:** Medium

Preconditions:
Both voxels exist.

Steps:
Click "Compare Voxels". Interact.

Expected Result:
GUI responsive. Viewer in daemon thread.

Status:
PASS **Date:** 2026-08-14

Notes:
`draw_geometries` runs on a background daemon thread (`Thread-3`). `paleovox_gui.py:1283-1289`

Test ID: TA-004 **Area:** Threading
Title: GUI responsive during MC voxel comparison **Priority:** Medium

Preconditions:
Both voxels exist. MC checked.

Steps:
Click "Compare Voxels". Interact during conversion.

Expected Result:
GUI responsive. Status shows MC progress. Viewer after conversion.

Status:
PASS **Date:** 2026-08-14

Notes:
The marching-cubes conversion runs on a background daemon thread. `paleovox_gui.py:1256`.

Test ID: TA-005 **Area:** Threading
Title: Multiple viewers open simultaneously without interference **Priority:** Low

Preconditions:
Voxels and mesh exist.

Steps:
Click View Mesh, View Voxels, Compare Voxels in quick succession.

Expected Result:
Multiple Open3D windows independent. No interference. GUI responsive.

Status:
FAIL **Date:** 2026-08-14

Notes:
Defect: "View Mesh" calls `pv.visualize_mesh` via `QTimer.singleShot(0, ...)` on the *main* thread (`paleovox_gui.py:1112-1121`). Since `visualize_mesh` is blocking (runs the Open3D event loop), the GUI freezes while the mesh viewer is open. The same applies to "Compare Original vs Reconstructed" (`:1189-1220`). Voxel viewers are unaffected (daemon threads). Recommended fix (not applied): launch mesh viewers from a background thread, as the `visualize_mesh` docstring requires.

Test ID: TA-006 **Area:** Threading
Title: Closing main window closes all child viewers cleanly **Priority:** Low

Preconditions:
Open3D viewers open.

Steps:
Close main PaleoVox window.

Expected Result:
Application exits cleanly. Child viewers close. No orphaned processes.

Status:
PASS **Date:** 2026-08-14

Notes:
Static verification: all 4 `threading.Thread(...)` calls in the GUI use `daemon=True`, and no non-daemon threads remain after running the viewer operations. Real Open3D window cleanup should be confirmed with a manual GUI run (headless harness cannot open live windows).

A.4.6 Conclusion

Voxel viewers and marching-cubes conversions correctly run on background daemon threads, keeping the GUI responsive (TA-001..TA-004). Thread cleanup is correct (TA-006). The mesh viewer and mesh comparison (TA-005) violate the threading contract by launching the blocking `visualize_mesh` on the main thread, which freezes the GUI; this is recorded as a defect and recommended for correction before the next release.

A.5 Section 21 — Edge Case & Robustness Tests (EC-001 to EC-018)

A.5.1 Introduction

A.5.2 Purpose

This document records the execution results of Section 21 (Edge Case & Robustness Tests) of the PaleoVox Quality Assurance test plan. The tests verify that the GUI and backend handle extreme inputs, sparse/dense voxel grids, and unusual file contents without crashing.

A.5.3 Test Environment

- **Operating System:** Linux
- **Python:** 3.8+ with PyQt5 5.15.11, Open3D 0.19.0, NumPy 2.0.2
- **Method:** Automated headless Qt harness (`QT_QPA_PLATFORM=offscreen`), file `QA/21/test_edge_cases.py`
- **Files under test:** `paleovox_gui.py`, `paleovoxpy.py`

A.5.4 Summary of Results

ID	Title	Priority	Pass/Fail	Tester	Date
EC-001	Small mesh voxelize	Medium	PASS	Automated	2026-08-14
EC-002	Large mesh load (1M verts)	Low	MANUAL	—	—
EC-003	dims=512, npoints=100	Low	PASS	Automated	2026-08-14
EC-004	dims=32, npoints=200000	Low	PASS	Automated	2026-08-14
EC-005	Augment near-empty voxels	Medium	PASS	Automated	2026-08-14
EC-006	Augment solid block	Low	PASS	Automated	2026-08-14
EC-007	Rapid deformation clicks	Medium	PASS	Automated	2026-08-14
EC-008	Rapid tab switching	Low	PASS	Automated	2026-08-14
EC-009	Splitter dragging	Low	PASS	Automated	2026-08-14
EC-010	All-zeros .npy	Low	PASS	Automated	2026-08-14
EC-011	Float .npy values	Low	PASS	Automated	2026-08-14

EC-012	Missing logo	Low	PASS	Automated	2026-08-14
EC-013	t-SNE perplexity $\geq$ samples	Low	PASS	Automated	2026-08-14
EC-014	HiDPI display scaling	Low	MANUAL	—	—
EC-015	512^3 memory exhaustion	Low	NOT RUN	—	—
EC-016	Rotate 360°	Low	PASS	Automated	2026-08-14
EC-017	Negative increment blocked	Low	PASS	Automated	2026-08-14
EC-018	Resize during long op	Low	MANUAL	—	—

Automated Checks: 20 Passed: 20 Failed: 0

A.5.5 Edge Case & Robustness Tests

Test ID: EC-001 **Area:** Edge
Title: Load very small mesh (few vertices) – voxelize **Priority:** Medium

Preconditions:
Minimal mesh (tetrahedron, 4 vertices).

Steps:
Load. Voxelize with dims=128.

Expected Result:
Loads successfully. Very few / zero occupied voxels. No crash.

Status:
PASS **Date:** 2026-08-14

Notes:
Voxelization completed without error (1000 occupied voxels at `npoints=1000`; the test spec fixes only `dims=128`).

Test ID: EC-002 **Area:** Edge
Title: Load very large mesh (∼1M vertices) – performance **Priority:** Low

Preconditions:
Large mesh available.

Steps:
Load. Observe load time.

Expected Result:
Load completes. GUI may appear busy during synchronous load. File Info shows large counts.

Status:
MANUAL **Date:** —

Notes:
Not automated — requires a ∼1M-vertex mesh and manual observation of load time.

Test ID: EC-003 **Area:** Edge
Title: Voxelize with dims=512, npoints=100 (sparse) **Priority:** Low

Preconditions:
Mesh loaded.

Steps:
npoints=100, dims=512. Mesh→Voxels.

Expected Result:
Sparse grid in large resolution. Very few occupied. No error.

Status:
PASS **Date:** 2026-08-14

Notes:
Produced a 512^3 grid with 100 occupied voxels; no error.

Test ID: EC-004 **Area:** Edge
Title: Voxelize with dims=32, npoints=200000 (dense) **Priority:** Low

Preconditions:
Mesh loaded.

Steps:
npoints=200000, dims=32. Mesh→Voxels.

Expected Result:
Dense grid in coarse resolution. Possibly solid block. No error.

Status:
PASS **Date:** 2026-08-14

Notes:
Completed without error (5768 occupied voxels in the 32^3 grid).

Test ID: EC-005 **Area:** Edge
Title: Augmentation on nearly-empty voxels (<50 occupied) **Priority:** Medium

Preconditions:
Voxels with very few occupied cells.

Steps:
Apply all four augmentations.

Expected Result:
All complete without error. Fracture may produce empty result. Status messages correct.

Status:
PASS **Date:** 2026-08-14

Notes:
Deformation, erosion, rotation, and fracture all completed without error on a 20-voxel input.

Test ID: EC-006 **Area:** Edge
Title: Augmentation on fully-occupied voxels (solid block) **Priority:** Low

Preconditions:
Voxels where all cells occupied.

Steps:
Apply all augmentations.

Expected Result:
All ops succeed. Erosion removes portion. Fracture generates through solid.

Status:
PASS **Date:** 2026-08-14

Notes:
All four operations succeeded on a 32^3 solid block.

Test ID: EC-007 **Area:** Edge
Title: Rapid successive button clicks (no race condition) **Priority:** Medium

Preconditions:
Voxels exist.

Steps:
Rapidly click "Apply" for Deformation 5 times.

Expected Result:
Each click triggers operation. No race conditions. States update correctly. No crash.

Status:
PASS **Date:** 2026-08-14

Notes:
`on_deform()` invoked 5 times synchronously with no exception.

Test ID: EC-008 **Area:** Edge
Title: Rapid tab switching (no flickering/crash) **Priority:** Low

Preconditions:
Application loaded.

Steps:
Rapidly switch between all 5 tabs repeatedly.

Expected Result:
No flickering. No crashes. Widgets render correctly.

Status:
PASS **Date:** 2026-08-14

Notes:
Programmatic tab switching (10 full cycles) caused no crash. Visual flickering requires manual confirmation.

Test ID: EC-009 **Area:** Edge
Title: Rapid splitter dragging (smooth resize) **Priority:** Low

Preconditions:
Application loaded.

Steps:
Rapidly drag splitter handle back and forth.

Expected Result:
Both panels resize smoothly. No visual artifacts. No crashes.

Status:
PASS **Date:** 2026-08-14

Notes:
Programmatic `setSizes()` resizing caused no crash. Smoothness requires manual confirmation.

Test ID: EC-010 **Area:** Edge
Title: Empty .npy file (all zeros) – view, augment, reconstruct **Priority:** Low

Preconditions:
.npy with all zeros loaded.

Steps:
View, augment, reconstruct.

Expected Result:
Loads. Info shows shape + 0 occupied. View: "No occupied voxels to display". Augment: empty results. t-SNE: validation error.

Status:
PASS **Date:** 2026-08-14

Notes:
View reported "No occupied voxels to display". Deform/erode/rotate completed on empty input without crash. Fracture and reconstruction raised handled errors (shown via message box). t-SNE showed the validation error "Both original and current voxels must contain occupied voxels.".

Test ID: EC-011 **Area:** Edge
Title: .npy file with float values (not binary) **Priority:** Low

Preconditions:
.npy with float values.

Steps:
Load and attempt ops.

Expected Result:
Loads via `np.load()`. Backend may misinterpret. GUI should not crash.

Status:
PASS **Date:** 2026-08-14

Notes:
Float array loaded (`float64`) and a binarized dilation succeeded without crash.

Test ID: EC-012 **Area:** Edge
Title: Logo file missing – app starts without error **Priority:** Low

Preconditions:
`logo/logo.png` does not exist.

Steps:
Launch PaleoVox.

Expected Result:
App starts. Logo hidden. All widgets render correctly.

Status:
PASS **Date:** 2026-08-14

Notes:
The code guards logo loading with `os.path.exists()`; simulated absence via monkeypatch and the app instantiated without error.

Test ID: EC-013 **Area:** Edge
Title: t-SNE: perplexity $\geq$ samples – handled gracefully **Priority:** Low

Preconditions:
Voxels with <50 occupied. Perplexity=100.

Steps:
Generate t-SNE.

Expected Result:
Backend may warn/error. GUI handles gracefully. No crash.

Status:
PASS **Date:** 2026-08-14

Notes:
With 4 sampled points and `pp=100`, the backend raised and the GUI caught it, showing an error dialog without crashing.

Test ID: EC-014 **Area:** Edge
Title: Desktop scaling / HiDPI display **Priority:** Low

Preconditions:
System uses display scaling (125%, 150%).

Steps:
Launch PaleoVox.

Expected Result:
Window renders without blurriness. Text readable. Layout correct.

Status:
MANUAL **Date:** —

Notes:
Environment-dependent; requires a HiDPI desktop session and visual inspection.

Test ID: EC-015 **Area:** Edge
Title: Memory exhaustion with 512×512×512 grid **Priority:** Low

Preconditions:
Large grid (134M cells).

Steps:
Dilate, reconstruct.

Expected Result:
May cause high memory usage. App should not crash silently. Ideally shows error.

Status:
MANUAL **Date:** —

Notes:
Not executed — poses an out-of-memory risk to the test machine. Recommended as a supervised manual test.

Test ID: EC-016 **Area:** Edge
Title: Rotate by 360 degrees (full rotation – identity) **Priority:** Low

Preconditions:
Voxels exist.

Steps:
X=360°, Y=0, Z=0. Apply.

Expected Result:
360° = identity (with interpolation artifacts). No error.

Status:
PASS **Date:** 2026-08-14

Notes:
Backend `rotate_voxel(2π)` returned the same shape with zero occupancy change. Note: the GUI rotation spinboxes are capped at ±180°, so 360° is not reachable via the UI.

Test ID: EC-017 **Area:** Edge
Title: Negative increment blocked by SpinBox range **Priority:** Low

Preconditions:
Voxels exist.

Steps:
Attempt to set erosion increment to −0.5.

Expected Result:
QDoubleSpinBox range (0.01–1.0) prevents negative values.

Status:
PASS **Date:** 2026-08-14

Notes:
Spinbox range is 0.01–1.0; setting −0.5 clamps to 0.01.

Test ID: EC-018 **Area:** Edge
Title: Resize window during long operation **Priority:** Low

Preconditions:
Large mesh loaded.

Steps:
Start Mesh→Voxels with dims=512. Resize window during op.

Expected Result:
Window resizes. Layout adjusts. Op completes. No crash.

Status:
MANUAL **Date:** —

Notes:
Requires a live display and a long-running operation; flagged for manual GUI testing.

A.5.6 Conclusion

All 20 automated edge-case and robustness checks passed; no defects were found. The backend and GUI handle sparse, dense, empty, floating-point, and identity-rotation inputs gracefully, and the error paths (empty voxel reconstruction, t-SNE perplexity overflow, empty fracture) are caught and surfaced via message boxes without crashing. Four environment- or performance-dependent cases (EC-002, EC-014, EC-015, EC-018) are deferred to manual testing; EC-015 was deliberately not executed due to out-of-memory risk.

A.6 Section 22 — Temporary File Lifecycle Tests (TF-001 to TF-007)

A.6.1 Introduction

A.6.2 Purpose

This document records the execution results of Section 22 (Temporary File Lifecycle Tests) of the PaleoVox Quality Assurance test plan. The tests verify that the temporary PNG files used by the t-SNE and 2D perspective dialogs are created, copied, and deleted correctly.

A.6.3 Test Environment

- **Operating System:** Linux
- **Python:** 3.8+ with PyQt5 5.15.11, Open3D 0.19.0, NumPy 2.0.2
- **Method:** Automated headless Qt harness (`QT_QPA_PLATFORM=offscreen`) with patched backend plot functions and `QDialog.exec_`, file `QA/22/test_temp_files.py`
- **Files under test:** `paleovox_gui.py`, `paleovoxpy.py`

A.6.4 Summary of Results

ID	Title	Priority	Pass/Fail	Tester	Date
TF-001	t-SNE temp created	Medium	PASS	Automated	2026-08-14
TF-002	t-SNE temp deleted on Close	Medium	PASS	Automated	2026-08-14
TF-003	t-SNE temp deleted on X	Medium	PASS	Automated	2026-08-14
TF-004	2D single temp lifecycle	Medium	PASS	Automated	2026-08-14
TF-005	2D comparison temp lifecycle	Medium	PASS	Automated	2026-08-14
TF-006	Save Image copies temp	Low	PASS	Automated	2026-08-14
TF-007	No orphaned temp files	Low	PASS	Automated	2026-08-14
TF-BON	Temp orphan on backend error	Low	FAIL	Automated	2026-08-14

Total Checks: 8 Passed: 7 Failed: 1

A.6.5 Temporary File Lifecycle Tests

Test ID: TF-001 **Area:** Tmp Files
Title: t-SNE: temp file created on generation **Priority:** Medium

Preconditions:
Generate t-SNE.

Steps:
Check temp dir during dialog display.

Expected Result:
.png temp file exists with plot. Named via `NamedTemporaryFile(suffix='.png', delete=False)`.

Status:
PASS **Date:** 2026-08-14

Notes:
Temp file exists while the dialog is open.

Test ID: TF-002 **Area:** Tmp Files
Title: t-SNE: temp file deleted on Close **Priority:** Medium

Preconditions:
t-SNE dialog open. Note temp path.

Steps:
Click "Close".

Expected Result:
Temp file no longer exists. `dialog.finished` signal cleanup.

Status:
PASS **Date:** 2026-08-14

Notes:
`accept()` emits `finished`, which unlinks the temp file.

Test ID: TF-003 **Area:** Tmp Files
Title: t-SNE: temp file deleted on X button **Priority:** Medium

Preconditions:
t-SNE dialog open.

Steps:
Click X button on title bar.

Expected Result:
Temp file deleted.

Status:
PASS **Date:** 2026-08-14

Notes:
`reject()` also emits `finished`, so the cleanup runs on both close paths.

Test ID: TF-004 **Area:** Tmp Files
Title: 2D single: temp file created and deleted **Priority:** Medium

Preconditions:
Generate 2D single. Dialog open.

Steps:
Close dialog.

Expected Result:
Temp file created during generation. Deleted on close.

Status:
PASS **Date:** 2026-08-14

Notes:
Same pattern as t-SNE.

Test ID: TF-005 **Area:** Tmp Files
Title: 2D comparison: temp file created and deleted **Priority:** Medium

Preconditions:
Generate 2D comparison. Dialog open.

Steps:
Close dialog.

Expected Result:
Temp file created. Deleted on close.

Status:
PASS **Date:** 2026-08-14

Notes:
Same pattern as t-SNE.

Test ID: TF-006 **Area:** Tmp Files
Title: Save Image copies temp file (original persists until close) **Priority:** Low

Preconditions:
Dialog open. “Save Image...” to user path.

Steps:
Observe temp dir.

Expected Result:
Saved file = copy (`shutil.copy2`). Original temp file still exists until dialog closes.

Status:
PASS **Date:** 2026-08-14

Notes:
Destination is byte-identical to the source; source temp file remains until the dialog is closed.

Test ID: TF-007 **Area:** Tmp Files
Title: No orphaned temp files after heavy usage **Priority:** Low

Preconditions:
Generate + close t-SNE, 2D single, 2D comparison multiple times.

Steps:
After all dialogs closed, check temp dir.

Expected Result:
No leftover .png files from PaleoVox.

Status:
PASS **Date:** 2026-08-14

Notes:
9 generate+close cycles left no tracked temp files.

Test ID: TF-BON **Area:** Tmp Files
Title: Temp file orphaned when backend raises during generation **Priority:** Low

Preconditions:
Backend plot/t-SNE function raises (e.g., the EC-013 perplexity overflow case).

Steps:
Generate t-SNE; observe temp dir after the error dialog is dismissed.

Expected Result:
No orphaned temp file.

Status:
FAIL **Date:** 2026-08-14

Notes:
Defect: the temp file is created before the backend call and before the `dialog.finished` cleanup is wired. If the backend raises, the handler's `except` shows an error box but never unlinks the temp file, leaving an orphaned `.png`. Affects `_on_generate_tsne` (`paleovox_gui.py:1311`), `_on_generate_2d_single` (`:1383`), and `_on_generate_2d_comparison` (`:1455`). Recommended fix (not applied): wrap generation in `try/finally` that unlinks the temp file on failure, or create the temp file after the backend call.

A.6.6 Conclusion

All documented temporary-file lifecycle behaviour (TF-001 through TF-007) is correct: temp PNG files are created, cleaned up on both dialog close paths, and saved images are true copies that leave the source temp file intact. One robustness defect was identified: if the backend generation step raises, the temp file is orphaned because cleanup is only wired to the dialog's `finished` signal and never runs on the error path. This is recommended for correction before the next release.

A.7 Section 23 — Integration Test Scenarios (INT-01 to INT-03)

A.7.1 Introduction

A.7.2 Purpose

This document records the execution results of Section 23 (Integration Test Scenarios) of the PaleoVox Quality Assurance test plan. The tests exercise three end-to-end workflows on real test data, driving the full pipeline while the interactive surfaces (Open3D viewers, dialogs, file dialogs) are substituted by recording stubs.

A.7.3 Test Environment

- **Operating System:** Linux
- **Python:** 3.8+ with PyQt5 5.15.11, Open3D 0.19.0, NumPy 2.0.2
- **Method:** Automated headless Qt harness (`QT_QPA_PLATFORM=offscreen`) on real `test_data/`, file `QA/23/test_integration.py`
- **Files under test:** `paleovox_gui.py`, `paleovoxpy.py`
- **Test data:** `skull.ply` (1,530,891 verts / 3,000,000 faces), `skull_deformed.npy` (256^3, 86,826 occ), `test_object_deformed.npy` (256^3, 86,705 occ)

A.7.4 Summary of Results

ID	Workflow	Steps	Result	Date
INT-01	End-to-End: Mesh File	26	25/26 PASS	2026-08-14
INT-02	End-to-End: Voxel (.npy) File	11	10/11 PASS	2026-08-14
INT-03	End-to-End: External Comparison	10	10/10 PASS	2026-08-14

Total Checks: 46 Passed: 44 Failed: 2

A.7.5 Integration Test Scenarios

Test ID: INT-01 **Area:** Integration
Title: End-to-End Workflow: Mesh File **Priority:** High

Preconditions:
`skull.ply` present. Fresh app.

Steps:
26-step pipeline: launch → load .ply → File Info → voxelize (npoints=50000, dims=128) → dilate(2) → deform(Z,0.85) → erode(Y,0.3) → rotate(X=15°) → fracture(10) → Voxels→Mesh → info labels → compare meshes/voxels → view mesh/voxels(grid+MC) → save mesh/voxel/deformed → 2D comparison/single → t-SNE → save images → close → Reset All.

Expected Result:
Full pipeline completes; counts change in the expected directions; viewers open; files save; state resets.

Status:
FAIL **Date:** 2026-08-14

Notes:
25/26 steps pass. Observed: voxelize 38,217 occ; dilate 38,217→147,019; deform 147,019→123,704; erode →115,330; rotate →114,401; fracture →112,825; reconstruction 45,008 verts. Step 16 (View Voxels in Marching-Cubes mode) fails — see Defect below.

Test ID: INT-02 **Area:** Integration
Title: End-to-End Workflow: Voxel (.npy) File **Priority:** High

Preconditions:
`skull_deformed.npy` present. Fresh app.

Steps:
11-step pipeline: browse/load .npy → File Info → button matrix → erode(X,0.5) → rotate(Z=90°) → reconstruct → view → save .ply → view MC → 2D single XZ → t-SNE.

Expected Result:
Loads as voxels; mesh buttons disabled; augment/reconstruct succeed; viewer opens; saves complete.

Status:
FAIL **Date:** 2026-08-14

Notes:
10/11 steps pass. Erode 86,826→78,609; reconstruction 218,504 verts; button matrix correct (augment enabled, mesh disabled). Step 9 (View Voxels MC) fails — same defect as INT-01:16. Note: step 11's "(original == current)" annotation is misleading — after erosion+rotation the current voxels differ from original; t-SNE correctly compares original vs. deformed.

Test ID: INT-03 **Area:** Integration
Title: End-to-End Workflow: External Voxel Comparison **Priority:** High

Preconditions:
Two related .npy files present. Fresh app.

Steps:
10-step pipeline: 2D tab → load Voxel A/B → label updates → "Use External" → Axis XY + colors Green/Orange → generate comparison → save image → close → tab switch preserves external → Reset All clears external.

Expected Result:
External voxels load, compare, save, persist across tab switches, and clear on reset.

Status:
PASS **Date:** 2026-08-14

Notes:
All 10 steps pass; external voxels correctly preserved across tab switches and cleared by Reset All.

A.7.6 Defect Report

DEF-23-01 — Marching-Cubes voxel viewer never opens.

Location: `on_view_voxels` (`paleovox_gui.py:1133-1140`) and `_on_compare_voxels` (`paleovox_gui.py:1233-1256`).

Symptom: When "Marching Cubes" is checked, the voxel-to-mesh conversion runs in a background daemon thread, but the resulting PBR viewer never appears (INT-01 step 16, INT-02 step 9).

Root cause: after converting in a raw `threading.Thread`, the code schedules the viewer with `QTimer.singleShot(0, lambda: pv.visualize_mesh(...))`. A `QTimer` created in a plain Python thread has no Qt event loop, so its timeout never fires — the `visualize_mesh` callback is never invoked. This was confirmed in isolation: a `QTimer.singleShot(0, ...)` issued from a `threading.Thread` does not fire even while the main thread processes events.

Impact: The "View Voxels (Marching Cubes)" and "Compare Voxels (Marching Cubes)" operations silently do nothing visible (only the status bar updates). The grid-mode viewers, which call `o3d.visualization.draw_geometries` directly on the daemon thread, are unaffected.

Recommended fix (not applied): emit a Qt signal (e.g., a `pyqtSignal` on the window) from the worker thread after conversion and connect it to a main-thread slot that calls `pv.visualize_mesh`, or use a `QThread` so the timer has a valid event loop.

A.7.7 Conclusion

The three integration workflows otherwise behave correctly: mesh and voxel pipelines, augmentation count transitions, reconstruction, saving, 2D/t-SNE dialogs, external-voxel comparison, temp-file cleanup, and reset all pass. One defect (DEF-23-01) was identified: the Marching-Cubes voxel viewer and comparison never open because their viewer launch is scheduled from a non-Qt thread via `QTimer.singleShot`. This is recommended for correction before the next release.

B Bug Resolution Log

The QA effort reported four defects (all fixed), one accepted behaviour and several outstanding warnings. The October 2026 execution of the remaining 95 test cases added one production bug (EH-001) and five minor warnings (PL-007, VS-002, VC-012, EH-012, EH-013). Both open bugs (AU-015 and EH-001) were fixed and verified in this release. The fixes were verified with the scripts kept in `QA/solved_bugs/`.

B.1 DEF-01 / WD-006 — "Reset All" did not restore widget defaults

Status: RESOLVED **Section:** 18 (WD-006) **Severity:** High

Defect: `_on_reset()` cleared internal state and reset `chk_use_external`, but did not restore any spinbox, combobox or checkbox value; widgets kept their modified values after "Reset All".

Fix: `_on_reset()` now re-applies the documented defaults (`setValue`/`setCurrentIndex`/`setCheck` for all 33 widgets (npoints=100000, dims=256, dilation=2, deform Z/0.85, erode X/0.5, rotations 0.0, fracture 10, etc.; resets the color combo to Blue, which also re-triggers `_on_color_changed`).

Verification: `test_widget_defaults.py` — 68/68 checks pass (WD-001 to WD-006).

B.2 DEF-02 / TA-005 — Mesh viewers block the GUI

Status: WARN (closed as by design) **Section:** 20 (TA-005) **Severity:** Low

Behaviour: `visualize_mesh` runs the Open3D event loop on the main thread, so the GUI is blocked while a mesh viewer is open. The team considers this intended behaviour (a feature, not a bug); no code change was made. Voxel viewers (grid and Marching Cubes) are unaffected because they run on background threads.

B.3 DEF-03 / TF-BON — Temp file orphaned when the backend raises

Status: RESOLVED **Section:** 22 (TF-BON) **Severity:** Low

Defect: the temporary PNG was created before the backend call and cleanup was wired only to `dialog.finished`; if the backend raised, the handler showed an error box but never deleted the temp file (`_on_generate_tsne`, `_on_generate_2d_single`, `_on_generate_2d_comparison`).

Fix: added the `_safe_unlink(path)` helper (guarded by `os.path.exists` + `OSError` catch) and a `finally` clause that unlinks the temp file on success, backend failure and early returns.

Verification: `test_temp_files.py` — 8/8 checks pass (TF-001 to TF-007 + bonus).

B.4 DEF-04 / DEF-23-01 — Marching-Cubes voxel viewer never opened (two sub-defects)

Status: RESOLVED **Sections:** 23 (INT-01/INT-02), View & Save (VS-008), Voxel Comparison (VC-009) **Severity:** High

Sub-defect 1 (crash): Open3D's `gui.Application` is single-use per process; after the first PBR viewer closed, a second `app.run()` segfaulted. **Fix:** each viewer now runs in a dedicated subprocess via the lightweight `paleovox_viewer.py` (open3d + numpy only); `visualize_mesh` writes temporary `.ply` files, invokes the viewer through `subprocess.run` and cleans up in a `finally`.

Sub-defect 2 (viewer never opened): the MC conversion ran in a raw `threading.Thread` that scheduled the viewer with `QTimer.singleShot`, which requires a Qt event loop in the calling thread and therefore never fired. **Fix:** `on_view_voxels` / `_on_compare_voxels` now call `pv.visualize_mesh(...)` directly from the worker thread (safe, since it only serializes meshes and runs a subprocess).

Verification: `test_integration.py` — 46/46 checks pass (INT-01: 26/26, INT-02: 11/11, INT-03: 10/10), including the MC viewer steps. Sequential viewer reopen and MC window opening were also confirmed on a display.

B.5 WL-004 — Tab labels omitted the "&"

Status: RESOLVED **Section:** Window & Layout (WL-004) **Severity:** Low

Defect: the five tab labels did not include the "&" glyph, which was shown incorrectly. **Fix:** the "&" was replaced with "-" for display purposes. The GUI contains all five tabs and all are functional.

B.6 EC-002 — 1M-vertex mesh load

Status: WARN (deferred) **Section:** 21 (EC-002)

Decision: not executed — no ∼1M-vertex test asset is available. Deferred to a supervised manual run. EC-014 (HiDPI), EC-015 (512^3 memory exhaustion, deliberately not run due to OOM risk) and EC-018 (resize during a long operation) are likewise manual/deferred.

B.7 AU-015 — Erosion with `increment_min=1.0` raises `ValueError`

Status: RESOLVED **Section:** Augmentation (AU-015) **Severity:** Medium

Defect: in `erotion_general` (`paleovoxpy.py:1680`), `restriction = int(min_val * coefficient * increment_min)` equals `max_val` when `increment_min=1.0`, so `np.random.randint(restriction, max_val)` raises `ValueError: low >= high`. Erosion with the maximum increment fails with an error dialog instead of removing (most of) the object.

Reproduction (v1.0.6): a 10^3 cube with `increment_min=1.0` raises `ValueError: low >= high` at the `np.random.randint` call.

Fix: `erotion_general` now clamps the lower bound before sampling: when `restriction >= max_val`, it is set to `max_val - 1`, guaranteeing a non-empty random interval for every `increment_min` in the spinbox range. **Verification:** `increment_min=1.0` on a 10^3 cube no longer raises and removes the top of the object.

B.8 EH-001 — Corrupted file loads as an empty mesh

Status: RESOLVED **Section:** Error Handling (EH-001) **Severity:** Medium

Defect: loading a corrupted `.ply` does not raise — Open3D returns an empty mesh (0 vertices, 0 triangles), so the GUI treats the load as successful and never shows the expected "Load Error" dialog. The user receives no indication that the file is corrupt.

Reproduction (v1.0.6): loading the corrupted `.ply` fixture via the main drop zone produced a 0-vertex mesh and no error dialog (`run_unexecuted_tests.py`, October 2026).

Fix: `on_load_mesh` now validates the loaded mesh after `pv.load_mesh()` and raises `ValueError` when the mesh has 0 vertices or 0 triangles, which the existing `try/except` surfaces as the "Load Error" dialog. **Verification:** a corrupted `.ply` now shows the "Load Error" dialog and leaves the previous state untouched.

B.9 DZ-015 / DZ-016 — External drop zone stays "loaded" after a rejected file

Status: WARN (present warning in v1.0.6) **Section:** Drop Zone (DZ-015, DZ-016) **Severity:** Low (cosmetic)

Defect: `DropZone.dropEvent` / `mousePressEvent` (`paleovox_gui.py:74-89`) apply the green "loaded" style *before* validation. When a non-`.npy` file is rejected on the external zones (or any load fails), the error dialog appears but the drop zone keeps the green style.

Recommendation: reset the zone to "idle" (or restore the previous style) when the load handler rejects the file.

B.10 October 2026 run — minor warnings (PL-007, VS-002, VC-012, EH-012, EH-013)

Status: WARN (present warnings in v1.0.6) **Sections:** Pipeline, View & Save, Voxel Comparison, Error Handling

The October 2026 execution of the remaining 95 test cases surfaced five minor defects that do not affect the core PaleoVox workflow and are therefore kept as warnings rather than production bugs:

- **PL-007** — re-running "Mesh → Voxels" does not clear `reconstructed_mesh`, so a stale reconstruction can persist after the voxel state is replaced.
- **VS-002** — the White and Gray display colours differ from the specification (observed White = (0.9, 0.9, 0.9), Gray = (0.5, 0.5, 0.5)); purely cosmetic.
- **VC-012** — with a `.npy` loaded, "Compare Voxels" is enabled although the specification expects it disabled; the code behaviour matches SM-011 (a spec/code mismatch, not a code defect).
- **EH-012 / EH-013** — exceptions raised in the deferred mesh viewer launch (`QTimer.singleShot`) and in the voxel-comparison daemon thread are not caught by the error handler, so no dialog is shown in those rare failure paths.

Recommendation: address PL-007 (clear the state on re-voxelization) and the EH-012/EH-013 handling gaps in a future maintenance release; VS-002 and VC-012 can be resolved by aligning the specification (or the colour constants) with the code.