Cheatsheet: CSS Overview & HTML5 Elements

Element	Description	Example

<!DOCTYPE html>	All HTML documents must start with this declaration. It tells the browser what document type to expect. Note that this element has no ending tag.	`<!DOCTYPE html>`
		`<html>`
		`  <head>`
		`  <title>Document Title</title>`
		`  </head>`
		`  <body>`
		`  Document body here`
		`  </body>`
		`</html>`

<a href= "path">	This tag, called an "anchor tag" creates hyperlinks using the href attribute. In place of **path** enter the URL or path name to the page you want to link to.	`<a href="https://www.ibm.com">IBM</a>`

<article>	Identifies a self-contained piece of content that could be distributed to other websites and platforms as a stand-alone unit. Similar to tag in that it does not render as anything special in the browser unless it is styled with CSS.	`<article class="CSS-Style-Reference">`
		`<h2>HTML</h2>`
		`<p>HTML stands for Hypertext Markup Language.`
		`It is a standardized system for tagging text files to display specific`
		`font, color, graphics, and hyperlinks on World Wide Web pages.</p>`
		`</article>`

<aside>	Defines some content aside from the content it is placed	`<aside>`
		`Use the aside tag to represent a section of a page that consists`
		`of content tangentially related to the content.`
		`</aside>`

	in. Similar to tag in that it does not render as anything special in the browser unless it is styled with CSS.	

<body>	Contains the contents of the HTML document. It should contain all other tags besides the <head> element to display the body of the document.	`<!DOCTYPE html>`
		`<html>`
		`<head>`
		`<title>Document Title</title>`
		`</head>`
		`<body>`
		`Document body here`
		`</body>`
		`</html>`

** **	Often used to separate sections in the body of a document in order to style that content with CSS.	`<div>`
		`This element has no particular semantic meaning but is often used`
		`in conjunction with CSS for styling purposes.`
		`</div>`

<fieldset>	Groups related elements in a form and puts a box around them.	`<form action= "/script.php">` `<fieldset>` `<legend>User:</legend>` `<label for="fname">First name:</label>` `<input type="text" id="fname" name="fname">  ` `<label for="lname">Last name:</label>` `<input type="text" id="lname" name="lname">  ` `<input type="submit" value="Submit">` `</fieldset>` `</form>`

<figcaption>	Used in conjunction with the <figure> tag to mark up an image.	`<figure>`
		`<img src="durham.jpg">`
		`<figcaption>Fig.1 - Durham, NC</figcaption>`
		`</figure>`

<figure>	Used to mark up an image in	`<figure>`
		`<img src="durham.jpg">`
		`<figcaption>Fig.1 - Durham, NC</figcaption>`
		`</figure>`

	conjunction with the <figcaption> tag.	

<footer>	Contains a footer of a document and often contains information such as authoring, copyright info, contact info, sitemap, and related documents.	`<footer>`
		`<p>Author: Christopher Moore</p>`
		`</footer>`

<form>	Creates an HTML form for user input.	`<form action="/script.php">` `<fieldset>` `<legend>User:</legend>` `<label for= "fname">First name:</label>` `<input type="text" id="fname" name="fname">  ` `<label for= "lname">Last name:</label>` `<input type="text" id="lname" name="lname">  ` `<input type="submit" value="Submit">` `</fieldset>` `</form>`
<h1>	Adds a level 1 heading to the HTML document.	`<h1>Thomas J. Watson</h1>`

<head>	Contains metadata and should be placed after the <html> tag and before the <body> tag.	`<!DOCTYPE html>`
		`<html>`
		`<head>`
		`<title>Document Title</title>`
		`</head>`
		`<body>`
		`Document body here`
		`</body>`
		`</html>`

<header>	A container for introductory content such as heading elements, logo, or	`<header>`
		`<h1>Header tag example</h1>`
		`<p>It works as a container for introductory content such as heading elements, logo, or authoring inform`
		`<p>Author: Christopher Moore</p>`
		`</header>`

	authoring information.	

<html>	The root element of an HTML document. All other tags in the document should be contained in this tag.	`<!DOCTYPE html>`
		`<html>`
		`<head>`
		`<title>Document Title</title>`
		`</head>`
		`<body>`
		`Document body here`
		`</body>`
		`</html>`

<img src="path" width="dim1" height="dim2">	This tag is used to place an img. In place of path insert a URL or a relative file path to the image location. Other optional attributes include width and height of the image in pixels.	`<img`
		`src="https://upload.wikimedia.org/wikipedia/commons/7/7e/Thomas_J_Watson_Sr.jpg"`
		`width="300"`
		`height="300">`

<input type="?">	Specifies an input field on a form with the type attribute. Common input types include: "color," "date," "datetime-local," "email," "number," "range," "search," "url", "tel,""text" and "submit"	`<form action="/script.php">` `<fieldset>` `<legend>User:</legend>` `<label for="fname">First name:</label>` `<input type="text" id="fname" name="fname">  ` `<label for="lname">Last name:</label>` `<input type="text" id="lname" name="lname">  ` `<input type="submit" value="Submit">` `</fieldset>` `</form>`

<li>	Element that creates bulleted line items in an ordered or unordered list. Should	`<ul>`
		`<li>Bullet point 1</li>`
		`<li>Bullet point 2</li>`
		`</ul>`

	be used in conjunction with the <ul> or <ol> tags.	

<link>	Used to link a CSS document to an HTML document.	`<head>`
		`<link rel="stylesheet" href="styles.css">`
		`</head>`

<meta>	Used to provide metadata about the HTML document.	`<head>`
		`<meta name="author" content="Christopher Moore">`
		`</head>`

<nav>	Used to define a set of navigational elements.	`<nav>`
		`<a href="home.html">Home</a>`
		`<a href="page1.html">Page 1</a>`
		`<a href="page2.html">Page 2</a>`
		`</nav>`

<ol>	Element that creates an ordered list using numbers. Should be used in conjunction with the <li> tag.	`<ol>`
		`<li>Numbered bullet point 1</li>`
		`<li>Numbered bullet point 2</li>`
		`</ol>`

<p>	This tag is used to identify a paragraph. It places a line break after the text it is enclosed in.	`<p>Thomas J. Watson, Sr. is the American`
		`industrialist, who built the International Business`
		`Machines Corporation (IBM) into the largest`
		`manufacturer of electric typewriters and data processing equipment in the world. </p>`

<script>	Used to embed Javascript in an HTML document.	`<script>`
		`alert("Hello World");`
		`</script>`

<section>	Defines an important section of a document. Can be used within headers and footers as well.	`<section>`
		` <h2>Introduction</h2>`
		` <p>This document provides some examples of how to`
		` use a variety of HTML elements</p>`
		`</section>`

<style>	Used to apply simple CSS to an HTML document.	`<head>`
		`<style>`
		`p {color:red}`
		`</style>`
		`</head>`
		`<body>`
		`<p>This paragraph will be red because I've styled`
		`the paragraph tag with CSS.</p>`
		`</body>`

<table>	This tag is used to denote a table. Should be used with <tr> (defines a table row) and <td> (defines a table cell within a row) tags. The <th> tag can also be used to define the table header row.	`<table>`
		`<tr>`
		`<th>Header cell 1</th>`
		`<th>Header cell 2</th></tr>`
		`<tr>`
		`<td>First row first cell</td>`
		`<td>First row second cell</td>`
		`</tr>`
		`<tr>`
		`<td>Second row first cell</td>`
		`<td>Second row second cell</td>`
		`</tr>`
		`</table>`

<td>	Denotes a cell within a row, within a table.	`<table>`
		`<tr>`
		`<th>Header cell 1</th>`
		`<th>Header cell 2</th>`
		`</tr>`
		`<tr>`
		`<td>First row first cell</td>`
		`<td>First row second cell</td>`
		`</tr>`
		`<tr>`
		`<td>Second row first cell</td>`
		`<td>Second row second cell</td>`
		`</tr>`

		`</table>`

<th>	Denotes the header cells within a row within a table.	`<table>`
		`<tr>`
		`<th>Header cell 1</th>`
		`<th>Header cell 2</th>`
		`</tr>`
		`<tr>`
		`<td>First row first cell</td>`
		`<td>First row second cell</td>`
		`</tr>`
		`<tr>`
		`<td>Second row first cell</td>`
		`<td>Second row second cell</td>`
		`</tr>`
		`</table>`

<title>	Defines the title of the HTML document displayed in the browser's title bar and tabs. It is required in all HTML documents. It should be contained in the <head> tag.	`<!DOCTYPE html>`
		`<html>`
		`<head>`
		`<title>Document Title</title>`
		`</head>`
		`<body>`
		`Document body here`
		`</body>`
		`</html>`

<tr>	Denotes a row within a table.	`<table>`
		`<tr>`
		`<th>Header cell 1</th>`
		`<th>Header cell 2</th>`
		`</tr>`
		`<tr>`
		`<td>First row first cell</td>`
		`<td>First row second cell</td>`
		`</tr>`
		`<tr>`
		`<td>Second row first cell</td>`
		`<td>Second row second cell</td>`
		`</tr>`
		`</table>`

<ul>	Element that creates an unordered list using	`<ul>`
		`<li>Bullet point 1</li>`
		`<li>Bullet point 2</li>`
		`</ul>`

	bullets. Should be used in conjunction with the <li> tag.	