TOUCH2KEY FULL-STACK ARCHITECTURE: GUI, CLI SCRIPTS, SQLITE STORE, TELEMETRY & 3-PHASE ENGINE PIPELINE (ADB -> OS DRIVERS)

LAYER 1: BOOTSTRAP, CLI SCRIPTS, ADB UTILITIES & DUAL-MODE DIALOGS (modules.scripts.* & modules.cli.*)

1A. Environment Preflight & ADB Discovery
touch2key-preflight (preflight.py) | touch2key-adb (check_adb.py)

check_adb()	Checks BIN_FOLDER/adb (ADB.exists()) -> fallback shutil.which('adb') -> resolves absolute binary path
check_driver()	Win32: Interception().valid check | Linux: Path('/dev/uinput').exists() verification
Failure Reporting	Returns bool; logs actionable remediation (touch2key-setup / sudo touch2key-setup / PC reboot)

1B. Platform Bootstrap & Uninstaller
touch2key-setup (setup.py) | touch2key-uninstall (uninstall.py) [--gui, -y, --no-restart, --purge, --purge-all]

Privilege Elevation	Win32: IsUserAnAdmin() -> ShellExecuteW('runas', sys.executable, '-m ...') | Linux: pkexec (GUI) or sudo (CLI)
OS Driver Setup	setup_windows() installs Interception & platform-tools | setup_linux() writes UDEV_RULE_PATH & reloads udevadm
Desktop Shortcuts	Win32: PowerShell WScript.Shell -> Touch2Key.lnk (pythonw.exe -m modules.gui.app) | Linux: touch2key.desktop (0o755)
Uninstall & Purge	store.close() -> _kill_adb() (taskkill/pkill) -> install-interception.exe /uninstall or udev rm -> rmtree(BIN/DATA/LOGS/DIAGNOSTICS)

1C. ADB Screen Capture & Wireless Handshake
touch2key-capture (adb_screen_capture.py) | touch2key-wireless (wireless_connect.py & wireless_connect_dialog.py)

Device Metrics	get_adb_device() -> _get_device_dpi() (get_dpi() or 'adb shell wm density', fallback BASELINE_DPI) + get_rotation() + rotate_resolution()
ADB Screencap	adb shell screencap -p /data/local/tmp/temp_cap.png (30s timeout) -> adb pull (20s) -> finally: adb shell rm
PIL & Layout Sync	Image.open() -> img.load() (releases Win32 file lock) -> img.save(dpi=(dpi,dpi)) -> store.layouts.update(id, image_path, w, h, dpi)
Wireless ADB	CLI: wireless_connect(continuous=True) | GUI: WirelessConnectDialog + WirelessConnectWorker(QThread) polling every 1.0s (10x0.1s)

1E. CLI Layout, Profile & Settings Manager
touch2key-manage (modules/cli/manage.py) — Argparse Flags & Interactive Loop

Profile & Zone CRUD	--list, --filter, --sort, --new [--dims W H DPI], --set-active, --duplicate, --rename, --delete, --clear-zones, --reset-zones
Zone Inspector CLI	--list-zones, --set-bezels ID TOP BOT, --edit-zone ZID [--zone-priority/pointer/sens-x/sens-y/deadzone/hysteresis], --reset-zone, --delete-zone
Directionals & Image	--show-directional-keys, --edit-layout-directionals ID --set-key {up,left,down,right}, --set-image ID PATH (calls apply_image_params)
Global Tuning & I/O	_normalize_key_seq() ('k1,k2' replace, '+k1' append, '+wasd'/'+arrows' presets, 'clear' wipe), --import/export-json/toml/bundle, --wipe-database

1D. Dual-Mode Window Selector & Key/Numeric Capture
select_window() (list_windows.py) | capture_sprint_key() & capture_performance_settings() (key_capture.py)

Window Enumeration	_gather_window_rows(WindowManager): find_visible_windows() -> filters width > 0 & height > 0 -> [wid, title, class, l, t, w, h]
CLI Selector	1.0s auto-refresh table via AppLogManager.console_write; 50ms non-blocking poll (Win32 msvcrt.getch | Unix tty.setcbreak + select)
GUI Selector	ListApp(QDialog): QTableWidget with 1000ms QTimer diff-sync (added_ids, removed_ids, current_ids) & UserRole wid storage
Capture Dialogs	KeyCaptureDialog(QDialog) (get_specific_qt_key -> get_scancode_from_key) & NumericCaptureDialog(QDialog) vs CLI input() prompts

LAYER 2: PYSIDE6 GRAPHICAL USER INTERFACE, DEBOUNCED SETTINGS & MATPLOTLIB PLOTTER (modules.gui.*)

2A. MainWindow & EngineProcessController
touch2key-gui (modules/gui/main_window.py) — Process Lifecycle & Thread-Safe Event Bridge

EngineProcessController	Manages engine multiprocessing.Process, holds lock for (window_id, window_title, k_id, m_id), pipes runtime IPC commands
Page Navigation & Dock	QStackedWidget hosting DashboardPage, LayoutStudioPage, SettingsPage + collapsible Log Dock fed by QtLogHandler
Close & Action Guards	save_all_pages(action) invokes LayoutStudioPage.save_state() (Save/Discard/Cancel prompt) & SettingsPage._flush_pending()

2B. DashboardPage (Live Telemetry & Session Summary)
modules/gui/pages/dashboard_page.py — 1000ms QTimer (Active Only While Visible)

Dispatcher Hooks	Registers ON_RELOAD -> _reload_requested Signal & ON_TARGET_WINDOW_CHANGE -> _target_window_changed Signal (queued to GUI thread)
Session Summary	Displays active Layout name/ID, non-bezel zone count (count_by_layout()), Target Window title/HWND, Toggle Hotkeys, Sprint, k_id/m_id
Snapshot Telemetry	read_snapshot(expected_pid) -> checks snapshot_age() > STALE_AFTER_S; renders rate_hz, rate_status, cap/pps drift warnings, DOWN/MOVE/UP/ALL counts
Process Tree Sampler	labeled_processes(engine, snap) -> cached psutil.Process.oneshot() sampling CPU %, RSS MB, thread count, worker respawns, VKB/Visualizer status

2C. LayoutStudioPage (3-Pane Editor & Pipeline Inspector)
modules/gui/pages/layout_studio_page.py & touch2key-plot (studio.py)

Left Sidebar (Profiles)	Sort QComboBox (synced to profile_sort_order), Ctrl+F filter, QListWidget with ★ Active, ● <24h recency, * dirty badge; Set Active/New/Rename/Duplicate
Center Toolbar	Select Image / Capture Screenshot (_apply_image -> get_image_params), Toggle Overlays (F4), Add Circle (F6), Add Rect (F7), Cancel (Esc), Save (Ctrl+S / Ctrl+Shift+S)
Right Inspector (Stack)	Page 0: Top/Bottom Bezel SpinBoxes (MIN..MAX_BEZEL_DP) + Reset All Zones | Page 1: Zone Priority, Ignore AppSettings, Sens X/Y, Deadzone, Hysteresis, Pointer
Unsaved Guards	_confirm_unsaved() prompts before profile switch, duplicate, import, export, or image change; _on_inspector_value_changed updates PipelineConfig JSON

2E. SettingsPage (Hardware Rebind, Key Filters & Debounced Writes)
modules/gui/pages/settings_page.py — 250ms Coalesced SpinBox Timer with Exponential Backoff

Hardware & Window	Select Target Window -> ON_TARGET_WINDOW_CHANGE | Win32 Detect & Rebind Hardware (select_keyboard_then_mouse) -> ON_DEVICES_CHANGE
Event Filter Captures	KeyCaptureFilter (single stroke for sprint_key) & ContinuousSequenceFilter (KeySequenceRow for toggle_hotkeys & typematic_excluded_keys; blocks Tab focus traversal)
Debounced SpinBoxes	_queue_save() batches sensitivity_x/y, deadzone, hysteresis, adb_rate_cap, pps_alert_threshold, typematic_delay_ms/rate_hz -> _flush_pending() every 250ms
Immediate Toggles	left_handed, floating_joystick, anchored_joystick, typematic_enabled, two_finger_tap_enabled, bezel_toggle_enabled -> immediate store.settings.update() + ON_RELOAD

2D. LayoutsPlotterWidget (Matplotlib QTAgg Blit Canvas)
modules/gui/widgets/layouts_plotter_widget.py — Interactive Geometry & Artist Manager

PlotterState FSM	IDLE | COLLECTING (3-pt Circle circumcenter / 4-pt Rect bbox) | WAITING_FOR_KEY | WAITING_FOR_WHEEL_INDICATOR | DELETING | CONFIRM_DELETE_ALL
Blit Drag Architecture	Single mpl_connect per event dispatches to _DraggableLabel, _DraggableCircle (rim resize vs drag), _DraggableRectangle (4 corners + 4 edges + drag)
Wheel & Sprint Coupling	MouseWheelIndicators (4 directional overlays 0:Up, 1:Left, 2:Down, 3:Right; _MouseWheelDragManager vetoes wheel drag); radially constrains Sprint outside wheel
Atomic DB Save	save_to_database() -> _build_zone_rows() -> store.layouts.save_with_zones() -> store.settings.update(active_layout_id) -> layout_saved Signal -> ON_RELOAD

LAYER 4: SQLITE SINGLE SOURCE OF TRUTH, CONFIG I/O & TELEMETRY SNAPSHOT (modules.database.* & modules.runtime_info)

4B. Config I/O & Legacy Migration Engine
modules/database/config_io.py & legacy_migration.py

Import Pipeline	import_any() auto-detects .json layouts (migrate_json_layout), .toml settings (migrate_toml_config), or bundle directories
Export Pipeline	export_layout_json(), export_settings_toml(linked_json_path), export_bundle() writing portable TOML + JSON pairs to data/profiles/

4C. Runtime Telemetry Snapshot & CLI Stats
modules/runtime_info.py | touch2key-stats (stats.py)

Snapshot Payload	JSON file (.touch2key_runtime): pid, timestamp, rate_hz, rate_status, rate_cap_hz, pps_threshold, menu_mode, downs/moves/ups/all, respawns, workers, device_width/height, window_lost
Consumers	Read every 1.0s by DashboardPage (_update_telemetry), every 2.0s by Visualizer (attach), and by touch2key-stats (-i, --once, --json, --clear)

4A. SQLite Relational Store (touch2key.db)
modules/database/ — Foreign-Key Cascaded Repositories (store.settings, store.layouts, store.zones)

SettingsRepository	Singleton AppSettings row: handedness, joystick modes, sens_x/y, deadzone, hysteresis, rate_cap, pps, typematic_*, toggle_hotkeys, active_layout_id
LayoutsRepository	Layout rows (width, height, dpi, mouse_wheel_radius, sprint_distance, image_path); apply_image_params() atomically rescales all non-bezel zones on resolution change
ZonesRepository	Zone rows (scancode, zone_type, cx, cy, r, x1..y2, priority, pointer, ignore_app_settings, pipeline_json); auto-heals Top (0x9905) & Bottom (0x9906) Bezels

LAYER 3: DIAGNOSTIC & RUNTIME IPC OVERLAYS (modules.gui.overlays.*)

3A. Live Touch & Input Curve Visualizer
touch2key-visualizer (visualizer.py) — Single-Instance Fullscreen Translucent QGraphicsView

Process Registration	check_single_instance('Touch2Key_Visualizer') -> register_process(VISUALIZER_RUNTIME_FILE) -> atexit unregister
5ms Poll & InputCurve	Polls Ctrl+Arrows (trail width/height 1..100) & Ctrl+F6/F7 (max trail 500..5000) via InputCurve (LINEAR/CUBIC/EXPONENTIAL cycled via Ctrl+F8)
Bresenham & Ripples	mouseMoveEvent draws interpolated bresenham() trail rects; key/mouse press spawns 5000ms expiring ripples + #00FF00/#00FFFF text with QGraphicsDropShadowEffect
Live Engine Secret Sync	Monitors toggle_hotkeys scancodes to flip ShowCursor/BlankCursor; every 2.0s calls attach() to read live device_width/height and rescale zone coordinates

3B. Low-Latency Virtual Keyboard (VKB)
touch2key-keyboard — Spawned via Bottom Bezel (0x9906) or CLI

Lifecycle & Tracking	Managed by Engine.toggle_virtual_keyboard(); PID published in runtime snapshot under workers['vkb']
Direct IPC Stream	Serializes virtual keystrokes into VKB_STRUCT (<BH: action, scancode) and pipes directly to Engine Mapper for zero-focus-loss injection

ENGINE PHASE 1: PIPELINE CONSTRUCTION, RELOAD TRANSACTION & DETERMINISTIC 5-KEY TIER SORTING

5.1 Initialization & Reload Triggers
Engine.start_headless() | MapperEvent(action='ON_RELOAD')

Initial Boot	store.settings.get() -> clamps rate_cap [30..1000Hz], pps [10..500], binds callbacks, starts WindowManager self-healing tracker
ON_RELOAD Sources	CLI [F5] Handedness | CLI [F6] Reload | CLI Arrow Key 250ms Commit | GUI Settings/Studio MapperEvent | IPC (0x03)
Debouncer	MapperEventDispatcher._debounce_loop (10ms tick); immediate synchronous delivery if cooldown == 0

5.2 Atomic Reload Transaction (Engine._on_reload under self.lock)
Layout Snapshot Sync & State Boundary Sanitation

LayoutLoader	load_layout() extracts SQLite snapshot: Layout (width, height, dpi), Settings, Zones, Bezels
Hotkeys Guard	Under _adjust_lock: syncs rate_cap & pps from DB only if not _settings_dirty
TouchReader	touch_reader.on_reload() & touch_reader.set_rate_cap(self.rate_cap)
_release_active_inputs()	_dispatch_generation += 1 | clears _contact_owners & _cursor_contacts | resets all pipelines & releases held keys/buttons

5.3 Submapper Pipeline Reconstruction
Deterministic Rebuild Sequence

Mapper.reload()	Updates device_width, device_height, dpi, toggle_hotkeys_str, pps
BezelMapper	TOP_BEZEL (0x9905) -> execute_toggle_hotkeys | BOTTOM_BEZEL (0x9906) -> toggle_virtual_keyboard (Prec: 4)
MouseMapper	Camera Look Pipeline: Always/Half-Screen Region -> DeltaTransform -> PointerSemantic (Prec: 0)
KeyMapper	update_bridge_typematics() (<B?IfH) + Button Pipelines (Button + optional PointerSemantic, Prec: 2)
WheelMapper	Joystick Pipeline: Fixed/Anchored/Dynamic Origin -> JoystickTransform -> DirectionalSemantic (Prec: 1)

5.4 Isolated 5-Stage Pipeline Contract (Pipeline[T])
Region -> Origin -> Constraint -> Transformation[T] -> list[Semantic[T]]

Stage 1: Region	AlwaysRegion (area=inf) | CircularRegion (pi*r^2) | RectangularRegion (w*h)
Stage 2: Origin	FixedOrigin (static) | DynamicOrigin (touch DOWN) | AnchoredOrigin (snap_radius=80.0 - default)
Stage 3: Constraint	NoConstraint | RadialConstraint (clamp r) | LeashConstraint (pulls origin if dist > leash_r)
Stage 4: Transform	IdentityTransform -> UNIT | DeltaTransform -> Vector | JoystickTransform -> frozenset[int]
Stage 5: Semantics	ButtonSemantic (key/mouse) | DirectionalSemantic (WASD diff) | PointerSemantic (dx,dy) | ToggleSemantic (tap)

5.5 Engine._build_pipeline_tiers()
Strict 5-Key Sort & Equivalence Grouping

Key 1: -precedence	Bezel (4) > Button (2) > Joystick (1) > Mouse/Pointer (0) [is_bezel forces max(4, prec)]
Key 2: -priority	Custom user priority tier (+200 down to -100)
Key 3: -multi_claim	allow_multi_claim: True (sorted first) before False (sorted last)
Key 4 & 5	+region.area (smaller hitboxes first) -> +creation_id (deterministic tie-breaker)
Output: self._tiers	list[list[Pipeline]] partitioned by identical (precedence, priority, allow_multi_claim)

ENGINE PHASE 2: RUNTIME TOUCH INGESTION, TWO-FINGER TAP FSM & CONTACT OWNERSHIP DISPATCH

6.1 TouchReader -> Engine._process_touch_event(touch_event)
ADB ABS_MT_* Stream (Synchronized under Engine.lock)

ADB Auto-Adapt	Queries ABS_MT_POSITION_X/Y & slot capabilities on connect; auto-pauses & resumes on USB/Wi-Fi drop
Event Payload	TouchEvent(contact_id: int, phase: DOWN | MOVE | UP, position: Point(x,y), timestamp: float)
Guard & Telemetry	Aborts if shutting down | Records TouchEventCount & increments mapper.event_count

Menu Mode Gesture Gate?
self.is_visible (cursor visible = Menu Mode only) and self.two_finger_tap_enabled

6.2 TwoFingerTapTracker.observe(touch_event)
Menu Mode only (cursor visible) | Ambiguity Buffer FSM (duration <= 0.25s, drift <= 25px, sync <= 0.12s)

PENDING	Buffers candidate event in _buffer and returns early (prevents single-tap leak)
REJECTED	Replays all buffered events in decision.replay through _dispatch_normal() in order
RECOGNIZED	Valid synchronized 2-finger tap -> gracefully shuts down the engine process
IDLE	Unbuffered non-DOWN event -> proceeds to _dispatch_normal(touch_event)

1. Is cid in self._contact_owners?
Ownership is locked at DOWN; MOVE/UP never re-evaluate tiers

6.3 Route to Owning Pipeline(s)
owners = self._contact_owners[cid]

Process	for pipeline in owners: pipeline.process(event, output_sink)
Generation Fence	Aborts immediately if generation != self._dispatch_generation
UP Cleanup	If event.phase is TouchPhase.UP: self._contact_owners.pop(cid, None)

2. Is cid in self._cursor_contacts?
Active Menu Mode Desktop Cursor Contact

3. Is event.phase == TouchPhase.DOWN?
Unowned MOVE / UP events are ignored

6.4 Evaluate Sorted self._tiers (DOWN Phase Only)
Deterministic Tier Claim Loop

Mode Filters	Skip bezel if not bezel_toggle_enabled | Skip non-bezel HUD if self.is_visible (Menu Mode)
Claim Test	pipeline.claims(event) -> _owned_contact is None and region.activates(event)
Multi-Claim Rule	If allow_multi_claim: claim all matching in tier | Else: break on first claim in tier
Lock Ownership	If claimed: self._contact_owners[cid] = tuple(claimed) & return

6.5 Engine._dispatch_cursor(event)
Menu Mode Absolute Cursor Fallback (self.is_visible and cid == 0)

Coordinate Map	gx, gy = mapper.device_to_game_abs(x, y) (rotation-aware window/screen normalization)
Driver Output	bridge.mouse_move_abs(round(gx), round(gy)) | DOWN: left_click_down() | UP: left_click_up()

ENGINE PHASE 3: 5-STAGE PIPELINE EXECUTION, FRACTIONAL MOUSE FLUSH & HARDWARE BRIDGE WORKERS

7.1 Pipeline.process(event, output_sink)
Isolated 5-Stage Per-Contact Execution

Stages 1 & 2	DOWN: _owned_contact = cid; origin.begin(pos) | All: origin.update(pos, constraint); origin_pt = origin.get()
Stage 3: Constraint	constrained = constraint.apply(origin_pt, pos) | Computes delta & frame_delta in PipelineContext
Stage 4: Transform	value = transformation.apply(context) -> UNIT | Vector(dx,dy) | frozenset[scancodes]
Stage 5: Semantics	For semantic in semantics: semantic.process(context, value, output_sink)
UP Teardown	If phase is UP: origin.end(), transformation.reset(), clears _owned_contact & _prev_position

7.2 BridgeOutputSink & Bezel Callbacks
Sub-Pixel Mouse Accumulator & Action Router

Keys & Clicks	key_down/up(scancode) | mouse_down/up(0x9900..0x9904) -> immediate Bridge call
Fractional Move	mouse_move(dx, dy) -> under _lock: accumulates _acc_x += dx, _acc_y += dy
Top Bezel Callback	Mapper.execute_toggle_hotkeys(): parse_seq -> key_down stack -> 15-35ms sleep -> LIFO key_up
Bottom Bezel Callback	Engine.toggle_virtual_keyboard(): spawns/stops VKB process -> VKB_STRUCT (<BH) pipe to Mapper

7.3 MouseFlushThread (Engine._mouse_flush_loop)
Rate-Capped Whole-Pixel Dispatcher (1.0 / max(rate_cap, 30.0) s)

flush_mouse_move()	idx, idy = clamp(round(_acc_x), -32767, 32767) -> bridge.mouse_move_rel(idx, idy)
Remainder & Reset	Retains fractional _acc_x -= idx, _acc_y -= idy | Resets to 0.0 when active_touches == 0

7.4 AbstractBridge -> OS Driver Worker Processes (k_proc & m_proc)
3 Dedicated IPC Pipes + 2 Threads Per Worker Process + Watchdog Respawner

Platform Signatures	Win32: keyboard_worker(k_pipe, log_q, k_handle), mouse_worker(m_pipe, mb_pipe, log_q, m_handle), NtSetTimerResolution | Linux: UInput(KEYBOARD_CAP / MOUSE_CAP)
k_proc Main Thread	Polls k_pipe (15s timeout -> _release_all_keys): unpacks PACK_KEY (<HB, maps E0/LINUX_KEY_MAP) -> key_queue | unpacks KEY_CONFIG (<B?IfH)
k_proc Injector Thread	Drains key_queue: DOWN sleeps 40-70ms dwell, UP sleeps 1ms (stretches fast taps) | Outer loop fires typematic repeat_key after delay_ns at repeat_rate
m_proc Main Thread	Polls m_pipe: coalesces up to MAX_COALESCE=20 TASK_REL (<Bhh, 0.8-1.2ms dwell) or TASK_WHEEL (<Bhh, 1ms dwell) + TASK_ABS (<Bii, MOUSE_VIRTUAL_DESKTOP) via send_lock
m_proc Button Thread	Polls mb_pipe (15s timeout -> _release_all_buttons): injects PACK_BUTTON (<Bi) under send_lock, then sleeps 25-40ms DOWN / 1ms UP outside lock (never blocks moves)

Target Window ID / Devices
Updates layout image_path, w, h, dpi
Direct CRUD on layouts, zones, settings
Import / Export JSON, TOML, Bundles
Persists sprint_key, rate_cap, pps
GUI Import / Export
1000ms telemetry & psutil tree poll
Transactional migration / read
2.0s live device_width/height sync
250ms debounced & immediate updates
Hosts canvas & syncs Inspector
_notify_reload() -> ON_RELOAD
Spawns Engine & dispatches IPC (0x03)
layout_saved -> ON_RELOAD
Publishes .touch2key_runtime (1Hz)
Reads active Layout, Zones, Bezels, Settings
VKB_STRUCT (<BH) pipe
Spawns VKB (0x9906)
True (Menu Mode)
False (In-Game: two-finger tap ignored)
IDLE / REJECTED (Replay)
Yes (MOVE/UP)
No
No
Yes (DOWN)
Yes
pipeline.process()
Claimed on DOWN
Unclaimed (Menu & cid==0)
Feeds sorted self._tiers
_acc_x, _acc_y
Keys / Clicks / Hotkeys
mouse_move_rel(idx, idy)
mouse_move_abs & left_click