TOUCH2KEY FULL-STACK ARCHITECTURE: GUI, CLI SCRIPTS, SQLITE STORE, TELEMETRY & 3-PHASE ENGINE PIPELINE (ADB -> OS DRIVERS)

Target Window ID / Devices
Updates layout image_path, w, h, dpi
Direct CRUD on layouts, zones, settings
Import / Export JSON, TOML, Bundles
Persists sprint_key, rate_cap, pps
250ms debounced & immediate updates
2.0s live window_info & screen bounds sync
1000ms telemetry & psutil tree poll
Transactional migration / read
save_with_zones() + apply_image_params()
GUI Import / Export
Hosts canvas & syncs Inspector
Spawns Engine & dispatches IPC (0x03)
_notify_reload() -> ON_RELOAD
layout_saved -> ON_RELOAD
Publishes .touch2key_runtime (1Hz)
Reads active Layout, Zones, Bezels, Settings
VKB_STRUCT (<BH) pipe
True (Menu Mode)
False (In-Game: 2-finger tap ignored)
IDLE / REJECTED (Replay)
Yes (Active Owner)
No (Unowned Contact)
Yes (DOWN)
No (Unowned MOVE/UP)
Unclaimed on DOWN
Claimed on DOWN
Yes (Menu Mode: self.is_visible)
pipeline.process()
mouse_move_abs & left_click
_acc_x, _acc_y
Keys / Clicks / Hotkeys
mouse_move_rel(idx, idy)

LAYER 1: BOOTSTRAP, CLI SCRIPTS, ADB UTILITIES & DUAL-MODE DIALOGS (modules.scripts.* & modules.cli.*)

1A. Environment Preflight & ADB Discovery
touch2key-preflight (preflight.py) | touch2key-adb (check_adb.py)

check_adb()	Checks BIN_FOLDER/adb (ADB.exists()) -> fallback shutil.which('adb') -> resolves absolute binary path
check_driver()	Win32: Interception().valid check | Linux: Path('/dev/uinput').exists() verification
Failure Reporting	Returns bool; logs actionable remediation (touch2key-setup / sudo touch2key-setup / PC reboot)

1B. Platform Bootstrap & Uninstaller
touch2key-setup (setup.py) | touch2key-uninstall (uninstall.py) [--gui, -y, --no-restart, --purge, --purge-all]

Privilege Elevation	Win32: IsUserAnAdmin() -> ShellExecuteW('runas', sys.executable, '-m ...') | Linux: pkexec (GUI) or sudo (CLI)
OS Driver Setup	setup_windows() installs Interception & platform-tools | setup_linux() writes UDEV_RULE_PATH & reloads udevadm
Desktop Shortcuts	Win32: PowerShell WScript.Shell -> Touch2Key.lnk (pythonw.exe -m modules.gui.app) | Linux: touch2key.desktop (0o755)
Uninstall & Purge	store.close() -> _kill_adb() (taskkill/pkill) -> install-interception.exe /uninstall or udev rm -> rmtree(BIN/DATA/LOGS/DIAGNOSTICS)

1C. ADB Screen Capture & Wireless Handshake
touch2key-capture (adb_screen_capture.py) | touch2key-wireless (wireless_connect.py & wireless_connect_dialog.py)

Device Metrics	get_adb_device() -> _get_device_dpi() (get_dpi() or 'adb shell wm density', fallback BASELINE_DPI) + get_rotation() + rotate_resolution()
ADB Screencap	adb shell screencap -p /data/local/tmp/temp_cap.png (30s timeout) -> adb pull (20s) -> finally: adb shell rm
PIL & Layout Sync	Image.open() -> img.load() (releases Win32 file lock) -> img.save(dpi=(dpi,dpi)) -> store.layouts.update(id, image_path, w, h, dpi)
Wireless ADB	CLI: wireless_connect(continuous=True) | GUI: WirelessConnectDialog + WirelessConnectWorker(QThread) polling every 1.0s (10x0.1s)

1E. CLI Layout, Profile & Settings Manager
touch2key-manage (modules/cli/manage.py) — Argparse Flags & Interactive Loop

Profile & Zone CRUD	–list, –filter, –sort, –new [–dims W H DPI], –set-active, –duplicate, –rename, –delete, –clear-zones, –reset-zones
Zone Inspector CLI	–list-zones, –set-bezels ID TOP BOT, –edit-zone ZID [–zone-priority/pointer/sens-x/sens-y/deadzone/hysteresis], –reset-zone, –delete-zone
Directionals & Image	–show-directional-keys, –edit-layout-directionals ID –set-key {up,left,down,right}, –set-image ID PATH (calls apply_image_params)
Global Tuning & I/O	_normalize_key_seq() ('k1,k2' replace, '+k1' append, '+wasd'/'+arrows' presets, 'clear' wipe), –import/export-json/toml/bundle, –wipe-database

1D. Dual-Mode Window Selector & Key Capture
select_window() | capture_sprint_key() & capture_toggle_hotkeys()

Window Enumeration	_gather_window_rows(WindowManager): find_visible_windows() -> filters width > 0 & height > 0 -> [wid, title, class, l, t, w, h] | X11 enumerates EWMH _NET_CLIENT_LIST (falls back to query_tree)
CLI Selector	1.0s auto-refresh table via AppLogManager.console_write; 50ms non-blocking poll (Win32 msvcrt.getch | Unix tty.setcbreak + select)
GUI Selector	ListApp(QDialog): QTableWidget with 1000ms QTimer diff-sync (added_ids, removed_ids, current_ids) & UserRole wid storage
Capture Key/Toggles	GUI: KeyCaptureDialog & KeySequenceRow vs. CLI: capture_toggle_hotkeys() using blocking msvcrt/tty prompt inputs

LAYER 2: PYSIDE6 GRAPHICAL USER INTERFACE, DEBOUNCED SETTINGS & MATPLOTLIB PLOTTER (modules.gui.*)

2A. MainWindow & EngineProcessController
touch2key-gui (modules/gui/main_window.py) — Process Lifecycle & Thread-Safe Event Bridge

EngineProcessController	Manages engine multiprocessing.Process, holds lock for (window_id, window_title, k_id, m_id), pipes runtime IPC commands
Page Navigation & Dock	QStackedWidget hosting DashboardPage, LayoutStudioPage, SettingsPage + collapsible Log Dock fed by QtLogHandler
Close & Action Guards	save_all_pages(action) invokes LayoutStudioPage.save_state() (Save/Discard/Cancel prompt) & SettingsPage._flush_pending()

2B. DashboardPage (Live Telemetry & Session Summary)
modules/gui/pages/dashboard_page.py — 1000ms QTimer (Active Only While Visible)

Dispatcher Hooks	Registers ON_RELOAD -> _reload_requested Signal & ON_TARGET_WINDOW_CHANGE -> _target_window_changed Signal (queued to GUI thread)
Session Summary	Displays active Layout name/ID, non-bezel zone count (count_by_layout()), Target Window title/HWND, Toggle Hotkeys, Sprint, k_id/m_id
Snapshot Telemetry	read_snapshot() -> renders rate_hz, cap drift, event counts | labeled_processes() links PIDs
Accurate Memory	psutil.cpu_percent() normalized by cpu_count(); psutil.memory_full_info().uss extracted to perfectly match Task Manager Private Working Set

2E. SettingsPage (Hardware Rebind, Key Filters & Debounced Writes)
modules/gui/pages/settings_page.py — 250ms Coalesced SpinBox Timer with Exponential Backoff

Hardware & Window	Select Target Window -> ON_TARGET_WINDOW_CHANGE | Win32 Detect & Rebind Hardware (select_keyboard_then_mouse) -> ON_DEVICES_CHANGE
Event Filter Captures	KeyCaptureFilter (single stroke) & ContinuousSequenceFilter (KeySequenceRow for toggle_hotkeys & typematic exclusions; intercepts OS events & blocks Tab focus)
Debounced SpinBoxes	_queue_save() batches sensitivity_x/y, deadzone, hysteresis, adb_rate_cap, pps, typematic_delay_ms/rate_hz -> _flush_pending() every 250ms
Immediate Toggles	left_handed, floating_joystick, anchored_joystick, typematic_enabled, two_finger_tap_enabled, bezel_toggle_enabled -> immediate store.settings.update() + ON_RELOAD

2C. LayoutStudioPage (3-Pane Editor & Pipeline Inspector)
modules/gui/pages/layout_studio_page.py & touch2key-plot (studio.py)

Left Sidebar (Profiles)	Sort QComboBox (synced to profile_sort_order), Ctrl+F filter, QListWidget with ★ Active, ● <24h recency, * dirty badge; Set Active/New/Rename/Duplicate
Center Toolbar	Select Image / Capture Screenshot (_apply_image -> get_image_params), Toggle Overlays (F4), Add Circle (F6), Add Rect (F7), Cancel (Esc), Save (Ctrl+S / Ctrl+Shift+S)
Right Inspector (Stack)	Page 0: Top/Bottom Bezel SpinBoxes (MIN..MAX_BEZEL_DP) + Reset All Zones | Page 1: Zone Priority, Ignore AppSettings, Sens X/Y, Deadzone, Hysteresis, Pointer
Unsaved Guards	_confirm_unsaved() prompts before profile switch, duplicate, import, export, or image change; _on_inspector_value_changed updates PipelineConfig JSON

2D. LayoutsPlotterWidget (Matplotlib QTAgg Blit Canvas)
modules/gui/widgets/layouts_plotter_widget.py — Interactive Geometry & Artist Manager

PlotterState FSM	IDLE | COLLECTING (3-pt Circle circumcenter / 4-pt Rect bbox) | WAITING_FOR_KEY | WAITING_FOR_WHEEL_INDICATOR | DELETING | CONFIRM_DELETE_ALL
Blit Drag Architecture	Single mpl_connect per event dispatches to _DraggableLabel, _DraggableCircle (rim resize vs drag), _DraggableRectangle (4 corners + 4 edges + drag)
Wheel & Sprint Coupling	MouseWheelIndicators (4 directional overlays 0:Up, 1:Left, 2:Down, 3:Right; _MouseWheelDragManager vetoes wheel drag); radially constrains Sprint outside wheel
Atomic DB Save	save_to_database() -> _build_zone_rows() -> store.layouts.save_with_zones() -> store.settings.update(active_layout_id) -> layout_saved Signal -> ON_RELOAD

LAYER 4: SQLITE SINGLE SOURCE OF TRUTH, CONFIG I/O & TELEMETRY SNAPSHOT (modules.database.* & modules.runtime_info)

4C. Runtime Telemetry Snapshot & CLI Stats
modules/runtime_info.py | touch2key-stats (stats.py)

Snapshot Payload	JSON file (.touch2key_runtime): pid, updated_at, rate_hz, rate_status, rate_cap_hz, pps_threshold, menu_mode, downs/moves/ups/all, respawns, workers, window_info, screen_x/screen_y/screen_width/screen_height (the Windows screen rectangle is the virtual desktop and may start at a negative origin), window_lost
Consumers	Read every 1.0s by DashboardPage (_update_telemetry), every 2.0s by Visualizer (attach), and by touch2key-stats (-i, –once, –json, –clear)

4B. Config I/O & Legacy Migration Engine
modules/database/config_io.py & legacy_migration.py

Import Pipeline	import_any() auto-detects .json layouts (migrate_json_layout), .toml settings (migrate_toml_config), or bundle directories
Export Pipeline	export_layout_json(), export_settings_toml(linked_json_path), export_bundle() writing portable TOML + JSON pairs to data/profiles/

4A. SQLite Relational Store (touch2key.db)
modules/database/ — Foreign-Key Cascaded Repositories (store.settings, store.layouts, store.zones)

SettingsRepository	Singleton AppSettings row: handedness, joystick modes, sens_x/y, deadzone, hysteresis, rate_cap, pps, typematic_*, toggle_hotkeys, active_layout_id
LayoutsRepository	Layout rows (width, height, dpi, mouse_wheel_radius, sprint_distance, image_path); apply_image_params() atomically rescales all non-bezel zones on resolution change
ZonesRepository	Zone rows (scancode, zone_type, cx, cy, r, x1..y2, priority, pointer, ignore_app_settings, pipeline_json); auto-heals Top (0x9905) & Bottom (0x9906) Bezels

LAYER 3: DIAGNOSTIC & RUNTIME IPC OVERLAYS (modules.gui.overlays.*)

3A. Live Touch & Active Layout Visualizer
touch2key-visualizer (visualizer.py) — Single-Instance Fullscreen Translucent QGraphicsView

Process Registration	check_single_instance('Touch2Key_Visualizer') -> register_process(VISUALIZER_RUNTIME_FILE) -> atexit unregister_process
Visual Feedback	mouseMoveEvent draws interpolated bresenham() trail rects; key/mouse press triggers active hitbox highlights and expiring touch ripples
Live Coordinate Sync	Monitors toggle_hotkeys to toggle cursor visibility; every 2.0s reads telemetry window_info & screen_x/screen_y/screen_width/screen_height to scale and offset layout zones (window position minus screen origin) to the active target window (or fullscreen viewport fallback)

3B. Low-Latency Virtual Keyboard (VKB)
touch2key-keyboard — Spawned via Bottom Bezel (0x9906) or CLI

Lifecycle & Tracking	Managed by Engine.toggle_virtual_keyboard(); PID published in runtime snapshot under workers['vkb']. Typematic is suspended while it is open; Engine.reap_virtual_keyboard() (called from the Mapper VKB listener) resumes it and releases held keys if the process exits on its own (Close button or crash)
Interaction Model	InteractionController owns one press from DOWN to UP: a key, or a window move/resize after a 300ms still-hold. Long-press (300ms) latches a non-lock key (red) until the next tap; modifiers toggle; releasing outside a key cancels; Close/Toggle act on release only. Frameless, focus-less window (WindowDoesNotAcceptFocus), painted 5px border, 8px radius, 12px resize margin
Release Safety	200ms watchdog cancels a press the OS reports as released (Windows GetAsyncKeyState, X11 XQueryPointer; inactive on Wayland). closeEvent releases held keys; a dead IPC pipe is flagged so shutdown does not retry per key
Direct IPC Stream	Serializes virtual keystrokes into VKB_STRUCT (<BH: action, scancode) and pipes directly to Engine Mapper for zero-focus-loss injection

ENGINE PHASE 1: PIPELINE CONSTRUCTION, RELOAD TRANSACTION & DETERMINISTIC 5-KEY TIER SORTING

5.1 Initialization & Reload Triggers
Engine.start_headless() | MapperEvent(action='ON_RELOAD')

Initial Boot	store.settings.get() -> clamps rate_cap [30..1000Hz], pps [10..500], binds callbacks, starts WindowManager self-healing tracker
ON_RELOAD Sources	CLI [F5] Handedness | CLI [F6] Reload | CLI Arrow Key 250ms Commit | GUI Settings/Studio MapperEvent | IPC (0x03)
Debouncer	MapperEventDispatcher._debounce_loop (10ms tick); immediate synchronous delivery if cooldown == 0

5.2 Atomic Reload Transaction (Engine._on_reload under self.lock)
Layout Snapshot Sync & State Boundary Sanitation

LayoutLoader	load_layout() extracts SQLite snapshot and normalizes zones into oriented device pixels (dev_w, dev_h, dev_dpi)
Hotkeys Guard	Under _adjust_lock: syncs rate_cap & pps from DB only if not _settings_dirty
TouchReader	touch_reader.on_reload() & touch_reader.set_rate_cap(self.rate_cap)
_release_active_inputs()	_dispatch_generation += 1 | clears _contact_owners | releases the cursor-fallback button (mouse_up(M_LEFT)) if a cursor contact is active | resets all active pipelines & releases held keys/buttons. Also runs on every Menu/Game mode switch and on shutdown

5.3 Submapper Pipeline Reconstruction
Deterministic Rebuild Sequence & Pointer Generation

Mapper.reload()	Updates device_width, device_height, dpi, toggle_hotkeys_str, pps
BezelMapper	TOP_BEZEL (0x9905) -> execute_toggle_hotkeys | BOTTOM_BEZEL (0x9906) -> toggle_virtual_keyboard (Prec: 2)
MouseMapper (Game)	Game Mode Camera Pipeline: Custom Look Zone or Handedness Half-Screen / AlwaysRegion -> DeltaTransform -> PointerSemantic (Prec: 0)
MouseMapper (Fallback)	get_fallback_mouse_pipeline(): Universal AlwaysRegion + MousePointer fallback created for Menu Mode cursor dispatch
KeyMapper	update_bridge_typematics() (PACK_TYPEMATIC_STRUCT <B?If?H: KEY_CONFIG, enabled, delay_ns, rate, ignore_typematic, count + <H excluded codes, pushed to the keyboard worker) + Button Pipelines (Button + optional PointerSemantic, Prec: 3)
WheelMapper	Joystick Pipeline: Fixed/Anchored/Dynamic Origin -> JoystickTransform -> DirectionalSemantic (Prec: 1)

5.4 Isolated 5-Stage Pipeline Contract (Pipeline[T])
Region -> Origin -> Constraint -> Transformation[T] -> list[Semantic[T]]

Stage 1: Region	AlwaysRegion (area=inf) | CircularRegion (pi*r^2) | RectangularRegion (w*h)
Stage 2: Origin	FixedOrigin (static) | DynamicOrigin (touch DOWN) | AnchoredOrigin (snap_radius=80.0 default)
Stage 3: Constraint	NoConstraint | RadialConstraint (clamp r) | LeashConstraint (pulls origin if dist > leash_r)
Stage 4: Transform	IdentityTransform -> UNIT | DeltaTransform -> Vector | JoystickTransform -> frozenset[int]
Stage 5: Semantics	ButtonSemantic (key/mouse) | DirectionalSemantic (WASD diff) | PointerSemantic (dx,dy) | ToggleSemantic (tap)

5.5 Engine._build_pipeline_tiers()
Strict 5-Key Sort & Equivalence Grouping

Key 1: -precedence	Button (3) > Bezel (2) > Joystick (1) > Mouse/Pointer (0) [allows overlapping buttons to claim touches over bezel zones]
Key 2: -priority	Custom user priority tier (+200 down to -100)
Key 3: -multi_claim	allow_multi_claim: True (sorted first) before False (sorted last)
Key 4 & 5	+region.area (smaller hitboxes first) -> +creation_id (deterministic tie-breaker)
Output: self._tiers	list[list[Pipeline]] partitioned by identical (precedence, priority, allow_multi_claim)

ENGINE PHASE 2: RUNTIME TOUCH INGESTION, TWO-FINGER TAP FSM & CONTACT OWNERSHIP DISPATCH

6.1 TouchReader -> Engine._process_touch_event(touch_event)
ADB ABS_MT_* Stream (Synchronized under Engine.lock)

ADB Auto-Adapt	Queries ABS_MT_POSITION_X/Y & slot capabilities on connect; auto-pauses & resumes on USB/Wi-Fi drop
Event Payload	TouchEvent(contact_id: int, phase: DOWN | MOVE | UP, position: Point(x,y), timestamp: float)
Guard & Telemetry	Aborts if shutting down | Records TouchEventCount & increments mapper.event_count

Menu Mode Gesture Gate?

self.is_visible (cursor visible = Menu Mode only) and self.two_finger_tap_enabled

6.2 TwoFingerTapTracker.observe(touch_event) - uses time-driven polling to avoid stationary holds
Menu Mode only (cursor visible) | Ambiguity Buffer FSM (duration <= 0.25s, drift <= 25px, sync <= 0.12s)

PENDING	Buffers candidate event in _buffer and returns early (prevents single-tap leak)
REJECTED	Replays all buffered events in decision.replay through _dispatch_normal() in order
RECOGNIZED	Valid synchronized 2-finger tap -> gracefully shuts down the engine process
IDLE	Unbuffered non-DOWN event -> proceeds to _dispatch_normal(touch_event)

1. Is cid in self._contact_owners?

Ownership is locked at DOWN; MOVE/UP route exclusively to owning pipelines

6.3 Route to Owning Pipeline(s)
owners = self._contact_owners[cid]

Process	for pipeline in owners: pipeline.process(event, output_sink)
Generation Fence	Aborts immediately if generation != self._dispatch_generation
UP Cleanup	If event.phase is TouchPhase.UP: self._contact_owners.pop(cid, None)

2. Is event.phase == TouchPhase.DOWN?

New contact arrivals evaluate sorted tiers; unowned MOVE/UP fall through to cursor fallback

6.4 Evaluate Sorted self._tiers (DOWN Phase Only)
Strict Deterministic Precedence Claims

Mode Filters	Skip bezel if not bezel_toggle_enabled | Skip non-bezel HUD if self.is_visible (Menu Mode)
Claim Test	pipeline.claims(event) -> _owned_contact is None and region.activates(event)
Game Look Claim	In Game Mode, MouseMapper's Look Pipeline (Prec: 0) claims camera look contacts
Multi-Claim Rule	If allow_multi_claim: claim all matching in tier | Else: break on first claim in tier
Lock Ownership	If claimed: self._contact_owners[cid] = tuple(claimed) & returns immediately

3. Universal Fallback (self.is_visible)?

Unclaimed contact or unowned MOVE/UP: evaluate desktop cursor fallback

6.5 Engine._dispatch_cursor(event)
Menu Mode Absolute Desktop Cursor Fallback

Single Cursor Contact	The first unclaimed DOWN becomes self._cursor_contact; other contacts are ignored until its UP (or until _release_active_inputs() clears it and releases the button)
Click Sequence	DOWN: mouse_move_abs(x, y) -> fallback_mouse_pipeline.process() -> mouse_down(M_LEFT), with no sleeps (ABS and button share one ordered pipe) | UP: pipeline.process() -> mouse_up(M_LEFT)
Slop Deadzone	MOVE is ignored until the finger leaves a CURSOR_SLOP_DP radius around DOWN; the first forwarded MOVE then carries the accumulated displacement
Fallback Pipeline	fallback_mouse_pipeline.process(event, output_sink): AlwaysRegion + MousePointer fallback

ENGINE PHASE 3: 5-STAGE PIPELINE EXECUTION, FRACTIONAL MOUSE FLUSH & HARDWARE BRIDGE WORKERS

7.1 Pipeline.process(event, output_sink)
Isolated 5-Stage Per-Contact Execution

Stages 1 & 2	DOWN: _owned_contact = cid; origin.begin(pos) | All: origin.update(pos, constraint); origin_pt = origin.get()
Stage 3: Constraint	constrained = constraint.apply(origin_pt, pos) | Computes delta & frame_delta in PipelineContext
Stage 4: Transform	value = transformation.apply(context) -> UNIT | Vector(dx,dy) | frozenset[scancodes]
Stage 5: Semantics	For semantic in semantics: semantic.process(context, value, output_sink)
UP Teardown	If phase is UP: origin.end(), transformation.reset(), clears _owned_contact & _prev_position

7.2 BridgeOutputSink & Bezel Callbacks
Sub-Pixel Mouse Accumulator & Action Router

Keys & Clicks	key_down/up(scancode) | mouse_down/up(0x9900..0x9904) -> immediate Bridge call
Absolute Move	mouse_move_abs(dev_x, dev_y): normalizes by the device size, then maps into the target window rect (left + norm * (w - 1)) or, with no window (or while the VKB is alive), into the screen rect (screen_x + norm * (screen_w - 1)); the viewport tuple is (dev_w, dev_h, win, screen_x, screen_y, screen_w, screen_h)
Fractional Move	mouse_move(dx, dy) -> under _lock: accumulates _acc_x += dx, _acc_y += dy
Top Bezel Callback	Mapper.execute_toggle_hotkeys(): parse_seq -> key_down stack -> 15-35ms sleep -> LIFO key_up
Bottom Bezel Callback	Engine.toggle_virtual_keyboard(): spawns/stops the VKB process and suspends typematic while it is open (resumed on close, or by reap_virtual_keyboard() if the VKB exits on its own); VKB_STRUCT (<BH) pipe to Mapper

7.3 MouseFlushThread (Engine._mouse_flush_loop)
Rate-Capped Whole-Pixel Dispatcher (1.0 / max(rate_cap, 30.0) s)

flush_mouse_move()	idx, idy = clamp(round(_acc_x), -32767, 32767) -> bridge.mouse_move_rel(idx, idy)
Remainder & Reset	Retains fractional _acc_x -= idx, _acc_y -= idy | Resets to 0.0 when active_touches == 0

7.4 AbstractBridge -> OS Driver Worker Processes (k_proc & m_proc)
3 Dedicated IPC Pipes + 2 Threads Per Worker Process + Watchdog Respawner

Platform Signatures	Win32: keyboard_worker(k_pipe, log_q, k_handle), mouse_worker(m_pipe, mb_pipe, log_q, m_handle), NtSetTimerResolution | Linux: UInput(KEYBOARD_CAP / MOUSE_CAP)
Pipes	k_pipe: keys + KEY_CONFIG | m_pipe: REL + WHEEL (coalesced) | mb_pipe: ABS + BUTTON, executed in arrival order by one thread so 'move, then click' is ordered by construction
k_proc Main Thread	Polls k_pipe every 1s; held keys with no traffic for 15s are released through the injector (the bridge heartbeat KEY_PING keeps genuinely held keys alive): unpacks PACK_KEY (<HB) -> key_queue (Win32 keeps the E0 prefix in the full code, so numpad/nav and left/right Ctrl/Alt never collide; Linux maps via LINUX_KEY_MAP) | applies (PACK_TYPEMATIC_STRUCT <B?If?H: KEY_CONFIG, enabled, delay_ns, rate, ignore_typematic, count + <H excluded codes). Releases anything still held on exit
k_proc Injector Thread	Event-driven: blocks on key_queue until the next repeat deadline, with an outer try so it never dies silently. DOWN sleeps 40-70ms dwell, UP sleeps 1ms (stretches fast taps) | Typematic repeat fires after delay_ns at repeat_rate unless ignore_typematic is set (VKB open) or the key is excluded; Linux repeats as evdev value 2
m_proc Main Thread	Polls m_pipe every 1s: coalesces up to MAX_COALESCE=20 TASK_REL (<Bhh, 0.8-1.2ms dwell) or TASK_WHEEL (<Bhh, 1ms dwell) via send_lock | Exits if the button thread dies, so the bridge health check respawns the worker
m_proc Button Thread	Polls mb_pipe in order: TASK_ABS (<Bii, MOUSE_VIRTUAL_DESKTOP; Win32 state field is 0) then PACK_BUTTON (<Bi) under send_lock, then sleeps 25-40ms DOWN / 1ms UP outside the lock (never blocks moves) | Releases held buttons after 15s of silence | Logs and keeps running on per-event errors
Bridge Process-Side	bridge_lock serializes key/button/ABS writes; _motion_lock serializes REL/WHEEL writers | Heartbeat every KEEPALIVE_INTERVAL (5s) pings held keys and buttons | Respawn builds fresh pipes and swaps them in only if start() succeeds; a keyboard respawn releases keys and a mouse respawn releases buttons; | Win32 reload_devices() and shutdown() release everything and wait 0.1s before terminating workers