

## Parsing with Python

We'll use the term “parsing” to mean deriving meaning from structured text. For example, we can use `argparse` to find meaning from command-line arguments that may or may not have flags or be defined by positions. In this chapter, we'll look at common file formats in bioinformatics like CSV, FASTA/Q, and GFF.

### Command-line Arguments

If you have not already, I encourage you to copy the “new\_py.py” script into your `$PATH` and then execute it with the `-a` argument to start a new script with `argparse`:

```
$ ./new_py.py -a test
Done, see new script "test.py."
```

If you check out the new script, it has a `get_args` function that will show you how to create named arguments for strings, integers, booleans, and positional arguments:

```
1  #!/usr/bin/env python3
2  """
3  Author : kyclark
4  Date   : 2019-02-19
5  Purpose: Rock the Casbah
6  """
7
8  import argparse
9  import sys
10
11
12  # -----
13  def get_args():
14      """get command-line arguments"""
15      parser = argparse.ArgumentParser(
16          description='Argparse Python script',
17          formatter_class=argparse.ArgumentDefaultsHelpFormatter)
18
19      parser.add_argument(
20          'positional', metavar='str', help='A positional argument')
21
22      parser.add_argument(
23          '-a',
24          '--arg',
25          help='A named string argument',
```

```

26         metavar='str',
27         type=str,
28         default='')
29
30     parser.add_argument(
31         '-i',
32         '--int',
33         help='A named integer argument',
34         metavar='int',
35         type=int,
36         default=0)
37
38     parser.add_argument(
39         '-f', '--flag', help='A boolean flag', action='store_true')
40
41     return parser.parse_args()
42
43
44 # -----
45 def warn(msg):
46     """Print a message to STDERR"""
47     print(msg, file=sys.stderr)
48
49
50 # -----
51 def die(msg='Something bad happened'):
52     """warn() and exit with error"""
53     warn(msg)
54     sys.exit(1)
55
56
57 # -----
58 def main():
59     """Make a jazz noise here"""
60     args = get_args()
61     str_arg = args.arg
62     int_arg = args.int
63     flag_arg = args.flag
64     pos_arg = args.positional
65
66     print('str_arg = {}'.format(str_arg))
67     print('int_arg = {}'.format(int_arg))
68     print('flag_arg = {}'.format(flag_arg))
69     print('positional = {}'.format(pos_arg))
70
71

```

```

72 # -----
73 if __name__ == '__main__':
74     main()

```

If you run without any arguments or with `-h|--help`, you get a usage statement:

```

$ ./test.py
usage: test.py [-h] [-a str] [-i int] [-f] str
test.py: error: the following arguments are required: str
[cholla@~/work/biosys-analytics/lectures/09-python-parsing]$ ./test.py -h
usage: test.py [-h] [-a str] [-i int] [-f] str

```

Argparse Python script

positional arguments:

```
str          A positional argument
```

optional arguments:

```

-h, --help            show this help message and exit
-a str, --arg str     A named string argument (default: )
-i int, --int int     A named integer argument (default: 0)
-f, --flag            A boolean flag (default: False)

```

And the `argparse` module is able to turn the command line arguments into useful information:

```

$ ./test.py -a foo -i 42 -f ABCDE
str_arg = "foo"
int_arg = "42"
flag_arg = "True"
positional = "ABCDE"

```

If you try to write the code to parse `-a foo -i 42 -f ABCDE`, you will quickly appreciate how much effort using this module will save you!

## CSV Files

“CSV” stands for “comma-separated values” and describes structured text that looks like:

```

foo,bar,baz
flip,burp,quux

```

More generally, these are values that are separated by some marker. Commas are typical but can cause problems when a comma can be a legitimate value, e.g., in addresses or formatted numbers, so tabs are often used as delimiters. Tab-delimited files may have the extension “`.tsv`,” “`.dat`,” “`.tab`”, or “`.txt`.” Usually CSV files have “`.csv`” and are especially common in the R/Pandas world.

Delimited text files are a standard way to distribute non/semi-hierarchical data – e.g., records that can be represented each on one line. (When you get into data that have relationships, e.g., parents/children, then structures like XML and JSON are more appropriate, which is not to say that people haven’t sorely abused this venerable format, e.g., GFF3.) Let’s first take a look at the `csv` module in Python to parse the output from Centrifuge (<http://www.ccb.jhu.edu/software/centrifuge/>). Despite the name, this module parses any line-oriented, delimited text, not just CSV files.

For this, we’ll use some data from a study from Yellowstone National Park (<https://www.imicrobe.us/#/samples/1378>). For each input file, Centrifuge creates two tab-delimited output files:

1. a file (“YELLOWSTONE\_SMPL\_20723.sum”) showing the taxonomy ID for each read it was able to classify and
2. a file (“YELLOWSTONE\_SMPL\_20723.tsv”) of the complete taxonomy information for each taxonomy ID.

One record from the first looks like this:

```
readID      : Yellowstone_READ_00007510
seqID       : cid|321327
taxID       : 321327
score       : 640000
2ndBestScore : 0
hitLength   : 815
queryLength : 839
numMatches  : 1
```

One from the second looks like this:

```
name        : synthetic construct
taxID       : 32630
taxRank     : species
genomeSize  : 26537524
numReads    : 19
numUniqueReads : 19
abundance   : 0.0
```

Let’s write a program that shows a table of the number of records for each “taxID”:

```
$ cat -n read_count_by_taxid.py
1  #!/usr/bin/env python3
2  """Counts by taxID"""
3
4  import csv
5  import os
6  import sys
7  from collections import defaultdict
```

```

8
9     args = sys.argv[1:]
10
11     if len(args) != 1:
12         print('Usage: {} SAMPLE.SUM'.format(os.path.basename(sys.argv[0])))
13         sys.exit(1)
14
15     sum_file = args[0]
16
17     _, ext = os.path.splitext(sum_file)
18     if not ext == '.sum':
19         print('File extension "{}" is not ".sum"'.format(ext))
20         sys.exit(1)
21
22     counts = defaultdict(int)
23     with open(sum_file) as csvfile:
24         reader = csv.DictReader(csvfile, delimiter='\t')
25         for row in reader:
26             taxID = row['taxID']
27             counts[taxID] += 1
28
29     print('\t'.join(['count', 'taxID']))
30     for taxID, count in counts.items():
31         print('\t'.join([str(count), taxID]))

```

As always, it prints a “usage” statement when run with no arguments. It also uses the `os.path.splitext` function to get the file extension and make sure that it is “.sum.” Finally, if the input looks OK, then it uses the `csv.DictReader` module to parse each record of the file into a dictionary:

```

$ ./read_count_by_taxid.py
Usage: read_count_by_taxid.py SAMPLE.SUM
$ ./read_count_by_taxid.py YELLOWSTONE_SMPL_20723.tsv
File extension ".tsv" is not ".sum"
$ ./read_count_by_taxid.py YELLOWSTONE_SMPL_20723.centrifuge.sum
count    taxID
6432     321327
80       321332
19       32630

```

That’s a start, but most people would rather see the a species name rather than the NCBI taxonomy ID, so we’ll need to go look up the taxIDs in the “.tsv” file:

```

$ cat -n read_count_by_tax_name.py
1     #!/usr/bin/env python3
2     """Counts by tax name"""
3
4     import csv

```

```

5     import os
6     import sys
7     from collections import defaultdict
8
9     args = sys.argv[1:]
10
11    if len(args) != 1:
12        print('Usage: {} SAMPLE.SUM'.format(os.path.basename(sys.argv[0])))
13        sys.exit(1)
14
15    sum_file = args[0]
16
17    basename, ext = os.path.splitext(sum_file)
18    if not ext == '.sum':
19        print('File extension "{}" is not ".sum"'.format(ext))
20        sys.exit(1)
21
22    tsv_file = basename + '.tsv'
23    if not os.path.isfile(tsv_file):
24        print('Cannot find expected TSV "{}"'.format(tsv_file))
25        sys.exit(1)
26
27    tax_name = {}
28    with open(tsv_file) as csvfile:
29        reader = csv.DictReader(csvfile, delimiter='\t')
30        for row in reader:
31            tax_name[row['taxID']] = row['name']
32
33    counts = defaultdict(int)
34    with open(sum_file) as csvfile:
35        reader = csv.DictReader(csvfile, delimiter='\t')
36        for row in reader:
37            taxID = row['taxID']
38            counts[taxID] += 1
39
40    print('\t'.join(['count', 'taxID']))
41    for taxID, count in counts.items():
42        name = tax_name.get(taxID) or 'NA'
43        print('\t'.join([str(count), name]))
$ ./read_count_by_tax_name.py YELLOWSTONE_SMPL_20723.sum
count      taxID
6432      Synechococcus sp. JA-3-3Ab
80       Synechococcus sp. JA-2-3B'a(2-13)
19       synthetic construct

```

## tabchk

A huge chunk of my time is spent doing ETL operations – extract, transform, load – meaning someone sends me data (Excel or delimited-text, JSON/XML), and I put it into some sort of database. I usually want to inspect the data to see what it looks like, and it’s hard to see the data when it’s in columnar format like this:

```
$ head oceanic_mesopelagic_zone_biome.csv
Analysis,Pipeline version,Sample,MGnify ID,Experiment type,Assembly,ENA run,ENA WGS sequence
MGYA00005220,2.0,ERS490373,MGYS00000410,metagenomic,,ERR599044,
MGYA00005081,2.0,ERS490507,MGYS00000410,metagenomic,,ERR599005,
MGYA00005208,2.0,ERS492680,MGYS00000410,metagenomic,,ERR598999,
MGYA00005133,2.0,ERS490633,MGYS00000410,metagenomic,,ERR599154,
MGYA00005272,2.0,ERS488769,MGYS00000410,metagenomic,,ERR599062,
MGYA00005209,2.0,ERS490714,MGYS00000410,metagenomic,,ERR599124,
MGYA00005243,2.0,ERS493822,MGYS00000410,metagenomic,,ERR599051,
MGYA00005117,2.0,ERS491980,MGYS00000410,metagenomic,,ERR599132,
MGYA00005135,2.0,ERS493705,MGYS00000410,metagenomic,,ERR599152,
```

I’d rather see it formatted vertically:

```
$ tabchk.py oceanic_mesopelagic_zone_biome.csv
// ***** Record 1 ***** //
Analysis           : MGYA00005220
Pipeline version   : 2.0
Sample             : ERS490373
MGnify ID          : MGYS00000410
Experiment type    : metagenomic
Assembly           :
ENA run            : ERR599044
ENA WGS sequence set :
```

Sometimes I have many more fields and lots of missing values, so I can use the `-d` flag to the program indicates to show a “dense” matrix, i.e., leave out the empty fields:

```
$ tabchk.py -d oceanic_mesopelagic_zone_biome.csv
// ***** Record 1 ***** //
Analysis           : MGYA00005220
Pipeline version   : 2.0
Sample             : ERS490373
MGnify ID          : MGYS00000410
Experiment type    : metagenomic
ENA run            : ERR599044
```

Here is the `tabchk.py` program I wrote to do that. The program is generally useful, so I added it to the main `bin` directory of the repo so that you can use

that if you have already added it to your \$PATH.

```
1  #!/usr/bin/env python3
2  """
3  Author:  Ken Youens-Clark <kyclark@email.arizona.edu>
4  Purpose: Check the first/few records of a delimited text file
5  """
6
7  import argparse
8  import csv
9  import os
10 import re
11 import sys
12
13
14 # -----
15 def get_args():
16     """Get command-line arguments"""
17     parser = argparse.ArgumentParser(
18         description='Check a delimited text file',
19         formatter_class=argparse.ArgumentDefaultsHelpFormatter)
20
21     parser.add_argument('file', metavar='FILE', help='Input file')
22
23     parser.add_argument(
24         '-s',
25         '--sep',
26         help='Field separator',
27         metavar='str',
28         type=str,
29         default='')
30
31     parser.add_argument(
32         '-f',
33         '--field_names',
34         help='Field names (no header)',
35         metavar='str',
36         type=str,
37         default='')
38
39     parser.add_argument(
40         '-l',
41         '--limit',
42         help='How many records to show',
43         metavar='int',
44         type=int,
```



```

45         default=1)
46
47     parser.add_argument(
48         '-d',
49         '--dense',
50         help='Not sparse (skip empty fields)',
51         action='store_true')
52
53     parser.add_argument(
54         '-n',
55         '--number',
56         help='Show field number (e.g., for awk)',
57         action='store_true')
58
59     parser.add_argument(
60         '-N',
61         '--no_headers',
62         help='No headers in first row',
63         action='store_true')
64
65     return parser.parse_args()
66
67
68 # -----
69 def main():
70     """main"""
71     args = get_args()
72     file = args.file
73     limit = args.limit
74     sep = args.sep
75     dense = args.dense
76     show_numbers = args.number
77     no_headers = args.no_headers
78
79     if not os.path.isfile(file):
80         print("{} is not a file".format(file))
81         sys.exit(1)
82
83     if not sep:
84         _, ext = os.path.splitext(file)
85         if ext == '.csv':
86             sep = ','
87         else:
88             sep = '\t'
89
90     with open(file) as csvfile:

```

```

91         dict_args = {'delimiter': sep}
92
93     if args.field_names:
94         regex = re.compile(r'\s*,\s*')
95         names = regex.split(args.field_names)
96         if names:
97             dict_args['fieldnames'] = names
98
99     if args.no_headers:
100         num_flds = len(csvfile.readline().split(sep))
101         dict_args['fieldnames'] = list(
102             map(lambda i: 'Field' + str(i), range(1, num_flds + 1)))
103         csvfile.seek(0)
104
105     reader = csv.DictReader(csvfile, **dict_args)
106
107     for i, row in enumerate(reader, start=1):
108         vals = dict(
109             [x for x in row.items() if x[1] != '']) if dense else row
110         flds = vals.keys()
111         longest = max(map(len, flds))
112         fmt = '{:' + str(longest + 1) + '}: {}'.format(i)
113         print('// ***** Record {} ***** //'.format(i))
114         n = 0
115         for key, val in vals.items():
116             n += 1
117             show = fmt.format(key, val)
118             if show_numbers:
119                 print('{:3} {}'.format(n, show))
120             else:
121                 print(show)
122
123         if i + 1 == limit:
124             break
125
126
127     # -----
128     if __name__ == '__main__':
129         main()

```

...

## FASTA

Now let's finally get into parsing good, old FASTA files. We're going to need to install the

...

```
$ python3 -m pip install biopython
```

```
...
```

For this exercise, I'll use a few reads from the Global Ocean Sampling Expedition (<https://3>)

```
$ iget /iplant/home/shared/imicrobe/projects/26/samples/578/CAM_SMPL_GS108.fa
```

Since that file is 725M, I've added a sample to the repo in the `examples` directory.

```
$ head -2 CAM_SMPL_GS108.fa >CAM_READ_0231669761 /library_id="CAM_LIB_GOS108XLRVAL-4F-1-400" /sample_id="CAM_SMPL_GS108" raw_id=SRR066139.70645
raw_id=FG67BMZ02PUFIF  ATTTACAATAATTTAATAAAATTAACATA-
GAAATAAAATATTGTATGAAAATATGTTAAATAATGAAAGTTTTTCAGATCGTTTAATAATATTTTCT
```

The format of a FASTA file is:

- \* A record starts with a header row which has `>` as the first character on a line
- \* The string following the `>` up until the first whitespace is the record ID
- \* Anything following the ID up to the newline can be the "description," but here we see this
- \* Any line after a header that does not start with `>` is the sequence. The sequence may be

We **could** write our own FASTA parser, and we would definitely learn much along the way, b

There is a useful program called `seqmagick` that will give you information like the followi

```
...
```

```
$ seqmagick info *.fa
name           alignment  min_len  max_len  avg_len  num_seqs
CAM_SMPL_GS108.fa FALSE      47      594    369.65     499
CAM_SMPL_GS112.fa FALSE      50      624    383.50     500
...
```

You can install it like so:

```
$ python -m pip install seqmagick
```

Let's write a toy program to mimic part of the output. We'll skip the "alignment" and just c

```
...
```

```
$ ./seqmagique.py *.fa
name           min_len  max_len  avg_len  num_seqs
CAM_SMPL_GS108.fa 47      594    369.45     500
CAM_SMPL_GS112.fa 50      624    383.50     500
...
```

The code to produce this builds on our earlier skills of lists and dictionaries as we will p

```
$ cat -n seqmagique.py 1 #!/usr/bin/env python3 2 """ 3 Author: Ken Youens-Clark kyclark@email.arizona.edu 4 Purpose: Mimic seqmagick, print stats on FASTA sequences 5 """ 6 7 import os 8 import sys 9 import numpy as np 10 from Bio import SeqIO 11 12 files = sys.argv[1:] 13 14 if not files: 15 print('Usage: {} F1.fa [F2.fa ...]'.format(os.path.basename(sys.argv[0]))) 16 sys.exit(1) 17 18 info = [] 19 for file in files: 20 lengths = [] 21 for record in SeqIO.parse(file, 'fasta'): 22 lengths.append(len(record.seq)) 23 24 info.append({ 25 'name': os.path.basename(file), 26 'min_len': min(lengths), 27 'max_len': max(lengths), 28 'avg_len': '{:.2f}'.format(np.mean(lengths)), 29 'num_seqs': len(lengths) 30 }) 31 32 if info: 33 longest_file_name = max([len(f['name']) for f in info]) 34 fmt = '{:}' + str(longest_file_name) + '{:10} {:10} {:10} {:10}' 35 flds = ['name', 'min_len', 'max_len', 'avg_len', 'num_seqs'] 36 print(fmt.format(flds)) 37 for rec in info: 38 print(fmt.format([rec[fld] for fld in flds])) 39 else: 40 print('I had trouble parsing your data')
```

## ## FASTA subset

Sometimes you may only want to use part of a FASTA file, e.g., you want the first 1000 sequences

```
$ cat -n subset_fastx.py 1 #!/usr/bin/env python3 2 """ 3 Author: Ken Youens-Clark kyclark@email.arizona.edu 4 Purpose: Subset FASTA/Q files 5 """ 6 7 import argparse 8 import os 9 import sys 10 from Bio import SeqIO 11 12 13 # ----- 14 def get_args(): 15 """get args""" 16 parser = argparse.ArgumentParser( 17 description='Split FASTA files', 18 formatter_class=argparse.ArgumentDefaultsHelpFormatter) 19 20 parser.add_argument('file', help='Input file', metavar='FILE') 21 22 parser.add_argument( 23 '-f', 24 '--infmt', 25 help='Input file format', 26 type=str, 27 metavar='FMT', 28 choices=['fasta', 'fastq'], 29 default='fasta') 30 31 parser.add_argument( 32 '-F', 33 '--outfmt', 34 help='Output file format', 35 type=str, 36 metavar='FMT', 37 default=None) 38 39 parser.add_argument( 40 '-n', 41 '--num', 42 help='Number of records per file', 43 type=int, 44 metavar='NUM', 45 default=500000) 46 47 parser.add_argument( 48 '-o', 49 '--outdir', 50 help='Output directory', 51 type=str, 52 metavar='DIR', 53 default='subset') 54 55 return parser.parse_args() 56 57 # ----- 58 def warn(msg): 59 """Print a message to STDERR""" 60 print(msg, file=sys.stderr) 61 62 63 # ----- 64 def die(msg='Something bad happened'): 65 """warn() and exit with error""" 66 warn(msg) 67 sys.exit(1) 68 69 70 # ----- 71 def main(): 72 """main""" 73 args = get_args() 74 in_file = args.file 75 in_fmt = args.infmt 76 out_fmt = args.outfmt 77 if args.outfmt else args.infmt 78 out_dir = args.outdir 79 num_seqs = args.num 80 81 if not os.path.isfile(in_file): 82 die('-file "{}" is not a file'.format(in_file)) 83 84 if os.path.dirname(os.path.abspath(in_file)) == os.path.abspath(out_dir): 85 die('-outdir "{}" cannot be the same as input files'.format(out_dir)) 86 87 if num_seqs < 1: 88 die("-num cannot be less than one") 89 90 if not os.path.isdir(out_dir): 91 os.mkdir(out_dir) 92
```

```

basename = os.path.basename(in_file) 93 out_file = os.path.join(out_dir,
basename) 94 out_fh = open(out_file, 'wt') 95 num_written = 0 96 97
for record in SeqIO.parse(in_file, in_fmt): 98 SeqIO.write(record, out_fh,
out_fmt) 99 num_written += 1 100 101 if num_written == num_seqs:
102 break 103 104 print('Done, wrote {} sequence{} to "{}".format( 105
num_written, " if num_written == 1 else 's', out_file)) 106 107 108 #
----- 109 if name == 'main': 110 main() ""

```

## FASTA splitter

I seem to have implemented my own FASTA splitter a few times in as many languages. Here is one that writes a maximum number of sequences to each output file. It would not be hard to instead write a maximum number of bytes, but, for the short reads I usually handle, this works fine. Again I will use the BioPython SeqIO module to parse the FASTA files

```

$ cat -n fa_split.py
 1  #!/usr/bin/env python3
 2  """
 3  Author:  Ken Youens-Clark
 4  Purpose: Split FASTA files
 5  NB:      If you have FASTQ files, maybe just use "split"?
 6  """
 7
 8  import argparse
 9  import os
10  import sys
11  from Bio import SeqIO
12
13
14  # -----
15  def get_args():
16      """get args"""
17      parser = argparse.ArgumentParser(
18          description='Split FASTA/Q files',
19          formatter_class=argparse.ArgumentDefaultsHelpFormatter)
20
21      parser.add_argument('file', help='FASTA input file(s)', nargs='+')
22
23      parser.add_argument(
24          '-f',
25          '--input_format',
26          help='Input file format',
27          type=str,
28          metavar='FORMAT',

```

```

29         choices=['fasta', 'fastq'],
30         default='fasta')
31
32     parser.add_argument(
33         '-F',
34         '--output_format',
35         help='Output file format',
36         type=str,
37         metavar='FORMAT',
38         choices=['fasta', 'fastq'],
39         default='fasta')
40
41     parser.add_argument(
42         '-n',
43         '--sequences_per_file',
44         help='Number of sequences per file',
45         type=int,
46         metavar='NUM',
47         default=50)
48
49     parser.add_argument(
50         '-o',
51         '--out_dir',
52         help='Output directory',
53         type=str,
54         metavar='DIR',
55         default='fasplit')
56
57     return parser.parse_args()
58
59
60 # -----
61 def warn(msg):
62     """Print a message to STDERR"""
63     print(msg, file=sys.stderr)
64
65
66 # -----
67 def die(msg='Something bad happened'):
68     """warn() and exit with error"""
69     warn(msg)
70     sys.exit(1)
71
72
73 # -----
74 def main():

```

```

75     """main"""
76     args = get_args()
77     files = args.file
78     input_format = args.input_format
79     output_format = args.output_format
80     out_dir = args.out_dir
81     seqs_per_file = args.sequences_per_file
82
83     if not os.path.isdir(out_dir):
84         os.mkdir(out_dir)
85
86     if seqs_per_file < 1:
87         die('--sequences_per_file "{}" cannot be less than one'.format(
88             seqs_per_file))
89
90     num_files = 0
91     num_seqs_written = 0
92     for i, file in enumerate(files, start=1):
93         print('{:3d}: {}'.format(i, os.path.basename(file)))
94         num_files += 1
95         num_seqs_written += process(
96             file=file,
97             input_format=input_format,
98             output_format=output_format,
99             out_dir=out_dir,
100             seqs_per_file=seqs_per_file)
101
102     print('Done, processed {} sequence{} from {} file{} into "{}".format(
103         num_seqs_written, ' ' if num_seqs_written == 1 else 's', num_files, ' '
104         if num_files == 1 else 's', out_dir))
105
106
107 # -----
108 def process(file, input_format, output_format, out_dir, seqs_per_file):
109     """
110     Spilt file into smaller files into out_dir
111     Optionally convert to output format
112     Return number of sequences written
113     """
114     if not os.path.isfile(file):
115         warn('"{}" is not valid'.format(file))
116         return 0
117
118     basename, ext = os.path.splitext(os.path.basename(file))
119     out_fh = None
120     i = 0

```

```

121     num_written = 0
122     nfile = 0
123     for record in SeqIO.parse(file, input_format):
124         if i == seqs_per_file:
125             i = 0
126             if out_fh is not None:
127                 out_fh.close()
128                 out_fh = None
129
130             i += 1
131             num_written += 1
132             if out_fh is None:
133                 nfile += 1
134                 path = os.path.join(out_dir,
135                                     basename + '.' + '{:04d}'.format(nfile) + ext)
136                 out_fh = open(path, 'wt')
137
138             SeqIO.write(record, out_fh, output_format)
139
140     return num_written
141
142
143 # -----
144 if __name__ == '__main__':
145     main()

```

You can run this on the FASTA files in the `examples` directory to split them into files of 50 sequences each:

```
$ ./fa_split.py *.fa
```

```
1: CAM_SMPL_GS108.fa
```

```
2: CAM_SMPL_GS112.fa
```

Done, processed 1000 sequences from 2 files into "fasplit"

```
$ ls -lh fasplit/
```

```
total 1088
```

```

-rw-r--r-- 1 kyclark staff 22K Feb 19 15:41 CAM_SMPL_GS108.0001.fa
-rw-r--r-- 1 kyclark staff 28K Feb 19 15:41 CAM_SMPL_GS108.0002.fa
-rw-r--r-- 1 kyclark staff 27K Feb 19 15:41 CAM_SMPL_GS108.0003.fa
-rw-r--r-- 1 kyclark staff 23K Feb 19 15:41 CAM_SMPL_GS108.0004.fa
-rw-r--r-- 1 kyclark staff 22K Feb 19 15:41 CAM_SMPL_GS108.0005.fa
-rw-r--r-- 1 kyclark staff 26K Feb 19 15:41 CAM_SMPL_GS108.0006.fa
-rw-r--r-- 1 kyclark staff 29K Feb 19 15:41 CAM_SMPL_GS108.0007.fa
-rw-r--r-- 1 kyclark staff 27K Feb 19 15:41 CAM_SMPL_GS108.0008.fa
-rw-r--r-- 1 kyclark staff 26K Feb 19 15:41 CAM_SMPL_GS108.0009.fa
-rw-r--r-- 1 kyclark staff 24K Feb 19 15:41 CAM_SMPL_GS108.0010.fa
-rw-r--r-- 1 kyclark staff 26K Feb 19 15:41 CAM_SMPL_GS112.0001.fa
-rw-r--r-- 1 kyclark staff 27K Feb 19 15:41 CAM_SMPL_GS112.0002.fa

```



```
-rw-r--r-- 1 kyclark staff 28K Feb 19 15:41 CAM_SMPL_GS112.0003.fa
-rw-r--r-- 1 kyclark staff 27K Feb 19 15:41 CAM_SMPL_GS112.0004.fa
-rw-r--r-- 1 kyclark staff 27K Feb 19 15:41 CAM_SMPL_GS112.0005.fa
-rw-r--r-- 1 kyclark staff 27K Feb 19 15:41 CAM_SMPL_GS112.0006.fa
-rw-r--r-- 1 kyclark staff 28K Feb 19 15:41 CAM_SMPL_GS112.0007.fa
-rw-r--r-- 1 kyclark staff 29K Feb 19 15:41 CAM_SMPL_GS112.0008.fa
-rw-r--r-- 1 kyclark staff 27K Feb 19 15:41 CAM_SMPL_GS112.0009.fa
-rw-r--r-- 1 kyclark staff 16K Feb 19 15:41 CAM_SMPL_GS112.0010.fa
```

We can verify that things worked:

```
$ for file in fasplit/*; do echo -n $file && grep '^>' $file | wc -l; done
fasplit/CAM_SMPL_GS108.0001.fa      50
fasplit/CAM_SMPL_GS108.0002.fa      50
fasplit/CAM_SMPL_GS108.0003.fa      50
fasplit/CAM_SMPL_GS108.0004.fa      50
fasplit/CAM_SMPL_GS108.0005.fa      50
fasplit/CAM_SMPL_GS108.0006.fa      50
fasplit/CAM_SMPL_GS108.0007.fa      50
fasplit/CAM_SMPL_GS108.0008.fa      50
fasplit/CAM_SMPL_GS108.0009.fa      50
fasplit/CAM_SMPL_GS108.0010.fa      50
fasplit/CAM_SMPL_GS112.0001.fa      50
fasplit/CAM_SMPL_GS112.0002.fa      50
fasplit/CAM_SMPL_GS112.0003.fa      50
fasplit/CAM_SMPL_GS112.0004.fa      50
fasplit/CAM_SMPL_GS112.0005.fa      50
fasplit/CAM_SMPL_GS112.0006.fa      50
fasplit/CAM_SMPL_GS112.0007.fa      50
fasplit/CAM_SMPL_GS112.0008.fa      50
fasplit/CAM_SMPL_GS112.0009.fa      50
fasplit/CAM_SMPL_GS112.0010.fa      50
```

## GFF

Two of the most common output files in bioinformatics, GFF (General Feature Format) and BLAST's tab/CSV files do not include headers, so it's up to you to merge in the headers. Additionally, some of the lines may be comments (they start with # just like bash and Python), so you should skip those. Further, the last field in GFF is basically a dumping ground for whatever else the data provider felt like putting there. Usually it's a bunch of "key=value" pairs, but there's no guarantee. Let's take a look at parsing the GFF output from Prodigal:

```
$ cat -n parse_prodigal_gff.py
 1  #!/usr/bin/env python3
 2  """
```

```

3  Author:  Ken Youens-Clark <kyclark@email.arizona.edu>
4  Purpose: Parse the GFF output of Prodigal
5  """
6
7  import argparse
8  import os
9  import sys
10
11
12  # -----
13  def get_args():
14      """get args"""
15      parser = argparse.ArgumentParser(
16          description='Prodigal GFF parser',
17          formatter_class=argparse.ArgumentDefaultsHelpFormatter)
18
19      parser.add_argument('gff', metavar='FILE', help='Prodigal GFF file')
20
21      parser.add_argument(
22          '-m',
23          '--min',
24          help='Min score',
25          metavar='float',
26          type=float,
27          default=0)
28
29      return parser.parse_args()
30
31
32  # -----
33  def warn(msg):
34      """Print a message to STDERR"""
35      print(msg, file=sys.stderr)
36
37
38  # -----
39  def die(msg='Something bad happened'):
40      """warn() and exit with error"""
41      warn(msg)
42      sys.exit(1)
43
44
45  # -----
46  def main():
47      """main"""
48      args = get_args()

```

```

49     gff_file = args.gff
50     min_score = args.min
51
52     if not os.path.isfile(gff_file):
53         die('GFF "{}" is not a file'.format(gff_file))
54
55     flds = [
56         'seqname', 'source', 'feature', 'start', 'end', 'score', 'strand',
57         'frame', 'attribute'
58     ]
59
60     for line in open(gff_file):
61         if line.startswith('#'):
62             continue
63
64         vals = line.rstrip().split('\t')
65         rec = dict(zip(flds, vals))
66         attrs = {}
67
68         for x in rec['attribute'].split(';'):
69             if '=' in x:
70                 key, value = x.split('=')
71                 attrs[key] = value
72
73         score = attrs.get('score')
74         if score is not None and float(score) >= min_score:
75             print('{} {}'.format(rec['seqname'], score))
76
77
78     # -----
79     if __name__ == '__main__':
80         main()

```