

	-chean d="-dataSource" friedressevor; light classes* org springfragnework; light classes (losses* org springfragnework; light classes) -chean d="-dataSource" friedressevor; light classes (losses) -chean d= "dataSource" friedressevor; light classes (losses)	
	cbean is="dataSource" class="org springframework.jtbc.datasource DriverManagerDataSource">	
	Struptly reamer basement value "Sjutic basements" /> Spooply a reamer basement value "Sjutic basements" /> Spooply reamer basement value "Sjutic basements" /> Spoop	
	<context location="jdbc properties" property-placeholder="">>></context>	
	*Spring Framework와 라이브러리 파일	_
	1. Spring - context = Spring IoC 컨테이너와 관련된 라이브라리 Spring Freamwork 2. Spring - jdbc = Spring IDBC 관련 라이브라리	
	Spring Freamwork 2. Spring - Jobc = Spring JDBC 2번 것이 발라진	
	implementation group: 'org.springframework', name: 'spring-jidbc', version: '5.3.23'	
	implementation group. Organization records a state of the	_
	'Spring for 컨테이너 콘테과캠	
	new AnnotationConfigApplicationContext(AppConfig.class) 1.AppConfig(자바 config) 격계 생성	
	LAppcomig/Art comig) 4/4 8/3	
	★예보기)055. 클리스 정보를 알아내서 예노데이션 경보를 꺼내서 생성사 격제를 통해서 인스템스를 만드는것. = miniwebserver	
	etring objection = clazz.— constructor -	
	constructors re-	
	*Spring webMVC	
	Spring webMvC implementation for gaspring framework:spring-webmvc:5.2.2'	
	Context는 제거한다. MVC가 의존하고 있음.	
	*Spring WebMvc© DispathcerServerlet	
1		

-									
1									
1									
1									

	1									
	1									
	l									
	l									
	l									
	l									
	l									

1									
l									
l									
l									
l									

_										

	1									
	l									
	l									
	1									
	1									
	l									
	l									
	l									
	l									
	1									
	l									

l .										
4										