

Topic 8

Dynamic array vs. linked list

資料結構與程式設計
Data Structure and Programming

11/04/ 2015

In the following topics,
we will introduce several **special** types of
Data Structures,
for example, list, array, set, map, hash, graph,
etc.

Some people call them
Abstract Data Types (ADT)
or (an easier-to-understand name)
Container Classes

Abstract Data Types (ADTs)


- ◆ Or called “container classes”. Usually treated as special “utilities” for a programmer
 - Examples are:
 - List, array, queue, stack, set, map, heap, hash, string, bit vector, matrix, tree, graph, etc.
- ◆ What they provide ---
 - Interface functions to operate on the data stored in the class
 - The implied complexity of these functions
- ◆ What they don't show (Abstracted away...) ---
 - What are the data members inside?
 - How the functions are implemented?

Classification of ADTs

1. Linear (Sequence) Data Types
 - List, array, queue, stack
 2. Associative Data Types
 - Set, map, hash, heap
 3. Topological Data Types
 - Tree, graph
 4. Miscellaneous Types
 - String, bit vector, matrix
- ◆ Usually OOP programmer will implement these classes just once (*or adopt the existing ones*), and later utilize them in various programs

Basic Concepts of Linked List

- ◆ An abstract data type in which the data are linked as a list



Data Structure and Programming

Prof. Chung-Yang (Ric) Huang

5

Linked List Implementation (I)

- ◆ Simple C-style implementation

```
struct MyStruct
{
    // define data here...
    int    _id;
    string _name;

    // define the pointer here...
    MyStruct* _next;
};

struct MyTop
{
    MyStruct* _dataList;
    MyStruct* _dataPointer;
};
```

data and pointer mixed together

list and pointer not distinguished

Data Structure and Programming

Prof. Chung-Yang (Ric) Huang

6

Linked List Implementation (II)

- Data encapsulation → Abstract Data Type
→ Like a container

```
class MyClass
{
    // define data here..
    int    _id;
    string _name;
};

class ListNode
{
    MyClass _data;
    ListNode* _next;
};

class List
{
    ListNode* _head;
    ListNode* _tail;
};

class MyTop
{
    List _dataList;
    MyClass* _dataPtr;
};
```


Data Structure and Programming

Prof. Chung-Yang (Ric) Huang

7

In other words...

class MyTop



- However, whenever we need a list with different data type, we still need to define a new List class

Data Structure and Programming

Prof. Chung-Yang (Ric) Huang

8

Linked List Implementation (III)

◆ Template implementation

```
template <class T>
class ListNode
{
    T          _data;
    ListNode<T>* _next;
};

template <class T>
class List
{
    ListNode<T>* _head;
    ListNode<T>* _tail;
};
```

One implementation
multiple instantiations


```
List<int>      intList;
List<char>     charList;
List<MyClass>  myList;
...
```

Complexity Analysis (Singly Linked List)

push_front()	O(1)
push_back()	O(1) // if tail is known, else O(n)
pop_front()	O(1)
pop_back()	O(n)
size()	O(n) or O(1)
empty()	O(1) // not equal to (size() == 0)
insert(pos, data)	O(n) (before pos) or O(1) (after pos)
erase(pos)	O(n)
find(data)	O(n)

Singly vs. Doubly Linked List

- ◆ Some operations, like “erase(node)” have linear complexity for singly linked list (Why?)
 - Don't know the previous nodes
- ◆ Doubly Linked List



Memory Overhead

- ◆ Assume (32-bit machine)
 - Pointer: 4 Bytes
 - Data: d Bytes
 - Total: n data
 - ◆ Overhead = total memory – data memory
 - Data memory = d * n
1. Singly Linked List: $(d + 4) * n + 8$
 - Overhead = $4 * n + 8$ (~4Bytes/data)
 2. Doubly Linked List: $(d + 8) * n + 8$
 - Overhead = $8 * n + 8$ (~8Bytes/data)

Complexity Analysis (Doubly Linked List)

◆ push_front()	O(1)
push_back()	O(1)
pop_front()	O(1)
pop_back()	O(1)
size()	O(n) or O(1)
empty()	O(1) // != (size() == 0)
insert(pos, data)	O(1)
erase(pos)	O(1)
find(data)	O(n) ←

“Find” Operation

- ◆ One common way to speed up “find” operation is to keep the data always sorted


- [Note] Binary Search: $O(\log_2 n)$

	10	100	1000	10K	100K
O(1)	1	1	1	1	1
$O(\log_2 n)$	4	7	10	14	17
O(n)	10	100	1000	10K	100K

- ◆ But, can we implement “binary search” by using Linked List?

Why not?
Linear access
vs.
Random access

Hierarchy of STL Iterators



Container	Iterator type	Operators
list	bidirectional	*, ++, --
slist	forward	*, ++
vector	random access	*, ++, --, +/-
deque	random access	*, ++, --, +/-
map	bidirectional	*, ++, --
multimap	bidirectional	*, ++, --
set	bidirectional	*, ++, --
multiset	bidirectional	*, ++, --
Adaptors	none	N/A

Access a ListNode & Traverse a List

```
template <class T>
class ListNode
{
    T          _data;
    ListNode<T>* _next;
};
template <class T>
class List
{
    ListNode<T>* _head;
    ListNode<T>* _tail;
};

→ for (ListNode<T>* node = myList.getHead();
      node != 0; node = node->getNext()) {
    ... }
```

List Iterator

- ◆ In many standard List implementations, “class ListNode” is actually ***hidden*** from the user ---
 - Why should user know about the class “ListNode”?
 - User only interfaces with “class List”
 - The internal data field “ListNode*” is just one way of implementing “List”
- ◆ Use a generic interface class “List Iterator” to traverse a List

The Goal...

```
iterator li;
for (li = myList.begin();
     li != myList.end(); li++) ...
----- (compared to) -----
ListNode<T> *n;
for (n = myList.head();
     n != 0; n = n->getNext());

→ Overload “=”, “!=”, “++” for
   class iterator
```

List Iterator Implementation

```
◆ class iterator {
    // Conventionally, use lower case “i” for “iter...”
    ListNode<T>* _node;

public:
    iterator(const ListNode<T>* const n = 0):
        _node(n) {}

    const T& operator *() const;
    iterator& operator ++ ();
    iterator operator ++ (int);
    iterator& operator = (const iterator& i);
    bool operator != (const iterator& i) const;
};

→ Act as a “wrapper class” for ListNode<T>*
```

But the question is:
“How to distinguish this generic iterator
class from others?”

➔ One possible way is to declare it
inside the “List” class

List Iterator Implementation (cont'd)

```
◆ template <class T>
class List {
    ListNode<T>* _head;
    ListNode<T>* _tail;

    // Conventionally, use lowercase "i"
    class iterator {
        ListNode<T>* _node;
    public:
        iterator(const ListNode<T>* const n = 0):
            _node(n) {}

        ...
    }

    // implicitly calling the iterator(_head) constructor
    iterator() {
        return iterator(_head);
    };
};
```

Why return '0'?
Is this a good
implementation?

A List Example

```
int main() {
    List<int> intList;
    for (int i = 0; i < 10; ++i)
        intList.push_back(i * 2);

    List<int>::iterator li;
    for (li = intList.begin();
         li != intList.end(); li++) {
        cout << *li << endl;
    }
}
```

List<T>::push_back(const T& d)

```
void push_back(const T& d) {
    ListNode<T>* t
    = new ListNode<T>(d, 0);
    if (_tail != 0)
        _tail->setNext(t);
    else // _head = _tail = 0
        _head = t;
    _tail = t;
}
```

```
template <class T>
class ListNode {
    T _data;
    ListNode<T>* _next;
};
```

[Question] Who frees the ListNode*
memory?

List<T>::pop_front()

```
void pop_front() {
    if (empty()) return;
    ListNode<T>* t = _head->getNext();
    delete _head;
    _head = t;
}
```

[Question] How about "_tail"?

[Question] How about "_data" inside
"_head"? Will it be destructed or
"deleted"?

Destructors of List and ListNode


```
ListNode<T>::~~ListNode() {
    // Do nothing.
    // But Will call the destructor of "T _data"
    // But if "T" is a pointer type,
    // → will not free its memory (why??)
}

List<T>::~~List() {
    ListNode<T>* thisNode = _head;
    while (thisNode != 0) {
        ListNode<T>* nextNode = thisNode->getNext();
        delete thisNode;
        thisNode = nextNode;
    }
}
```

Note about the "end()"

- ◆ Remember, in STL, "end()" actually points to the next to the last node.
- ◆ In the previous example, we return '0' for "end()"
 - Any problem?
 - Potential misjudgment on "n == end()"
 - How to do backward traversal?
- ◆ The solution in HW#5 (also in STL's list<T>)
 - Create a dummy ListNode<T>* as the end

Dummy ListNode<T>* as the end()



Dummy `ListNode<T>*` as the end()

- ◆ Things to consider...
 1. What happens when the `List<T>` is just constructed?
 2. `size()`, `empty()`?
 3. `push_back()`, `push_front()`
 - ➔ need to properly update `_head`, `_tail`
 4. `pop_back()`, `pop_front()`
 - ➔ when happen if it has just one element or is empty?

Sorting in Linked List

- ◆ As we say, since the iterators in linked list are not randomly accessible, it's not possible to implement binary search on it.
- ◆ Sorting on Linked List: $O(n^2)$
 - Bubble sort, selection sort, etc.

Classification of ADTs

1. Linear (Sequence) Data Types
 - List, array, queue, stack
 2. Associative Data Types
 - Set, map, hash, heap
 3. Topological Data Types
 - Tree, graph
 4. Miscellaneous Types
 - String, bit vector, matrix
- ◆ Usually OOP programmer will implement these classes just once (*or adopt the existing ones*), and later utilize them in various programs

Array vs. List

- ◆ In many programmers' view, "array" is less favorable than "list" because they think the array class is ---
 1. Limited in size (i.e. array bound)
 2. Expensive in "erase" operation
 3. No clear advantage other than "random access by index"
- ➔ That's because they don't know enough about "Dynamic Array"


Static Array

- ◆ Array with fixed size // e.g. `int arr[100];`
- ◆ “Insert/erase()” operation
 - $O(1)$ if inserted at the end
 - If the element order is not important
 - $O(1)$ insert anywhere (how?)
 - $O(1)$ erase
 - If the element order does matter
 - $O(n)$ insert at the beginning
 - $O(n)$ erase
- Is this common? (comparing to list...)
- ◆ “Find()” operation
 - Can have $O(\log_2 n)$ complexity (how?)

Static vs. Dynamic Array

- ◆ Static array is indeed limited in usage, and may create memory problems
 - Not recommended in general
- ◆ However, dynamic array removes the array size limitation, and when compared with linked list, its performance (runtime and memory) is much better
 - Highly recommended

Basic Concept of Dynamic Array



Dynamic Array Implementation

```
template <class T>
class Array
{
    T*      _data;
    size_t  _size;
    size_t  _capacity

public:
    Array(size_t t = 0)
        : _size(t), _capacity(t) {
        _data = initCapacity(t);
    }
};
```

“Size” in Dynamic Array

- ◆ [Note] In previous example, `_size = t`, not 0
 - ➔ follow the semantics of STL
 - We can access `array[0 ~ (t-1)]` after construction
- ◆ [compare]
 - `Array<int> arr1; // size = 0`
`arr1[0] = i; // Error!!`
`arr1.push_back(i); // OK; size becomes 1`
 - `Array<int> arr2(10); // size = 10`
`arr2[0] = i; // OK`
`arr2.push_back(j); // What's the size now?`

“Capacity” in Dynamic Array

- ◆ Initialized in array constructor
- ◆ When `_size == _capacity`, how to grow?
 - ➔ Doubled (e.g. $2 \rightarrow 4$, $3 \rightarrow 6$, $5 \rightarrow 10$, etc)
 - Issue: How to do memory management?
 - Remember: difficult to recycle if different in size
- [Sol#1] Powered of 2 in memory allocation
- Issue: waste memory
 - Many arrays may have size < 10 , but only have capacity choices as $\{2, 4, 8, 16\}$
- [Sol#2] Hybrid $(1, 2, 3, \dots, 7, 8, 16, \dots, 2^n, \dots)$

Important Member Functions for Array

1. `T& operator [] (size_type i);`
2. `const T& operator [] (size_type i) const;`
3. `void push_back(const T& d) {`
 `if (_size == _capacity)`
 `expand();`
 `data[_size++] = d;`
 `}`
4. `void resize(size_type s);`
 // s can be smaller or larger than `_size`

Complexity Analysis (Dynamic Array)

- ◆ `push_front()` $O(n)$ or $O(1)$ // if order not matters
- `push_back()` $O(1)$
- `pop_front()` $O(n)$ or $O(1)$ // if order not matters
- `pop_back()` $O(1)$
- `size()` $O(1)$ // not $O(n)$, why?
- `empty()` $O(1)$
- `insert(pos, data)` $O(n)$ or $O(1)$ // if order not matters
- `erase(pos)` $O(n)$ or $O(1)$ // if order not matters
- `find(data)` $O(n)$ or $O(\log n)$

If order does not matter, almost all operations are $O(1)$!!

Memory Overhead of Dynamic Array

- ◆ Assume (32-bit machine)
 - Pointer: 4 Bytes
 - Data: d Bytes
 - Total: n data
- ◆ Overhead = total memory – data memory
 - Data memory = $d * n + 4$
- ◆ Dynamic Array Overhead = 8 Bytes only (why??)
 - (cf) Singly Linked List = $4 * n + 8$
 - (cf) Doubly Linked List = $8 * n + 8$

The Data in the Array Can be Sorted

- ◆ Option #1 (dynamic)
 - Whenever a data is inserted, update the array so that the elements are in right order
 - $O(\log n)$ in finding the place to insert; $O(n)$ in updating the array
 - Inserting n elements → $O(n^2)$ // NOT $O(n \log n)$
 - Array may not be the best ADT
 - In such case, “balanced binary search tree (BST)” (e.g. STL Set/Map) should be better
- ◆ Option #2 (static)
 - If we care about the order only after all the elements are inserted
 - Sorted only once
 - Inserting n elements → $O(n \log n)$
 - Has the same “find()” complexity as “set” or “map”, but much less memory overhead than BST!!

Some notes about the Array<T> in HW#5

- ◆ Don't worry about sorting for Array<T>, we call STL:
 - `void sort(RandomAccessIterator first, RandomAccessIterator last, StrictWeakOrdering comp);`
- ◆ No need to implement class ArrayNode<T>. Why??
- ◆ The capacity should grow: $0 \rightarrow 1 \rightarrow \rightarrow \rightarrow n$

Performance Comparison: Dynamic Array vs. Linked List

- ◆ Task 1
 1. Insert n data (1 by 1)
- ◆ Task 2
 1. Insert n data (1 by 1)
 2. Destroy the ADT (remove all)
- ◆ Task 3
 1. Alternatively insertions and deletions
- ◆ Task 4
 1. Sort the data

(Try different scenarios and report in HW #5)

“vector” and “list” in STL

- ◆ In fact, many wrapper classes around the real data members
- ◆ In essence...

- class vector {
 T* _M_start;
 T* _M_finish;
 T* _M_end_of_storage;
};
- class list {
 std::_List_node_base* _M_node;
};
- class _List_node_base {
 std::_List_node_base* _M_next;
 std::_List_node_base* _M_prev;
};

Other Linear ADT

1. Queue (also known as FIFO)
2. Stack (also known as FILO)

- ◆ Use “adaptor class” to implement on top of other linear ADT

- For example,

```
template <class T, class C = Array<T> >  
class Stack {  
    C _elements;  
public:  
    // only define operations  
    // that make sense to “stack”  
    // e.g. push(), pop(), top(), etc  
};
```