TL074

Low noise JFET quad operational amplifier

Features

- Wide common-mode (up to V_{CC}^+) and differential voltage range
- Low input bias and offset current
- Low noise $e_n = 15$ nV/$\sqrt{Hz}$ (typ)
- Output short-circuit protection
- High input impedance JFET input stage
- Low harmonic distortion : 0.01% (typical)
- Internal frequency compensation
- Latch up free operation
- High slew rate: 16 V/μs (typical)

Description

The TL074, TL074A and TL074B are high-speed JFET input single operational amplifiers. Each of these JFET input operational amplifiers incorporates well matched, high-voltage JFET and bipolar transistors in a monolithic integrated circuit.

The devices feature high slew rates, low input bias and offset currents, and low offset voltage temperature coefficient.

N
DIP14
(Plastic package)

D
SO-14
(Plastic micropackage)

Pin connections
(Top view)

Output 1	1	14 Output 4
Inverting Input 1	2	13 Inverting Input 4
Non-inverting Input 1	3	12 Non-inverting Input 4
V_{CC}^+	4	11 V_{CC}^-
Non-inverting Input 2	5	10 Non-inverting Input 3
Inverting Input 2	6	9 Inverting Input 3
Output 2	7	8 Output 3

2 Absolute maximum ratings and operating conditions

Table 1.   Absolute maximum ratings

Symbol	Parameter	Value		Unit
		TL074I, AI, BI	**TL074C, AC, BC**	
V_{CC}	Supply voltage [1]	±18		V
V_i	Input voltage[2]	±15		V
V_{id}	Differential input voltage[3]	±30		V
P_{tot}	Power dissipation	680		mW
R_{thja}	Thermal resistance junction to ambient [4] [5] DIP14 SO-14	80 105		°C/W
R_{thjc}	Thermal resistance junction to case [4] [5] DIP14 SO-14	33 31		°C/W
	Output short-circuit duration[6]	Infinite		
T_{oper}	Operating free-air temperature range	-40 to +105	0 to +70	°C
T_{stg}	Storage temperature range	-65 to +150		°C
ESD	HBM: human body model[7]	1		kV
	MM: machine model[8]	200		V
	CDM: charged device model[9]	1.5		kV

1. All voltage values, except differential voltage, are with respect to the zero reference level (ground) of the supply voltages where the zero reference level is the midpoint between V_{CC}^+ and V_{CC}^-.

2. The magnitude of the input voltage must never exceed the magnitude of the supply voltage or 15 volts, whichever is less.

3. Differential voltages are the non-inverting input terminal with respect to the inverting input terminal.

4. Short-circuits can cause excessive heating. Destructive dissipation can result from simultaneous short-circuits on all amplifiers.

5. Rth are typical values.

6. The output may be shorted to ground or to either supply. Temperature and/or supply voltages must be limited to ensure that the dissipation rating is not exceeded.

7. Human body model: 100pF discharged through a 1.5kΩ resistor between two pins of the device, done for all couples of pin combinations with other pins floating.

8. Machine model: a 200pF cap is charged to the specified voltage, then discharged directly between two pins of the device with no external series resistor (internal resistor < 5Ω), done for all couples of pin combinations with other pins floating.

9. Charged device model: all pins plus package are charged together to the specified voltage and then discharged directly to the ground.

Table 2.   Operating conditions

Symbol	Parameter	TL074I, AI, BI	TL074C, AC, BC	Unit
V_{CC}	Supply voltage	6 to 36		V
T_{oper}	Operating free-air temperature range	-40 to +105	0 to +70	°C

3 Electrical characteristics

Table 3. V$_{CC}$ = ±15V, T$_{amb}$ = +25°C (unless otherwise specified)

Symbol	Parameter	TL074I,AC,AI, BC,BI			TL074C			Unit
		Min.	Typ.	Max.	Min.	Typ.	Max.	

V$_{io}$	Input offset voltage (R$_S$ = 50Ω)
	T$_{amb}$ = +25°C TL074
	                            TL074A
	                            TL074B
	T$_{min}$ ≤ T$_{amb}$ ≤ T$_{max}$ TL074
	                            TL074A
	                            TL074B
			3
			3
			1
				10
				6
				3
				13
				7
				5
						3	10
							
							13
								mV

DV$_{io}$	Input offset voltage drift		10			10		µV/°C
I$_{io}$	Input offset current T$_{amb}$ = +25°C T$_{min}$ ≤ T$_{amb}$ ≤ T$_{max}$		5	100 4		5	100 10	pA nA
I$_{ib}$	Input bias current -note [1] T$_{amb}$ = +25°C T$_{min}$ ≤ T$_{amb}$ ≤ T$_{max}$		20	200 20		30	200 20	pA nA
A$_{vd}$	Large signal voltage gain R$_L$= 2kΩ, V$_o$=±10V T$_{amb}$ = +25°C T$_{min}$ ≤ T$_{amb}$ ≤ T$_{max}$	50 25	200		25 15	200		V/mV
SVR	Supply voltage rejection ratio (R$_S$ = 50Ω) T$_{amb}$ = +25°C T$_{min}$ ≤ T$_{amb}$ ≤ T$_{max}$	80 80	86		70 70	86		dB
I$_{CC}$	Supply current, no load T$_{amb}$ = +25°C T$_{min}$ ≤ T$_{amb}$ ≤ T$_{max}$		1.4	2.5 2.5		1.4	2.5 2.5	mA
V$_{icm}$	Input common mode voltage range	±11	+15 -12		±11	+15 -12		V
CMR	Common mode rejection ratio (R$_S$ = 50Ω) T$_{amb}$ = +25°C T$_{min}$ ≤ T$_{amb}$ ≤ T$_{max}$	80 80	86		70 70	86		dB
I$_{os}$	Output short-circuit current T$_{amb}$ = +25°C T$_{min}$ ≤ T$_{amb}$ ≤ T$_{max}$	10 10	40	60 60	10 10	40	60 60	mA

±V$_{opp}$	Output voltage swing
	T$_{amb}$ = +25°C RL = 2kΩ
	                            RL = 10kΩ
	T$_{min}$ ≤ T$_{amb}$ ≤ T$_{max}$ RL = 2kΩ
	                            RL = 10kΩ
		10
		12
		10
		12
			12
			13.5
					10
					12
					10
					12
						12
						13.5
								V

SR	Slew rate V$_{in}$ = 10V, R$_L$ = 2kΩ, C$_L$ = 100pF, unity gain	8	13		8	13		V/µs

Table 3. V_{CC} = ±15V, T_{amb} = +25°C (unless otherwise specified) (continued)

Symbol	Parameter	TL074I,AC,AI, BC,BI			TL074C			Unit
		Min.	Typ.	Max.	Min.	Typ.	Max.	
t_r	Rise time V_{in} = 20mV, R_L = 2kΩ, C_L = 100pF, unity gain		0.1			0.1		µs
K_{ov}	Overshoot V_{in} = 20mV, R_L = 2kΩ, C_L = 100pF, unity gain		10			10		%
GBP	Gain bandwidth product V_{in}= 10mV, R_L= 2kΩ, C_L = 100pF, = 100kHz	2	3		2	3		MHz
R_i	Input resistance		10^{12}			10^{12}		Ω
THD	Total harmonic distortion f= 1kHz, R_L = 2kΩ, C_L = 100pF, A_v = 20dB, V_o = 2V_{pp})		0.01			0.01		%
e_n	Equivalent input noise voltage R_S = 100Ω, f = 1kHz		15			15		$\frac{nV}{\sqrt{Hz}}$
∅m	Phase margin		45			45		degrees
V_{o1}/V_{o2}	Channel separation A_v = 100		120			120		dB

1.   The input bias currents are junction leakage currents which approximately double for every 10° C increase in the junction temperature.

6   Package information

In order to meet environmental requirements, ST offers these devices in ECOPACK® packages. These packages have a lead-free second level interconnect. The category of second level interconnect is marked on the package and on the inner box label, in compliance with JEDEC Standard JESD97. The maximum ratings related to soldering conditions are also marked on the inner box label. ECOPACK is an ST trademark. ECOPACK specifications are available at: www.st.com.

6.1   DIP14 package information

Figure 24.   DIP14 package mechanical drawing

**Table 4.   DIP14 package mechanical data**

Ref.	Millimeters			Inches		
	Min.	**Typ.**	**Max.**	**Min.**	**Typ.**	**Max.**
a1	0.51			0.020		
B	1.39		1.65	0.055		0.065
b		0.5			0.020	
b1		0.25			0.010	
D			20			0.787
E		8.5			0.335	
e		2.54			0.100	
e3		15.24			0.600	
F			7.1			0.280
I			5.1			0.201
L		3.3			0.130	
Z	1.27		2.54	0.050		0.100

7 Ordering information

Table 6.   Order codes

Order code	Temperature range	Package	Packing	Marking
TL074IN TL074AIN TL074BIN	-40°C, +105°C	DIP14	Tube	TL074IN TL074AIN TL074BIN
TL074ID/IDT TL074AID/AIDT TL074BID/BIDT		SO-14	Tube or tape & reel	074I 074AI 074BI
TL074IYD/IYDT[1] TL074AIYD/AIYDT[1] TL074BIYD/BIYDT[1]		SO-14	Tube or tape & reel	074IY 074AIY 074BIY
TL074CN TL074ACN TL074BCN	0°C, +70°C	DIP14	Tube	TL074CN TL074ACN TL074BCN
TL074CD/CDT TL074ACD/ACDT TL074BCD/BCDT		SO-14	Tube or tape & reel	074C 074AC 074BC

1. Qualification and characterization according to AEC Q100 and Q003 or equivalent, advanced screening according to AEC Q001 & Q 002 or equivalent are on-going.