# CS 5003: Parameterized Algorithms Lectures 1 and 2

Krithika Ramaswamy

IIT Palakkad

#### \* Text Books

- \* Parameterized Algorithms by Cygan et al.
- \* Kernelization by Fomin et al.

#### \* Evaluation Scheme

- \* Quiz 1 20%
- \* Quiz 2 20%
- \* Assignments 15%
- \* Endsem 45%
- \* Presentation (optional)

#### Review of Basic Concepts: Algorithms and Problems


- \* Algorithm
  - \* A finite sequence of steps to solve a problem


- \* Computational Problem
  - \* Input encoded in binary
  - Specification of the output desired for each input

- \* Instance of a problem
  - \* Specific input to the problem

#### Review of Basic Concepts: Vertex Cover

Vertex cover - set of vertices that has at least one endpoint of each edge







#### Review of Basic Concepts: Independent Set

Independent set - set of vertices that are pairwise non-adjacent

S is a vertex cover => V(G)-S is an independent set







#### Review of Basic Concepts: Example of a Problem

Minimum Vertex Cover

Instance: An undirected graph G

Output: A minimum-size vertex cover of G






#### Review of Basic Concepts: Decision Problems

\* Pecision Problem: answer is yes or no

#### **Vertex Cover**

Instance: An undirected graph G and an integer k

Question: Poes there exist a vertex cover of G of size at most k?



- \* (G1) is a no-instance of Vertex Cover
- \* (G,2) is an yes-instance of Vertex Cover
- \* (G,3) is an yes-instance of Vertex Cover

#### Review of Basic Concepts: Classes P and EXP

- Complexity Class P
  - \* P is the set of all decision problems solvable in polynomial time
  - \* O(nc) time for some constant c where n is the input size
  - \* Examples: Shortest Path, Matching, Longest Path in directed acyclic graphs
- Complexity Class EXP
  - \* EXP is the set of all decision problems solvable in exponential time
  - \* 0(2<sup>nc</sup>) time for some constant c where n is the input size
  - \* Examples: Vertex Cover, Travelling Salesperson, Longest Path

# Review of Basic Concepts: Class NP

\* Complexity Class NP

NP is the set of decision problems for which the problem instances, where the ans

- \* A problem is in NP if any yes-instance can be verified that it is indeed an yes-instance in polynomial time
  - polynomial-size certificate
- Vertex Cover
  - \* Certificate is a vertex cover of size at most k
    - \* Certificate is polynomial-size
    - \* Can verify if a set of vertices is a vertex cover or not in polynomial time

#### Review of Basic Concepts: Reductions

- \* Polynomial-time Reductions
  - \* Problem A reduces to problem B if there is a polynomial time algorithm h such that for every instance x of A
    - \* h(x) is an instance of B
    - \* x is an yes-instance of A if and only if h(x) is an yes-instance of B
- \* Complexity Classes NP-hard and NP-complete
  - Problem A is NP-hard if every problem in NP reduces to it in polynomial time
    - \* If an NP-hard problem has a polynomial-time algorithm then P=NP
  - \* Problem A is NP-complete if it is in NP and NP-hard

#### Review of Basic Concepts: Approaches to NP-hardness

- Consequence of a problem being NP-hard
  - \* No polynomial time (in the worst case) algorithm that solves all instances optimally is likely to exist
    - \* Near-optimum solution: approximation algorithms
    - \* Average case: Randomized algorithms
    - \* Restrict the input
    - \* Exponential time

Parameterized algorithms (or) Fixed-parameter tractable algorithms

#### Parameterized Problem

\* Each instance is associated with a non-negative integer called parameter

Parameterized Graph Problem Template

Instance: A graph G and integer k

Question: Poes & have a solution of size k?

Parameter: k

 $2^{0(k^2)}$  poly(n)

20(k log k) poly(n)

size of an instance (G,k) is IGI + k

|G| is in binary whereas k is in unary

Goal: Design f(k) poly(n) algorithm

n - input size

k - parameter

fixed-parameter tractable algorithm
or
parameterized algorithm

complexity Class FPT is the set of all parameterized problems that are fixed-parameter tractable

#### Parameterized Algorithms

- \* Find solution in exponential time
  - \* Exponential factor in running time is restricted to only the parameter

Vertex Cover (parameterized by solution size)

Instance: A graph G on n vertices m edges and integer k

Question: Poes 6 have a vertex cover of size at most k?

Parameter: k

Goal: f(k) poly(n,m) algorithm

### Multiple Parameterizations

Vertex Cover (parameterized by max degree)

Instance: A graph G with max degree r and integer k Question: Does G have a vertex cover of size at most k?

Parameter: r

Goal: f(r) poly(n,m) algorithm

Vertex Cover (parameterized by min degree)

Instance: A graph & with min degree q and integer k

Question: Poes & have a vertex cover of size at most k?

<u>Parameter:</u> q

Goal: f(q) poly(n,m) algorithm

Not all parameterized problems are FPT

Instance: A graph G on n vertices m edges and integer k Question: Does G have a vertex cover of size at most k?

Parameter: k

Instance: (G,k)

Preprocessing Rule 1: Delete isolated vertices

Resulting Instance: (G-u,k)


(G,k) is an yes-instance => (G-u,k) is an yes-instance

(G-u,k) is an yes-instance => (G,k) is an yes-instance

Time: O(n)

Instance: (6',k')

Preprocessing Rule 2: Delete high degree vertices



>= k'+1 neighbours

Add v into the solution

Resulting Instance: (G'-v,k'-1)

(G',k') is an yes-instance => (G'-v,k'-1) is an yes-instance

(G'-v,k'-1) is an yes-instance => (G',k') is an yes-instance

We have to repeatedly apply this preprocessing rules

Time:  $O(nk^2)$ 


Instance: (H,r)

(G,k) is an yes-instance iff (H,r) is an yes-instance

Suppose (H,r) is an yes-instance



S a vertex cover of H with ISI <= r <=k




Independent Set

Suppose (H,r) is an yes-instance



S a vertex cover of H with ISI <= r <=k




Independent Set


Can H have more than r<sup>2</sup> edges?

If H has more than r<sup>2</sup> edges then (H,r) is no yes-instance

Otherwise, H has at most  $r^2$  edges and at most  $r+r^2$  vertices







G on n vertices and m edges Poes G have a VC of size <= k? Parameter: k H on r+r<sup>2</sup> vertices and r<sup>2</sup> edges
Poes H have a VC of size <= r?
Parameter: r

|(H,r)| = f(k)

Kernel

(G,k) is an yes-instance iff (H,r) is an yes-instance

Kernel => FPT