

EG3411

EG3411

DWS6080

0 to 150 kg

0.01 kg

DIGITAL SCALE

MONOLITHOLT

23.5°C / 41 % RH

Certificate of Calibration

Certificate Number: 5523631030543381

Customer:

MP Control #:

Asset ID:

Size:

Description:

Resolution:

Temp./RH:

Manufacturer:

Model Number:

ZHONGLI TALESUN HONG KONG LIMITED CARRETERA GUADALAJARA MORELIA #19200 INT. 3 COL. BUENAVISTA TLAJOMULCO DE ZUÑIGA JALISCO 45640





DIMENSIONAL MEASUREMENT

Accreditation Number: AC-1969

Date: Dec 8, 2023 Work Order: GDL-449089

SDWS105107FF4871 Serial Number:

N/A Department:

ON SITE CALIBRATION Location:

IN TOLERANCE Received Condition: IN TOLERANCE Returned Condition:

Nov 17, 2023 Cal. Date:

12 MONTHS Cal. Interval: Nov 17, 2024 Cal. Due Date:

STATEMENTS OF PASS OR FAIL CONFORMANCE: The uncertainty of measurement has been taken into account when determining compliance with specification. All measurements and test results guard banded to ensure the probability of false-accept does not exceed 2% in compliance with ANSI/NCSL Z540,3-2006.

THE CALIBRATION REPORT STATUS:

PASS - Term used when compliance statement is given, and the measurement result is PASS.

PASS² - Term used when compliance statement is given, and the measurement result is conditional passed or PASS²

FAIL - Term used when compliance statement is given, and the measurement result is FAIL.

FAIL^z - Term used when compliance statement is given, and the measurement result is conditional failed or FAIL^z.

REPORT OF VALUE - Term used when reported measurement is not requiring compliance statement in report. ADJUSTED - When adjustments are made to an instrument which changes the value of measurement from what was measured as found to new value as left.

LIMITED - When an instrument fails calibration but is still functional in a limited manner.

The expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%, unless otherwise stated. This calibration report complies with ISO/IEC 17025:2017 and ANSI/NCSL Z540.3. Calibration cycles and resulting due dates were submitted/approved by the customer. Any number of factors may cause an instrument to drift out of tolerance before the next scheduled calibration. Recalibration cycles should be based on frequency of use, environmental conditions and customer's established systematic accuracy. All standards are traceable to SI through the National Institute of Standards and Technology (NIST) and/or recognized national or international standards laboratories. Services rendered include proper manufacturer's service instruction and are warranted for no less than thirty (30) days. The information on this report pertains only to the instrument identified, this may not be reproduced in part or in a whole without the prior written approval of the issuing MP Calibration Laboratory.

Standards Used to Calibrate Equipment

Standards Used to Calibrate Equipment		pment	Model	Traceability Number	Cal. Due Date
I.D. BP4618 BP4633 BP4632 BP4627	Manufacturer METTLER TOLEDO METTLER TOLEDO METTLER TOLEDO METTLER TOLEDO METTLER TOLEDO METTLER TOLEDO EXTECH INSTRUMENTS	Description WEIGHT WEIGHT WEIGHT WEIGHT WEIGHT WEIGHT HYGRO-THERMOMETER CLOCK	CLASS OIML M2 CLASS OIML M2 CLASS M2 CLASS OIML M2 CLASS OIML M2 CLASS M2 445702	551220085614381 551220085364944 5523631030194931 551220085614413 551220085614748 5523631030188484	Nov 25, 2023 Sep 14, 2024 Jul 12, 2024 Nov 25, 2023 Jan 17, 2024 Aug 3, 2024

Procedures Used in this Event

Procedure Name

MPC-WEI-001

Description

Weighing Instruments, General, Rev.07, Jul-07-2021

Additional notes: See attached data.

Calibrating Technician:

JESUS GONZALEZ

Approved By:

FELIPE DELGADO

MP-FLC-004 ANAB Rev.03, Sep-10-2022