

Certificate of Calibration

Certificate Number: 5523631030114250

Customer:

ZHONGLI TALESUN HONG KONG LIMITED CARRETERA GUADALAJARA MORELIA #19200 INT. 3 COL. BUENAVISTA TLAJOMULCO DE ZUÑIGA JALISCO 45640 lac-MRA

N/A

N/A



CALIBRATION AND DIMENSIONAL MEASUREMENT

Accreditation Number: AC-1969

Date : Jun 8, 2023 Work Order : GDL-446114

MP Control #: DU7314 Serial Number:

Asset ID: DU7314 Department:

Description: PATTERN WEIGHT Location:

Description: PATTERN WEIGHT Location: MP LAB

Manufacturer: REMEX Received Condition: IN TOLERANCE

Model Number: CLASS M2 Returned Condition: IN TOLERANCE
Size: 20 kg Cal. Date: Jun 06, 2023
Resolution: N/A Cal. Interval: 12 MONTHS

Temp/RH: 20.8°C / 40.2 % RH Cal. Due Date: Jun 06, 2024

STATEMENTS OF PASS OR FAIL CONFORMANCE: The uncertainty of measurement has been taken into account when determining compliance with specification. All measurements and test results guard banded to ensure the probability of false-accept does not exceed 2% in compliance with ANSI/NCSL Z540.3-2006.

THE CALIBRATION REPORT STATUS:

PASS - Term used when compliance statement is given, and the measurement result is PASS.

PASS^z - Term used when compliance statement is given, and the measurement result is conditional passed or PASS^z.

FAIL - Term used when compliance statement is given, and the measurement result is FAIL.

Lz - Term used when compliance statement is given, and the measurement result is conditional failed or FAILz.

PORT OF VALUE - Term used when reported measurement is not requiring compliance statement in report.

ADJUSTED - When adjustments are made to an instrument which changes the value of measurement from what was measured as found to new value as left.

LIMITED - When an instrument fails calibration but is still functional in a limited manner.

The expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%, unless otherwise stated. This calibration report complies with ISO/IEC 17025:2017 and ANSI/NCSL Z540.3. Calibration cycles and resulting due dates were submitted/approved by the customer. Any number of factors may cause an instrument to drift out of tolerance before the next scheduled calibration. Recalibration cycles should be based on frequency of use, environmental conditions and customer's established systematic accuracy. All standards are traceable to SI through the National Institute of Standards and Technology (NIST) and/or recognized national or international standards laboratories. Services rendered include proper manufacturer's service instruction and are warranted for no less than thirty (30) days. The information on this report pertains only to the instrument identified, this may not be reproduced in part or in a whole without the prior written approval of the issuing MP Calibration Laboratory.

Standards Used to Calibrate Equipment

Ottalian and Down in Carrier and Inc.					
I.D.	Manufacturer	Description	Model	Traceability Number	Cal. Due Date
	EXTECH INSTRUMENTS	TEMPERATURE & HUMIDITY DATALOGG	42280	551220085150538	Jun 16, 2023
DJ8045			LP34001P	551220085661030	Feb 3, 2024
DL0701	SARTORIUS	SCALE	7. 7.17.1		
DG9410	N/A	WEIGHT	CLASE M1	MAEF-MA9972-21	Jul 14, 2023

Procedures Used in this Event

Procedure Name Description

MPC-WGT-001 Weight Calibration using ABBA Method, General, Rev.05, Jul-07-2021

Additional notes: See attached data.

Calibrating Technician:

JOSE JUAN CABRERA

Approved By: Victor Cruz

VICTORCRUZ

MICRO PRECISION CALIBRATION DE MEXICO S. DE R.L. DE C.V.

MP-FLC-004 ANAB Rev.03, Sep-10-2022

CALLE PARAISO # 1596 COLONIA DEL FRESNO GUADALAJARA, JALISCO. MEXICO C.P. 44900

(33) 3616-1555

Page 1 of 1