

# A Sample Document for the Usages of **lstEventB** Package

Thai Son Hoang  
ECS, University of Southampton  
<T dot S dot Hoang at ecs dot soton dot ac dot uk>

October 9, 2017

For convenient, we define macro `\eventB` for Event-B.

We start first with some inline Event-B code by embedding them using a pair of `|`, for example `|@grd1: "SNSR = FALSE"|` gives `@grd1: "SNSR = FALSE"`. Any Event-B formulae including Unicode symbols will be typeset using the `bsymb` package accordingly.

More complete piece of code (including the Unicode symbols) can be typeset using the `EventBcode` environment. Below is the typesetting of an Event-B machine.

---

```
1 machine Sensor_m0.SNSR
2 variables
3   SNSR
4 invariants
5   @thm0.1: "SNSR ∈ BOOL" theorem
6 events
7
8   INITIALISATION
9   begin
10     @act1: "SNSR := FALSE"
11   end
12
13   SNSR_on
14   when
15     @grd1: "SNSR = FALSE"
16   then
17     @act1: "SNSR := TRUE"
18   end
19
20   SNSR_off
21   when
22     @grd1: "SNSR = TRUE"
23   then
24     @act1: "SNSR := FALSE"
25   end
26
27 end
```

---

One can include external file containing Event-B code using the `\EventBinputlisting` command. For example the following is the result of including the code in the file `Sensor_m1_DEP.bumx` using `\EventBinputlisting{Sensor_m1_DEP.bumx}`.

```

1 machine Sensor_m1_DEP
2 refines Sensor_m0_SNSR
3 variables
4   SNSR
5   DEP
6 invariants
7   @inv0_1: "DEP ∈ ℕ"
8 events
9
10  INITIALISATION extended
11  begin
12    @act2: "DEP := 0"
13  end
14
15  SNSR_on extended
16  refines SNSR_on
17  end
18
19  SNSR_off extended
20  refines SNSR_off
21  begin
22    @act2: "DEP := DEP + 1"
23  end
24
25 end

```

More specifically, one can specify more details on the inclusion, e.g., the ranges, as the following example `\EventBinputlisting[firstline=16,lastline=20]{Sensor_m2_snsr.bumx}` gives

```

1 machine Sensor_m3_Ctrl
2
3 refines
4
5   Sensor_m2_Snsr
6
7 variables
8
9   SNSR
10
11  DEP
12
13  Snsr_01
14
15  Snsr_10
16

```

```

17  ctrl_snsr
18
19  ctrl_dep
20
21  ctrl_snsr_01
22
23  ctrl_snsr_10
24
25  invariants
26
27  @inv2_1:
28  "Snsr_01 = FALSE ∧ Snsr_10 = FALSE ∧ ctrl_snsr_01 = FALSE ∧ ctrl_snsr_10 =
    FALSE ⇒ ctrl_snsr = SNSR"
29
30  @inv2_2: "ctrl_dep ∈ ℕ"
31
32  @inv2_3: "Snsr_10 = FALSE ∧ ctrl_snsr_10 = FALSE ⇒ ctrl_dep = DEP"
33
34  @inv2_4: "Snsr_10 = TRUE ∨ ctrl_snsr_10 = TRUE ⇒ ctrl_dep = DEP 1"
35
36  @inv2_5: "ctrl_snsr_01 = TRUE ⇒ SNSR = TRUE"
37
38  @inv2_6: "ctrl_snsr_10 = TRUE ⇒ SNSR = FALSE"
39
40  @inv2_7: "ctrl_snsr_01 = TRUE ⇒ Snsr_01 = FALSE"
41
42  @inv2_8: "ctrl_snsr_10 = TRUE ⇒ Snsr_10 = FALSE"
43
44  events
45
46  INITIALISATION extended
47  refines INITIALISATION
48  begin
49    @act5: "ctrl_snsr := FALSE"
50    @act6: "ctrl_dep := 0"
51    @act7: "ctrl_snsr_01 := FALSE"
52    @act8: "ctrl_snsr_10 := FALSE"
53  end
54
55  SNSR_on extended
56  refines SNSR_on
57  when
58    @grd3: "ctrl_snsr_10 = FALSE"
59  end
60
61  SNSR_off extended
62  refines SNSR_off
63  when
64    @grd3: "ctrl_snsr_01 = FALSE"
65  end
66
67  ctrl_Senses_Snsr_01 extended
68  refines ctrl_Senses_Snsr_01
69  begin
70    @act2: "ctrl_snsr_01 := TRUE"
71  end

```

```
72
73 ctrl.Senses.Snsr_10 extended
74 refines ctrl.Senses.Snsr_10
75 begin
76   @act2: "ctrl_snsr_10 := TRUE"
77 end
78
79 ctrl_on
80 when
81   @grd1: "ctrl_snsr_01 = TRUE"
82 then
83   @act1: "ctrl_snsr_01 := FALSE"
84   @act2: "ctrl_snsr := TRUE"
85 end
86
87 ctrl_off
88 when
89   @grd1: "ctrl_snsr_10 = TRUE"
90 then
91   @act1: "ctrl_snsr_10 := FALSE"
92   @act2: "ctrl_snsr := FALSE"
93   @act3: "ctrl_dep := ctrl_dep + 1"
94 end
95
96 end
```