

Fourier Series (Part 3)

Agenda

Last time

- ▶ Exponents and Euler's Equation
- ▶ The Exponential Fourier series
- ▶ Symmetry in Exponential Fourier Series
- ▶ Example

This Time

- ▶ Line spectra
- ▶ Power in periodic signals
- ▶ Steady-state response of an LTI system to a periodic signal

Scope and Background Reading

This session concludes our introduction to Fourier Series.

Last time we saw that we could exploit the complex exponential $e^{j\omega t}$ to redefine trigonometric Fourier Series into the Exponential Fourier Series and in so doing we eliminate one integration and at the same time simplify the calculation of the coefficients of the Fourier series.

In this session we show how the Exponential form of the Fourier Series leads us to the ability to present waveforms as line spectra, simplifies the calculation of power for systems with harmonics and leads in the limit as the T approaches infinity to the Fourier Transform.

The material in this presentation and notes is based on Chapter 7 (Starting at Section 7.10) of Steven T. Karris, Signals and Systems: with Matlab Computation and Simulink Modelling, 5th Edition. from the Required Reading List. Some clarification was needed and I used Chapter 4 of Benoit Boulet, Fundamentals of Signals and Systems from the Recommended Reading List for this.

Line Spectra

Line Spectra

When the Exponential Fourier series are known it is useful to plot the amplitude and phase of the harmonics on a frequency scale.

The next slide shows the spectrum of the Exponential Fourier Series calculated for the square wave.




Figure 1: Spectrum of the Exponential Fourier Series for a Square Wave

Line Spectra for Trig. FS

If we take the results for the Exponential Fourier Series and gather terms, the amplitudes for the Trig. Fourier Series are given by:

$$a_0 = 2C_0$$

$$a_k = (C_k + C_{-k})$$

$$b_k = j(C_k - C_{-k})$$

Applying this to the previous result we get the next slide




Figure 2:Line spectra for trig. FS

Example 1

Compute the exponential Fourier series for the waveform shown below and plot its line spectra.




Figure 3:Example 1

Solution

The recurrent rectangular pulse is used extensively in digital communication systems. To determine how faithfully such pulses will be transmitted, it is necessary to know the frequency components.

What do we know?

- ▶ The pulse duration is T/w .
- ▶ The recurrence interval T is w times the pulse duration.
- ▶ w is the ratio of pulse repetition time to the pulse duration – normally called the *duty cycle*.

Coefficients of the Exponential Fourier Series?

Given

$$C_k = \frac{1}{2\pi} \int_{-\pi}^{\pi} f(t) e^{-jk(\omega t)} d(\omega t)$$

- ▶ Is the function **even** or **odd**?
- ▶ Does the signal have **half-wave symmetry**?
- ▶ What are the consequences of symmetry on the form of the coefficients C_k ?
- ▶ What function do we actually need to integrate to compute C_k ?

Answers

Given

$$C_k = \frac{1}{2\pi} \int_{-\pi}^{\pi} f(t) e^{-jk(\omega t)} d(\omega t)$$

- ▶ Is the function **even** or **odd**? **even** $f(t) = f(-t)$!
- ▶ Does the signal have **half-wave symmetry**? No!
- ▶ What are the consequences of symmetry on the form of the coefficients C_k ? C_k **will be real values. Trig. equivalent no sine terms.**
- ▶ What function do we actually need to integrate to compute C_k ?

We only need to integrate between the limits $-\pi/w \rightarrow \pi/w$

$$C_k = \frac{1}{2\pi} \int_{-\pi/w}^{\pi/w} A e^{-jk(\omega t)} d(\omega t) = \frac{A}{2\pi} \int_{-\pi/w}^{\pi/w} e^{-jk(\omega t)} d(\omega t)$$

DC Component?

Let $k = 0$ then perform the integral

Harmonic coefficients?

Integrate for $k \neq 0$

Exponential Fourier Series?

Results

$$C_0 = \frac{A}{w}$$

$$C_k = \frac{A}{w} \frac{\sin(k\pi/w)}{k\pi/w}$$


$$f(t) = \sum_{k=-\infty}^{\infty} \frac{A}{w} \frac{\sin(k\pi/w)}{k\pi/w} e^{k\omega t}$$

Effect of pulse width on frequency spectra

- ▶ Recall pulse width = T/w


$$w = 2$$

$$\omega = 1 \text{ rad/s}; w = 2; T = 2\pi \text{ s}; T/w = \pi \text{ s}.$$




$$w = 5$$

$$\omega = 1 \text{ rad/s}; w = 5; T = 2\pi \text{ s}; T/w = 2\pi/5 \text{ s}.$$



$$w = 10$$

$$\omega = 1 \text{ rad/s}; w = 10; T = 2\pi \text{ s}; T/w = \pi/5 \text{ s}.$$



Observations

- ▶ As the width of the pulse **reduces** the width of the frequency spectra needed to fully describe the signal **increases**
- ▶ more bandwidth is needed to transmit the pulse.

Example 2

Use the result of Example 1 to compute the exponential Fourier series of the impulse train $\delta(t \pm 2\pi k)$ shown below




Figure 7:Example 2

Solution

To solve this we take the previous result and choose amplitude (height) A so that area of pulse is unity. Then we let width go to zero while maintaining the area of unity. This creates a train of impulses $\delta(t \pm 2\pi k)$.

$$C_n = \frac{1}{2\pi}$$

and, therefore

$$f(t) = \frac{1}{2\pi} \sum_{k=-\infty}^{\infty} e^{jk\omega t}$$

Try it!

Pulse with unit area

The area of each pulse is then

$$2\pi \quad w$$




Figure 8:Pulses with unit area

Spectrum of Unit Impulse Train

The line spectrum of a sequence of unit impulses $\delta(t \pm kT)$ is shown below:




Figure 9: Spectrum of unit pulse train

Another Interesting Result

Consider the pulse train again:




Figure 10: Another interesting result

What happens when the pulses to the left and right of the centre pulse become less and less frequent? That is what happens when $T \rightarrow \infty$?

Well?

- ▶ As $T \rightarrow \infty$ the fundamental frequency $\omega \rightarrow 0$
- ▶ We are then left with just one pulse centred around $t = 0$.
- ▶ The frequency difference between harmonics also becomes smaller.
- ▶ Line spectrum becomes a continuous function.

This result is the basis of the *Fourier Transform* which is coming next.

Power in Periodic Signals

Power in Periodic Signals

In your previous courses you may have come across the definitions of Signal Energy, Average Signal Power and Root Mean Square Power:

$$E = \int_0^T |f(t)|^2 dt$$

$$P_{\text{av}} = \frac{1}{T} \int_0^T |f(t)|^2 dt$$

$$P_{\text{RMS}} = \sqrt{\frac{1}{T} \int_0^T |f(t)|^2 dt}$$

Parseval's Theorem

Parseval's Theorem states that the total average power of a periodic signal $f(t)$ is equal to the sum of the average powers of all its harmonic components.

The power in the k th harmonic $C_k e^{jk\omega t}$ is given by

$$P_k = \frac{1}{T} \int_0^T |C_k e^{jk\omega t}|^2 dt = \frac{1}{T} \int_0^T |C_k|^2 dt = |C_k|^2$$

Since $P_k = P_{-k}$, the total power of the k th harmonic is $2P_k$.

Parseval's theorem states that

$$P = \frac{1}{T} \int_0^T |f(t)|^2 dt = \sum_{k=-\infty}^{\infty} |C_k|^2.$$

RMS Power

By a similar argument:

$$P_{\text{RMS}} = \sqrt{\frac{1}{T} \int_0^T |f(t)|^2 dt} = \sqrt{\sum_{k=-\infty}^{\infty} |C_k|^2}.$$

Example 3

Compute the average power of a pulse train for which the pulse width is $T/2$ (duty cycle 50%). Use the previous result:

$$C_n = \frac{A}{w} \cdot \frac{\sin(k\pi/w)}{k\pi/w}$$

as your starting point.

Power Spectrum

The *power spectrum* of signal is the sequence of average powers in each complex harmonic: $|C_k|^2$. For real periodic signals the power spectrum is a real even sequence as $|C_{-k}|^2 = |C_k^*|^2 = |C_k|^2$.

This is the power spectrum for a pulse with width $T/8$.





Figure 11: Power spectrum

Total Harmonic Distortion

Suppose that a signal that is supposed to be a pure sine wave of amplitude A is distorted as shown below



THD Defined

Clearly, some of the harmonics for $k \neq \pm 1$ are nonzero. One way to characterize the distortion is to compute the ratio of average power in all the harmonics that “should not be present”, that is for $k > 1$, to the total average power of the distorted sine wave. The square-root of this ratio is called the *total harmonic distortion* (THD) of the signal.

If the signal is real and based on a sine wave (that is *odd*), then $C_0 = 0$ and

$$f_{\text{RMS}} = \sqrt{\sum_{k=1}^{\infty} 2|C_k|^2}$$

and we can define the THD as the ratio of the RMS value for all the harmonics for $K > 1$ (the distortion) to the RMS of the fundamental which is $\sqrt{2|C_1|^2}$:

$$\text{THD} = 100 \sqrt{\frac{\sum_{k=2}^{\infty} |C_k|^2}{|C_1|^2}} \%$$

Computation of THD




Figure 13: Computation of THD

Steady-State Response of an LTI System to a Periodic Signal

Steady-State Response of an LTI System to a Periodic Signal

The response of an LTI system with impulse response $h(t)$ to a complex exponential signal e^{st} is the same complex exponential multiplied by a complex gain: $y(t) = H(s)e^{st}$, where:

$$H(s) = \int_{-\infty}^{\infty} h(\tau)e^{-s\tau} d\tau.$$

In particular, for $s = j\omega$, the output is simply $y(t) = H(j\omega)e^{j\omega t}$.

The complex functions $H(s)$ and $H(j\omega)$ are called the system's *transfer function* and *frequency response*, respectively.

By superposition

The output of an LTI system to a periodic function with period T represented by a Fourier series is given by:

$$y(t) = \sum_{k=-\infty}^{\infty} C_k H(jk\omega_0) e^{jk\omega_0 t}$$

where $\omega_0 = T/2\pi$ is the fundamental frequency.

Thus $y(t)$ is a Fourier series itself with coefficients D_k :

$$D_k = C_k H(jk\omega_0)$$

Implications of this important result

The effect of an LTI system on a periodic input signal is to modify its Fourier series through a multiplication by its frequency response evaluated at the harmonic frequencies.

Illustration

This picture below shows the effect of an LTI system on a periodic input in the frequency domain.




Figure 14: Illustration - system operating as a filter

Filtering

A consequence of the previous result is that we can design a system that has a desirable frequency spectrum $H(jk\omega_0)$ that retains certain frequencies and cuts off others.

We will return to this idea later.

End of Part 3

Summary

- ▶ Line spectra
- ▶ Power in periodic signals
- ▶ Steady-state response of an LTI system to a periodic signal

Next Time

- ▶ The Fourier Transform

Home work

Compute the exponential Fourier series of a full-wave requified sinusoid. Give the power spectrum for this signal and estimate the total harmonic distortion for the first 7 harmonics.

Lab Work

In the lab we will continue to explore Fourier Series and their applications