

Package ‘rpostgis’

June 14, 2016

Version 0.7

Date 2016-01-05

Title PostGIS and PostgreSQL related functions

Description This package provides additional functions to the RPostgreSQL package, mostly convenient wrappers, with some PostGIS oriented functions.

Author Mathieu Basille, David Bucklin

Maintainer David Bucklin <david.bucklin@gmail.com>

Depends raster,
rgeos,
RPostgreSQL,
sp

License GPL (>= 3)

URL <http://ase-research.org/basille/rpostgis>

RoxygenNote 5.0.1

R topics documented:

pgAddKey	2
pgAsDate	3
pgColumn	3
pgColumnInfo	4
pgComment	5
pgDrop	6
pgGetBoundary	7
pgGetLines	8
pgGetPolys	9
pgGetPts	10
pgGetRast	11
pgIndex	12
pgInsert	13
pgInsertize	14
pgInsertizeGeom	15
pgMakePts	16
pgSchema	18
pgVacuum	18
rpostgis	19
Index	20

`pgAddKey`*Add key*

Description

Add a primary or foreign key to a table column.

Usage

```
pgAddKey(conn, name, colname, type = c("primary", "foreign"), reference,  
         colref, display = TRUE, exec = TRUE)
```

Arguments

<code>conn</code>	A connection object.
<code>name</code>	A character string specifying a PostgreSQL table name.
<code>colname</code>	A character string specifying the name of the column to which the key will be assign.
<code>type</code>	The type of the key, either primary or foreign
<code>reference</code>	A character string specifying a foreign table name to which the foreign key will be associated.
<code>colref</code>	A character string specifying the name of the primary key in the foreign table to which the foreign key will be associated.
<code>display</code>	Logical. Whether to display the query (defaults to TRUE).
<code>exec</code>	Logical. Whether to execute the query (defaults to TRUE).

Author(s)

Mathieu Basille <basille@ase-research.org>

See Also

The PostgreSQL documentation: <http://www.postgresql.org/docs/current/static/sql-altertable.html>

Examples

```
pgAddKey(name = c("fla", "bli"), colname = "id", type = "foreign",  
         reference = c("flu", "bla"), colref = "id", exec = FALSE)
```

pgAsDate	<i>Converts to timestamp</i>
----------	------------------------------

Description

Convert a date field to a timestamp with or without time zone.

Usage

```
pgAsDate(conn, name, date = "date", tz = NULL, display = TRUE,  
         exec = TRUE)
```

Arguments

conn	A connection object.
name	A character string specifying a PostgreSQL table name.
date	A character string specifying the date field.
tz	A character string specifying the time zone, in "EST", "America/New_York", "EST5EDT", "-5".
display	Logical. Whether to display the query (defaults to TRUE).
exec	Logical. Whether to execute the query (defaults to TRUE).

Author(s)

Mathieu Basille <basille@ase-research.org>

See Also

The PostgreSQL documentation: <http://www.postgresql.org/docs/current/static/datatype-datetime.html>

Examples

```
pgAsDate(name = c("fla", "bli"), date = "date", tz = "GMT", exec = FALSE)
```

pgColumn	<i>Add or remove a column</i>
----------	-------------------------------

Description

Add or remove a column to/from a table.

Usage

```
pgColumn(conn, name, colname, action = c("add", "drop"),  
         coltype = "integer", cascade = FALSE, display = TRUE, exec = TRUE)
```

Arguments

conn	A connection object.
name	A character string specifying a PostgreSQL table name.
colname	A character string specifying the name of the column to which the key will be associated.
action	A character string specifying if the column is to be added ("add", default) or removed ("drop").
coltype	A character string indicating the type of the column, if action = "add".
cascade	Logical. Whether to drop foreign key constraints of other tables, if action = "drop".
display	Logical. Whether to display the query (defaults to TRUE).
exec	Logical. Whether to execute the query (defaults to TRUE).

Author(s)

Mathieu Basille <basille@ase-research.org>

See Also

The PostgreSQL documentation: <http://www.postgresql.org/docs/current/static/sql-altertable.html>

Examples

```
## Add an integer column
pgColumn(name = c("fla", "bli"), colname = "field", exec = FALSE)
## Drop a column (with CASCADE)
pgColumn(name = c("fla", "bli"), colname = "field", action = "drop",
         cascade = TRUE, exec = FALSE)
```

pgColumnInfo

Get information about columns in a PostgreSQL table.

Description

Get information about columns in a PostgreSQL table.

Usage

```
pgColumnInfo(conn, name, allinfo = FALSE)
```

Arguments

conn	A connection object to a PostgreSQL database
name	A character string specifying a PostgreSQL schema (if necessary), and table or view name geometry (e.g., name = c("schema","table"))
allinfo	logical, Get all information on table? Default is column names, types, nullable, and maximum length of character columns

Value

data frame

Author(s)

David Bucklin <david.bucklin@gmail.com>

Examples

```
## Not run:

library(RPostgreSQL)
drv<-dbDriver("PostgreSQL")
conn<-dbConnect(drv, dbname='dbname', host='host', port='5432',
               user='user', password='password')
pgColumnInfo(conn, c("schema", "table"))

## End(Not run)
```

pgComment

Comment table/view/schema

Description

Comment on a table, a view or a schema.

Usage

```
pgComment(conn, name, comment, type = c("table", "view", "schema"),
          display = TRUE, exec = TRUE)
```

Arguments

conn	A connection object.
name	A character string specifying a PostgreSQL table, view or schema name.
comment	A character string specifying the comment.
type	The type of the object to comment, either table or view
display	Logical. Whether to display the query (defaults to TRUE).
exec	Logical. Whether to execute the query (defaults to TRUE).

Author(s)

Mathieu Basille <basille@ase-research.org>

See Also

The PostgreSQL documentation: <http://www.postgresql.org/docs/current/static/sql-comment.html>

Examples

```
pgComment(name = c("fla", "bli"), comment = "Comment on a view.",
          type = "view", exec = FALSE)
pgComment(name = "fla", comment = "Comment on a schema.", type = "schema",
          exec = FALSE)
```

pgDrop	<i>Drop table/view/schema</i>
--------	-------------------------------

Description

Drop a table, a view or a schema.

Usage

```
pgDrop(conn, name, type = c("table", "view", "schema"), ifexists = FALSE,
       cascade = FALSE, display = TRUE, exec = TRUE)
```

Arguments

conn	A connection object.
name	A character string specifying a PostgreSQL table, view or schema name.
type	The type of the object to comment, either table or view
ifexists	Do not throw an error if the table does not exist. A notice is issued in this case.
cascade	Automatically drop objects that depend on the table (such as views).
display	Logical. Whether to display the query (defaults to TRUE).
exec	Logical. Whether to execute the query (defaults to TRUE).

Author(s)

Mathieu Basille <basille@ase-research.org>

See Also

The PostgreSQL documentation: <http://www.postgresql.org/docs/current/static/sql-droptable.html>, <http://www.postgresql.org/docs/current/static/sql-dropview.html>, <http://www.postgresql.org/docs/current/static/sql-dropschema.html>

Examples

```
pgDrop(name = c("fla", "bli"), type = "view", exec = FALSE)
pgDrop(name = "fla", type = "schema", cascade = "TRUE", exec = FALSE)
```

pgGetBoundary	Returns bounding envelope of all combined geometries or rasters stored in a table in a PostgreSQL database.
---------------	---

Description

Retrieve bounding envelope (rectangle) of all geometries or rasters in a table in Postgresql.

Usage

```
pgGetBoundary(conn, name, geom = "geom")
```

Arguments

conn	A connection object to a PostgreSQL database
name	A character string specifying a PostgreSQL schema (if necessary), and table or view name for the table holding the geometries/raster(s) (e.g., name = c("schema","table"))
geom	character, Name of the column in 'name' holding the geometry or raster object (Default = 'geom')

Value

SpatialPolygon

Author(s)

David Bucklin <david.bucklin@gmail.com>

Examples

```
## Not run:
library(RPostgreSQL)
drv<-dbDriver("PostgreSQL")
conn<-dbConnect(drv,dbname='dbname',host='host',port='5432',
                user='user',password='password')

pgGetBoundary(conn,c('schema','polys'),geom = 'polygon')
pgGetBoundary(conn,c('schema','rasters'),geom='rast')

## End(Not run)
```

pgGetLines

Load a linestring geometry stored in a PostgreSQL database into R.

Description

Retrieve line geometries from a PostGIS table, and convert it to a SpatialLines or a SpatialLines-DataFrame.

Usage

```
pgGetLines(conn, name, geom = "geom", gid = NULL, other.cols = "*",
  query = NULL)
```

Arguments

conn	A connection object to a PostgreSQL database
name	A character string specifying a PostgreSQL schema (if necessary), and table or view name for the table holding the lines geometry (e.g., name = c("schema","table"))
geom	character, Name of the column in 'name' holding the geometry object (Default = 'geom')
gid	character, Name of the column in 'name' holding the ID for each line. Should be unique if additional columns of unique data are being appended. gid=NULL (default) automatically creates a new unique ID for each row in the table.
other.cols	character, names of additional columns from table (comma-seperated) to append to dataset (Default is all columns, NULL returns a SpatialLines object)
query	character, additional SQL to append to modify select query from table

Value

SpatialLinesDataFrame or SpatialLines

Author(s)

David Bucklin <david.bucklin@gmail.com>

Examples

```
## Not run:
library(RPostgreSQL)
drv<-dbDriver("PostgreSQL")
conn<-dbConnect(drv,dbname='dbname',host='host',port='5432',
  user='user',password='password')

pgGetLines(conn,c('schema','tablename'))
pgGetLines(conn,c('schema','roads'),geom='roadgeom',gid='road_ID',
  other.cols=NULL, query = "AND field = \'highway\'")

## End(Not run)
```


pgGetPolys

*Load a polygon geometry stored in a PostgreSQL database into R.***Description**

Retrieve polygon geometries from a PostGIS table, and convert it to a SpatialPolygons or a SpatialPolygonsDataFrame.

Usage

```
pgGetPolys(conn, name, geom = "geom", gid = NULL, other.cols = "*",
  query = NULL)
```

Arguments

conn	A connection object to a PostgreSQL database
name	A character string specifying a PostgreSQL schema (if necessary), and table or view name for the table holding the polygon geometry (e.g., name = c("schema", "table"))
geom	character, Name of the column in 'name' holding the geometry object (Default = 'geom')
gid	character, Name of the column in 'name' holding the ID for each polygon geometry. Should be unique if additional columns of unique data are being appended. gid=NULL (default) automatically creates a new unique ID for each row in the table.
other.cols	character, names of additional columns from table (comma-seperated) to append to dataset (Default is all columns, other.cols=NULL returns a SpatialPolygons object)
query	character, additional SQL to append to modify select query from table

Value

SpatialPolygonsDataFrame or SpatialPolygons

Author(s)

David Bucklin <david.bucklin@gmail.com>

Examples

```
## Not run:
library(RPostgreSQL)
drv<-dbDriver("PostgreSQL")
conn<-dbConnect(drv, dbname='dbname', host='host', port='5432',
  user='user', password='password')

pgGetPolys(conn, c('schema', 'tablename'))
pgGetPolys(conn, c('schema', 'states'), geom='statesgeom', gid='state_ID',
  other.cols='area, population',
  query = "AND area > 1000000 ORDER BY population LIMIT 10")

## End(Not run)
```

pgGetPts

*Retrieve point geometries***Description**

Retrieve point geometries from a PostGIS table, and convert it to a SpatialPoints or a SpatialPointsDataFrame.

Usage

```
pgGetPts(conn, name, geom = "geom", gid = NULL, other.cols = "*",
         query = NULL)
```

Arguments

conn	A connection object to a PostgreSQL database
name	A character string specifying a PostgreSQL schema (if necessary), and table or view name for the table holding the points geometry (e.g., name = c("schema","table"))
geom	The name of the point geometry column. (Default = 'geom')
gid	Name of the column in 'name' holding the ID. Should be unique if additional columns of unique data are being appended. gid=NULL (default) automatically creates a new unique ID for each row in the table.
other.cols	Names of specific columns in the table to retrieve, comma seperated in one character element (e.g. other.cols='col1,col2'. The default is to attach all columns in a SpatialPointsDataFrame. Setting other.cols=NULL will return a SpatialPoints.
query	character, additional SQL to append to modify select query from table

Value

A Spatial(Multi)Points or a Spatial(Multi)PointsDataFrame

Author(s)

David Bucklin <david.bucklin@gmail.com>
Mathieu Basille <basille@ase-research.org>

Examples

```
## Not run:
## Retrieve a SpatialPointsDataFrame with all data from table 'schema.tablename',
## with geometry in the column 'geom'
pgGetPts(conn, c('schema','tablename'))
## Return a SpatialPointsDataFrame with columns c1 & c2 as data
pgGetPts(conn, c('schema','tablename'), other.cols = 'c1,c2')
## Return a SpatialPoints, retaining id from table as rownames
pgGetPts(conn, c('schema','tablename'), gid = 'table_id', other.cols = FALSE)

## End(Not run)
```

pgGetRast

*Load a raster stored in a PostgreSQL database into R.***Description**

Retrieve rasters from a PostGIS table

Usage

```
pgGetRast(conn, name, rast = "rast", digits = 9, boundary = NULL)
```

Arguments

conn	A connection object to a PostgreSQL database
name	A character string specifying a PostgreSQL schema (if necessary), and table or view name for the table holding the raster (e.g., name = c("schema","table"))
rast	Name of the column in 'name' holding the raster object
digits	numeric, precision for detecting whether points are on a regular grid (a low number of digits is a low precision) - From rasterFromXYZ function (raster package)
boundary	sp object or numeric. A Spatial* object, whose bounding box will be used to select the part of the raster to import. Alternatively, four numbers (e.g. c(north, south, east, west)) indicating the projection-specific limits with which to clip the raster. NULL (default) will return the full raster.

Value

RasterLayer

Author(s)

David Bucklin <david.bucklin@gmail.com>

Examples

```
## Not run:
library(RPostgreSQL)
drv<-dbDriver("PostgreSQL")
conn<-dbConnect(drv,dbname='dbname',host='host',port='5432',
                user='user',password='password')

pgGetRast(conn,c('schema','tablename'))
pgGetRast(conn,c('schema','DEM'),digits=9,
          boundary=c(55,50,17,12))

## End(Not run)
```

pgIndex

*CREATE INDEX***Description**

Defines a new index.

Usage

```
pgIndex(conn, name, colname, idxname, unique = FALSE, method = c("btree",
    "hash", "rtree", "gist"), display = TRUE, exec = TRUE)
```

Arguments

conn	A connection object.
name	A character string specifying a PostgreSQL table name.
colname	A character string specifying the name of the column to which the key will be associated.
idxname	A character string specifying the name of the index to be created. By default, this is the name of the table (without the schema) suffixed by <code>_idx</code> .
unique	Logical. Causes the system to check for duplicate values in the table when the index is created (if data already exist) and each time data is added. Attempts to insert or update data which would result in duplicate entries will generate an error.
method	The name of the method to be used for the index. Choices are "btree", "hash", "rtree", and "gist". The default method is btree.
display	Logical. Whether to display the query (defaults to TRUE).
exec	Logical. Whether to execute the query (defaults to TRUE).

Author(s)

Mathieu Basille <basille@ase-research.org>

See Also

The PostgreSQL documentation: <http://www.postgresql.org/docs/current/static/sql-createindex.html>; the PostGIS documentation for GiST indexes: http://postgis.net/docs/using_postgis_dbmanagement.html#id541286

Examples

```
pgIndex(name = c("fla", "bli"), colname = "wkb_geometry", method = "gist",
    exec = FALSE)
```

pgInsert	<i>Inserts data from a pgInsertize* object into a PostgreSQL table</i>
----------	--

Description

Inserts data from a pgInsertize* object into a PostgreSQL table

Usage

```
pgInsert(conn, pgi, name = NULL, encoding = NULL)
```

Arguments

conn	A connection object to a PostgreSQL database
pgi	The output PostgreSQL insert object (pgi) created by pgInsertize() or pgInsertizeGeom()
name	character strings specifying a PostgreSQL schema and table name to insert into (e.g., name = c("schema", "table")). If table was specified in the pgInsertize* through create.table or force.match, leave this NULL.
encoding	Character vector of length 2, containing the from/to encodings for the data (as in the function iconv. For example, if your dataset contain certain latin characters (e.g., accent marks), and the database is in UTF-8, use encoding = c("latin1", "UTF-8"). Left NULL, no conversion will be done.

Value

DBIResult

Author(s)

David Bucklin <david.bucklin@gmail.com>

Examples

```
library(sp)
data(meuse)
coords <- SpatialPoints(meuse[, c("x", "y")])
spdf<- SpatialPointsDataFrame(coords, meuse)

#remove "." from column name
colnames(spdf@data)[colnames(spdf@data) == 'dist.m']<-"dist_m"

#format data for insert
pgi<-pgInsertizeGeom(spdf,geom="point")

## Not run:
library(RPostgreSQL)
drv<-dbDriver("PostgreSQL")
conn<-dbConnect(drv,dbname='dbname',host='host',port='5432',
                user='user',password='password')
```

```
# insert data in database table (note that an error will be given if
# all insert columns do not match exactly to database table columns)
pgInsert(conn,c("schema","meuse_data"),pgi=pgi)

## End(Not run)
```

pgInsertize	<i>Formats an R data frame for insert into a PostgreSQL table (for use with pgInsert)</i>
-------------	---

Description

Formats an R data frame for insert into a PostgreSQL table (for use with pgInsert)

Usage

```
pgInsertize(df, create.table = NULL, force.match = NULL, conn = NULL)

## S3 method for class 'pgi'
print(pgi)
```

Arguments

df	A data frame
create.table	character, schema and table of the PostgreSQL table to create (actual table creation will be done in later in pgInsert().) Column names will be converted to PostgreSQL-compliant names. Default is NULL (no new table created).
force.match	character, schema and table of the PostgreSQL table to compare columns of data frame with If specified, only columns in the data frame that exactly match the database table will be kept, and reordered to match the database table. Default is NULL (all columns names will be kept, and in the same order given in the data frame.)
conn	A database connection (required if a table is given in for "force.match" parameter)
object	A list of class pgi, output from the pgInsertize() or pgInsertizeGeom() functions from the rpostgis package.

Value

pgi object, a list containing four character strings- (1) in.table, the table name which will be created or inserted into, if specified by either create.table or force.match, (2) db.new.table, the SQL statement to create the new table, if specified in create.table, (3) db.cols.insert, a character string of the database column names to make inserts on, and (4) insert.data, a character string of the data to insert. See examples for usage within the pgInsert function.

Author(s)

David Bucklin <david.bucklin@gmail.com>

Examples

```
## Not run:
#connect to database
library(RPostgreSQL)
drv<-dbDriver("PostgreSQL")
conn<-dbConnect(drv,dbname='dbname',host='host',port='5432',
                user='user',password='password')

## End(Not run)

data<-data.frame(a=c(1,2,3),b=c(4,NA,6),c=c(7,'text',9))

#format all columns for insert
values<-pgInsertize(df=data)

## Not run:
# insert data in database table (note that an error will be given if all insert columns
# do not match exactly to database table columns)
pgInsert(conn,c("schema","table"),pgi=values)

##
#run with forced matching of database table column names
values<-pgInsertize(df=data,force.match=c("schema","table"),conn=conn)

pgInsert(conn,c("schema","table"),pgi=values)

## End(Not run)
```

pgInsertizeGeom	<i>Formats an R Spatial*DataFrame for insert (with geometry) into a PostgreSQL table (for use with pgInsert).</i>
-----------------	---

Description

Formats an R Spatial*DataFrame for insert (with geometry) into a PostgreSQL table (for use with pgInsert).

Usage

```
pgInsertizeGeom(sdf, geom = "geom", multi = FALSE, force.match = NULL,
               conn = NULL)

## S3 method for class 'pgi'
print(pgi)
```

Arguments

sdf	A Spatial*DataFrame
geom	character string, the name of geometry column in the database table. (defaults to 'geom')
multi	Logical, if PostGIS geometry column is of Multi* type set to TRUE

force.match	character, schema and table of the PostgreSQL table to compare columns of data frame with. If specified, only columns in the data frame that exactly match the database table will be kept, and reordered to match the database table. If NULL, all columns will be kept in the same order given in the data frame.
conn	A database connection (if a table is given in for "force.match" parameter)
object	A list of class <code>pgi</code> , output from the <code>pgInsertize()</code> or <code>pgInsertizeGeom()</code> functions from the <code>rpostgis</code> package.

Value

List containing two character strings- (1) `db.cols.insert`, a character string of the database column names to make inserts on, and (2) `insert.data`, a character string of the data to insert. See examples for usage within the `pgInsert` function.

Author(s)

David Bucklin <david.bucklin@gmail.com>

Examples

```
library(sp)
data(meuse)
coords <- SpatialPoints(meuse[, c("x", "y")])
spdf<- SpatialPointsDataFrame(coords, meuse)

#remove "." from column name
colnames(spdf@data)[colnames(spdf@data) == 'dist.m']<-"dist_m"

#format data for insert
pgi<-pgInsertizeGeom(spdf,geom="point_geom")

## Not run:

library(RPostgreSQL)
drv<-dbDriver("PostgreSQL")
conn<-dbConnect(drv,dbname='dbname',host='host',port='5432',
                user='user',password='password')

# insert data in database table (note that an error will be given if all
# insert columns do not match exactly to database table columns)
pgInsert(conn,c("schema","meuse_data"),pgi=pgi)

## End(Not run)
```

pgMakePts

Add a POINT or LINESTRING geometry field.

Description

Add a new POINT or LINESTRING geometry field.

Usage

```
pgMakePts(conn, name, colname = "pts_geom", x = "x", y = "y", srid,
          index = TRUE, display = TRUE, exec = TRUE)
```

```
pgMakeStp(conn, name, colname = "stp_geom", x = "x", y = "y", dx = "dx",
          dy = "dy", srid, index = TRUE, display = TRUE, exec = TRUE)
```

Arguments

conn	A connection object.
name	A character string specifying a PostgreSQL table name.
colname	A character string specifying the name of the new geometry column.
x	The name of the x/longitude field.
y	The name of the y/latitude field.
srid	A valid SRID for the new geometry.
index	Logical. Whether to create an index on the new geometry.
display	Logical. Whether to display the query (defaults to TRUE).
exec	Logical. Whether to execute the query (defaults to TRUE).
dx	The name of the dx field (i.e. increment in x direction).
dy	The name of the dy field (i.e. increment in y direction).

Author(s)

Mathieu Basille <basille@ase-research.org>

See Also

The PostGIS documentation for ST_MakePoint: http://postgis.net/docs/ST_MakePoint.html, and for ST_MakeLine: http://postgis.net/docs/ST_MakeLine.html, which are the main functions of the call.

Examples

```
## Create a new POINT field called "pts_geom"
pgMakePts(name = c("fla", "bli"), x = "longitude", y = "latitude",
          srid = 4326, exec = FALSE)

## Create a new LINESTRING field called "stp_geom"
pgMakeStp(name = c("fla", "bli"), x = "longitude", y = "latitude",
          dx = "xdiff", dy = "ydiff", srid = 4326, exec = FALSE)
```

pgSchema	<i>Create schema</i>
----------	----------------------

Description

Create a schema.

Usage

```
pgSchema(conn, name, display = TRUE, exec = TRUE)
```

Arguments

conn	A connection object.
name	A character string specifying a PostgreSQL schema name.
display	Logical. Whether to display the query (defaults to TRUE).
exec	Logical. Whether to execute the query (defaults to TRUE).

Author(s)

Mathieu Basille <basille@ase-research.org>

See Also

The PostgreSQL documentation: <http://www.postgresql.org/docs/current/static/sql-createschema.html>

Examples

```
pgSchema(name = "schema", exec = FALSE)
```

pgVacuum	<i>VACUUM</i>
----------	---------------

Description

Performs a VACUUM (garbage-collect and optionally analyze) on a table.

Usage

```
pgVacuum(conn, name, full = FALSE, verbose = FALSE, analyze = TRUE,  
display = TRUE, exec = TRUE)
```

Arguments

conn	A connection object.
name	A character string specifying a PostgreSQL table name.
full	Logical. Whether to perform a "full" vacuum, which can reclaim more space, but takes much longer and exclusively locks the table.
verbose	Logical. Whether to print a detailed vacuum activity report for each table.
analyze	Logical. Whether to update statistics used by the planner to determine the most efficient way to execute a query (default to TRUE).
display	Logical. Whether to display the query (defaults to TRUE).
exec	Logical. Whether to execute the query (defaults to TRUE).

Author(s)

Mathieu Basille <basille@ase-research.org>

See Also

The PostgreSQL documentation: <http://www.postgresql.org/docs/current/static/sql-vacuum.html>

Examples

```
pgVacuum(name = c("fla", "bli"), full = TRUE, exec = FALSE)
```

rpostgis

PostGIS and PostgreSQL functions

Description

rpostgis

Details

This package provides additional functions to the RPostgreSQL package, mostly convenient wrappers to PostgreSQL queries, with some PostGIS oriented functions. For a list of documented functions, use `library(help = "rpostgis")`

Author(s)

Mathieu Basille <basille@ase-research.org>

Index

`pgAddKey`, [2](#)
`pgAsDate`, [3](#)
`pgColumn`, [3](#)
`pgColumnInfo`, [4](#)
`pgComment`, [5](#)
`pgDrop`, [6](#)
`pgGetBoundary`, [7](#)
`pgGetLines`, [8](#)
`pgGetPolys`, [9](#)
`pgGetPts`, [10](#)
`pgGetRast`, [11](#)
`pgIndex`, [12](#)
`pgInsert`, [13](#)
`pgInsertize`, [14](#)
`pgInsertizeGeom`, [15](#)
`pgMakePts`, [16](#)
`pgMakeStp` (`pgMakePts`), [16](#)
`pgSchema`, [18](#)
`pgVacuum`, [18](#)
`print.pgi` (`pgInsertizeGeom`), [15](#)
`print.pgi` (`pgInsertize`), [14](#)

`rpostgis`, [19](#)
`rpostgis-package` (`rpostgis`), [19](#)