Databricks Lakehouse Bootcamp

Databricks SQL Student Workbook

Working with APJuice Data


As part of this workshop section, we will be working with simulated APJuice data derived from retail juice stores across multiple cities in ANZ. We will use two key fact tables and 3 dimension tables to visualize data curated as part of the Data Modelling exercise completed earlier. Ultimately, we want to create a dashboard that can be used by our business to view the status of the APJuice business in ANZ.

- Make sure to run these notebooks in <u>Lab 02 SQL</u> folder:
 - 01 Data Setup
 - 02 Data Modeling: Note you're <database_name> from Cmd 5. You will need to replace the <database_name> in the queries below if you do not write your own.

Run Queries and Create Visualizations

Step 1: Access Databricks SQL

- 1. Click the persona navigator on the top left and select 'SQL'.
- 2. Tap the 'Queries' icon in the sidebar.
- 3. Click the 'New Query' button.
- 4. Your SQL endpoint should already be selected. If it is not, please use the menu to select an appropriate SQL endpoint.
- 5. In the schema browser panel select the database used as part of the earlier Data Modelling exercise (this database will be your username followed by ap_juice_db_dbsql).



Step 2: Build your Orders Master queries

Please note: If you are working in a shared workspace. In this step, you will create and save a query appearing in the shared Databricks workspace. To avoid confusion, please **prepend** the saved name of any query with your initials and any 3-digit number. For example, Han Solo might name his saved query: **hs130 Orders Master**. Later, you can then use the search functionality to identify your queries.

We can start to do some analysis on orders by country and city.

- Name this query 'Orders Master'. Don't forget to prepend that name with the identifier you chose using the pattern in the note above if in a shared workspace.
- Write a query to join apj_sales_fact table with dim_store_locations table. Use the editor and the schema browser to try writing your own query to accomplish this, **or** copy and paste the following code into the editor (make sure to replace **'deepak_sekar_ap_juice_db'** with the relevant database name derived as part of Step 1). Execute the query.

```
select
 a.store id,
 a.order source,
 a.order state,
 b.city,
 b.country code,
 b.name as store name,
 count(*) as cnt
from
  deepak sekar ap juice db.apj sales fact a
  join deepak sekar ap juice db.dim store locations b
on a.slocation skey = b.slocation skey
group by
 a.store id,
 a.order source,
 a.order state,
 b.city,
 b.country code,
 b.name
```


Your table should look like this:

store_id	order_source	order_state	city	country_code	store_name	cnt
MEL01	ONLINE	COMPLETED	Melbourne	AUS	Melbourne CBD	4509
AKL02	ONLINE	CANCELED	Auckland	NZL	Auckland CBD	186
SYD01	IN-STORE	CANCELED	Sydney	AUS	Sydney CBD	13838
AKL02	IN-STORE	CANCELED	Auckland	NZL	Auckland CBD	4353
WLG01	ONLINE	CANCELED	Wellington	NZL	Wellington CBD	337
SYD01	ONLINE	PENDING	Sydney	AUS	Sydney CBD	1584
AKL02	IN-STORE	PENDING	Auckland	NZL.	Auckland CBD	4561
PER01	IN-STORE	COMPLETED	Perth	AUS	Perth CBD	60275
AKL01	ONLINE	COMPLETED	Auckland	NZL	Auckland Airport	1330
WLG01	ONLINE	PENDING	Wellington	NZL	Wellington CBD	467
AKL01	ONLINE	CANCELED	Auckland	NZL 1	Auckland Airport 2 3 >	239


Step 3: Add 4 Visualizations

- Click the 'Add Visualization' button for every time you want to create a new visualization and then create the following 4 visualizations.
- Make sure to go to the Data Labels tab in the visualization panel and turn on "Show Data Labels" for every visualization you create.
- Save every visualization with an appropriate name, as indicated in the screenshots below.


Orders by Country




Order State by Country



Orders by City



Order State by City



Step 4: Build your Products Master queries

Please note: If you are working in a shared workspace. In this step, you will create and save a query appearing in the shared Databricks workspace. To avoid confusion, please **prepend** the saved name of any query with your initials and any 3-digit number. For example, Han Solo might name his saved query: **hs130 Orders Master**. Later, you can then use the search functionality to identify your queries.

١

We can start to do some analysis on orders by country and city.

- Name this query Products Master'. Don't forget to prepend that name with the identifier you chose using the pattern in the note above.
- Write a query to join apj_sales_fact table with dim_store_locations table. Use the editor and the schema browser to try writing your own query to accomplish this, **or** copy and paste the following code into the editor (make sure to replace **'deepak_sekar_ap_juice_db'** with the relevant database name derived as part of Step 1). Execute the query.

```
select
 b.city,
 b.country code,
 b.name as store name,
  a.product size,
  c.name as product name,
  count(*) as cnt,
  sum(product cost) as total product cost
from
  deepak sekar ap juice db.apj sale items fact a
  join deepak sekar ap juice db.dim store locations b
on a.slocation skey = b.slocation skey
  join deepak sekar ap juice db.dim products c on a.product skey
= c.product skey
where
  a.unique customer id is not null
  and b.current record = 'Y'
  and c.current record = 'Y'
group by
 b.city,
 b.country code,
 b.name,
  a.product size,
  c.name
```


Your table should look like this:

city	country_code	store_name	product_size	product_name	cnt	total_product_cost
Wellington	NZL	Wellington CBD	Large	Justified	1428	12852.00
Wellington	NZL	Wellington CBD	Medium	Fit Drink	1401	9807.00
Sydney	AUS	Sydney CBD	Small	Fruit Warehouse	3128	15640.00
Auckland	NZL	Auckland Airport	Small	Drink Your Vitamins	850	4250.00
Wellington	NZL	Wellington CBD	Medium	Packed Punch	1407	9849.00
Auckland	NZL	Auckland CBD	Large	Fit Fuel	1177	10593.00
Melbourne	AUS	Melbourne Airport	Small	Jumpstart	304	1520.00
Canberra	AUS	Canberra Airport	Small	Craze	548	2740.00
Perth	AUS	Perth CBD	Large	Nothing To Lose	1501	13509.00
Perth	AUS	Perth CBD	Small	Jungle	1613	8065.00
Canberra	AUS	Canberra Airport	Large	Get Clean	580	5220.00
Sydney	AUS	Sydney CBD	Small	Power Punch	3074	15370.00
Sydney	AUS	Sydney CBD	Large	Fit Fuel	3100	27900.00
			1	2 3 4 5	40 >	


Step 5: Add 2 Visualizations

- Click the 'Add Visualization' button for every time you want to create new visualization and then create the following 2 visualizations.
- Make sure to go to the Data Labels tab in the visualization panel and turn on "Show Data Labels" for every visualization you create.
- Save every visualization with an appropriate name as indicated in the screenshots below.

Product Size by Country



Product Size by City



Create and Customize Your Dashboard

Now, let's work on building our dashboard so that we can share our visualizations with the business.

Step 1: Create New Dashboard


• Click on the Dashboards tab, and then click the Create Dashboard' button. • Name your new dashboard "<Your Unique Identifier> APJuice Lakehouse' (ensuring that you prepend the title with your unique identifier).

Step 2: Add Visualization

- Click on the 'Add Visualization' button.
- Type the identifier you selected into the search bar.
- Select all the visualizations you created (6 in total) and add to the dashboard one after another

Step 3: Arrange and Resize

Once you've added the widgets above, you can use drag-and-drop functionality and resizing tools to arrange them. Drag, drop and resize the 13 visualizations so that they are placed next to one other in a 2 column style. Ideally, country-based visualizations on the left side and city-based visualizations on the right side. Please refer to the below screenshot as an example



Parameterized Queries

Now, let's explore some more features in the query editor that will allow us to create dashboards that our users can interact with. This dataset represents ANZ and NZL APJuice retail outlets. So far, we have created queries and visualizations that capture metrics that include all of the data across all of the stores. Now, we'll amend our existing queries and visualizations to allow the viewer to drill down based on country code.


For this, we will write a parameterized query. Parameterized queries allow the viewer to substitute values into a query at runtime without editing the query source.

The next few steps will walk through an example of how you might use parameterized queries in practice.

Step 1: Add a Parameter to Orders Master Query

Let's update an existing query to incorporate a query parameter that we can then leverage as part of the dashboard that we have created.

- Navigate to the 'Queries' tab and type the identifier you selected into the search bar using the 'Search Queries' text box on the right-hand side of the user interface. Click on the query titled '<Your unique identifier> Orders Master".
- Tap the 'Add New Parameter' button ('{{ }}').
- Enter 'country_code' in the 'Keyword field.
- Update the 'Title' field to read 'Country_Code'.
- Amend the 'Type' field to read 'Dropdown List'.
- In the 'Values' field, enter 'All' and press the 'Enter' key.
- Type 'AUS' in the subsequent line, followed by 'NZL' in the third line
- Tick the 'Allow multiple values' checkbox.
- Update the 'Quotation' field to read 'Single Quotation Marks':



- Click the 'Add Parameter' button.
- You should now see the query parameter visible in the UI and represented in the query editor text box.
- Update your query to incorporate the country_code query parameter that has been created (using a WHERE clause) or copy and paste the following code into the editor (make sure to replace 'deepak_sekar_ap_juice_db' with the relevant database name derived as part of the first section).

- Select 'All' from the Country_Code field and tap the 'Apply Changes' button.
- Click 'Save' to save the changes to the query.


```
select
  a.store id,
  a.order source,
  a.order state,
 b.city,
 b.country_code,
 b.name as store name,
  count(*) as cnt
from
  deepak sekar ap juice db.apj sales fact a
  join deepak sekar ap juice db.dim store locations b on
a.slocation skey = b.slocation skey
WHERE
    'All' IN ({{ Country Code }})
   OR country code IN ({{ Country Code }})
group by
  a.store id,
  a.order source,
  a.order state,
 b.city,
 b.country code,
 b.name
```

Step 2: Update Products Master Query to Include the Parameter

- Navigate to the 'Queries' tab and type the identifier you selected into the search bar using the 'Search Queries' text box on the right-hand side of the user interface. Click on the query titled '<Your unique identifier> Products Master".
- Tap the 'Add New Parameter' button ('{{ }}').



- Enter 'country_code' in the 'Keyword field.
- Update the 'Title' field to read 'Country_Code'.
- Amend the 'Type' field to read 'Dropdown List'.
- In the 'Values' field, enter 'All' and press the 'Enter' key.
- Type 'AUS' in the subsequent line, followed by 'NZL' in the third line
- Tick the 'Allow multiple values' checkbox.
- Update the 'Quotation' field to read 'Single Quotation Marks':




- Click the 'Add Parameter' button.
- You should now see the query parameter visible in the UI and represented in the query editor text box.
- Update your query to incorporate the country_code query parameter that has been created (using a WHERE clause) or copy and paste the following code into the editor (make sure to replace 'deepak_sekar_ap_juice_db' with the relevant database name derived as part of the first section).
- Select 'All' from the Country Code field and tap the 'Apply Changes' button.
- Click 'Save' to save the changes to the query.

```
select
 b.city,
 b.country code,
 b.name as store name,
  a.product size,
  c.name as product name,
  count(*) as cnt,
  sum(product cost) as total product cost
from
  deepak sekar ap juice db.apj sale items fact a
  join deepak_sekar_ap_juice_db.dim_store_locations b
on a.slocation skey = b.slocation skey
  join deepak sekar ap juice db.dim products c on a.product skey
= c.product skey
WHERE
  (
    'All' IN ({{ Country Code }})
    OR country code IN ({{ Country_Code }})
  ) and
  a.unique customer id is not null
  and b.current record = 'Y'
  and c.current record = 'Y'
group by
 b.city,
 b.country code,
 b.name,
  a.product size,
  c.name
```

Step 3: Create Dashboard Filters


- Click on the Dashboards tab, and type the identifier you selected into the search bar using the 'Search' text box on the right-hand side of the user interface.
- Click on the '<Your Unique Identifier> APJuice Lakehouse' dashboard and note that you should now see the query parameters that you have created within each dashboard widget.
- Tap the kebab button on the right-hand side of the user interface and click the 'Edit' menu option.




- Select the 'Use Dashboard Level Filters' checkbox.
- Click the kebab button that appears in the upper right corner of any of the widgets and click the 'Edit Widget Settings' from the menu option.



• Tap the edit icon next to the text that reads 'Widget parameter' and, from the dialogue box that is displayed, select the 'New dashboard parameter' option and click the 'OK' button. ● Tap the 'Save' button, and you should now see the 'Country_Code' filter represented on the dashboard itself (and no longer visible within the dashboard widget). ● Repeat this for all the other widgets except this time select the 'Existing dashboard parameter' option, ensure that 'Country_Code' is populated in the 'Key' field and click the 'OK' button.



• Once done, tap the 'Done Editing' button.



• Using the 'Country_Code' dashboard filter, experiment with contextualizing the visualizations based on the appropriate country that has been selected from the drop-down menu.