## THE CINEX

ВСЕ ДЛЯ ВСІХ



```
1  [paths]
2  default = http://myserver/hg/repo1
3  default-push = ../mytestrepo
4
5  [ui]
6  username = Firstname Lastname <firstname.lastname@example.net>
7  verbose = True
8
9  [alias]
10  killitwithfire = revert --no-backup --all
```

перевірка через командний рядок:

```
hg paths gives the relationship between each path name and its url.
2
3 > hg paths
4 default = ssh://hg@example.org/repo
  local = /local/path/to/repo
6 ha paths <name> gives the url for the name.
8 > hg paths default
  ssh://hg@example.org/repo
10
11 > ha paths local
12 /local/path/to/repo
13 BTW, to get just the path names:
14
15 > hq paths -q
16 default
17 local
```

## список команд:

Commands	Description
hg pull	get latest changes like git pull use flags like -u IDK why yet
hg add	only for new files
hg commit	add changes to commit with -m for message just like git



## ОСТАННІ НОТАТКИ

20 Laravel Eloquent порад і трюків

15.12.2019

Як зробити скріншот сайту по URL на PHP

04.08.2019

**Docker Cheat Sheet** 

05.07.2019

Гарячі клавіші Ubuntu Linux

01.07.2019

Git happens! 6 типових помилок Git і як їх виправити

22.06.2019

## НЕДАВНІ КОМЕНТАРІ

Commands	Description
hg addremove	adds new files and removes file not in your file system
hg incoming	see changes commited by others
hg outgoing	see local commits
hg commitamend	same as git commitamend
hg record filename	shows history of changes to file uses extension
hg merge	like a git merge http://hgbook.red-bean.com/read/a-tour-of-mercurial-merging-work.html
hg log -r tip	tip changelog
hg log -l 5	last 5 changelog statuses
hg status -m	show modified files only
hg status -r	show removed files only
hg status -a	show added files only
hg strip "0000"	remove commit from history and delete changes before push, if pushed you are fucked
hg log - u email@accout.com	see all account commits   type -v for a verbose version
hg diff -r 0000:0000 /dir/location/path	Diff versions of same file from different CHANGESET
hg diff   less; hg commit	show changes committed
hg out	See what is not pushed to remote branch

Commands	Description
hg update 0000	CHANGESET = 0000 or branchname
hg checkout branch	works like a git checkout branch
hg record	shows record of pending changes
hg update -C	resets your head and removes commits not pushed like <code>git reset - hard</code>
hg backout 0000	CHANGESET = 0000 like a git revert tag/hash
hg blame or hg annotate	same as a git blame
hg bisect	lets you test inbetween commits to find bugs http://mercurial.selenic.com/wiki/BisectExtension
hg shelve	like a git stash (Requires the ShelveExtension or the AtticExtension.)
hg graftedit 0000	lets you pick what changes to push to default or commit CHANGESET = 0000 git cherry-pick <commit> http://selenic.com/hg/help/graft</commit>
hg graftedit 0000::0005	add a series of commits from 0000 to 0005 as a batch
hg heads	shows changes in child and parent branches
hg identifynum	current changeset
hg branch feature	go to default branch and use this command to create a new branch namded "feature" based off of it
hg commitclose- branch -m 'closing this branch'	Inside branch you want to close commit this and push so branch disapears and keeps your coworkers happy

Commands Description				
note	Hg .hgignore, syntax: glob is the same behaviour as git's .gitignore.			
MERCURIAL TIP	S AND TRICKS ШПАРГА	лки		
<u> </u>		ДАЛІ»		
Замітки по основам Python		Невеликий посібник по git	git	
ЗАЛИШТЕ ПЕРШИЙ К	ОМЕНТАР			
5,0,0,0				
Залишити ко	ментар			
Вашу адресу електронної пошти не буде опубліковано				
Коментувати				
			//	
lm'я*				

Email \*

☐ Збережіть моє ім'я, електром коментуватиму.	оонну пошту у цьому веб-переглядачі наступного разу, коли я
ОПУБЛІКУВАТИ КОМЕНТАР	

Copyright © 2020