

COMMERCIAL STANDARDS, SLIP RESISTANCE INDICES & FAÇADE CLADDING SPECS

Technical reference manual for commercial construction, ventilated facades, high-load industrial floors, and public infrastructure projects.

FEATURED PRODUCT COLLECTION

1. Granito Heavy Duty 12mm

INDUSTRIAL PORCELAIN

8000N breaking load rating. Engineered to withstand heavy forklift traffic, automotive showrooms, and warehouse spaces.

TILE SIZE	SURFACE FINISH	THICKNESS	TRAFFIC RATING
600 x 600 mm	Matt R11 Anti-Skid	12 mm	Class 5 (Heavy Ind.)

2. HydroShield Exterior Cladding

VENTILATED FAÇADE

UV-resistant, thermal shock resistant exterior cladding slab with self-cleaning titanium dioxide surface technology.

TILE SIZE	SURFACE FINISH	THICKNESS	TRAFFIC RATING
1200 x 2400 mm	Weather-Proof Satin	8 mm	Class 5 (Exterior)

3. Acoustic Backed Porcelain

SOUND DAMPENING WALL

Integrated sound-dampening backing reducing ambient reverb in office corridors, auditoriums, and hotel lobbies.

TILE SIZE	SURFACE FINISH	THICKNESS	TRAFFIC RATING
600 x 1200 mm	Silky Matte	11 mm	Class 4 (Interior Wall)