

C - Language

01. What is the Output?

```
#include <stdio.h>
int main()
{
    printf("ECEN");
}
```

O/P - ECEN

02. What is the Output?

```
#include <stdio.h>
int main()
{
    int x;
    x = 200;
    printf("Value of x = %d",x);
}
```

O/P – value of x = 200

03. What is the Output?

```
#include <stdio.h>
int main()
{
    int x,y,z;
    x = 50;
    y = 60;
    z = x + y;
    printf("Sum of x & y = %d",z);
}
```

O/P – Sum of x & y = 110

04. What is the Output?

```
#include <stdio.h>
int main()
{
    int x,y,z;
    x = 60;
    y = 50;
    z = x - y;
    printf("Difference between x & y = %d",z);
}
```

O/P – Difference between x & y = 10

05. What is the Output?

```
#include <stdio.h>
int main()
{
    int x,y,z;
    x = 60;
    y = 50;
    z = x * y;
    printf("Multiplication of x & y = %d",z);
}
```

O/P – Multiplication of x & y = 3000

06. What is the Output?

```
#include <stdio.h>
int main()
{
    int x,y,z;
    x = 20;
    y = 8;
    z = x / y;
    printf("quotient of x divided by y = %d",z);
}
```

O/P – quotient of x divided by y = 2

07. What is the Output?

```
#include <stdio.h>
int main()
{
    int x,y,z;
    x = 20;
    y = 8;
    z = x % y;
    printf("remainder of x divided by y = %d",z);
}
```

O/P – remainder of x divided by y = 4

08. What is the Output?

```
#include <stdio.h>
int main()
{
    int x,y,z;
    x = 20;
    y = 8;
    z = x - ( ( x / y ) * y );
    printf("z = %d",z);
}
```

O/P – z = 4

09. What is the Output?

```
#include <stdio.h>
int main()
{
    int x,y,z;
    x = 40;
    y = 3;
    z = x - y * 7;
    printf("z = %d",z);
}
```

O/P – z = 19

10. What is the Output?

```
#include <stdio.h>
int main()
{
    int x,y,z;
    x = 40;
    y = 3;
    z = x + y / 7;
    printf("z = %d",z);
}
```

O/P – z = 40

11. What is the Output?

```
#include <stdio.h>
int main()
{
    int x,y;
    printf("Enter a TWO digit Number : ");
    scanf("%d",&x); /* Entered Number is 98 */
    y = x % 10;
    printf("%d",y);
}
```

O/P – 8

12. What is the Output?

```
#include <stdio.h>
int main()
{
    int x,y;
    printf("Enter a TWO digit Number : ");
    scanf("%d",&x); /* Entered Number is 94 */
    y = x / 10;
    printf("%d",y);
}
```

O/P – 9

13. What is the Output?

```
#include <stdio.h>
int main()
{
    int x,y;
    printf("Enter a THREE digit Number : ");
    scanf("%d",&x); /* Entered Number is 953 */
    y = x % 10;
    printf("%d",y);
}
```

O/P – 3

14. What is the Output?

```
#include <stdio.h>
int main()
{
    int x,y,z;
    printf("Enter a THREE digit Number : ");
    scanf("%d",&x); /* Entered Number is 678 */
    y = x / 10;
    z = y % 10;
    printf("%d",z);
}
```

O/P – 7

15. What is the Output?

```
#include <stdio.h>
int main()
{
    int x,y;
    printf("Enter a THREE digit Number : ");
    scanf("%d",&x); /* Entered Number is 678 */
    y = x / 100;
    printf("%d",y);
}
```

O/P – 6

16. What is the Output?

```
#include <stdio.h>
int main()
{
    int x,y,z,s;
    printf("Enter a TWO digit Number : ");
    scanf("%d",&x); /* Entered Number is 78 */
    y = x / 10;
    z = x % 10;
    s = y + z;
    printf("%d",s);
}
```

O/P – 15

17. What is the Output?

```
#include <stdio.h>
int main()
{
    int x;
    printf("Enter a TWO digit Number : ");
    scanf("%d",&x); /* Entered Number is 78 */
    if(x < 40)
    {
        printf("Fail");
    }
    else
    {
        printf("Pass");
    }
}
```

O/P – Pass

18. What is the Output?

```
#include <stdio.h>
int main()
{
    int i,s;
    s = 0;
    i = 0;
    loop:
    if(i < 5)
    {
        s = s + i;
        i = i + 1;
        goto loop;
    }
    printf("%d",s);
}
```

O/P – 10

19. What is the Output?

```
#include <stdio.h>
int main()
{
    int i,s;
    s = 0;
    for(i=0; i<5; i++)
    {
        s = s + i;
    }
    printf("%d",s);
}
```

O/P – 10

20. What is the Output?

```
#include <stdio.h>
int main()
{
    int i,s;
    s = 0;
    i = 0;
    while(i<5)
    {
        s = s + i;
        i = i+1;
    }
    printf("%d",s);
}
```

O/P – 10

21. What is the Output?

```
#include <stdio.h>
int main()
{
    int i,s;
    s = 0;
    i = 0;
    for(i=0; i<10;i++)
    {
        if((i%2) == 0)
        {
            s = s + i;
        }
    }
    printf("%d",s);
}
```

O/P – 20

22. What is the Output?

```
#include <stdio.h>
int main()
{
    int i,s;
    s = 0;
    i = 0;
    for(i=0; i<10;i++)
    {
        if((i%2) == 1)
        {
            s = s + i;
        }
    }
    printf("%d",s);
}
```

O/P – 25

23. What is the Output?

```
#include <stdio.h>
int main()
{
    int i,s;
    s = 0;
    i = 0;
    for(i=0; i<100;i++)
    {
        if((i%6) == 0)
        {
            s = s + i;
        }
    }
    printf("%d",s);
}
```

O/P – 816

24. What is the Output?

```
#include <stdio.h>
int main()
{
    int m0,m1,m2,m3,m4,s,a;
    m0 = 12;
    m1 = 25;
    m2 = 27;
    m3 = 30;
    m4 = 11;
    s = m0 + m1 + m2 + m3 + m4;
    a = s / 5;
    printf("%d",a);
}
```

O/P – 21

25. What is the Output?

```
#include <stdio.h>
int main()
{
    int m[5],s,a;
    m[0] = 10;
    m[1] = 25;
    m[2] = 31;
    m[3] = 14;
    m[4] = 15;
    s = m[0] + m[1] + m[2] + m[3] + m[4];
    a = s / 5;
    printf("%d",a);
}
```

O/P – 19

26. What is the Output?

```
#include <stdio.h>
int main()
{
    int m[5],s,a,i;
    m[0] = 15;
    m[1] = 40;
    m[2] = 32;
    m[3] = 11;
    m[4] = 22;
    s = 0;
    for(i=0; i<5; i++)
    {
        s = s + m[i];
    }
    a = s / 5;
    printf("%d",a);
}
```

O/P – 24

27. What is the Output?

```
#include <stdio.h>
int main()
{
    int m[5] = {25,32,43,55,60};
    int s,a,i;
    s = 0;
    for(i=0; i<5; i++)
    {
        s = s + m[i];
    }
    a = s / 5;
    printf("%d",a);
}
```

O/P – 43

28. What is the Output?

```
#include <stdio.h>
int main()
{
    int m[] = {15,32,43,55,60};
    int s,a,i;
    s = 0;
    for(i=0; i<5; i++)
    {
        s = s + m[i];
    }
    a = s / 5;
    printf("%d",a);
}
```

O/P – 41

29. What is the Output?

```
#include <stdio.h>
int main()
{
    int m[] = {15,32,43,55,60,23,17,0};
    int s,a,i;
    s = 0;
    i = 0;
    while(m[i] != 0)
    {
        s = s + m[i];
        i = i+1;
    }
    a = s / i;
    printf("%d",a);
}
```

O/P – 35

30. What is the Output?

```
#include <stdio.h>
int main()
{
    int m[] = {13,32,40,55,60,21,17,0};
    int s,a,i;
    s = 0;
    i = 0;
    while(m[i] != 0)
    {
        s = s + m[i];
        i = i+1;
    }
    a = s / i;
    printf("%d %d %d",i,s,a);
}
```

O/P – 7 238 34

31. What is the Output?

```
#include <stdio.h>
int main()
{
    char c;
    scanf("%c",&c); /* Entered Value = A */
    printf("%c",c);
}
```

O/P – A

32. What is the Output?

```
#include <stdio.h>
int main()
{
    char c;
    scanf("%c",&c); /* Entered Value = A */
    printf("%d",c);
}
```

O/P – 65

33. What is the Output?

```
#include <stdio.h>
int main()
{
    char c;
    scanf("%d",&c); /* Entered Value = 67 */
    printf("%c",c);
}
```

O/P – C

34. What is the Output?

```
#include <stdio.h>
int main()
{
    char c;
    c = 66;
    printf("%c",c);
}
```

O/P – B

35. What is the Output?

```
#include <stdio.h>
int main()
{
    char c;
    c = 'E';
    printf("%d",c);
}
```

O/P – 69

36. What is the Output?

```
#include <stdio.h>
int main()
{
    char c;
    c = '3';
    printf("%c",c);
}
```

O/P – 3

37. What is the Output?

```
#include <stdio.h>
int main()
{
    char c[5],i;
    c[0] = '1';
    c[1] = '2';
    c[2] = '3';
    c[3] = '4';
    c[4] = '5';
    for(i=0; i<5; i++)
    {
        printf("%c",c[i]);
    }
}
```

O/P – 12345

38. What is the Output?

```
#include <stdio.h>
int main()
{
    char c[5],i;
    c[0] = 49;
    c[1] = 50;
    c[2] = 51;
    c[3] = 52;
    c[4] = 53;
    for(i=0; i<5; i++)
    {
        printf("%c",c[i]);
    }
}
```

O/P – 12345

39. What is the Output?

```
#include <stdio.h>
int main()
{
    char c[5] = {65,66,67,68,69};
    int i;
    for(i=0; i<5; i++)
    {
        printf("%c",c[i]);
    }
}
```

O/P – ABCDE

40. What is the Output?

```
#include <stdio.h>
int main()
{
    char c[7] = {'S','U','R','A','B','E','E'};
    int i;
    for(i=0; i<7; i++)
    {
        printf("%c",c[i]);
    }
}
```

O/P – SURABEE

41. What is the Output?

```
#include <stdio.h>
int main()
{
    char c[7] = "SURABEE";
    int i;
    for(i=0; i<7; i++)
    {
        printf("%c",c[i]);
    }
}
```

O/P – SURABEE

42. What is the Output?

```
#include <stdio.h>
int main()
{
    char c[8] = "SURABEE";
    printf("%s",c);
}
```

O/P – SURABEE

43. What is the Output?

```
#include <stdio.h>
int main()
{
char c[8];
scanf("%s",c); /* Entered Value = Surabee */
printf("%s",c);
}
```

O/P – Surabee

44. What is the Output?

```
#include <stdio.h>
int main()
{
char c[8];
int i;
scanf("%s",c); /* Entered Value = Surabee */
for(i=0; i<7; i++)
{
printf("%c",c[i]);
}
}
```

O/P – Surabee

45. What is the Output?

```
#include <stdio.h>
int main()
{
char c[8];
int i;
scanf("%s",c); /* Entered Value = Surabee */
i = 0;
while(c[i] != 0)
{
printf("%c",c[i]);
i = i+1;
}
}
```

O/P – Surabee

46. What is the Output?

```
#include <stdio.h>
int main()
{
char c[8];
scanf("%s",c); /* Entered Value = Surabee */
printf("%d",c[7]);
}
```

O/P – 0

47. What is the Output?

```
#include <stdio.h>
int main()
{
char c[8] = "Surabee";
char b[8] = "Welcome";
c[8] = b[8];
printf("%s",c);
}
```

O/P – Surabee

48. What is the Output?

```
#include <stdio.h>
int main()
{
char c[8] = "Surabee";
char b[8] = "Welcome";
c[0] = b[0];
printf("%s",c);
}
```

O/P – Wurabee

49. What is the Output?

```
#include <stdio.h>
int main()
{
    char c[8] = "Surabee";
    char b[8] = "Welcome";
    c = b;
    printf("%s",c);
}
```

O/P – Does not compile for c=b. The error is – “assignment to expression with array type”

50. What is the Output?

```
#include <stdio.h>
int main()
{
    char c[8] = "Surabee";
    char b[8] = "Welcome";
    int i;
    for(i=0; i<8; i++)
    {
        c[i] = b[i];
    }
    printf("%s",c);
}
```

O/P – Welcome

51. What is the Output?

```
#include <stdio.h>
int main()
{
    int i;
    i = 67;
    printf("%o",i);
}
```

O/P – 103

52. What is the Output?

```
#include <stdio.h>
int main()
{
    int i;
    i = 067;
    printf("%d",i);
}
```

O/P – 55

53. What is the Output?

```
#include <stdio.h>
int main()
{
    int i;
    i = 0x67;
    printf("%d",i);
}
```

O/P – 103

54. What is the Output?

```
#include <stdio.h>
int main()
{
    int i;
    i = 'A';
    printf("%d",i);
}
```

O/P – 65

55. What is the Output?

```
#include <stdio.h>
int main()
{
    int i;
    i = 67;
    printf("%o",i);
}
```

O/P – 103

56. What is the Output?

```
#include <stdio.h>
int main()
{
    int i;
    i = 067;
    printf("%o",i);
}
```

O/P – 67

57. What is the Output?

```
#include <stdio.h>
int main()
{
    int i;
    i = 0x67;
    printf("%o",i);
}
```

O/P – 147

58. What is the Output?

```
#include <stdio.h>
int main()
{
    int i;
    i = 'A'; // Here i contains the ASCII value of 'A' as it is a
             // character
    printf("%o",i);
}
```

O/P – 101

59. What is the Output?

```
#include <stdio.h>
int main()
{
    int i;
    i = "A"; // Here i contains the address value of 'A' as it is
             // a string
    printf("%d",i);
}
```

O/P – (The address of 'A' in decimal)

60. What is the Output?

```
#include <stdio.h>
int main()
{
    int i;
    i = "A";
    printf("%o",i);
}
```

O/P – (The address of 'A' in octal)

61. What is the Output?

```
#include <stdio.h>
int main()
{
    int i;
    i = 67;
    printf("%x",i);
}
```

O/P – 43

62. What is the Output?

```
#include <stdio.h>
int main()
{
    int i;
    i = 067;
    printf("%x",i);
}
```

O/P – 37

63. What is the Output?

```
#include <stdio.h>
int main()
{
    int i;
    i = 0x67;
    printf("%x",i);
}
```

O/P – 67

64. What is the Output?

```
#include <stdio.h>
int main()
{
    int i;
    i = 'A';
    printf("%x",i);
}
```

O/P – 41

65. What is the Output?

```
#include <stdio.h>
int main()
{
    int i;
    i = 67;
    printf("%c",i);
}
```

O/P – C

66. What is the Output?

```
#include <stdio.h>
int main()
{
    int i;
    i = 067;
    printf("%c",i);
}
```

O/P – 7

67. What is the Output?

```
#include <stdio.h>
int main()
{
    int i;
    i = 0x67;
    printf("%c",i);
}
```

O/P – g

68. What is the Output?

```
#include <stdio.h>
int main()
{
    int i;
    i = 'A'; // Here i contains the ASCII value of 'A' as it is a character
    printf("%c",i);
}
```

O/P – A

69. What is the Output?

```
#include <stdio.h>
int main()
{
    int i;
    i = "A";
    printf("%x",i);
}
```

O/P – (The address of 'A' in hexa decimal)

70. What is the Output?

```
#include <stdio.h>
int main()
{
    int i;
    i = "A"; // Here i contains the address value of 'A' as it is a string
    printf("%c",i);
}
```

O/P – d

Note – the binary value of the address of 'A' is – 100000001010000**01100100** and when we use %c, then the last 8 bit is allocated & print it as character & the character of **01100100** is – 'd'

71. What is the Output?

```
#include <stdio.h>
int main()
{
    int i,*p;
    i = 5;
    p = &i;
    *p = 10;
    printf("%d",i);
}
```

O/P – 10

72. What is the Output?

```
#include <stdio.h>
int main()
{
    char a[] = "Surabee";
    char *p;
    p = a; // Here the pointer p copy the starting address of array a[]
    printf("%d", *p);
}
```

O/P – 83 // 83 is the ASCII value of S character

73. What is the Output?

```
#include <stdio.h>
int main()
{
    char a[] = "Surabee";
    char *p;
    p = a;
    printf("%c", *p);
}
```

O/P – S

74. What is the Output?

```
#include <stdio.h>
int main()
{
    char a[] = "Surabee";
    char *p;
    p = a;
    printf("%s", p);
}
```

O/P – Surabee

75. What is the Output?

```
#include <stdio.h>
int main()
{
    char a[] = "Surabee";
    char *p;
    p = &a[7];
    printf("%d", *p);
}
```

O/P – 0

76. What is the Output?

```
#include <stdio.h>
int main()
{
    char a[] = "Surabee";
    char *p;
    p = a;
    while(*p != 0)
    {
        printf("%c", *p);
        p = p+1;
    }
}
```

O/P – Surabee

77. What is the Output?

```
#include <stdio.h>
int main()
{
    char a[] = "Surabee";
    char *p;
    p = a;
    while(*p)
    {
        printf("%c", *p);
        p = p+1;
    }
}
```

O/P – Surabee

78. What is the Output?

```
#include <stdio.h>
int main()
{
    char a[] = "Surabee";
    char *p;
    p = a;
    while(*p)
    {
        printf("%c", *p++);
    }
}
```

O/P – Surabee

79. What is the Output?

```
#include <stdio.h>
int main(){
char a[] = "Surabee";
char *p;
p = a;
do
{
printf("%c",*p);
} while(*p++);
}
```

O/P – Surabee

80. What is the Output?

```
#include <stdio.h>
int main(){
char a[] = "Surabee";
char *p;
a[4] = 0;
p = a;
do
{
printf("%c",*p);
} while(*p++);
}
```

O/P – Sura

81. What is the Output?

```
#include <stdio.h>
int add(int x, int y);
int main()
{
int a,b,c;
a = 10;
b = 20;
c = add(a,b);
printf("%d",c);
}
int add(int x, int y){
int z;
z = x + y;
return z;
}
```

O/P – 30

82. What is the Output?

```
#include <stdio.h>
int add(int x, int y);
int main()
{
int a,b,c;
a = 10;
b = 20;
c = 25;
c = add(a,b);
printf("%d",c);
}
int add(int x, int y){
int z;
z = x + y;
return z;
}
```

O/P – 30

83. What is the Output?

```
#include <stdio.h>
int add(int x, int y);
int main()
{
int a,b,c;
a = 10;
b = 20;
c = 25;
add(a,b);
printf("%d",c);
}
int add(int x, int y){
int z;
z = x + y;
return z;
}
```

O/P – 25

84. What is the Output?

```
#include <stdio.h>
int add(int x, int y);
int a,b,c;
int main()
{
int a,b,c;
a = 10;
b = 20;
c = 25;
c = add(a,b);
printf("%d",c);
}
int add(int a, int b){
int c;
c = a + b;
return b;
}
```

O/P – 20

85. What is the Output?

```
#include <stdio.h>
int add(int x, int y);
int a,b,c;
int main()
{
    a = 10;
    b = 20;
    c = 25;
    add(a,b);
    printf("%d",c);
}
int add(int a, int b)
{
    c = a + b;
    return b;
}
```

O/P – 30 // Here a,b,c is the global variable not any local variable

86. What is the Output?

```
#include <stdio.h>
int add(int x, int y);
int a,b,c; // Here c is the global variable
int main()
{
    int a,b,c;
    a = 10;
    b = 20;
    c = 25;
    add(a,b);
    printf("%d",c); // Here c is local variable
}
int add(int a, int b)
{
    c = a + b;
    return b;
}
```

O/P – 25

87. What is the Output?

```
#include <stdio.h>
int add(int x, int y);
int a,b,c;
int main()
{
    int a,b,c;
    a = 10;
    b = 20;
    c = b - a;
    add(a,b);
    printf("%d",c);
}
```

```
int add(int a, int b)
{
    c = a + b;
    return b;
}
```

O/P – 10

88. What is the Output?

```
#include <stdio.h>
void add(void);
int a,b,c;
int main()
{
    a = 10;
    b = 20;
    add();
    printf("%d",c);
}
```

```
void add(void)
{
    c = a + b;
}
```

O/P – 30

89. What is the Output?

```
#include <stdio.h>
void add(void);
int a,b,c;
int main()
{
a = 10;
b = 20;
add();
c = a+b;
printf("%d",c);
}
void add(void)
{
int a,b; // This a & b are local variable
a = 45;
b = 15;
c = a + b;
}
```

O/P – 30

90. What is the Output?

```
#include <stdio.h>
void add(void);
int a,b,c;
int main()
{
a = 10;
b = 20;
add();
c = a+b;
printf("%d",c);
}
void add(void)
{
a = 45; // Here no any local variable, 45 & 15 assign to the
global variable a & b respectively
b = 15;
c = a + b;
}
```

O/P – 60

91. What is the Output?

```
#include <stdio.h>
int add(int *x, int *y);
int main()
{
int a,b,c;
a = 10;
b = 20;
c = add(&a,&b);
printf("%d",c);
}
int add(int *x, int *y)
{
int z;
*x = 21;
*y = 33;
z = *x + *y;
return z;
}
```

O/P – 54

92. What is the Output?

```
#include <stdio.h>
int add(int *x, int *y, int *z);
int main()
{
int a,b,c;
a = 10;
b = 20;
add(&a,&b,&c);
printf("%d",c);
}
int add(int *x, int *y, int *z)
{
*z = *x + *y;
}
```

O/P – 30

93. What is the Output?

```
#include <stdio.h>
int add(int *x, int *y, int *z);
int a,b,c;
int main()
{
    int a,b,c;
    a = 10;
    b = 20;
    add(&a,&b,&c);
    printf("%d",c);
}
int add(int *x, int *y, int *z)
{
    *z = *x + *y;
}
```

O/P – 30

94. What is the Output?

```
#include <stdio.h>
int add(int *x);
int a,b,c;
int main()
{
    int a[3];
    a[0] = 12;
    a[1] = 21;
    add(a);
    printf("%d",a[2]);
}
int add(int *x)
{
    *(x+2) = *(x+0) + *(x+1);
}
```

O/P – 33

95. What is the Output?

```
#include <stdio.h>
int ps(char *s);
int main()
{
    char s[] = "Surabee";
    ps(s);
}
int ps(char *p)
{
    while(*p)
    {
        printf("%c",*p++);
    }
}
```

O/P – Surabee

96. What is the Output?

```
#include <stdio.h>
int sp(char *s,char *d);
int main()
{
    char s[10] = "Surabee";
    char d[10];
    sp(s,d);
    printf("%s",d);
}

int sp(char *src,char *dst)
{
    while(*src)
    {
        *dst = *src;
        dst = dst+1;
        src = src+1;
    }
}
```

O/P – Surabee

97. What is the Output?

```
#include <stdio.h>
int sp(char *s,char *d);
int main()
{
    char s[10] = "Surabee";
    char d[10];
    sp(s,d);
    printf("%s",d);
}

int sp(char *src,char *dst)
{
    while(*src)
    {
        *dst++ = *src++;
    }
    *dst = 0;
}
```

O/P – Surabee

98. What is the Output?

```
#include <stdio.h>
int sc(char *s,char *d);
int main()
{
    char s[20] = "Surabee ";
    char d[10] = "School";
    sc(s,d);
    printf("%s",s);
}

int sc(char *src,char *dst)
{
    while(*src)
    {
        *src++;
    }
    while(*dst)
    {
        *src++ = *dst++;
    }
    *dst = 0;
}
```

O/P – SurabeeSchool

99. What is the Output?

```
#include <stdio.h>
int sm(char *s,char *d);
int main()
{
    char s[20] = "Surabee";
    char d[10] = "Surabee ";
    if(sm(s,d) == 1)
    {
        printf("Both the strings are equal\n");
    }
    else
    {
        printf("Both the strings are not equal\n");
    }
}

int sm(char *src,char *dst){
    while(*src)
    {
        if(*src++ != *dst++)
        {
            return(0);
        }
    }
    if(*dst != 0)
    {
        return(0);
    }
    return(1);
}
```

O/P – Both strings are equal

100. What is the Output?

```
#include <stdio.h>
int sr(char *s,char *d);
int main()
{
    char s[10] = "Surabee";
    char d[10];
    sr(s,d);
    printf("%s",d);
}

int sr(char *src,char *dst)
{
    int i=0;
    while(*(src+i) != 0) i++;
    while(i)
    {
        *dst++ = *(src + i - 1);
        i--;
    }
    *dst = 0;
}
```

O/P – eebaruS