UNIDAD 2 PRACTICA 1:

IP del servidor:

```
ciro@servidor:~$ ip a
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
       valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host noprefixroute
       valid_lft forever preferred_lft forever
2: ens33: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP group default qlen 1000
    link/ether 00:0c:29:0a:80:40 brd ff:ff:ff:ff:ff:ff
    altname enp2s1
    inet 192.168.77.128/24 metric 100 brd 192.168.77.255 scope global dynamic ens33
       valid_lft 1402sec preferred_lft 1402sec
    inet6 fe80::20c:29ff:fe0a:8040/64 scope link
       valid_lft forever preferred_lft forever
```

Rol de PostgreSQL:

```
ciro@servidor:~$ sudo -u postgres psql -c "\du"
[sudo] password for ciro:
                             List of roles
 Role name |                         Attributes
-----------+------------------------------------------------------------
 consulta  |
 odoo18    | Create DB
 postgres  | Superuser, Create role, Create DB, Replication, Bypass RLS

ciro@servidor:~$
```

Versión de wkhtmltopdf:

```
ciro@servidor:~$ wkhtmltopdf --version
wkhtmltopdf 0.12.6.1 (with patched qt)
```

Estado del servicio y puerto:

```
ciro@servidor:~$ sudo systemctl status odoo18
sudo ss -tlnp | grep 8069
Warning: The unit file, source configuration file or drop-ins of odoo18.service changed on disk. Run 'systemctl daemon-
● odoo18.service - Odoo 18
     Loaded: loaded (/etc/systemd/system/odoo18.service; enabled; preset: enabled)
     Active: active (running) since Thu 2026-10-29 21:23:51 UTC; 10min ago
   Main PID: 1565 (python3)
      Tasks: 4 (limit: 6955)
     Memory: 151.5M (peak: 151.9M)
        CPU: 2.463s
     CGroup: /system.slice/odoo18.service
             └─1565 /opt/odoo18/venv/bin/python3 /opt/odoo18/odoo/odoo-bin -c /etc/odoo18.conf

oct 29 21:23:51 servidor systemd[1]: Started odoo18.service - Odoo 18.
lines 1-12/12 (END)
```

Base de datos:

```
                                                List of databases
   Name    |  Owner   | Encoding | Locale Provider |   Collate   |    Ctype    | ICU Locale | ICU Rules |   Access privi
leges
-----------+----------+----------+-----------------+-------------+-------------+------------+-----------+---------------
--------
 postgres  | postgres | UTF8     | libc            | es_ES.UTF-8 | es_ES.UTF-8 |            |           |
 pruebas   | odoo18   | UTF8     | libc            | C           | es_ES.UTF-8 |            |           |
 template0 | postgres | UTF8     | libc            | es_ES.UTF-8 | es_ES.UTF-8 |            |           | =c/postgres
       +
           |          |          |                 |             |             |            |           | postgres=CTc/p
ostgres
 template1 | postgres | UTF8     | libc            | es_ES.UTF-8 | es_ES.UTF-8 |            |           | =c/postgres
       +
           |          |          |                 |             |             |            |           | postgres=CTc/p
ostgres
(4 rows)

(END)
```