

module > repository_sync

Sync a Repository or Product

- [Synopsis](#)
- [Parameters](#)
- [Examples](#)

Synopsis

- Sync a repository or product

Requirements

- requests

Parameters

Parameter	Choices/ Defaults	Comments
organization string / required		Organization that the entity is in
password string / required		Password of the user accessing the Foreman server. If the value is not specified in the task, the value of environment variable <code>SATELLITE_PASSWORD</code> will be used instead.
product string / required		Product to which the <i>repository</i> lives in
repository string		Name of the repository to sync If omitted, all repositories in <i>product</i> are synced.
server_url string / required		URL of the Foreman server. If the value is not specified in the task, the value of environment variable <code>SATELLITE_SERVER_URL</code> will be used instead.

username string / required		Username accessing the Foreman server. If the value is not specified in the task, the value of environment variable <code>SATELLITE_USERNAME</code> will be used instead.
validate_certs boolean	Choices: <ul style="list-style-type: none"> no yes 	Whether or not to verify the TLS certificates of the Foreman server. If the value is not specified in the task, the value of environment variable <code>SATELLITE_VALIDATE_CERTS</code> will be used instead.

Examples

```
- name: "Sync repository"
  redhat.satellite.repository_sync:
    username: "admin"
    password: "changeme"
    server_url: "https://satellite.example.com"
    repository: "My repository"
    product: "My Product"
    organization: "Default Organization"
```