

module > subscription_manifest

Manage Subscription Manifests

- [Synopsis](#)
- [Parameters](#)
- [Examples](#)

Synopsis

- Upload, refresh and delete Subscription Manifests

Requirements

- requests

Parameters

Parameter	Choices/Defaults	Comments
manifest_path path		Path to the manifest zip file This parameter will be ignored if <i>state=absent</i> or <i>state=refreshed</i>
organization string / required		Organization that the entity is in
password string / required		Password of the user accessing the Foreman server. If the value is not specified in the task, the value of environment variable <code>SATELLITE_PASSWORD</code> will be used instead.
repository_url string		URL to retrieve content from aliases: <code>redhat_repository_url</code>

server_url string / required		URL of the Foreman server. If the value is not specified in the task, the value of environment variable <code>SATELLITE_SERVER_URL</code> will be used instead.
state string	Choices: <ul style="list-style-type: none"> • absent • present ← • refreshed 	The state of the manifest
username string / required		Username accessing the Foreman server. If the value is not specified in the task, the value of environment variable <code>SATELLITE_USERNAME</code> will be used instead.
validate_certs boolean	Choices: <ul style="list-style-type: none"> • no • yes ← 	Whether or not to verify the TLS certificates of the Foreman server. If the value is not specified in the task, the value of environment variable <code>SATELLITE_VALIDATE_CERTS</code> will be used instead.

Examples

```
- name: "Upload the RHEL developer edition manifest"
  redhat.satellite.subscription_manifest:
    username: "admin"
    password: "changeme"
    server_url: "https://satellite.example.com"
    organization: "Default Organization"
    state: present
    manifest_path: "/tmp/manifest.zip"
```