

module > organization

Manage Organizations

- [Synopsis](#)
- [Parameters](#)
- [Examples](#)
- [Return Values](#)

Synopsis

- Manage Organizations

Requirements

- requests

Parameters

Parameter	Choices/Default s	Comments
descriptionstring		Description of the Organization
labelstring		Label of the Organization
namestring / required		Name of the Organization
parameterslist / elements =dictionary		Entity domain specific host parameters
namestring / required		Name of the parameter

parameter_typestring
g

Choices:

- string ←
- boolean
- integer
- real
- array
- hash
- yaml
- json

Type of the parameter

value raw / required

Value of the parameter

passwordstring /
required

Password of the user accessing the Foreman server.

If the value is not specified in the task, the value of environment variable SATELLITE_PASSWORD will be used instead.

server_urlstring /
required

URL of the Foreman server.

If the value is not specified in the task, the value of environment variable SATELLITE_SERVER_URL will be used instead.

statestring

Choices:

- present ←
- absent

State of the entity

usernamestring /
required

Username accessing the Foreman server.

If the value is not specified in the task, the value of environment variable SATELLITE_USERNAME will be used instead.

validate_certsboolean

Choices:

- no
- yes ←

Whether or not to verify the TLS certificates of the Foreman server.

If the value is not specified in the task, the value of environment variable SATELLITE_VALIDATE_CERTS will be used instead.

Examples

```
- name: "Create CI Organization"
  redhat.satellite.organization:
    username: "admin"
    password: "changeme"
    server_url: "https://satellite.example.com"
    name: "My Cool New Organization"
    state: present
```

Return Values

Key	Returned	Description
entity (dict)	success	Final state of the affected entities grouped by their type.
organizations (list)		List of organizations.