

Cisco Secure Email Threat Defense Lab

Last Updated: August - 2025

IMPORTANT! This content is community-developed and is not subject to standard Cisco verification or support.

About This Lab

In this lab, you'll explore Cisco Secure Email Threat Defense (ETD), a powerful solution designed to safeguard email environments against advanced threats. Email remains one of the most common and high-risk channels for cyberattacks, with threats ranging from spam and phishing to sophisticated malware and Business Email Compromise (BEC) attacks. Cisco Secure Email Threat Defense integrates seamlessly with on-premises or cloud-based email systems, providing real-time protection through machine learning, threat intelligence, and advanced analytics.

Objectives

This hands-on lab will guide you through key features of ETD:

Setting up and Connection to MS365: Learn the simple process of setting up ETD and connecting it to Microsoft 365 environments

Policy Configuration: Learn to set up policies for detecting and mitigating various threats, including phishing attempts, malware, and spam.

Threat Intelligence: Discover how Cisco leverages AI/ML/others, to identify and block new and emerging threats in real-time.

Reporting and Analytics: Use the ETD dashboard to view threat reports and analyze trends, giving you insights into email security within your organization.

Integration and APIs: Understand how to leverage REST APIs to build powerful integration between ETD and your Security applications and/or processes.

Lab Structure

Throughout this lab, you'll configure security policies, test threat detection capabilities, and monitor and respond to malicious messages. By the end of it, you should have a robust understanding of how Cisco Secure Email Threat Defense can strengthen your organization's email security posture.

Let's get started on securing email communications and defending against today's most advanced email-based threats!

Table of Contents

- ABOUT THIS LAB1
- OBJECTIVES1
- REQUIREMENTS3
- ABOUT THIS SOLUTION.....3
- TOPOLOGY4
- SCENARIO – INTEGRATION WITH EMAIL THREAT DEFENSE5
 - Use Case.....5
 - Objective5
- TASK – ACTIVATE CISCO SECURE EMAIL THREAT DEFENSE ACCOUNT.6
 - Lesson learned.15
- TASK – CONFIGURE EMAIL THREAT DEFENSE ACCOUNT.....16
 - Lesson learned.20
 - Configure Cisco Secure Email Threat Defense Policy21
 - Lesson learned.24
- TASK – CONFIGURE EXCHANGE ONLINE.25
 - Connector in O365 for ETD traffic.....31
 - Lesson learned.36
- TASK –REVIEW THE PERMISSIONS ASSIGNED IN MICROSOFT (OPTIONAL)37
- TASK – TEST THE SOLUTION.41
 - Lesson learned.44
- TASK - HIGH IMPACT PERSONNEL45
- TASK – “ATTACK” YOUR ENVIRONMENT.....52
 - Send Email Threats.52
- TASK – DASHBOARD USE CASE58
 - Search Messages58
 - Manual Remediation.60
 - Lesson learned.64
- TASK – API & POSTMAN.65
 - Authentication API.....65
 - Search API.....71
- CONCLUSION77
- APPENDIX79
 - Postman Installation.....79



Requirements

This lab will use cloud-based applications and solutions. It is not a requirement to install any application on your laptop, although you have the option to do so.

The requirements are:

- Laptop
- Internet connectivity
- Mobile phone to install the Cisco DUO mobile app

During this lab, we will create accounts on:

- Cisco Email Threat Defense
- Postman Cloud
- Cisco DUO
- Free Email Service (you can also use any other business email account)

About This Solution

Email Threat Defense augments native Microsoft 365 security and provides complete visibility to inbound, outbound, and internal user-to-user messages.

With Email Threat Defense customers can:

- Detect and block threats with superior threat intelligence from Cisco Talos, one of the largest threat research and efficacy teams.
- Combat advanced threats using Secure Endpoint, and Secure Malware Analytics
- Get complete visibility to inbound, outbound, and internal messages.
- Leverage fast API-driven remediation of messages with malicious content.
- Use an integrated dashboard for search, reporting, and tracking, including conversation view and message trajectory.
- Enhance Microsoft 365 security in less than 5 minutes without changing the mail flow.


For additional information about Cisco Secure Email solutions, visit

<https://www.cisco.com/site/us/en/products/security/secure-email/index.html>.

Topology

In this diagram, we can see the different elements that we are going to use in our lab environment:

Figure 1. Lab Topology



Item Description:

Workstation 1	A workstation that allows lab attendees to access other devices in the same topology
Attacker	A Linux machine that acts as the bad actor, which sends random email messages to other users.
Exchange Online	An Exchange Online mail server provided by the proctor.
Email Threat Defense	An email security cloud account provided by the trainer.

Scenario – Integration with Email Threat Defense

Use Case

Attackers are becoming increasingly creative. To detect and prevent the latest attacks, AI/ML should complement what customers currently use for email security, such as gateways or Microsoft 365.

Objective

This lab goal is to deploy ETD in a Microsoft O365 environment.


For production environments, we may encounter scenarios and situations where some configurations may be different, but the chosen scenario is one of the most common for customers who want to increase security in their Microsoft O365 environment.

Task – Activate Cisco Secure Email Threat Defense account.


In this lab, we are going to use the ETD beta portal. This means that some steps may be different from those in a production environment.

1. Please go to O365 portal <https://outlook.office.com/mail/>
For authentication credentials, please use the lab number assigned by the proctor.
Administrator 1: alexwayne6@emailseclabXX.emailsec.io
User 2: bsmith@emailseclabXX.emailsec.io
2. Open the inbox, and you will see a “Welcome to Cisco Email Threat Defense” email.


Note: If you don't get a welcome email, please use this URL: <https://beta-ui.cmd.cisco.com/>



3. Click on the link inside the email (see the picture)



- For the email address, please use the one you used to log in to O365. Click on **Sign up now**.



- For the email address, please use the one given to you by your proctor, choose the correct information, check the **"I agree..."** box, and click on **"Sign up"**

Email: alexwayne6@emailseclabXX.emailsec.io First Name: Alex Last Name: Wayne Country: United States Password:	Email: bsmith@emailseclabXX.emailsec.io First Name: Blake Last Name: Smith Country: United States Password:
--	---

Account Sign Up

Provide following information to create enterprise account.

[Back to login page](#)

Email *
alexwayne4@emailseclab1.emailsec.io

First name *
Alex

Last name *
Wayne

Country *
United States

Password *
..... [Show](#)

Confirm Password *
..... [Show](#)

☒ I agree to the [End user license agreement](#) and [Privacy statement](#).

[Sign up](#)

[Cancel](#)

Password Requirements

- ✓ At least 8 character(s)
- ✓ At least 1 number(s)
- ✓ At least 1 symbol(s)
- ✓ At least 1 lowercase letter(s)
- ✓ At least 1 uppercase letter(s)
- ✓ Does not contain part of username
- ✓ Does not contain 'First name'
- ✓ Does not contain 'Last name'

6. You should expect this screen:




Security Cloud Sign On

Your account is successfully created!


A verification email has been sent to alexwayne4@emailseclab1.emailsec.io
finish signing in please verify your email

[Back to login page](#)


7. Go back to your administrator mailbox in O365: <https://outlook.office.com/mail/>
8. Open the new message and press "Activate Account."




- By default, you need to set up MFA when creating an ETD account. Press the “**Get started**” button:




- Click on **Next**.



11. Press the “*Duo Mobile*” button.




12. Introduce your phone number and press **Continue**.




A screenshot of a mobile application interface for entering a phone number. At the top left is a blue back arrow and the text 'Back'. The main heading is 'Enter your phone number' in bold. Below it, a subtitle reads 'You'll have the option to log in with Duo Mobile.' There are two input fields: 'Country code' with a dropdown menu showing '+1' and a flag icon, and 'Phone number' with an empty text box. Below these fields is an example: 'Example: "201-555-5555"'. A large, light gray 'Continue' button is centered below the example. At the bottom, there is a blue link 'I have a tablet' and the text 'Secured by Duo' in small font.

13. Verify the number and press **Yes, it's correct**.




A screenshot of a mobile application interface for verifying a phone number. At the top left is a blue back arrow and the text 'Back'. The main heading is 'Is this correct?' in bold. Below it is a large blue button with the text 'Yes, it's correct'. Underneath the button is a blue link 'No, I need to change it'. At the bottom right, the text 'Secured by Duo' is displayed in small font.


14. Now, click on “Send me a passcode” to confirm that you are the owner.




15. Introduce the code and press **Verify**.




16. Open DUO or the camera to scan the QR code presented on the web page.




17. If you have DUO installed, you will see this image. For the ones that need to be installed, follow the steps presented in the browser.




18. Press **Continue**
19. Click on **Skip for now**.



20. Now, you can log in with Duo MFA. Click on **Log in with Duo**



21. Approved the push in your phone and click on *Finish*




22. Please close the current window, open a new tab, and connect directly with <https://beta-ui.cmd.cisco.com/login>

This step is required because we are using the beta environment.


This step needs to be done by one Administrator only

23. Introduce the email address provided by the proctor and used to activate the service. Click on **Continue**.



The screenshot shows the Cisco Security Cloud Sign On interface. At the top is the Cisco logo. Below it, the title "Security Cloud Sign On" is centered. Under the title, there is a label "Email" followed by a text input field containing the email address "alexwayne4@emailsec1.emailsec.io". Below the input field is a blue button labeled "Continue", which is highlighted with a red rectangular box. Below the button, there is a link "Don't have an account? Sign up now". Further down, there is a horizontal line with the word "Or" in the center, followed by the text "Other login options". At the bottom of the page, there are two links: "System status" and "Policy statement".

24. You should now be at the ETD interface. If you see this screen, click on the button with "I agree.."



The screenshot shows the Cisco Secure Email Threat Defense "Terms and Conditions" screen. The header includes the "Secure Email Threat Defense" logo on the left and "SECURE" on the right. The main heading is "Welcome to Cisco Secure Email Threat Defense" followed by "Terms and Conditions". The body of the page contains several paragraphs of legal text regarding the use of Cisco Technology, the EULA, and data collection. At the bottom of the text, there is a blue button labeled "I agree with the terms and conditions", which is highlighted with a red rectangular box. In the bottom right corner of the page, there is a small green circular icon with a white 'X' inside.


Lesson learned.

In this task, we have seen how to activate an Email Threat Defense account. This will be common for all types of deployments, although in today's lab, we will integrate it with O365. The steps are simple and will always be executed with our client's account.


Task – Configure Email Threat Defense account.

The steps we are going to see below are not the usual steps when deploying ETD. This is because we are using an already partially configured BETA environment.

1. Log in again to the beta portal: <https://beta-ui.cmd.cisco.com/login>




2. Accept the push from DUO on your mobile.




3. As we mentioned at the beginning, these are not the usual steps.

Click on **Configuration**



4. The Email Threat Defense account you have access to is already activated to work with a gateway with no integration with O365. We need to connect with O365 and to do this, we need to move from Gateway/No auth to Microsoft 365/Read-Write. Click on **the edit icon**.



5. Click on **“No, Secure Email Gateway is not present”** and then click on **Continue** and **Next**.

Account
TME_Emailsec_1

Dashboard

Messages

Insights

Configuration

Administration

← Back

Edit Analysis Configuration

1 Secure Email Gateway

2 Message sources

3 Visibility

4 Summary

Secure Email Gateway (SEG)

Do you have a Secure Email Gateway?

☒ Yes, Secure Email Gateway is present

☐ No, Secure Email Gateway is not present

Indicate type of SEG and header

☒ Cisco SEG default header (X-ironPort-RemoteIP)

☐ Cisco SEG custom header

☐ Non Cisco SEG custom header

Cancel

Next

Edit Analysis Configuration

1 Secure Email Gateway

2 Message sources

3 Visibility

4 Summary

Secure Email Gateway (SEG)

Do you have a Secure Email Gateway?

☐ Yes, Secure Email Gateway is present

☒ No, Secure Email Gateway is not present

Switch Message Source

You are changing your message source. You will need to reconfigure your current message source to generate a new ID. Do you want to continue?

Cancel

Continue

← Back

Edit Analysis Configuration

1 Secure Email Gateway

2 Message sources

3 Visibility

4 Summary

Secure Email Gateway (SEG)

Do you have a Secure Email Gateway?

☐ Yes, Secure Email Gateway is present

☒ No, Secure Email Gateway is not present

Switch Message Source

Please configure your Gateway to stop sending messages to Secure Email Threat Defense. For details, see the [Cloud Email Gateway documentation](#). Once you have completed this step, select the checkbox below, then click Next to continue.

☒ I have completed this step to stop sending messages to Secure Email Threat Defense.

Back

Next

6. Select “**Read and write**” and click on **Next**.

Account
TME_Emailsec_1

Dashboard

Messages

Insights

Configuration

Administration

← Back

Edit Analysis Configuration

- Secure Email Gateway
- Message sources
- 3 Visibility**
- 4 Summary

Visibility
Select Microsoft 365 permission mode for visibility and remediation.

- ☒ **Read and write (Recommended)**
 - Visibility
 - On-demand remediation
 - Automated remediation (optional)
 - EML Download
- ☐ Read
 - Visibility
 - No remediation
 - EML Download

Cancel

Next

© 2025 Cisco Systems, Inc. Privacy policy Terms of service

7. Let's start the integration with MS365. We need to use the MS365 account provided:
alexwayne6@emailseclabXX.emailsec.io
Click on **Next**

Microsoft

Sign in


alexwayne4@emailseclab1.emailsec.io

No account? [Create one!](#)


Can't access your account?

Next

8. After the password, a new window will appear, asking to move to enable MFA.
Click on **Ask Later**.



9. Click on **Accept**.



Lesson learned.

After activating Email Threat Defense, as in the first task, we made the first connection between Cisco Email Threat Defense and MS365. This connection will still need to analyze the mail. We have activated the ability of Cisco Email Threat Defense to clean the mailboxes, in addition to having decided how we wanted to integrate it.


Configure Cisco Secure Email Threat Defense Policy

Depending on the customer scenario, we may need to adjust which features are enabled. If the customer has a Cisco Secure Gateway (on-prem or cloud), we should leave SPAM and Graymail disabled. In this case, we will enable all the analysis modules.


If you want to learn more:

<https://www.cisco.com/c/en/us/td/docs/security/email-threat-defense/user-guide/secure-email-threat-defense-user-guide/policy.html>



1. On the Cisco Secure Email Threat Defense console, click on **Configuration**:





2. Double check that Secure Email gateway is not selected.
In this lab we don't have any security gateway in front of O365.



3. Click on **Global settings** and then click on the **pencil icon** for Unwanted message analysis. Select all the options and click on **Save**.



4. Now, we are going to enable the malware scanning for all the flows. Click on content analysis **pencil icon**, and check that all the options are marked.



5. We will keep all the Automated Remediation actions disabled. For POV/POC scenarios, you should enable this feature after a couple of weeks, because the AI/ML engines already learned from the customer mail flow. Click on **Policy Configuration**, and then on **pencil icon**.

Configuration

Mail flow configuration
Global settings
Policy configuration

Policy configuration

Configure the remediation actions the system will use for verdict returned by the scanners and exceptions the system will use based on specific senders and recipients.

Incoming
Internal
Outgoing

Incoming rules
Internal rules

Rule name	Sender	No verdict	Threat	Spam	Graymail	Last edited by	Status
Default Base Policy	All	No Action	Move to Junk	Move to Trash	Move to Trash	—	Active

6. Select no Action in incoming and internal rules and then lick on **Save**.

Back
Edit Default Base Policy

Default Base Policy

Configure the remediation actions the system will use for verdict returned by the scanners.

Incoming rules
Internal rules

Category	Action
Threats ⓘ	No Action
Spam ⓘ	No Action
Graymail ⓘ	No Action
No Verdict	No Action

Policy status
Active

Save
Cancel

Lesson learned.


It is essential to understand this task that we have done now. Before managing traffic, we must configure a policy in our Email Threat Defense account. If we do not do this, we may have unexpected behavior since it could be deleting emails we do not want to delete. Therefore, before carrying out the next task, we must have the policy we want to implement configured. In most cases, this will have a monitor mode configuration.

Task – Configure Exchange Online.


In this task, we will configure Exchange Online and review the permissions automatically configured in the previous step.

1. Now we need to go to the Purview Microsoft Admin center and configure the journaling rule.
<https://purview.microsoft.com/>
Microsoft updates the console from time to time. In this case, you can see either the legacy portal or the new Purview portal.
The configuration presented here is for the new Purview console.


Click on **Solutions** and then in **Data Lifecycle Management**.



2. Click in **Settings** and **Data Lifecycle management** and then **Exchange (legacy)**.




3. Click on **Replace**. Before configuring the Journaling rule, you must indicate an email address to receive Undeliverable Reports. Please note that in a production environment, this step may already have been completed by the client.




In the new Microsoft Purview console verify the email address, if the email address is not present, please add it.


admin@inline.emailseclab20.emailsec.io




4. Click on **“Data Lifecycle management”**:





5. Click on **“Exchange Legacy”** and on **“journal Rules”**.
If you see a rule created, please select and remove it.




6. Click on **“New Rule”**



7. Before to fill the rule information, we need to get the journaling email address. Go back to Cisco Secure Email Threat Defense. Open **Settings → Administration** Copy the **Journal Address**.




8. Now in the O365 window, fill all the data. Add a rule name, copy the journal address, and choose **Everyone** and **All Messages**. (Name should be the last box to fill). Click on **Next**:



9. Click on “*Submit*”

This is the most crucial step. All traffic will be sent to Email Threat Defense when you press the submit button. Since we are in a lab, we will not see anything. In a production environment, messages will be sent to ETD immediately, so we must ensure we have the correct policy settings before clicking the Submit button.



10. You should see this screen:




This concludes the ETD and Microsoft integration scenario.


Connector in O365 for ETD traffic.

In some environments, with secure gateways, Exchange on-premises devices, etc., more connectors will be configured. If this happens, it's important that the traffic delivered to ETD goes through one of these platforms without being stopped or delayed. Creating a connector for this traffic will force O365 to send this traffic directly to ETD.

1. Open Exchange Online administration console at <https://admin.exchange.microsoft.com/>
2. Click on **“Mail Flow”** and **“Connectors”**.



3. Click on **“Add a connector”**.



4. Select Connection From “**Office 365**” and Connection to “**Partner Organization**” and click **Next**

The screenshot shows the 'Add a connector' wizard in Microsoft Exchange Online. The left sidebar contains a progress bar with steps: New connector, Name, Use of connector, Routing, Security restrictions, Validation email, and Review connector. The main area is titled 'New connector' and includes the instruction: 'Specify your mail flow scenario, and we'll let you know if you need to set up a connector.' Under 'Connection from', the 'Office 365' radio button is selected and highlighted with a red box. Under 'Connection to', the 'Partner organization' radio button is selected and highlighted with a red box. A blue 'Next' button is at the bottom right.

5. Write a name, in our case we can use “**Outbound to Cisco Secure Email Threat Defense**” and click **Next**.

The screenshot shows the 'Add a connector' wizard at the 'Connector name' step. The left sidebar shows 'New connector' as completed and 'Name' as the current step. The main area is titled 'Connector name' and includes the instruction: 'This connector enforces routing and security restrictions for email messages sent from Office 365 to your partner organization or service provider.' The 'Name' field is populated with 'Outbound to Cisco Secure Email Threat Defense'. The 'Description' field is empty. Under 'What do you want to do after connector is saved?', the 'Turn it on' checkbox is checked. 'Back' and 'Next' buttons are at the bottom.

6. Write the domain that is in your journaling email address. In this lab the domain is ***“beta.cmd.cisco.com”***

Click on **+**

The screenshot shows the 'Add a connector' wizard in the Cisco Email Security Service. The left sidebar contains a progress bar with steps: New connector, Name, Use of connector (current), Routing, Security restrictions, Validation email, and Review connector. The main panel is titled 'Use of connector' and contains the instruction 'Specify when you want to use this connector.' There are two radio button options: 'Only when I have a transport rule set up that redirects messages to this connector' and 'Only when email messages are sent to these domains'. The second option is selected. Below it is a text input field with a placeholder 'Example: * or *.contoso.com or *.com' and a '+' button. The domain 'beta.cmd.cisco.com' has been entered and is highlighted with a red box. A trash icon is visible to the right of the input field. At the bottom of the wizard are 'Back' and 'Next' buttons.

7. Click on **Next**
8. Select ***“Use the MX record associated with the partner’s domain”*** and click on **Next**

Add a connector

- ✓ New connector
- ✓ Name
- ✓ Use of connector
- Routing**
- Security restrictions
- Validation email
- Review connector

Routing

How do you want to route email messages?

Specify one or more smart hosts to which Office 365 will deliver email messages. A smart host is an alternative server and can be identified by using a fully qualified domain name (FQDN) or an IP address.

☒ Use the MX record associated with the partner's domain
 ☐ Route email through these smart hosts

Back Next

9. Select **“Always use Transport Layer Security (TLS) to secure the connection (recommended); Issued by a trusted certificate authority (CA)”** and Click on **Next**

Add a connector

- ✓ New connector
- ✓ Name
- ✓ Use of connector
- ✓ Routing
- Security restrictions**
- Validation email
- Review connector

Security restrictions

How should Office 365 connect to your partner organization's email server?

☒ Always use Transport Layer Security (TLS) to secure the connection (recommended)
 Connect only if the recipient's email server certificate matches this criteria

☐ Any digital certificate, including self-signed certificates

☒ Issued by a trusted certificate authority (CA)

☐ Add the subject name or subject alternative name (SAN) matches this domain name:
 Example: contoso.com or *.contoso.com

Back Next

- Copy the journaling address to validate the connector. Click on “**Validate**”

Note: The connector validation may fail if your O365 tenant is already configured with conditional mail routing using an Exchange transport rule to route outbound mail to an existing connector. While journal messages are system-privileged and are not affected by transport rules, the connector validation test email is not privileged and is affected by transport rules.

The screenshot shows the 'Add a connector' wizard with the 'Validation email' step selected. The left sidebar lists the steps: New connector, Name, Use of connector, Routing, Security restrictions, Validation email (selected), and Review connector. The main area is titled 'Validation email' and contains instructions: 'Specify an email address for an active mailbox that's on your partner domain. You can add multiple addresses if your partner organization has more than one domain.' Below this, there is a text input field with 'Example: user@contoso.com' and a '+' button. A second email address, 'd24f1c54-c134-40c4-9a30-dea6a8322e28@beta.cmd.cisco.com', is listed below the input field with a trash icon to its right. A 'Validate' button is positioned below the email list. At the bottom of the wizard, there are 'Back' and 'Next' buttons.

Validation process takes some time to perform and not always is successful. If everything works you will see something like the picture below.

The screenshot shows the confirmation screen after a successful validation. At the top, the email address 'd24f1c54-c134-40c4-9a30-dea6a8322e28@beta.cmd.cisco.com' is displayed with a copy icon. Below this is a 'Validate' button. A green banner with a checkmark icon and the text 'Validation successful' is shown. Underneath, there is a table with two columns: 'Task' and 'Status'.

Task	Status
Send test email	Succeed

- Click on “**Create Connector**”

Add a connector

✓ New connector

✓ Name

✓ Use of connector

✓ Routing

✓ Security restrictions

✓ Validation email

● Review connector

Review connector

Mail flow scenario

From: Office 365
To: Partner organization

Name

Outbound to Cisco Secure Email Threat Defense

Status

Turn it on after saving
[Edit name](#)

Use of connector

Use only for email sent to these domains: beta.cmd.cisco.com
[Edit use](#)

Routing

Use the MX record associated with the partner's domain.
[Edit routing](#)

Security restrictions

Back

Create connector

Lesson learned.

We have already finished the integration between ETD and O365 in both directions.
The next step is to verify the operation and carry out tests.


Task –Review the permissions assigned in Microsoft (optional)

Frequently, customers ask about the permissions required to integrate ETD with Microsoft to be able to use the Read-Write mode on ETD.


Let's see what Microsoft permissions are assigned to Cisco ETD.

1. Open the Azure portal with the O365 account provided for this lab:


<https://azure.microsoft.com/en-us/get-started/azure-portal/>




2. Click on ***All resources***




3. Click on ***Microsoft Entra ID***.




4. Click on “**Enterprise Applications**”.



5. If the integration is correct, you will see an entry with the name “**Cisco Secure Email...**”



6. Click on Permissions



7. If you open the application, you can see the permissions assigned.

Enterprise Application

Permissions

Overview

Deployment Plan

Diagnose and solve problems

Manage

- Properties
- Owners
- Roles and administrators
- Users and groups
- Single sign-on
- Provisioning
- Self-service
- Custom security attributes

Security

- Conditional Access
- Permissions
- Token encryption

Activity

Review permissions

Refresh

Got feedback?

Permissions

Below is the list of permissions that have been granted for your organization. As an administrator, you can grant permissions to this app on behalf of all users (delegated permissions). You can also grant permissions directly to this app (app permissions).
[Learn more](#)

You can review, revoke, and restore permissions.
[Learn more](#)

Grant admin consent for emailsec2

Admin consent

User consent

Search permissions

API name	Claim value	Permission	Type	Granted through	Granted by
Microsoft Graph (3)					
Microsoft Graph	Mail.ReadWrite	Read and write mail in all mailboxes	Application	Admin consent	An administrator
Microsoft Graph	Domain.Read.All	Read domains	Application	Admin consent	An administrator
Microsoft Graph	Organization.Read.All	Read organization information	Application	Admin consent	An administrator

CISCO

Copyright © 2025 Cisco Systems, Inc. All rights reserved. Cisco, Cisco Systems and the Cisco Systems logo are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries. Cisco International Ltd, 9-11 New Square, Bedford Lakes, Feltham, Middlesex, TW14 8HA, United Kingdom. Registered number: 2558939 Registered in England and Wales.


Page 40 of 83

Task – Test the solution.


To continue this lab, you are going to generate email traffic. Since the account is valid, you can send emails from your own business or personal account, and you see how it appears in the ETD admin interface.

You will test all the options to verify that everything is working as expected.


1. Open your Email client(business or personal) and send an email to the account created in Exchange Online. Something like alexwayne6@emailsec1.emailsec.io (Please use your admin user and pod number)




2. In the Email Threat Defense dashboard, on the **Messages** tab, you will see information about the email you just sent:



- Using your business or any other email account, send an email to **alexwayne6+test@emailseclabXX.emailsec.io** or **bsmith+test@emailseclabXX.emailsec.io**. (Please use your pod number)



- You should see something like this in your ETD console.



- Open both messages and compare the “Delivered To” field. As you can see, both messages arrived in the same mailbox. “Delivered To” means who is the destination (final Mailbox). Many times, we will see “To”, “Envelope To” and “Delivered To” totally different. This happens when email is going to a Distribution List, Alias, BCC, etc.


ETD allows you to understand exactly where the email was sent to and who received it.

Recipients (1) To/Cc alexwayne4@emailsec1b1.emailsec.io	Envelope Recipients (1) Envelope to jalcxwayne4@emailsec1b1.emailsec.io
Mailbox List (1) Mailboxes alexwayne4@emailsec1b1.emailsec.io	Status at time of remediation N/A


Recipients (1) To/Cc alexwayne4+test@emailsec1b1.emailsec.io	Envelope Recipients (1) Envelope to alexwayne4+test@emailsec1b1.emailsec.io
Mailbox List (1) Mailboxes alexwayne4@emailsec1b1.emailsec.io	Status at time of remediation N/A

6. If you want to confirm that both messages were delivered to the same destination, please open Outlook for your O365 admin user by clicking on <https://outlook.office.com/mail/>


You should have these two emails.



7. Go back to the ETD dashboard, and on the Messages tab, please select one of the messages and remove the email. Select **“Keep Verdict”** and **“Move to Junk”**. Then click **“Update”**.



8. Automatically the email should disappear from the user's inbox and appear in the junk folder. Please go back to Outlook and confirm that the message is now in the Junk folder:



This concludes this task, and you may continue to the next one.

Lesson learned.


In this task, we have carried out several tests and seen how Email Threat Defense displays the information in the console. We have also conducted a test with an alias to understand what some of the parameters appearing in the console mean.

Task - High Impact Personnel

Important personnel, such as members of executive leadership teams, are at risk of being impersonated in an attempt to compromise other targets. The high-impact personnel list helps Secure Email Threat Defense defend your organization from impersonation attacks.

Admins can create a list of up to 100 people that is sent to Cisco Talos for higher scrutiny on Display Name and Sender Email Address. Deviations from the configured information for an individual will be identified as a Technique in the Verdict Details panel of convicted messages.

1. Open the Cisco Email Threat Defense console.
2. Click on Administration → High Impact Personnel.



3. Click on **“Add New Personnel”**
4. We can add some names. In the list below we have the list of users created by Microsoft by default. Then you can add some of them manually in your environment. Add the users that you have in your environment. (You can see a list below)

Add New Personnel

✕

First Name

Last Name

First Name

↑

First Name

↑

Title

Business Phone

Mobile Phone

Email Address

0 of 5 max email addresses entered

Enter multiple email addresses separated by comma

Cancel

Submit

First Name	Last Name	Title	Email Address
Alex	Wayne	SE Manager	Alexwayne6@ emailseclabXX.emailsec.io
Blake	Smith	SE Director	Bsmith@ emailseclabXX.emailsec.io

Exchange admin center

Home

Recipients

Mailboxes

Groups

Resources

Contacts

Mail flow

Roles

Migration

Mobile

Reports

Insights

Home > Mailboxes

Manage mailboxes

Create and manage settings for shared mailboxes. You can also manage settings for user mailboxes, but to add or delete them you must go to the [Microsoft 365 admin center](#) and do this on the [active users](#) page. [Learn more about mailboxes](#)


+ Add a shared mailbox

Mailflow setting

Refresh

Export mailboxes

Display name ↑	Email address	Recipient type
Jane Noone	janoone@emailsec lab2.emailsec.io	UserMailbox
Marc Marquez	marcmarquez@emailsec lab2.emailsec.io	UserMailbox



5. Open the web site: <https://emkei.cz/>

6. Fill the form with this information. (the name must be one of the ones from your list).

From Name: Alex Wayne

From Email: Jane@pepe.com

To: alexwayne6@emailseclabXX.emailsec.io or Bsmith@emailseclabXX.emailsec.io (You must put your O365 email domain).

Content Type: text/html

Subject: This is a test

Body: Hello

PEPE'S MAILER

Free online fake mailer with attachments, encryption,
HTML editor and advanced settings...

From Name:

From E-mail:

To:

Subject:

Attachment: No file chosen

Content-Type: ☒ text/plain ☐ text/html ☐ Editor

Text:
 Finance
 Veronica

Captcha: ☐ I am human 


7. Repeat the same as before but change the body content adding [http://www\[.\]ihaveabadreputation\[.\]com](http://www[.]ihaveabadreputation[.]com)

Content-Type: ☒ text/plain ☐ text/html ☐ Editor

Text:
 bla bla bla
<https://www.ihaveabadreputation.com>

Captcha: ☐ I am human 

8. Review If both messages were processed by Cisco Secure Email Threat Defense.



9. If you don't see a message processed by Email Threat Defense, then maybe O365 detected as malicious and quarantined it. In this case, open the O365 quarantine and release the email. Remember that Microsoft will process all the emails before Cisco Secure Email Threat Defense.
<https://security.microsoft.com/quarantine?viewid=Email>

Microsoft Defender

Home

Investigation & response

Threat intelligence

Microsoft Sentinel

Email & collaboration

Reports

Trials

More resources

Search

Review > Quarantine

Learn more

Quarantine

Email

Refresh

Release

Approve release

Deny

Delete messages

Preview message


More

1 of 2 selected


Search

Filters: Time received: Last 30 days


☐ Time received	Subject	Sender	Quarantine reason	Release status	Policy type	Expires	Recipient
☒ Apr 24, 2024 1:26:03 PM	This is a test 2	veronica@pepe.com	Malware	Needs review	Anti-malware policy	May 24, 2024 1:26...	johnnoone@pod10...
☐ Apr 24, 2024 4:47:19 AM	This is a test	diego@pepe.com	Malware	Released	Anti-malware policy	May 24, 2024 4:47...	johnnoone@pod10...




10. Go back to Cisco Secure Email Threat Defense and Open **“High Impact Personnel”**.



11. You should see a number next to the name, this indicates how many HIP detections have occurred.



- Click on Messages and expand the message detected as phishing. You should see a “User Impersonation” technique.




Task – “Attack” your environment.

Send Email Threats.


To be able to see ETD detection capabilities, threat messages must be sent to users. For this lab, we have prepared a group of threat messages (around 60) to be sent to users created within the Microsoft E5 dev account.

Use this email tool just for lab purposes. Actions are being logged.
Microsoft can block the traffic coming from these IPs, if this happens you can create traffic manually from a free account or from <https://emkei.cz/>.
As a malicious IOC you can use [http://www\[.\]ihaveabadreputation\[.\]com](http://www[.]ihaveabadreputation[.]com)


1. Connect to any of the sites below, insert your email domain, and press **Submit**.
<http://3.19.33.33:5000/>




2. Wait for the “Thank you for submitting your domain:” message to be displayed on the screen. **This message may take up to 3min to show.**



- Go back to your ETD dashboard. On the Home tab or at the Messages tab, you should be able to see threat messages in the 6 categories: BEC, Scam, Phishing, Malicious, Spam, and Graymail




- Open on of the messages and check the information. In the picture we are opening a phishing email.




5. You should see emails have come in. In some cases, O365 will stop some emails. These will remain in the Microsoft quarantine and will not be analyzed by ETD. If, for some reason, this email is released from quarantine, that email will be scanned by ETD.
Open the Microsoft Quarantine <https://security.microsoft.com/quarantine?viewid=Email> and review if there is any email. You can release them.
Remember that Microsoft may display the emails after some minutes.


6. Open one message and click on “**Conversation view**”.




7. In the screen you will see one circle with two + symbols, click on both + symbols. Nothing must change.



8. Open Your Administrator mailbox and forward the same message to another internal user. In the screen the message that we are using is "Search results For: Solar-Power In Homes " <https://outlook.office.com/mail/>




9. We will forward to ***bsmith@emailsecclabXX.emailsec.io***. (Use your pod number)




- Now, go back to Email Threat Defense dashboard and click on messages. Search for the internal email you sent to Blake Smith.

☐	Verdict	Action	Rule	Received	Sender (Display Name)	Recipients	Subject	Direction	Actions
☐				Apr 24 202...	John Noone <Jo...	veronicastroll@p...	Fw: " Search results For: Solar-Power In Hom...	Internal	>

- You can see an internal email. Open the message and click on **“Conversation View”**



12. Your output should be as the next picture.




Task – Dashboard use case

Search Messages

This task will allow us to learn how to use searches from the Cisco Email Threat Defense console. We cannot see all the options in this lab, but it is essential that you perform searches so you can see how it works.

1. Click on Messages



2. Click on the “filters” text.

The image shows a close-up of the 'Filters' button in the Cisco Secure Email Threat Defense dashboard. The button is located below the search bar and is highlighted with a red box. The text 'Filters' is visible next to the button. The table of messages is also visible in the background.

Verdict	Action	Rule	Received	Sender	Recipients	Subject	Direction
BEC	—	—	Jan 27 2025 02:43 PM CST	Veronica Stroll <john...	johnnoone@emailsec...	test	Incoming
Malicious	—	—	Jan 27 2025 02:38 PM CST	Veronica Stroll <john...	johnnoone@emailsec...	This a test	Incoming
BEC	—	—	Jan 27 2025 02:36 PM CST	Veronica Stroll <john...	johnnoone@emailsec...	This is a test	Incoming
Malicious	—	—	Jan 27 2025 02:32 PM CST	Greg Barnes (grebarn...	johnnoone@emailsec...	test rep	Incoming
—	—	—	Jan 27 2025 02:13 PM CST	Greg Barnes (grebarn...	johnnoone+test@em...	test 3	Incoming
—	—	—	Jan 27 2025 02:03 PM CST	Greg Barnes (grebarn...	johnnoone@emailsec...	Test 2	Incoming
—	—	—	Jan 27 2025 01:42 PM CST	Greg Barnes (grebarn...	johnnoone@emailsec...	test	Incoming

3. Using the options, search for all the emails detected as “All Threats” and click “Apply”.

Secure Email Threat Defense

Search Messages for a URL, subject line, recipient, or IP

Gregory

Account

TME_Emailsec_2

Dashboard

Messages

Insights

Policy

Administration

Threats

4 Total

BEC: 2

Scam: 0

Phishing: 0

Malicious: 2

Messages

7 Total

Incoming: 7

Internal: 0

Outgoing: 0

Trend comparison

last 24h

6

0

2pm 4pm 6pm 8pm 10pm 12am 2am

7 results as of Jan 27 2025 02:44 PM CST

Verdict	Action	Rule	Received	Sender	Recipients	Subject
BEC	—	—	Jan 27 2025 02:43 PM CST	Veronica Strolli <john...>	johnnoone@emailsec...	test
Malicious	—	—	Jan 27 2025 02:38 PM CST	Veronica Strolli <john...>	johnnoone@emailsec...	This a
BEC	—	—	Jan 27 2025 02:36 PM CST	Veronica Strolli <john...>	johnnoone@emailsec...	This is a t
Malicious	—	—	Jan 27 2025 02:32 PM CST	Greg Barnes (grebam...	johnnoone@emailsec...	test re
—	—	—	Jan 27 2025 02:13 PM CST	Greg Barnes (grebam...	johnnoone+test@em...	test 3
—	—	—	Jan 27 2025 02:03 PM CST	Greg Barnes (grebam...	johnnoone@emailsec...	Test 2
—	—	—	Jan 27 2025 01:42 PM CST	Greg Barnes (grebam...	johnnoone@emailsec...	test

Filters

Verdicts

All Threats

BEC

Scam

Phishing

Malicious

Spam

Graymail

Neutral

No Verdicts

Last action

Move to Junk

Move to Trash

Move to Inbox

Move to Quarantine

Delete

No Actions

Message rules

Allow List

Verdict Override

Bypass Analysis

No Rules

Reset all


Cancel

Apply


Manual Remediation.

We are going to manually remove/remediate some phishing emails discovered in the previous task.

1. Open the admin mailbox in another browser window. <https://outlook.office.com/mail/>



2. You must have two windows, one with Cisco Email Threat Defense and other with the administrator Mailbox.
3. In Cisco Email Threat Defense console, select one email. A new menu will appear.




4. Click on the Reclassify dropdown menu.


The screenshot shows the Cisco Secure Email Threat Defense interface. The top navigation bar includes the Cisco logo, the product name "Secure Email Threat Defense", a search bar, and a user profile "Gregory". The left sidebar contains navigation links for Account, Dashboard, Messages, Insights, Policy, and Administration. The main content area is titled "Messages" and displays a "Threats" summary (4 Total) with a donut chart showing counts for BEC (2), Scam (0), Phishing (0), and Malicious (2). It also shows a "Messages" summary (4 Total) with a donut chart for Incoming (4), Internal (0), and Outgoing (0). A "Trend comparison" graph for the last 24 hours shows Threats (red line) and Messages (blue line). Below these summaries is a table of messages with columns for Verdict, Action, Sender, Recipients, Subject, and Direction. A dropdown menu is open over the "Reclassify" button, showing options: BEC, Scam, Phishing, Malicious, Spam, Graymail, Neutral, and Keep verdict. The "Keep verdict" option is highlighted. The table shows four messages, all with a "BEC" verdict and "Incoming" direction.

5. Select "Keep verdict".


If we change the verdict, the information will be sent automatically to Talos. As this is a lab, we don't want to send anything.




6. Click on the “Request Action” dropdown menu and select “**Move to Junk**”




7. Click on **Update**




8. You should see this information.



9. Open the window browser with the admin Mailbox. The email should be moved to the junk folder.



10. On the Cisco Email Threat Defense console, open the message click in the arrow. In this window you can see the timeline, and last step is the remediation process.



Lesson learned.

In this task, we have seen how to perform searches, and we have seen the "Timeline" option. There are other options, such as "Download the EML", which you can try. This allows you to download a copy of the email in EML format.

Task – API & Postman.

As you know, APIs are being promoted in all security platforms, and email platforms are no exception. Saying this, Cisco Secure Email Gateways and Cisco Email Threat Defense provide REST APIs to integrate with external tools and applications.

Cisco XDR is one of the applications that can use the APIs to improve the detection, analysis, and convictions of messages.

Today, you will see how the Message Search API in Email Threat Defense works.

In this lab, you will learn how to use Postman's as an API client.

Postman can be installed on our workstation or you can use their cloud application without installation.

If you want to use the cloud application, we need to create an account on the Postman portal. It is explained in [Appendix A](#).

To use the Message Search API there are 2 steps required:


- 1 – Use the client credentials to authenticate and to get an access token
- 2 – Use the access token from Step 1 and query the message information

If you want to learn more:


<https://developer.cisco.com/docs/message-search-api/>

Authentication API

1. You must create API credentials in our Email Threat Defense account.
Open the Email Threat Defense console. <https://beta-ui.cmd.cisco.com/>
2. Click on “*Administration*” -> “*API Clients*”.



3. Click on “[Add New Client](#)”.



4. Fill in the “[Client Name](#)” box. We can name it “[Postman](#)”, and then click on “[Submit](#)”.

Add New API Client

Client Name
Postman

Description
Add description...

Cancel Submit

5. Copy the “*Client ID*” and “*Client Password*” in your text editor.

Please make sure you copy the Client Password. You will not be able to retrieve it later.

Add New API Client

⚠ The Client Password cannot be recovered, once you close this window.
Please store securely.

Client ID
70edcdce-f51b-4f16-ae99-abd056d2d755

Client Password
GVSLQIL22F7Qyc1waCKbgmef3DE8EtP8-gUzEWgmgOE

Close


6. Click on “*Close*”

7. Open “**Postman**” application


If you don't have the Postman application installed, you can go to Appendix A and check the steps to create an account or install the application on your desktop.

<https://www.postman.com/api-platform/api-client/>


8. Create a “*New collection*”.



9. You can use the name “*ETD LAB BETA*”.



10. Click on “*Add a request*” inside the “*New collection*” you created in the previous step.



11. You can name “*authentication*” as the new name.

ETD LAB BETA / Authentication

GET Enter URL or paste text

Params Authorization Headers (6) Body Pre-request Script Tests Settings

Query Params

	Key	Value
	Key	Value

12. Put the following link in the “**Enter URL..**” box: <https://api.beta.etd.cisco.com/v1/oauth/token>
13. Click on the “**Headers tab**” and add the API key to identify the ETD tenant.


POST https://api.de.etd.cisco.com/v1/oauth/token Send

Params Authorization Headers (10) Body Scripts Settings Cookies

Headers 9 hidden

	Key	Value	Description		Bulk Edit	Presets
☒	x-api-key	hGEaUD4VyI3WLA5rHfjuA1ZRstqT7dgf7mDaxKTL				
	Key	Value	Description			

14. Select “**Authorization tab**” and select “**Basic Auth**”. In the Basic auth, you will use “Client ID” as username and “Client Password” as Password. The method used in this query must be “**POST**”.




You should see a message with the “*accessToken*” in the response. This will be the token you will query message information in the next task.

Search API


Once we have completed the authentication process, we will use the token obtained for the search API.

In the exercise, we will carry out several searches, but you can do more.


1. Click on “+” to create a new request.




2. Click on **Save**.



3. Name the query “**ETD Search Phishing**”.
You will create a query to search all the phishing emails during the last 2 hours.



4. Put the following link in the “*Enter URL..*” box: <https://api.beta.etd.cisco.com/v1/messages/search> And Select **Post**.



5. Open **Authorization** tab and select **Bearer Token**.

Params Authorization Headers (10) Body Scripts Settings		
Headers 9 hidden		
Key	Value	Description
☒ x-api-key	hGEaUD4Vyl3WLA5rHfjuA1ZRstqT7dgf7mDaxKTL	
Key	Value	Description

8. Now, click on the **"Body"** tab, and inside the Body tab select **"raw"**.
In the body, we will configure the search query. There are different attributes that we can use, the first task will be simple, and we will search all the Phishing emails in the last 24 hours.

POST ETD Search Phishing • POST ETD Token Request + ... No Environment

ETD API Search / ETD Search Phishing Save Send Cookies

POST https://api.beta.etd.cisco.com/v1/messages/search

Params Authorization Headers (9) **Body** Pre-request Script Tests Settings

none form-data x-www-form-urlencoded **raw** binary GraphQL Text

```

1 {
2   "verdicts": [
3     "phishing"
4   ],
5   "timestamp": [
6     "2023-10-09T06:00:00Z",
7     "2023-10-09T08:00:00Z"
8   ]
9 }
10

```

9. Copy the JSON text into the **raw** section. (Review the timestamp and adapt this to your current date).

```

{
  "timestamp":[
    "2024-11-06T08:00:00.300Z", "2024-11-06T13:00:00.000Z"
  ],
  "verdicts":[
    "bec", "scam", "phishing", "malicious"
  ]
}

```

}

Adapting the time zone to UTC to use the search API query is essential.


DateTimeRange ▾ [

example: List ["2019-09-19T12:00:00Z", "2019-09-20T23:59:59Z"]


ISO 8601 formatted date time string range e.g ["2019-09-19T12:00:00Z", "2019-09-20T23:59:59Z"]. Beginning and end dates are inclusive. Timestamps should be in UTC timezone only. No other timezone is supported. First timestamp should be smaller than second.

string]

10. Click on **Send**.




11. If everything is working, you will see something like this.



12. You can use this online tool to work with the JSON response.

<https://jsonpathfinder.com/>

13. Copy the output from Postman to the JsonPathFilder tool.



In this link, we can see all the options that we can use in the queries.



<https://developer.cisco.com/docs/message-search-api/#!/message-search-api>

```
{
  "subject": "string",
  "from": "string",
  "recipient": "string",
  "filename": "string",
  "fileSHA256": "string",
  "verdicts": [
    "spam"
  ],
  "directions": [
    "incoming"
  ],
  "url": "string",
  "internetMessageId": "string",
  "pageSize": 100,
  "pageToken": "string",
  "timestamp": [
    "2023-10-01T12:00:00Z",
    "2023-10-02T23:59:59Z"
  ]
}
```

14. Change the verdict and test other from the list.

Verdict ▾ `string`

Search for messages with specific verdicts.

Enum:

▾ [`spam`, `malicious`, `phishing`, `neutral`, `graymail`, `bec`, `scam`]

Conclusion

If you have arrived here, you have reached the end of the laboratory. Congratulations.
You can repeat some of the exercises performed using different parameters, different emails, etc.




Remember that the deployment method and environment were simple.
Yes in. In our scenario, we find security gateways, local exchange, etc, and some configurations could change.

APPENDIX


Postman Installation

This is not intended to be a Postman manual, simply to highlight the steps to take to create a Postman account. As you can see they are very simple.

1. Open the link <https://www.postman.com/product/api-client/>
2. Click on “**Sign Up**”



3. Fill the form. You can use your cisco email, or whatever you want. And click on “**Create free account**”.



POSTMAN

Why sign up?

- Organize all your API development within Postman Workspaces
- Sync your Postman data across devices
- Backup your data to the Postman cloud
- It's free!



Create Postman Account [Sign In instead?](#)

Email
admin@3vzsvh.onmicrosoft.com

Username
admin3vzsvh

Password SHOW
.....

☐ Sign up to get product updates, news, and other marketing communications.

☒ Stay signed in

By creating an account, I agree to the [Terms](#) and [Privacy Policy](#).


Create free account

or

 **Sign up with Google**

Sign in with SSO

4. Fill the form and click on **Continue**



POSTMAN


Welcome to Postman! Tell us a bit about yourself.

Your name
John Lab


What is your role?
Knowing your role will help us offer you a better experience

Technical Architect

Continue




5. Now you are inside of Postman cloud service.




6. Save and reserve the credentials for the lab.

7. If you want, you can download a local client. Click on [Home](#)



8. Click on “Download Desktop App”



9. Select your SO and install the application.

The screenshot shows the Postman website on the left and the Postman application interface on the right. The website has a navigation bar with links for Product, Pricing, Enterprise, Resources and Support, and Explore. A 'Launch Postman' button is in the top right. The main heading is 'Download Postman', followed by a subheading: 'Download the app to get started using the Postman API Platform today. Or, if you prefer a browser experience, you can try the web version of Postman.' Below this, there are three sections: 'The Postman app' with download links for Mac Intel Chip and Mac Apple Chip (highlighted with a red box), 'Postman on the web' with a 'Launch Postman' button, and 'Postman Enterprise' with a 'Learn more' link. The application interface on the right shows a sidebar with 'Collectors' and 'Environments'. The main area displays a 'GET' request to 'https://api.notion.com/v1/databases/id' with a 'Send' button. Below the request, there are tabs for 'Params', 'Auth', 'Headers', 'Body', 'Pre-req', 'Tests', and 'Settings'. The 'Params' tab is active, showing a table with columns 'KEY', 'VALUE', and 'DESCRIPTION'. The table contains one row with 'id' as the key and '((DATABASE_ID))' as the value. The 'Body' tab is also visible, showing a JSON response.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

