



# Deploy the ASAv Auto Scale Solution on GCP

---

- [Auto Scale Solution for ASAv on GCP, on page 1](#)
- [Download the Deployment Package, on page 3](#)
- [Auto Scale Solution Components, on page 3](#)
- [Auto Scale Solution Prerequisites, on page 6](#)
- [Deploy the Auto Scale Solution, on page 12](#)
- [Auto Scale Logic, on page 17](#)
- [Auto Scale Logging and Debugging, on page 17](#)
- [Auto Scale Guidelines and Limitations, on page 18](#)
- [Auto Scale Troubleshooting, on page 19](#)

## Auto Scale Solution for ASAv on GCP

The following sections describe how the components of the auto scale solution work for the ASAv on GCP.

### About the Auto Scale Solution

ASAv auto scale for GCP is a complete serverless implementation that makes use of serverless infrastructure provided by GCP (Cloud Functions, Load Balancers, Pub/Sub, Instance Groups, etc.).

Some of the key features of the ASAv auto scale for GCP implementation include:


- GCP Deployment Manager template-based deployment.
- Support for scaling metrics based on CPU.
- Support for ASAv deployment and multi-availability zones.
- Completely automated configuration automatically applied to scaled-out ASAv instances.
- Support for Load Balancers and multi-availability zones.
- Cisco provides an auto scale for GCP deployment package to facilitate the deployment.

## Auto Scale Use Case

The ASAv auto scale for GCP is an automated horizontal scaling solution that positions an ASAv instance group sandwiched between a GCP Internal load balancer (ILB) and a GCP External load balancer (ELB).

- The ELB distributes traffic from the Internet to ASAv instances in the instance group; the firewall then forwards traffic to the application.
- The ILB distributes outbound Internet traffic from an application to ASAv instances in the instance group; the firewall then forwards traffic to the Internet.
- A network packet will never pass through both (internal & external) load balancers in a single connection.
- The number of ASAv instances in the scale set will be scaled and configured automatically based on load conditions.

**Figure 1: ASAv Auto Scale Use Case**



## Scope

This document covers the detailed procedures to deploy the serverless components for the ASAv Auto Scale for GCP solution.

**Important**

- Read the entire document before you begin your deployment.
- Make sure the prerequisites are met before you start deployment.
- Make sure you follow the steps and order of execution as described herein.

## Download the Deployment Package

The ASAv Auto Scale for GCP solution is a GCP Deployment Manager template-based deployment that makes use of the serverless infrastructure provided by GCP (Cloud Functions, Load Balancers, Pub/Sub, Instance Groups, etc.).

From the download location specified by your beta manager, download the files required to launch the ASAv auto scale for GCP solution. Deployment scripts and templates for your ASA version are available at the specified download location.

**Attention**

Note that Cisco-provided deployment scripts and templates for auto scale are provided as open source examples, and are not covered within the regular Cisco TAC support scope.


## Auto Scale Solution Components

The following components make up the ASAv auto scale for GCP solution.

**Deployment Manager**

- Treat your configuration as code and perform repeatable deployments. Google Cloud Deployment Manager allows you to specify all the resources needed for your application in a declarative format using YAML. You can also use Python or Jinja2 templates to parameterize the configuration and allow the reuse of common deployment paradigms.
- Create configuration files that define the resources. The process of creating those resources can be repeated over and over with consistent results. See <https://cloud.google.com/deployment-manager/docs> for more information.


Figure 2: Deployment Manager View



### Managed Instance Group in GCP

A Managed Instance Group (MIG) creates each of its managed instances based on the instance template and optional stateful configuration that you specify. See <https://cloud.google.com/compute/docs/instance-groups> for more information.

Figure 3: Instance Group Features




### Target Utilization Metrics

- The following diagram alongside shows the target utilization metrics. Only average CPU utilization metrics are used in making autoscaling decisions.
- The autoscaler continuously collects usage information based on the selected utilization metric, compares actual utilization to your desired target utilization, and uses this information to determine whether the group needs to remove instances (Scale In) or add instances (Scale Out).
- The target utilization level is the level at which you want to maintain your virtual machine (VM) instances. For example, if you scale based on CPU utilization, you can set your target utilization level at 75% and

the autoscaler will maintain the CPU utilization of the specified group of instances at or close to 75%. The utilization level for each metric is interpreted differently based on the autoscaling policy. See <https://cloud.google.com/compute/docs/autoscaler> for more information.

**Figure 4: Target Utilization Metrics**



### Serverless Cloud Functions

You use serverless Google Cloud functions for setting the SSH Password, enable Password, and Changing the Hostname when the instance comes up in the Instance Group Manager.


- When a new ASAv instance comes up in the instance group during Scale Out, you need to set the SSH Password, enable Password, and change the Hostname because you cannot always monitor the Scale Out process.
- Cloud functions are triggered through a Cloud Pub/Sub Topic during the Scale Out process. You also have a Log Sink with a filter that is exclusive to the addition of instances while Scale Out.

### Serverless License Deregistering using Cloud Functions

- While the instances are getting deleted during Scale In, you need to deregister the license from the ASAv instance.
- Cloud functions are triggered through a Cloud Pub/Sub Topic. Particularly for the deletion process, you have a Log Sink with a filter that is exclusive to the deletion of instances while Scale In.
- Cloud Function, when triggered, will SSH into the deleting ASAv instance and run the command for license deregistration.

## High-Level Overview of Autoscale Solution

Figure 5: Autoscale Solution Overview



# Auto Scale Solution Prerequisites

## GCP Resources

### GCP Project

An existing or newly created project is required to deploy all the components of this solution.

### Networking

Make sure three VPCs are available/created. An auto scale deployment will not create, alter, or manage any networking resources.

The ASAv requires 3 network interfaces, thus your virtual network requires 3 subnets for:

- Management traffic
- Inside traffic
- Outside traffic

**Figure 6: VPC Network View**

New Tab

VPC networks - VPC network -

https://console.cloud.google.com/networking/networks/list?project=asavgcp-poc-4km

Google Cloud Platform

ASAVGCP

Search products and resources

VPC network

VPC networks

External IP addresses

Bring your own IP

Firewall

Routes

VPC network peering

Shared VPC

Serverless VPC access

Packet mirroring

VPC networks

CREATE VPC NETWORK

REFRESH

	asia-south2	default		10.190.0.0/20	10.190.0.1
	australia-southeast2	default		10.192.0.0/20	10.192.0.1
▼ demo-test-inside		1	1460	Custom	2 Off
	us-central1	demo-test-inside-subnt		10.61.1.0/24	10.61.1.1
▼ demo-test-mgmt		2	1460	Custom	1 Off
	us-central1	demo-test-mgmt-subnt		10.61.3.0/24	10.61.3.1
	us-central1	demo-test-vpcconnect		10.62.1.0/28	10.62.1.1
▼ demo-test-outside		1	1460	Custom	1 Off
	us-central1	demo-test-outside-subnt		10.61.2.0/24	10.61.2.1

## Firewall

Firewall rules that allow inter VPC communication and also allow health probes are required to be created. You must note the firewall tags which are used later in the deployment manager template.

The following ports should be open in the Network Security Group to which the subnets are connected:

- SSH(TCP/22) — Required for the health probe between the Load Balancer and ASAv. Required for communication between the serverless functions and ASAv.
- Application-specific protocol/ports — Required for any user applications (for example, TCP/80, etc.).

## Prepare the ASA Configuration File

Prepare an ASAv configuration file which will be put into the deployment manager jinja configuration file. This configuration will be used as a startup script in the instance template for ASAv in the project.

The configuration file should have the following (at a minimum):

- Set DHCP IP assignment to all the interfaces.
- Nic0 should be marked as 'outside' because GCP Load Balancer forwards traffic only to nic0.
- Nic0 will be used to SSH to ASAv as it only supports IP forwarding.
- Enable SSH on the outside interface in ASA configuration.
- Create NAT configuration to forward traffic from outside to inside interface.
- Create Access policy to allow desired traffic.
- For the health status of resources, their health probes should be redirected to the metadata server using proper NAT rules.

The following is a sample ASA configuration file for reference only.

```

!ASA Version 9.15.1.10
!Interface Config
interface G0/0
nameif inside
security-level 100
ip address dhcp setroute
no shutdown

interface G0/1
nameif management
security-level 50
ip address dhcp setroute
no shutdown

interface M0/0
no management-only
nameif outside
security-level 0
ip address dhcp setroute
no shutdown
!
same-security-traffic permit inter-interface
!
!Due to some constraints in GCP,
!"GigabitEthernet0/0" will be used as a Management interface
!"Management0/0" will be used as a data interface
crypto key generate rsa modulus 2048
ssh 0.0.0.0 0.0.0.0 management
ssh version 2
ssh timeout 60
aaa authentication ssh console LOCAL
ssh authentication pubkey {{ properties["publicKey"] }}
username admin privilege 15
username admin attributes
service-type admin

! required config end
dns domain-lookup management
dns server-group DefaultDNS
name-server 8.8.8.8
!
access-list all extended permit ip any any
access-list out standard permit any4
access-group all global
! Objects
object network metadata
host 169.254.169.254
object network ilb
host $(ref.{{ properties["resourceNamePrefix"] }}-ilb-ip.address)
object network hc1
subnet 35.191.0.0 255.255.0.0
object network hc2
subnet 130.211.0.0 255.255.63.0
object network elb
host $(ref.{{ properties["resourceNamePrefix"] }}-elb-ip.address)
object network appServer
host 10.61.2.3
object network defaultGateway
subnet 0.0.0.0 0.0.0.0
! Nat Rules
nat (inside,outside) source dynamic hc1 ilb destination static ilb metadata

```



```

nat (inside,outside) source dynamic hc2 ilb destination static ilb metadata
nat (inside,outside) source dynamic defaultGateway interface
!
object network appServer
nat (inside,outside) static $(ref.{{ properties["resourceNamePrefix"] }}-elb-ip.address)
object network defaultGateway
nat (outside,inside) dynamic interface
! Route Add
route inside 0.0.0.0 0.0.0.0 10.61.1.1 2
route management 0.0.0.0 0.0.0.0 10.61.3.1 3
license smart register idtoken <licenseIDToken>

```

## Build the GCP Cloud Function Package

The ASAv GCP auto scale solution requires that you build two archive files that deliver the cloud functions in the form of a compressed ZIP package.

- scalein-action.zip
- scaleout-action.zip

See the auto scale deployment instructions for information on how to build the scalein-action.zip and scaleout-action.zip packages.

These functions are as discrete as possible to carry out specific tasks and can be upgraded as needed for enhancements and new release support.

## Input Parameters

The following table defines the template parameters and provides an example. Once you decide on these values, you can use these parameters to create the ASAv device when you deploy the GCP Deployment Manager template into your GCP project.

**Table 1: Template Parameters**

Parameter Name	Allowed Values/Type	Description	Resource Creation Type
resourceNamePrefix	String	All the resources are created with name containing this prefix. Example: demo-test	New
region	Valid regions supported by GCP [String]	Name of the region where project will be deployed. Example: us-central1	
serviceAccountMailId	String [ Email Id]	Email address that identifies the service account.	

Parameter Name	Allowed Values/Type	Description	Resource Creation Type
vpcConnectorName	String	Name of the connector that handles the traffic between your serverless environment and your VPC network.  Example: demo-test-vpc-connector	
bucketName	String	Name of the GCP storage bucket where the cloud function ZIP package will be uploaded.  Example: demo-test-bkt	
cpuUtilizationTarget	Decimal (0,1]	The average CPU utilization of the VMs in the instance group the autoscaler should maintain.  Example: 0.5	
healthCheckFirewallRuleName	String	Tag of the firewall rule that allows packets from health check probe IP ranges.  Example: demo-test-healthallowall	Existing
insideFirewallRuleName	String	Tag of the firewall rules that allows communication in Inside VPC.  Example: demo-test-inside-allowall	Existing
insideVPCName	String	Name of Inside VPC.  Example: demo-test-inside	Existing
insideVPCSubnet	String	Name of Inside subnet.  Example: demo-test-inside-subnt	Existing
machineType	String	Machine type for the ASAv VM.  Example: e2-standard-4	

Parameter Name	Allowed Values/Type	Description	Resource Creation Type
maxASACount	Integer	The maximum ASAv instances allowed in the instance group. Example: 3	
mgmtFirewallRuleName	String	Tag of the firewall rules which allows communication in Management VPC. Example: demo-test-mgmt-allowall	
mgmtVPCName	String	Name of Management VPC. Example: demo-test-mgmt	
mgmtVPCSubnet	String	Name of Management Subnet. Example: demo-test-mgmt-subnt	
minASACount	Integer	The minimum ASAv instances available in the Instance Group at any given time. Example: 1	
outsideFirewallRuleName	String	Tag of the firewall rules which allows communication in outside VPC. Example: demo-test-outside-allowall	
outsideVPCName	String	Name of Outside VPC. Example: demo-test-outside	
outsideVPCSubnet	String	Name of Outside Subnet. Example: demo-test-outside-subnt	
publicKey	String	SSH key of the ASAv VM.	

Parameter Name	Allowed Values/Type	Description	Resource Creation Type
sourceImageURL	String	Image of the ASAv which is to be used in the project.  Example: <a href="https://www.googleapis.com/compute/v1/projects/cisco-public/global/images/cisco-asav-9-15-1-15">https://www.googleapis.com/compute/v1/projects/cisco-public/global/images/cisco-asav-9-15-1-15</a>	
Application server IP address	String	Internal IP address of the inside Linux machine.  Example: 10.61.1.2	
Inside VPC Gateway IP address	String	Gateway of Inside VPC.  Example: 10.61.1.1	
Management VPC Gateway IP address	String	Gateway of Management VPC.  Example: 10.61.3.1	

## Deploy the Auto Scale Solution

**Step 1** Clone the Git repository to a local folder.

```
git clone git_url -b branch_name
```

**Example:**

```
Last login: Thu Jun  3 13:01:32 on ttys002
(base) pransm@PRANS-M-F9KA ~ % git clone https://bitbucket-eng-bgl1.cisco.com/bitbucket/scm/vcb/cloud_autoscale.git -b saanwar_asa_autoscale_public_key
Cloning into 'cloud_autoscale'...
remote: Enumerating objects: 1604, done.
remote: Counting objects: 100% (1604/1604), done.
remote: Compressing objects: 100% (1507/1507), done.
remote: Total 1604 (delta 759), reused 0 (delta 0), pack-reused 0
Receiving objects: 100% (1604/1604), 58.35 MiB | 8.54 MiB/s, done.
Resolving deltas: 100% (759/759), done.
(base) pransm@PRANS-M-F9KA ~ %
```

**Step 2** Create the bucket in gcloud CLI.

```
gsutil mb -c nearline gs://bucket_name
```

**Example:**



```
pransm@cloudshell:~ (asavgcp-poc-4krn) $ gsutil mb -c nearline gs://demo-function-bucket
Creating gs://demo-function-bucket/...
pransm@cloudshell:~ (asavgcp-poc-4krn) $
```

**Step 3**

Build compressed Zip packages:

- a) Create compressed Zip packages consisting of the following files from the folders `scalein_action` and `scaleout_action`.

- `main.py`
- `basic_functions.py`
- `requirements.txt`

- b) Rename the compressed Zip packages to `scaleout-action.zip` and `scalein-action.zip`.

**Note** Navigate inside the folder, select the files, right-click, and select ‘compress | archive’ to make a .zip that GCP can read.

**Step 4**

Upload the compressed Zip packages (`scaleout-action.zip` and `scalein-action.zip`) to the Cloud Editor workspace.

**Step 5**

Upload the following files from the deployment manager template to the Cloud Editor workspace.

- `asav_autoscale.jinja`
- `asav_autoscale_params.yaml`
- `pre_deployment.jinja`
- `pre_deployment.yaml`

**Step 6**

Copy the compressed Zip packages to the Bucket Storage.

- `gsutil cp scaleout-action.zip gs://bucket_name`
- `gsutil cp scalein-action.zip gs://bucket_name`

**Example:**

```
pransm@cloudshell:~ (asavgcp-poc-4krn) $ gsutil cp scaleout-action.zip gs://demo-function-bucket
Copying file://scaleout-action.zip [Content-Type=application/zip]...
/ [1 files] [ 3.3 KiB/ 3.3 KiB]
Operation completed over 1 objects/3.3 KiB.
pransm@cloudshell:~ (asavgcp-poc-4krn) $ gsutil cp scalein-action.zip gs://demo-function-bucket
Copying file://scalein-action.zip [Content-Type=application/zip]...
/ [1 files] [ 3.3 KiB/ 3.3 KiB]
Operation completed over 1 objects/3.3 KiB.
pransm@cloudshell:~ (asavgcp-poc-4krn) $
```

**Step 7**

Create VPC and Subnet for inside, outside, and management interfaces.

In the management VPC, you need to have /28 subnet, for example, 10.8.2.0/28.

**Step 8** You need three firewall rules for the interfaces inside, outside, and management. Also, you should have a firewall rule to allow the health check probes.

**Step 9** Update the parameters in the Jinja and YAML files for the Pre-Deployment and ASAv Autoscale deployment.

a) Open the `asav_autoscale_params.yaml` file and update the following parameters:

- **resourceNamePrefix:** <resourceNamePrefix>
- **region:** <region>
- **serviceAccountMailId:** <serviceAccountMailId>
- **publicKey:** <publicKey>
- **insideVPCName:** <Inside-VPC-Name>
- **insideVPCSubnet:** <Inside-VPC-Subnet>
- **outsideVPCName:** <Outside-VPC-Name>
- **outsideVPCSubnet:** <Outside-VPC-Subnet>
- **mgmtVPCName:** <Mgmt-VPC-Name>
- **mgmtVPCSubnet:** <Mgmt-VPC-Subnet>
- **insideFirewallRuleName:** <Inside-Network-Firewall-Tag>
- **outsideFirewallRuleName:** <Outside-Network-Firewall-Tag>
- **mgmtFirewallRuleName:** <Mgmt-Network-Firewall-Tag>
- **healthCheckFirewallRuleName:** <HealthCheck-IP-Firewall-Tag>
- **machineType:** <machineType>

**Note** For the ASAv auto scale, the **cpuUtilizationTarget: 0.5** parameter is set and you can edit it according to your requirements.

This value signifies 50% CPU usage of all the ASAv Instance Group.

b) Open the `asav_autoscale.jinja` file and update the following parameters.

- **host:** <Application server IP address>
- **route inside 0.0.0.0 0.0.0.0:** <Inside VPC Gateway IP address> 2
- **route management 0.0.0.0 0.0.0.0:** <Management VPC Gateway IP address> 3
- **license smart register idtoken:** <licenseIDToken>

c) Open the `pre_deployment.yaml` file and update the following parameters.

- **resourceNamePrefix:** <resourceNamePrefix>
- **region:** <region>
- **serviceAccountMailId:** <serviceAccountMailId>
- **vpcConnectorName:** <VPC-Connector-Name>

- **bucketName:** <bucketName>

**Step 10**

Create three secrets for the following using the Secret Manager GUI. See <https://console.cloud.google.com/security/secret-manager>.

- asav-en-password
- asav-new-password
- asav-private-key

Secret Manager lets you store, manage, and secure access to your application secrets.

[Learn more](#)

Filter Enter property name or value							
<input type="checkbox"/>	Name ↑	Location	Encryption	Labels	Created	Expiration	Actions
<input type="checkbox"/>	asav-en-password	Automatically replicated	Google-managed	None	4/26/21, 3:35 PM		⋮
<input type="checkbox"/>	asav-new-password	Automatically replicated	Google-managed	None	4/26/21, 3:36 PM		⋮
<input type="checkbox"/>	asav-private-key	Automatically replicated	Google-managed	None	4/26/21, 3:35 PM		⋮

**Step 11**

Create the VPC connector.

```
gcloud beta compute networks vpc-access connectors create <vpc-connector-name>
--region <region> --subnet=</28 subnet name>
```

**Example:**

```
gcloud beta compute networks vpc-access connectors create demo-vpc-connector
--region us-central1 --subnet=outside-connect-28
Create request issued for: [demo-vpc-connector]
Waiting for operation [projects/asavgcp-poc-4krn/locations/us-central1/operations/
10595de7-837f-4c19-9396-0c22943ecf15] to complete...done.
Created connector [demo-vpc-connector].
```

**Step 12**

Deploy the pre-deployment YAML configuration.

```
gcloud deployment-manager deployments create <pre-deployment-name>
--config pre_deployment.yaml
```

**Example:**

```
gcloud deployment-manager deployments create demo-predeployment
--config pre_deployment.yaml
The fingerprint of the deployment is b'9NOy0gsTPgg16SqUEVsBjA=='
Waiting for create [operation-1624383045917-5c55e266e596d-4979c5b6-66d1025c]...done.
Create operation operation-1624383045917-5c55e266e596d-4979c5b6-66d1025c
completed successfully
```

NAME	TYPE	STATE
demo-asav-delete-sink	gcp-types/logging-v2:projects.sinks	COMPLETED
demo-asav-insert-sink	gcp-types/logging-v2:projects.sinks	COMPLETED
demo-asav-pubsub-topic-delete	pubsub.v1.topic	COMPLETED
demo-asav-pubsub-topic-insert	pubsub.v1.topic	COMPLETED
demo-asav-scalein-action	gcp-types/cloudfunctions-v1:projects.locations.functions	COMPLETED
demo-asav-scaleout-action	gcp-types/cloudfunctions-v1:projects.locations.functions	COMPLETED

**Step 13**

Create the ASAv auto scale deployment.

```
gcloud deployment-manager deployments create <deployment-name>
--config asav_autoscale_params.yaml
```

**Example:**

```
gcloud deployment-manager deployments create demo-asav-autoscale
--config asav_autoscale_params.yaml
The fingerprint of the deployment is b'1JCQi7Il-laWOY7vOLza0g=='
Waiting for create [operation-1624383774235-5c55e51d79d01-1a3acf92-4f3daf16]...done.
Create operation operation-1624383774235-5c55e51d79d01-1a3acf92-4f3daf16
completed successfully.
```

NAME	TYPE	STATE
<i>demo-asav-autoscaler</i>	<i>compute.v1.regionAutoscaler</i>	<i>COMPLETED</i>
<i>demo-asav-backend-service-elb</i>	<i>compute.v1.regionBackendService</i>	<i>COMPLETED</i>
<i>demo-asav-backend-service-ilb</i>	<i>compute.v1.regionBackendService</i>	<i>COMPLETED</i>
<i>demo-asav-fr-elb</i>	<i>compute.v1.forwardingRule</i>	<i>COMPLETED</i>
<i>demo-asav-fr-ilb</i>	<i>compute.v1.forwardingRule</i>	<i>COMPLETED</i>
<i>demo-asav-hc-elb</i>	<i>compute.v1.regionHealthChecks</i>	<i>COMPLETED</i>
<i>demo-asav-hc-ilb</i>	<i>compute.v1.healthCheck</i>	<i>COMPLETED</i>
<i>demo-asav-health-check</i>	<i>compute.v1.healthCheck</i>	<i>COMPLETED</i>
<i>demo-asav-instance-group</i>	<i>compute.v1.regionInstanceGroupManager</i>	<i>COMPLETED</i>
<i>demo-asav-instance-template</i>	<i>compute.v1.instanceTemplate</i>	<i>COMPLETED</i>
<i>demo-elb-ip</i>	<i>compute.v1.address</i>	<i>COMPLETED</i>

**Step 14** Create a route for ILB to forward the packets from the inside application to the Internet.

```
gcloud beta compute routes create <ilb-route-name>
--network=<inside-vpc-name> --priority=1000 --destination-range=0.0.0.0/0
--next-hop-ilb=<ilb-forwarding-rule-name> --next-hop-ilb-region=<region>
```

**Example:**

```
gcloud beta compute routes create demo-ilb --network=sdt-test-asav-inside
--priority=1000 --destination-range=0.0.0.0/0 --next-hop-ilb=demo-asav-fr-ilb
--next-hop-ilb-region=us-central1
Created [https://www.googleapis.com/compute/beta/projects/asavgcp-poc-4krn/global
/routes/demo-ilb].
```

NAME	NETWORK	DEST_RANGE	NEXT_HOP	PRIORITY
<i>demo-ilb</i>	<i>sdt-test-asav-inside</i>	<i>0.0.0.0/0</i>	<i>10.7.1.60</i>	<i>1000</i>

**Step 15** Create Cloud Router and Cloud NAT.

```
gcloud compute routers create <cloud-router-name>
--project=<project-name> --region <region> --network=<outside-vpc-name>
--advertisement-mode=custom

gcloud compute routers nats create <cloud-nat-name>
--router=<cloud-router-name> --nat-all-subnet-ip-ranges --auto-allocate-nat-external-ips
--region=<region>
```

**Example:**

```
gcloud compute routers create demo-cloud-router --project=asavgcp-poc-4krn
--region us-central1 --network=sdt-test-asav-outside --advertisement-mode=custom
Creating router [demo-cloud-router]...done.
```

NAME	REGION	NETWORK
<i>demo-cloud-router</i>	<i>us-central1</i>	<i>sdt-test-asav-outside</i>

```
gcloud compute routers nats create demo-cloud-nat
--router=demo-cloud-router --nat-all-subnet-ip-ranges
```



```
--auto-allocate nat-external-ips --region=us-central1
Creating NAT [demo-cloud-nat] in router [demo-cloud-router]...done.
```

## Auto Scale Logic

- The autoscaler treats the target CPU utilization level as a fraction of the average use of all vCPUs over time in the instance group.
- If the average utilization of your total vCPUs exceeds the target utilization, the autoscaler adds more VM instances. If the average utilization of your total vCPUs is less than the target utilization, the autoscaler removes instances.
- For example, setting a 0.75 target utilization tells the autoscaler to maintain an average utilization of 75% among all vCPUs in the instance group.
- Only CPU utilization metrics are used in scaling decisions.
- This logic is based on the assumption that load balancer will try to equally distribute connections across all ASAs, and on average, all ASAs should be loaded equally.

## Auto Scale Logging and Debugging

Logs of cloud functions can be viewed as follows.

- Scale Out function logs

**Figure 7: Scale Out Function Logs**

SEVERITY	TIMESTAMP	ST	SUBGROUP	
>	2021-04-29 17:54:52.320 IST	demo-asa-scaled-out-action	z1632spc2u1f	Would you like to enable anonymous error reporting to help improve the product? [Y/n], [N/y], [A]lex later:
>	2021-04-29 17:54:52.320 IST	demo-asa-scaled-out-action	z1632spc2u1f	Password changed Successfully
>	2021-04-29 17:54:55.321 IST	demo-asa-scaled-out-action	z1632spc2u1f	Changing Hostname
>	2021-04-29 17:54:58.320 IST	demo-asa-scaled-out-action	z1632spc2u1f	conf t
>	2021-04-29 17:54:58.320 IST	demo-asa-scaled-out-action	z1632spc2u1f	ciscoasa(config)#
>	2021-04-29 17:55:01.320 IST	demo-asa-scaled-out-action	z1632spc2u1f	Hostname changed Successfully
>	2021-04-29 17:55:01.320 IST	demo-asa-scaled-out-action	z1632spc2u1f	Saving the Configuration
>	2021-04-29 17:55:01.320 IST	demo-asa-scaled-out-action	z1632spc2u1f	hostname ciscoasa-tbg6
>	2021-04-29 17:55:01.320 IST	demo-asa-scaled-out-action	z1632spc2u1f	ciscoasa-tbg6(config)#
>	2021-04-29 17:55:04.330 IST	demo-asa-scaled-out-action	z1632spc2u1f	write memory
>	2021-04-29 17:55:04.330 IST	demo-asa-scaled-out-action	z1632spc2u1f	Writing Configuration...
>	2021-04-29 17:55:04.330 IST	demo-asa-scaled-out-action	z1632spc2u1f	Cryptochecksum: 2a037374 e000b78c 3a7b598f 6606ab12
>	2021-04-29 17:55:04.330 IST	demo-asa-scaled-out-action	z1632spc2u1f	8985 bytes copied in 0.100 secs
>	2021-04-29 17:55:04.330 IST	demo-asa-scaled-out-action	z1632spc2u1f	[OK]
>	2021-04-29 17:55:04.330 IST	demo-asa-scaled-out-action	z1632spc2u1f	ciscoasa-tbg6(config)#
>	2021-04-29 17:55:04.330 IST	demo-asa-scaled-out-action	z1632spc2u1f	Configuration Saved
>	2021-04-29 17:55:04.332 IST	demo-asa-scaled-out-action	z1632spc2u1f	Function execution took 154790 ms, finished with status: 'ok'

Here we see hostname ciscoasa-tbg6 cmd been executed in the scaled-out ASAv instance, which means we scale-out function has executed successfully.



**Important**

Cisco recommends tracking the ASAv registration with the licensing server periodically to check if the scaled-out ASAs are registering with the licensing server as expected, and scaled-in ASAv instances are getting removed from the license server).

## Auto Scale Troubleshooting

The following are common error scenarios and debugging tips for ASAv auto scale for GCP:

- `main.py` not found—Make sure that the Zip package is made only from the files. You can go to cloud functions and check the file tree. There should not be any folder.
- Error while deploying the template—Make sure that all the parameters values within “`<>`” are filled in. `jinja` and `.yaml` as well, or the deployment by the same name exists already.
- Google Function cannot reach ASAv—Make sure that the VPC connector is created and the same name is mentioned in the YAML parameter file.
- Authentication Failed while SSH-ing ASAv—Make sure that the Public and Private key pair is correct.
- License Registration Failed—Make sure that the License ID token is correct. Also, ensure that the Cloud NAT is created and ASAv is able to reach `tools.cisco.com`.

