EXISTING PAVEMENT TACK EDGES WITH HOT CLASS B' ASPHALTIC CONC. PATCH MATCH EXIST THICKNESS (2 MIN) 240th Street S.W. TOP COURSE 11/2" OF 5/8"
MINUS CRUSHED POCK MINUS CRUSHED ROCK BANK RUN GRAVEL OR APPROVED BACKFILL MELLANICALLY COMPACTED CONSTRUCT CLEAN-ON (REFER: STANDARD PLAN NO. 45 APMA scale= 1"=50-BACKFILL AND RESTORATION DETAIL No Scale ALL PAVEMENT MUST BE SAW OUT BEFORE REMOVAL. CEMENT CONCRETE PIPE FOR SANITARY LINES SHALL BE RUBBER GASKET CLASS C 14 LOCATIONS OF 6 TEES AND LATERIALS ARE APPROXIMATE AND WILL BE FIELD LOCATED BY CITY ENGINEER IT SHALL BE THE CONTRACTORS
RESPONSIBILITY TO LOCATE ANY
EXISTING UTILITIES THAT MAY
CONFLICT WITH HIS OPERATIONS. MANHOLE # 1-95 ---- 4" Steel 1 COLISTRUCT MANHOLE (TYPE III-AB - REFEK STANDAED PLAN No. 37. A.P.WA) 241st Street 1 PIPE WITEE PIPE WITHE #1-954 SNOHOMISH CO. 5312 5306 5326 5320 VICINITY MAP Scale I' = (000) Scan Name: scans06158.pdf Scan Date: 95A 3+00 3+4 NEW MANHOLE: TOP 30010 EXIST MALLIQUE TOP SE 4.4% REVISED 8/20/76 .... 241st Street S.W. L.I.D. No. 45 - Sanitary Sewer City of Mountlake Terrace lofl HOLENN OUT BELL BUSING SENER PIE 82 (4 %) 53rd Avenue W. 1-20-A