

PROFILE		BY		DATE	
SURVEYED					
PLOTTED					
GRADES CHECKED					
B. M.'s NOTED					
STRUCTURE NOTATIONS CHECKED					

SCALE	DATE	SHEET NO.
DRAWN BY	CHECKED BY	JOB NO.

NOTES:

- | | | | |
|----------|-----|---|----------------------|
| GENERAL: | 1. | ALL WORK AND MATERIALS SHALL BE IN COMPLETE ACCORDANCE WITH THE SPECIFICATIONS AND STANDARDS OF THE CITY OF MOUNTLAKE TERRACE AND A.P.W.A. | |
| | 2. | THE CONTRACTOR SHALL INVESTIGATE AND LOCATE ALL BURIED UTILITIES OR OBSTRUCTIONS IN THE CONSTRUCTION AREA PRIOR TO COMMENCEMENT OF WORK. CONTRACTOR SHALL COORDINATE WITH WATER UTILITY, SEWER UTILITY, GAS, TELEPHONE AND ALL OTHER AFFECTED UTILITIES FOR FIELD LOCATION OF THE RESPECTIVE EXISTING FACILITIES. | |
| | 3. | THE CONTRACTOR SHALL "DIAL DIT" (342-5344) PRIOR TO CONSTRUCTION FOR AID IN LOCATING ANY UNDERGROUND UTILITIES AS APPLICABLE. | |
| SEWER: | 4. | CONTRACTOR SHALL VERIFY MANHOLE DEPTHS WITH ENGINEER PRIOR TO DELIVERY. | |
| | 5. | ALL MANHOLE JOINTS SHALL BE SEALED. | |
| | 6. | PIPE BEDDING SHALL BE PER GRAVEL TO A POINT ONE (1) FOOT OVER PIPE. | |
| | 7. | CONNECTION TO THE EXISTING SEWER SYSTEM SHALL BE MADE SO AS TO PREVENT FOREIGN MATERIAL FROM ENTERING THE EXISTING SEWER. | |
| | 8. | ALL MANHOLES SHALL BE CHANNLED AS SHOWN ON STANDARD PLAN NO. 34, A.P.W.A. STANDARDS AND SPECIFICATIONS. | |
| | 9. | ALL SEWER LINES SHALL BE CLEANED AND TESTED AS PER REQUIREMENTS OF THE CITY OF MOUNTLAKE TERRACE. | |
| WATER: | 10. | PIPE SHALL BE DUCTILE IRON AWWA CLASS 52. JOINTS SHALL BE RUBBER GASKETED, PUSH-ON TYPE OR MECHANICAL JOINT MEETING AWWA SPECIFICATIONS. VALVES AND HYDRANTS SHALL MEET AWWA SPECIFICATIONS. HYDRANTS SHALL BE FURNISHED WITH THREADED OUTLETS MEETING MOUNTLAKE TERRACE DISTRICT STANDARDS. | |
| | 11. | THE CITY OF MOUNTLAKE TERRACE SHALL BE NOTIFIED 48 HOURS PRIOR TO TIME OF CONNECTING TO ANY EXISTING MAINS. THE CONNECTION SHALL BE DONE IN ACCORDANCE WITH THE CITY STANDARDS AND CONDITIONS. | SEE ALSO
NOTE #17 |
| | 12. | PROVIDE THRUST BLOCKING AT ALL FITTING, BENDS, GATE VALVES AND UP-THRUST FITTINGS IN ACCORDANCE WITH CITY OF MOUNTLAKE TERRACE STANDARDS AND CONDITIONS. | |
| | 13. | PROVIDE BENDS, IN FIELD, TO SUIT CONSTRUCTION AND IN ACCORDANCE WITH PIPE MANUFACTURER'S RECOMMENDATIONS SO AS NOT TO EXCEED ALLOWABLE DEFLECTION AT PIPE JOINTS. | |
| | 14. | STANDARD CONSTRUCTION DETAILS FOR FIRE HYDRANTS, SERVICE CONNECTIONS AND OTHER RELATED ITEMS ARE AVAILABLE FOR REVIEW AT THE OFFICE OF CITY OF MOUNTLAKE TERRACE. THE CONTRACTOR SHOULD BE FAMILIAR WITH ALL OF THE CONSTRUCTION DETAIL REQUIREMENTS PRIOR TO THE BEGINNING OF WORK. | |
| | 15. | PRIOR TO ANY WORK BEING PERFORMED, THE CONTRACTOR SHALL CONTACT THE DISTRICT SUPERINTENDENT OR ENGINEER TO SET FORTH HIS PROPOSED WORK SCHEDULE. | |
| | 16. | A WATER SERVICE CHARGE PER LOT SHALL BE PAID TO THE CITY OF MOUNTLAKE TERRACE. CITY WILL FURNISH AND INSTALL ALL SERVICES. | |
| | 17. | THE CONNECTION TO THE EXISTING 6" D.I. WATERLINE SHALL BE MADE BY THE CITY OF MOUNTLAKE TERRACE. APPLICANT SHALL PROVIDE ALL MATERIALS, EXCAVATION AND BACKFILL PER CITY REQUIREMENTS. | |