



NARRATIVE:

--THIS SURVEY WAS ACCOMPLISHED AT THE REQUEST OF WEYERHAEUSER TO MARK AND MONUMENT THE BOUNDARY LINES SHOWN AS HATCHED IN SECTIONS 35 & 36 TOWNSHIP 5 NORTH, RANGE 5 WEST OF THE WILLAMETTE MERIDIAN.

--THE BASIS OF BEARINGS IS BETWEEN MONUMENT NO. 1 & 61 AS COMPUTED PER CS NO. 5388.

--FOR CONTROL I HELD THE MONUMENTS AS NOTED. I SET A POINT ON THE NORTH LINE OF SECTION 36 ON THE WEST BANK OF ROCK CREEK.

--ALL REFERENCES WERE MEASURED WITH A HAND COMPASS SET AT DECLINATION 16° EAST AND A STEEL TAPE. ALL NEW BEARING TREES WERE MEASURED TO THE HEAD OF A 60D SPIKE SET IN THE BASE BLAZE BETWEEN THE "B" AND THE "T". BEARING TREE TAGS WERE PLACED AT SHOULDER HEIGHT ABOVE THE BLAZES.

--BOUNDARY LINES SHOWN AS HATCHED WERE MARKED WITH RED AND WHITE RIBBON ON LINE. TREES ON WEYERHAEUSER PROPERTY WITHIN 10' OF THE BOUNDARY LINE WERE MARKED WITH QUARTER BLAZES AT CHEST HEIGHT FACING TOWARDS THE BOUNDARY LINE. TREES LOCATED DIRECTLY ON LINE WERE MARKED WITH TWO BLAZES AT CHEST HEIGHT AND, ON THE BOUNDARY LINE ON BOTH SIDES OF THE TREES. 1/2" X 6' FIBERGLASS POSTS WERE SET ON LINE AT ±150' INTERVALS.

LEGEND

- FOUND MONUMENT AS NOTED
- SET A 5/8" X 30" IRON ROD WITH A Y.P.C. MARKED "KLS SURVEYING INC."
- [X] MONUMENT POINT NO
- () RECORD SURVEY DATA
- CS NO. SURVEY NUMBER, COLUMBIA COUNTY SURVEY RECORDS
- Y.P.C. YELLOW PLASTIC CAP

REFERENCES:

SURVEYS
1 = CS NO. 5388
2 = CS NO. 5987

DEEDS
1 = INSTRUMENT NO. 2014-07397
2 = INSTRUMENT NO. 2022-08854
3 = BOOK 183, PAGE 961
4 = BOOK 263, PAGE 755

MONUMENT NOTES:

[1]
SECTION CORNER COMMON TO SECTIONS 25, 26, 35, & 36
FOUND A 2" BRASS DISK MARKED "SEC COR T5N R5W S26 S25 S35 S36 2006 65624LS"
PER CS NO. 5388
REFERENCES FOUND:
A 10" FIR BEARS S 79° E 1.94' TO SPIKE IN HEALED FACE
A 51" CEDAR BEARS N 5°W 18.15' TO HEALED FACE
A 10" FIR SNAG BEARS S 55°W 8.08' TO SPIKE
A 22" ROTTEN FIR HIGH STUMP BEARS S 71° E 6.10' TO SIDE CENTER
A 1/2" IRON PIPE BEARS NW 1.00'
A STEEL T-POST BEARS SOUTH 1.0'
NEW REFERENCES:
A FIBERGLASS POST BEARS WEST 0.2'

[34]
1/4 CORNER COMMON TO SECTIONS 26 & 35
FOUND A 3/4" IRON PIPE DOWN 1.50' PER CS NO. 3588
REFERENCES:
A FIBERGLASS POST BEARS SOUTH 1.00'
AN 18" ALDER BEARS N45°53'50" W 8.13' TO HEALED FACE
A 19" ALDER BEARS S85°54'09" E 43.35' TO HEALED FACE
A 29" MAPLE BEARS S 10°32'47" W 78.98' TO HEALED FACE
A 72" CEDAR BEARS S 46°08'40" E 62.62' TO HEALED FACE

[61]
1/4 CORNER COMMON TO SECTIONS 25 & 36
FOUND A 1 1/2" ALUMINUM PIPE UP 1.00' PER CS NO. 3588
REFERENCES:
A T-POST BEARS SOUTH 1.00'
A T-POST BEARS EAST 1.00'
A 25" CEDAR BEARS S 54°35'20" E 12.97' TO HEALED FACE
A 42" CEDAR BEARS N 80°53'45" E 18.46' TO HEALED FACE
A 3/4" IRON PIPE WITH A 2" BRASS CAP PER CS NO. 5388 BEARS S 83° W 20.01'

[69]
SET A 5/8" IRON ROD WITH A Y.P.C. MARKED "KLS SURVEYING INC"
NEW REFERENCES:
A FIBERGLASS POST BEARS WEST 0.1'
A 9" FIR BEARS S 10° E 17.74' TO SPIKE IN LOWEST OF FOUR BLAZES

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JANUARY 19, 1993
DONALD D WALLACE, JR
2601
RENEWS 6/30/24

K L S SURVEYING INC.
1224 ALDER STREET
VERNONIA, OREGON 97064
(503) 429-6115

RECORD OF SURVEY FOR
WEYERHAEUSER
IN THE NE 1/4 OF SECTION 35
AND IN THE NW 1/4 OF SECTION 36,
T5N, R5W, W.M.,
COLUMBIA COUNTY, OREGON
DECEMBER 21, 2023

DRAWN BY: ORM
FIELD: BTD/TZO
EQUIPMENT: NOMAD/NIKON
JOB No. 23-061
DRAWING NAME: 23-061 ROS
REVISED: 1-25-2024