JULY 24, 2021

RECORD OF SURVEY CLIENT DESIGNATED PROPERTY LINES IN THE SE 1/4 OF THE NW 1/4 SECTION 19 SITUATED IN NW 1/4 SECTION 19, T4N, R4W, W.M., COLUMBIA COUNTY. OREGON BASIS OF BEARINGS THE PURPOSE OF THIS SURVEY IS TO FLAG, BLAZE, AND PAINT CLIENT DESIGNATED PORTIONS OF THE SOUTHEAST QUARTER OF THE NORTHWEST QUARTER OF SECTIONS 19 TO FACILITATE TIMBERLAND MANAGEMENT INCLUDING TIMBER HARVEST AND ROAD CONSTRUCTION. THE BASIS OF BEARINGS FOR THIS SURVEY IS THE RECORD BEARING FROM MO # 954 TO MON # 991 PER CCSR MAP #6218. THE BASIS OF BEAHINGS FOR 1113 SOUTH. SEE CCSR MAP # 3250 -NW 1/16 C N 1/16-(S89 *48 '19 "E 1237.76 ') 2 -MON # 1074 NOTES: MON # 1086 -\$89 *47 '58 "E 1237.10 ' BEARINGS TO BEARING TREES ARE BASED UPON HAND COMPASS BEARINGS WITH A VAR 17 EAST; DISTANCES TO NEW BTS WERE MEASURED TO A 1 1/4" BRASS DISC STAMPED "MENDENHALL LS 2001" NAILED AT THE BOTTOM OF THE SCRIBING IN THE FACE (FOR NEW BEARING TREES) DISTANCES TO EXISTING BEARING TREES WERE MEASURED TO THE FACE (SIDE OF BOLE) OR 60D SPIKE IF PRESENT. ALL NEW BEARING TREES ARE POSTED WITH A 5" X 5" YELLOW LOCATION TAG. FLAGGED, TAGGED, BLAZED, AND PAINTED PROPERTY LINES ARE BLAZED ON THE HANCOCK SIDE OF THE BOUNDARY. TREES ON THE HANCOCK SIDE OF THE BOUNDARY ARE BLAZED BELOW STUMP HEIGHT. BLAZES AND BOTH SIDES OF LINE ARE PAINTED BRIGHT RED. RED AND WHITE FLAGGING IS HUNG TOGETHER "ON LINE" WHERE TREES ARE WIDELY SPACED OR ARE NOT AVAILABLE TO PAINT. 1/2" X 4' FIBERGLASS RODS WERE PLACED AT 100' TO 200' INTERVALS ALONG THE PROPERTY LINES (AND ADJACENT TO CORNERS- 1' NORTH UNLESS NOTED OTHERWISE) SCALE 1"=200' MONUMENT NOTES: 1313. 200 400 N 9345.83 E 24062.20 (MON) J.26' JO5,51') RINGS SE 1/4 OF NW 1/4 APPROX .35.59 ACRES EAST OF BANKS VERNONIA TRAIL REGISTERED 3"E 3"E 1. BEAR MAP **PROFESSIONAL** N 9678.39 E 23983.30 (MON) -MON # 1140 LAND SURVEYOR MANAGED BY HANCOCK FOREST MANAGEMENT POL S00 •06 (S0 •06 'E BASIS 0 SEE CC! 31.24 OREGON / gi JULY 16, 1982 NEILA, MENDENHALL JR. 2001 RENEWAL DATE: 12/2./22 MON # 1063 TO MON # 1062 S67 *49 '06 "E 58.93 ' TAIL LAT N 45 49.145', LONG W 123 13.880', ACC 18.' +/--S20 *54'15"E 91.89' (CHORD TIE) ___ MON # 1061 -S14 *22'02"E 158.88' (CHORD TIE) OF 20.0' NO SCRIBES VISIBLE. (TAPER T 2 1/2, DELTA 2 42')3 MON # 1103-- S89 *50 '09 "W 0.29 9" DOUG FIR SCRIBED "X BT" S68 E 5.1'. S89 *50'09"W 1023.14' LAT N 45 49.140', LONG W 123 13.591', ACC 22.' +/-MON # 1123 FOUND 3/4" IRON PIPE, TOP 0.3' ABOVE THE SURFACE, ORIGIN CCSR MAP #3250, HELD AS SW 1/16 SEC 19; N 8147.14 E 23898.94 (MON) MON # 1279 S89 50 09 W 1237.16 --- 506 *28 '27 "E 112.24' (CHORD TIE) C 1/4 SEC 19-90. -MON # 1059 (218+04.14 M.O.C)3 ~-S86 *40'04"W 60.65' SEE CCSR MAP # 3250 --- MON # 1058 PRIVATE LAT N 45 *49.026', LONG W 123 *13.884', ACC 20.' +/-CURVE TABLE: (HIGHWAY DEFINITION) CHORD BEARING CHORD DISTANCE CURVE RADIUS C-1 984.93' 159.06 09 15 10 S14 22 02 E 158.88 NON - TANGENT C-2 984.93' 112.30' 06 *31'59" 506 *28'27"E 112.24' NON - TANGENT LAT N 45 48.917', LONG W 123 13.834', ACC 24.' +/-NARRATIVE: I CONSIDERED CCSR MAP # 3250 TO BE A VALID SUBDIVISION OF SECTION 19. I HELD MONUMENTS # 1074, # 1086, # 1103, AND # 1123 SET ON THAT SURVEY TO DETERMINE THE BOUNDS OF THE SE 1/4 OF THE NW 1/4 OF SECTION 19. THESE MONUMENTS ARE IN REASONABLE PROXIMITY TO INTENDED POSITIONS IN MY OPINION. I FOUND AND TIED MONUMENTS #1058, # 1059, # 1061, # 1062, # 1063, AND # 1067 SET ON CCSR MAP # 3827 ALONG THE BOUNDARY OF THE BANKS VERNONIA TRAIL. MONUMENTS ON THE WESTERLY SIDE OF THE TRAIL WERE FOUND TO BE UP TO ABOUT A FOOT OUT OF POSITION RELATIVE TO MONUMENTS ON THE EASTERLY SIDE OF THE TRAIL. I HELD THE FOUND MONUMENTS ALONG THE EASTERLY SIDE OF THE TRAIL AS POINTS ON THE EASTERLY TRAIL BOUNDARY FOR PURPOSES OF ACC = EXPECTED HORIZONTAL ACCURACY OF LATITUDE AND LONGITUDE AS DETERMINED WITH A HAND HELD GPS RECEIVER (NOT SURVEY QUALITY)

EQUIPMENT: SOKKIA SET 530R TOTAL STATION

CREW: NAM. JH. DNM. LH

CATHLAMET, WA 98612 (360) 214-2195 ATTN: BRANDON METCALF

SURVEY FOR: HANCOCK FOREST MANAGEMENT INC.

SURVEY BY:
NEIL A. MENDENHALL JR, LS 2001
dba MENDENHALL & ASSOC
PO BOX 2025
GEARHART, OR 97138
(503) 738-6363
MENDENHALL 2025@GMAIL.COM

file: T5NR6WS6rot.pro

- MON # 1123

-SW 1/16

MON # 1058 FOUND 5/8" REBAR WITH PYC STAMPED "OREGON STATE PARKS", TOP 0.1' BELOW THE SURFACE, ORIGIN CCSR MAP # 3827, NOT HELD, USED TO CHECK AND LOCATE OTHER MONUMENTS;

MON # 1059 FOUND 5/8" REBAR WITH PYC STAMPED "OREGON STATE PARKS", TOP 0.1' ABOVE THE SURFACE, ORIGIN CCSR MAP # 3827, HELD AS MIDDLE OF CURVE EASTERLY R.O.W. TRAIL ROUTE, USED TO CALCULATE CURVE RADIUS; N 9349.35 E 24122.74 (MON)

MON # 1061 FOUND 5/8" REBAR WITH PYC STAMPED "OREGON STATE PARKS", TOP 0.1' BELOW THE SURFACE, ORIGIN CCSR MAP # 3827, HELD AS PC CURVE 30' LT. ON R.O.W. TRAIL ROUTE, USED TO CALCULATE CURVE RADIUS; N 9614.80 E 24070.66 (MON)

MON # 1062 FOUND 5/8" REBAR WITH PYC STAMPED "OREGON STATE PARKS", TOP FLUSH WITH THE SURFACE, ORIGIN CCSR MAP # 3827, HELD AS POINT ON WESTERLY R.O.W. TRAIL ROUTE;

MON # 1063 FOUND 5/8" REBAR WITH PYC STAMPED "OREGON STATE PARKS", TOP FLUSH WITH THE SURFACE, ORIGIN CCSR MAP # 3827, HELD AS POINT ON EASTERLY R.O.W. TRAIL ROUTE AND BEGINNING OF TAPER; N 9700.64 E 24037.87 (MON)

MON # 1067 FOUND 5/8" REBAR WITH PYC STAMPED "OREGON STATE PARKS", TOP 0.4' ABOVE THE SURFACE ORIGIN CCSR MAP # 3827, HELD AS POINT ON TANGENT 30' RT. ON WESTERLY TRAIL R.O.W.;

MON # 1074 FOUND 1" OD IRON PIPE, TOP 1.5' ABOVE THE SURFACE, QRIGIN CCSR MAP #3250, HELD AS NW 1/16 SEC 19; N 10773.40 E 23893.77 (MON) I FOUND BTS NOTED ON CCSR MAP #828B AS FOLLOWS; 3/4" SQUARE BAR S60 W 2.89' IS NOW A 3/4" BAR N61 E 2.80'; 27" MAPLE S10 E A DISTANCE OF 20.18' IS NOW A 3' DIAMETER MAPLE A DISTANCE OF 20.0' NO SCRIBES VISIBLE. I SCRIBED BT AS FOLLOWS; 6" CEDAR SCRIBED "X BT" N24 E 17.33';

MON # 1086 FOUND BENT 1" OD IRON PIPE, TOP 0.2' ABOVE THE SURFACE, TIED SPIN HOLE; ORIGIN CCSR MAP #3250, HELD AS CN 1/16 SEC 19; N 10769.07 E 25130.86 (MON) I FOUND BTS NOTED ON CCSR MAP #828B AS FOLLOWS; 15" DOUG FIR SB1 E 25.41' IS NOW A 20" DOUG FIR STUMP S87 E 25.8 WITH YELLOW TAG; 9" DOUG FIR N69 W A DISTANCE OF 29.29' IS MISSING.

I SCRIBED BTS AS FOLLOWS; 10" DOUG FIR SCRIBED "CN 1/16 S 19 BT" S89°W 3.8';

MON # 1103 FOUND 1" OD IRON PIPE, TOP FLUSH WITH THE SURFACE, ORIGIN CCSR MAP #3250, HELD AS C 1/4 SEC 19; N 9463.81 E 25133.51 (MON) I FOUND BTS NOTED ON CCSR MAP #828B AS FOLLOWS; 18" DOUG FIR S39 W 8.71' IS NOW A 17" DOUG FIR STUMP WITH YELLOW TAG AND ROTTEN FACE; 13" DOUG FIR MISSING.

I SCRIBED BTS AS FOLLOWS; 10" DOUG FIR SCRIBED "X BT" S80 E 13.1';
11" DOUG FIR SCRIBED "C 1/4 BT" S02 E 11.4'; 7" TRUE FIR SCRIBED "X BT" N69 W 24.7' LAT N 45 48.929', LONG W 123 13.593', ACC 17.' +/-

MON # 1140 SET 5/8" X 30" REBAR WITH POC STAMPED "MENDENHALL LS 2001", SET AT INTERSECTION OF NE TRAIL R.O.W. & N-S CENTERLINE SW 1/4, TOP FLUSH WITH THE SURFACE; N 10065.14 E 23895.16 (MON) I SCRIBED BTS AS FOLLOWS; 20" RED CEDAR SCRIBED "POL BT" N82 E 17.8'; 6" X 6' CREOSOTE GATE POST WITH YELLOW TAG N20 W 39.3'

MON # 1279 SET 5/8" X 30" REBAR WITH POC STAMPED "MENDENHALL LS 2001", SET ON E-W CENTERLINE SEC 19, TOP FLUSH WITH THE SURFACE; N 9460.88 E 24110.37 (MON) I SCRIBED BTS AS FOLLOWS; 11" DOUG FIR SCRIBED "POL BT" N55 W 14.6'; 12" DOUG FIR SCRIBED "X BT" S48 W 5.3'

COORDINATES ARE LOCAL - ASSUMED

Symbol	Description
B	FOUND 1" OD PIPE, SET CCSR MAP # 3250, HELD
•	FOUND 5/8" REBAR WITH PLASTIC YELLOW CAP STAMPED "OREGON STATE PARKS", HELD ALONG EAST SIDE OF TRAIL
•	SET 5/8" X 30" REBAR WITH PLASTIC ORANGE CAP STAMPED "MENDENHALL LS 2001"
A	CALCULATED POSITION ONLY
	FLAGGED, BLAZED, PAINTED PROPERTY LINE
	MONUMENT TIES

CALC = CALCULATED CCBT = COLUMBIA COUNTY BEARING TREE RECORDS
CCDR = COLUMBIA COUNTY DEED RECORDS CCSR = COLUMBIA COUNTY SURVEYOR'S RECORDS

NO () = MEASURED OR CALCULATED PER THIS SURVEY ()2 = PER CCSR MAP # 3250 ()3 = PER CCSR MAP # 3827

HAND HELD = HAND HELD PORTABLE GPS RECEIVER
USED TO DETERMINE LATITUDE AND LONGITUDE
FOR CORNER SEARCH (NOT SURVEY QUALITY) CCSR MAP # 828 CCSR MAP # 5025 MON = MONUMENT OD = OUTSIDE DIAMETER POL = POINT ON LINE CCSR MAP # 6048

OTHER REFERENCE SURVEYS