

LEGEND

- = MONUMENT FOUND AS NOTED
- \bigcirc = SET A 5/8" x 30" IRON ROD WITH A Y.P.C. MARKED "KEENON LAND SERVICES INC."
- () = RECORD SURVEY DATA
- [] = RECORD DEED DATA
- CS No. = RECORD SURVEY No.
- Y.P.C. = YELLOW PLASTIC CAP
- = CONTROL POINT No.

--THE PURPOSE OF THIS SURVEY WAS TO MARK AND MONUMENT THE NORTH LINE OF THAT TRACT OF LAND IN SECTION 9 AS DESCRIBED IN CLERKS INSTRUMENT No. 97-3998, COLUMBIA COUNTY RECORDS.

-- FOR CONTROL OF THE NORTH LINE OF THE SE 1/4 OF THE NE 1/4 I HELD THE MONUMENTATION PER CS No. 3516 AND 3785. I HELD THE RECORD BEARING (S00°29'45" E), PER CS No. 3785, FROM THE COMPUTED NE 1/16 CORNER TO COMPUTE THE WEST LINE OF THE SE 1/4 OF THE NE 1/4. I HELD THE AS TRAVELED CENTERLINE OF RIDGEWAY COUNTY ROAD TO DETERMINE THE SOUTHERN RIGHT OF WAY LINE.

TRACT DESCRIBED IN CLERKS INSTRUMENT No. 92-7820:
--I ESTABLISHED THE MOST WEST CORNER AT A POINT ON THE SOUTH LINE OF RIDGEWAY COUNTY ROAD THAT IS 98.00' SOUTHWESTERLY FROM THE INTERSECTION OF THE WEST LINE OF THE SE 1/4 OF THE NE 1/4 AND THE SOUTH LINE OF SAID CO. ROAD. I HELD THE DEEDED BEARING [S 38°00'00" E] FROM THE WEST CORNER AND INTERSECTED THE SOUTHEASTERLY LINE TO ESTABLISH THE SOUTHERN MOST CORNER. FOR THE SOUTHEASTERLY BOUNDARY I HELD A LINE THAT IS 30' NORTHWESTERLY FROM AND PARALLEL TO THE EXISTING AS-BUILT CENTERLINE OF THE ABANDONED 1948 LOG HAUL ROAD PER DEED.

CURVE & LINE TABLE

CURVE	RADIUS	LENGTH	CHORD	BEARING	DELTA
C1	172.00'	233.87	216.27	S 53°10'02" W	77°54'23"
C2	825.00'	264.74	263.60'	N 82°55'39" E	18 ° 23'09"
C3	150.00'	196.14'	182.46'	N 36°16'32" E	74°55'06"
LINE	DIRECTION	DISTANCE			
I.1	N 14°12'50" E	53.16'	7		

- 1 N 1/16 CORNER FOUND A 2" IRON PIPE WITH A 3" CROWN ZELLERBACH BRASS CAP PER CS No. 3516. REFERENCES FOUND: AN 8" HEMLOCK STUB S 19° W 8.5' A 1/2" IRON PIPE S 65° W 5.25' A WHITE FIBERGLASS POST NORTH 1.00'
- 5 FOUND A 5/8" IRON ROD, NO CAP, PER CS No. 3785. HELD FOR THE NORTH LINE OF THE SE 1/4 OF THE NE 1/4.
- SET A 5/8" X 30" IRON ROD WITH A Y.P.C. MARKED "KEENON LAND SERVICES INC." 1.0' NORTH OF AN E-W FENCE LINE. A 6' TALL WHITE FIBERGLASS POST NORTH 1.0'
- 41) FOUND A 5/8" IRON ROD, NO CAP, PER CS No. 3785. HELD FOR THE NORTH LINE OF THE SE 1/4 OF THE NE 1/4.
- PROPERTY CORNER SET A 5/8" X 30" IRON ROD WITH A Y.P.C. MARKED "KEENON LAND SERVICES INC." REFERENCES SET: A 14" ALDER N 20° E 10.55' TO SPIKE A 6' TALL WHITE FIBERGLASS POST NORTH 1.0'
- PROPERTY CORNER SET A 5/8" X 30" IRON ROD WITH A Y.P.C. MARKED "KEENON" LAND SERVICES INC." REFERENCE SET: AN 18" ALDER N 47° W 28.70' TO SPIKE. A 6' TALL WHITE FIBERGLASS POST NORTH 1.0'

REFERENCE SURVEYS

1 = CS No. 2022 = CS No. 4653 = CS No. 2810

4 = CS No. 28695 = CS No. 3516

6 = CS No. 3785

* NOTE:

THIS SURVEY HAS BEEN RECORDED FOR INFORMATIONAL

PURPOSES ONLY SUNUEPOR NO LONGER HAS AN ACTIVE LICENSE AND THE SURVEY WAS DONE FIFTEEN YEARS PRIOR.

7/14/15. Ma a. Whole

REGISTERED **PROFESSIONAL** LAND SURVEYOR

OREGON JULY 30, 1976 LESLIE G. KEENON RENEWAL DATE 6/30/01

RAWN BY: DDW

LAND ENON

1224 ALDER ST. (503) 429-6115

VERNONIA, OR 97064 FIELD: MWM/JDB

SURVEY FOR

HANCOCK T.R.G. IN THE NE 1/4 OF SECTION 9, T4N, R4W, W.M. COLUMBIA COUNTY, OREGON SCALE 1" = 100JULY 14, 2000

EQUIPMENT: GTS300/TDS48 JOB No.00-116 PROJECT No. 00-116

SURVEYORS OFFICE RECEIVED 7/16/15 ACCEPTED 7/6/15 CHECK #_

REVISED: 7/21/00

COLUMBIA COUNTY

CS M-621