

LEGEND

- - CORNER FOUND AS NOTED
- - CORNER ESTABLISHED
- CZBC = 2" X 30" CONCRETE FILLED GALVANIZED IRON PIPE WITH BRASS CAP
- RECORD TITLE LINE : BLAZED BOTH SIDES OF LINE
CZ SIDE TAGGED WITH P.L. TAGS AND ADJACENT SIDE PAINTED

SURVEY PLAT REFERENCE :
#1 = ORIGINAL G.L.O., BEARING & DISTANCE IN CHAINS
#2 = PLAT # 191A
#3 = PLAT # 2810
#4 = PLAT # 2869

REFERENCE SURVEYS : 191A, 202, 465, 1547, 2810, 2869 & 3413

NOTE : MEASUREMENTS TO NEW BEARING TREES ARE TO A 3/4" COPPER DISC NAILED TO THE BT FACE. THE 2ND DISTANCE IS TO THE CENTER OF THE TREE. MAGNETIC VARIATION = 21 1/2' EAST. SET A WHITE FIBER GLASS POST ADJACENT TO THE CORNER POINT.

SURVEYORS CERTIFICATE :
I, HAROLD J. RUSSELL, A LICENSED LAND SURVEYOR IN THE STATE OF OREGON, HEREBY CERTIFY THAT THIS PLAT REPRESENTS A SURVEY THAT WAS PERFORMED USING PROPER METHODS AND IN ACCORDANCE WITH STATE STATUTES AND THE B.L.M. MANUAL OF SURVEYING INSTRUCTIONS.


SURVEY BY :
HAROLD J. RUSSELL
ROUTE 3 BOX 268C
GASTON, OREGON 97119
DRAFTED ON HP 7478A PLOTTER



SCALE: 1" = 500 FEET

NARRATIVE :

PURPOSE OF THE SURVEY WAS TO SUBDIVIDE THE SECTION, ESTABLISH THE REQUIRED SUB-DIVISION AND PROPERTY CORNERS AND MARK CROWN ZELLERBACH'S RECORD TITLE BOUNDARY LINES BASED ON THE FOUND AND HELD FOR CONTROL CORNERS. SURVEY PLAT #2810 DID NOT SHOW A PROPER PROCEDURE FOR THE ESTABLISHMENT OF THE C 1/4 CORNER, SO I THEREFORE ESTABLISHED THE CORNER IN ITS CORRECT POSITION. CORNER #7 WAS ESTABLISHED WEST, ALONG THE SECTION LINE, 1680.00 FEET FROM THE 1/4 CORNER FOR SECTIONS 9 AND 16 AS PER THE DEED CALL.



COUNTY SURVEYOR

RECEIVED 3-13-86
FILED 3-25-86

SURVEY FOR: CROWN ZELLERBACH CORPORATION

IN SECTION 9, T.4 N., R.4 W., W.M.
COLUMBIA COUNTY, OREGON
DATE: MARCH 11, 1986

REFER TO MY LAND CORNER RECORDS NO. 1 THROUGH NO. 8 FOR FOUND (AND HELD FOR CONTROL) CORNER DETAIL. BASIS OF BEARING FROM SURVEY PLAT #3413 FROM THE SECTION LINE BETWEEN SETIONS 4 AND 9