"Q" BOOK 204, PAGE 674 BOOK 77, PAGE 508 265.44 419.48 ST (521) N 87°37'00" E 684.91' REFERENCE SURVEYS IVY ST. 1 = CS No. B-202 2 = CS No. 224 3 = CS No. 3972 4 = CS No. 4018 5 = CS No. 3025 6 = CS No. 4212 N 87°37'00" E 701.92' LEGEND

OREGON JULY 30, 1976

LESLIE G. KEENON

1080

RENEWAL DATE 6/30/97

DRAWN BY: DDW

N 87°26'10" W 266.75'

JUNIPER ST.

No.

HWY

N 87°37'00" E 439.95'

= MONUMENT FOUND AS NOTED

( ) = RECORD SURVEY DATA

[ ] = RECORD DEED DATA

CS No. = RECORD SURVEY No.

Y.P.C. = YELLOW PLASTIC CAP

= CONTROL POINT No.

 $\bigcirc$  = SET A 5/8" x 30" IRON ROD WITH A Y.P.C.

MARKED "KEENON LAND SERVICES INC."

REFERENCE DEEDS 1 = INSTRUMENT No. 91-25402 = INSTRUMENT No. 91-71633 = INSTRUMENT No. 94-48934 = INSTRUMENT No. 91-7647 5 = INSTRUMENT No. 95-5056 6 = INSTRUMENT No. 90-45227 = INSTRUMENT No. 96-52048 = INSTRUMENT No. 93-79289 = INSTRUMENT No. 96-4133 10 = INSTRUMENT No. 95-10154 11 = INSTRUMENT No. 88-3179 12 = DEED BOOK 204, PAGE 674

LAND PROPERTY LINE ADJ. AND BOUNDARY SURVEY FOR REGISTERED PROFESSIONAL ED BUCKNER, WES BAKER LAND SURVEYOR

1224 ALDER ST.

VERNONIA, OR 97064

FIELD: DDW/MM

(503) 429-6115

N 88°47'56" W 323.95'

1[EAST 590']

AND ROBIN BASSETT IN THE NW 1/4 OF SECTION 3, T4N, R4W, W.M. COLUMBIA COUNTY

N 89°30'13" W 127.35' 1(N 89°34'43" W 127.36')

SCALE 1" = 100

SHEET 1 OF 2

COLUMBIA COUNTY SURVEYORS OFFICE RECEIVED 8-4-91 ACCEPTED/0-30-91 CHECK # 186

JUNE 30, 1997 EQUIPMENT: GTS300/TDS48 JOB No. 97-073 PROJECT No. 95-160

REVISED: 9-20-97

NARRATIVE:

--THIS SURVEY WAS ACCOMPLISHED AT THE REQUEST OF ROBIN BASSETT, AND WES BAKER TO MONUMENT THE TRACTS AS SHOWN AND TO MONUMENT A PROPERTY LINE ADJUSTMENT FOR ED BUCKNER.

--THE BASIS OF BEARINGS IS FROM CS No. 42#2.

FOR CONTROL I HELD THE MONUMENTS OF RECORD AS NOTED IN THE CORNER NOTES. THE CS No. 3972 AND 4018 INCORRECTLY NOTED SEVERAL BEARINGS AND DISTANCES. THIS SURVEY CORRECTLY DENOTES THOSE MEASUREMENTS.

BAKER TRACT DESCRIBED IN CLERKS INSTRUMENT No. 91-7163.

--I ESTABLISHED THE SW CORNER AT THE MIDPOINT BETWEEN THE SW CORNER OF CLERKS INSTRUMENT No. 91-7647 608 AND THE SE CORNER OF

BAKER TRACT DESCRIBED IN CLERKS INSTRUMENT No. 94-4893.

--I HELD THE POINT OF BEGINNING BEING 1510.55' FROM THE SW CORNER OF SECTION 34. FOR THE SW CORNER I HELD THE DEEDED DISTANCE ON A LINE FROM THE POINT OF BEGINNING TO THE SW CORNER OF CLERKS INSTRUMENT No. 91-7163. I ESTABLISHED THE SE CORNER AT THE DEEDED DISTANCE FROM THE SW CORNER ON A BEARING THAT IS PARALLEL WITH THE NORTH LINE OF THE NW 1/4. I HELD THE EAST LINE PARALLEL WITH THE WEST LINE OF THE TRACT.

BUCKNER TRACT CLERKS INSTRUMENT No. 93-7928. --THIS TRACT IS DESCRIBED AS BEGINNING S 89°34' 00" E 810.55 FEET AND S 2'23'00" E 20.00 FEET FROM THE SW CORNER OF SECTION 34; THENCE SOUTH 619 FEET; THENCE EAST 590 FEET; THENCE NORTH 200; FEET THENCE WEST 390 FEET; THENCE NORTHWESTERLY 419 FEET; THENCE WEST 200 FEET TO THE POINT OF BEGINNING. IN 1926 ANDREW PARKER OWNED THE LAND SHOWN ON THIS SURVEY AND HAD A SURVEY DONE, CS No. 224, TO DIVIDED THE LAND. MOST OF THE DEEDS IN THIS AREA CONFORM TO CS No. 224. THE DESCRIPTION OF BUCKNER'S TRACT DOE'S NOT FOLLOW CS No. 224. BUT IT IS MY INTERPRETATION THAT THE INTENT OF THE DEED WAS TO CONFORM TO CS No. 224. THEREFORE FOR THE WEST LINE I HELD THE EAST LINE OF TRACTS "M" N"", "O", AND "P" PER CS No. 224. FOR THE SW CORNER OF THE TRACT I HELD THE SE CORNER OF TRACT "P" PER CS No. 224. THE DEEDED DISTANCE FROM THE POINT OF BEGINNING WOULD PLACE THIS CORNER APPROXIMATELY 5' NORTHERLY FROM THIS LOCATION. BUT BASED ON ADJOINER CALLS AND OCCUPATION I BELIEVE THE INTENT WAS TO GO TO THE SE CORNER OF TRACT "P". FOR THE SOUTH LINE OF THE TRACT I HELD THE SE CORNER OF TRACT "P", THE 5/8" IRON RODS (15) AND (16) AS ESTABLISHED IN CS No. 3025 FOR THE NORTH LINE OF DEED BOOK 77, PAGE 508. FOR THE EASTERLY LINE I HELD THE WEST LINE OF THAT TRACT DESCRIBED IN DEED BOOK 186, PAGE 885 AS MONUMENTED IN CS No. B-202 AND 3025. I ESTABLISHED THE SOUTHERLY NORTH LINE OF THE TRACT ON A LINE DEFINED BY A POINT ON THE EAST LINE THAT IS DEEDED AS BEING S 89'34'00" E 1361.05 FEET AND S 2'23'00" E 455.6 FEET FROM THE NW CORNER OF SECTION 3, AND A POINT ON THE WEST THAT IS DEEDED AS BEING S 89'34'00" E 761.05 FEET AND S 2'23' E 442.85 FEET FROM THE NW CORNER OF SECTION 3.

BASSETT TRACT DESCRIBED IN CLERKS INSTRUMENT 88-3179.

--THIS TRACT IS DESCRIBED BY A METES AND BOUNDS DESCRIPTION
THAT FOLLOWS TRACT "D" AND "E" EXCEPTING THE EASTERLY 46.5' OF
TRACT "F" PER CS No. 224

## MONUMENT NOTES:

- NORTH 1/4 CORNER SECTION 3
  1 1/2" IRON PIPE WITH A PINCHED TOP IN MONUMENT BOX
- 7 A 1/2" IRON PIPE PER CS No. L-156. S 1.26', W 0.21'
- 15 FOUND A 5/8" IRON ROD WITH A MARIS CAP PER CS No. 3025. HELD FOR THE NW CORNER OF DEED BOOK 77, PAGE 508 AND SOUTH LINE OF BUCKNER TRACT
- 16 FOUND A 5/8" IRON ROD WITH A MARIS CAP PER CS No. 3025. HELD FOR THE SW CORNER OF DEED BOOK 186, PAGE 885 AND SE CORNER OF BUCKNER TRACT.
- SW CORNER OF SECTION 34 FOUND A 1 1/2" IRON PIPE.
- SOUTH 1/4 CORNER SECTION 34
  A 5/8" IRON ROD WITH MORRIS CAP PER CS No. L-1073 BEARS S 89'19'W
  8 23'
- 520 FOUND A 5/8" IRON ROD WITH A Y.P.C. MARKED "KEENON LS 1080" PER
- FOUND A 5/8" IRON ROD WITH A MARIS CAP PER CS No. 3025. HELD FOR THE SE CORNER OF DEED BOOK 145, PAGE 393 AND THE NORTH LINE OF IVY STREET.
- FOUND A 5/8" IRON ROD WITH A MARIS CAP PER CS No. 3025. HELD FOR THE SOUTH LINE OF IVY STREET.
- 525 FOUND A 5/8" IRON ROD WITH A Y.P.C. MARKED "KEENON LS 1080" PER CS No. 3972. HELD FOR NW CORNER OF TRACT "O" PER CS No. 224.
- FOUND A 5/8" IRON ROD WITH A Y.P.C. MARKED "KEENON LS 1080" PER CS No. 3972. HELD FOR NE CORNER OF TRACT "O" PER CS No. 224.
- FOUND A 5/8" IRON ROD WITH A Y.P.C. MARKED "KEENON LS 1080" PER CS No. 3972. HELD FOR NW CORNER OF TRACT "F" PER CS No. 224.
- 545 FOUND A 5/8" IRON ROD WITH A Y.P.C. MARKED "KEENON LS 1080" PER
- CS No. 3972. HELD FOR SW CORNER OF TRACT "P" PER CS No. 224.

  546 FOUND A 5/8" IRON ROD WITH A Y.P.C. MARKED "KEENON IS 1080" PER
- CS No. 3972. HELD FOR SE CORNER OF TRACT "O" PER CS No. 224.
- 547) FOUND A 5/8" IRON ROD WITH A Y.P.C. MARKED "KEENON LS 1080" PER CS No. 3972. HELD FOR SW CORNER OF TRACT "O" PER CS No. 224.
- 558 FOUND A 5/8" IRON ROD WITH A Y.P.C. MARKED "KEENON LS 1080" PER CS No. 3972. HELD.
- 559 FOUND A 5/8" IRON ROD WITH A Y.P.C. MARKED "KEENON LS 1080" PER CS No. 3972. HELD.
- 561) FOUND A 5/8" IRON ROD WITH A Y.P.C. MARKED "KEENON LS 1080" PER CS No. 3972 HELD
- 607) FOUND A 5/8" IRON ROD WITH A Y.P.C. MARKED "KEENON LS 1080" PER CS No. B-202. HELD
- 609 FOUND A 5/8" IRON ROD WITH A Y.P.C. MARKED "KEENON LS 1080" PER CS No. B-202. HELD

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 30, 1976
LESLIE G. KEENON
1080

RENEWAL DATE 6/30/97

1224 ALDER ST.
VERNONIA, OR 97064
(503) 429-6115

ED BUCKNER, WES BAKER
AND ROBIN BASSETT
IN THE NW 1/4 OF SECTION 3,
T4N, R4W, W.M.
COLUMBIA COUNTY
JUNE 30, 1997

PROPERTY LINE ADJ. AND BOUNDARY SURVEY FOR

SHEET 2 OF 2

DRAWN BY: DDW

FIELD: DDW/MM

EQUIPMENT: GTS300/TDS48 | JOB No. 97-073 | PROJECT No. 95-160

REVISED: 9-20-97

4347 20FZ

2007