



CORNER ① FOUND
section corner common to T, 18, 12, 13
T4N R4E5W W.B. & M.
fd. a 40" DF STUMP S 20 E - 8 1/2' SCARRED
" 36" DF STUMP S 50 W - 14'
" 40" DF STUMP N 50 W - 18 1/2'
SCRIBED (1895)
" 36" DF STUMP S 50 E - 13'
SCRIBED (1895)
blazed & scribed
" 16" DF S33W - 20 1/2'
" 23" DF N50W - 26 1/2'
" 14" DF N20E - 26 1/2'
" 16" DF S54E - 30'

CORNER ② SET
w 1/6 corner T, 18
SET 1" AL. PIPE W/BRASS CAP
SCRIBED:
16" DF N57W - 4 1/2'
11" DF S03W - 23 1/2'
SET A YELLOW TAG
N - 2' ON 4" DF

CORNER ③ FOUND (1 1/2" I.P. BURIED & BENT)
1/4 corner T, 18
T4N R4W W.B. & M.
fd. 48" STUMP N66W - 41' DECAYED
" 48" STUMP N76E - 49' DECAYED
" 1" I.P. 16" HIGH IN A 1 1/2" I.P. 12" HIGH
N88E - 30 1/2'
SET 1" X 12" BRIDGE SPIKE IN PAVEMENT
" YELLOW TAG N77E - 12'
ON POWER POLE
" YELLOW TAG N88W - 32'
ON FENCE CORNER POST

COLUMBIA COUNTY SURVEYOR
DATE RECEIVED 5-27-77
DATE FILED 5-27-77

REGISTERED
PROFESSIONAL
LAND SURVEYOR
Leslie S. Keenon
OREGON
JULY 30, 1976
LESLIE G. KEENON
P.L.S. 1080

		DRAWN BY EGD
		CHECKED BY
		SCALE 1" = 400'
DATE	REVISIONS	

TITLE COLUMBIA COUNTY, OREGON
Sec. 7, T4N, R4W.



DATE 5-19-77
SHEET NO. 1 of 1
DRAWING NO. 1 of 1

BY *MW*