SECTION CORNER SECTION CORNER COMMON TO SECTIONS 23, 24, 25, AND 26 FOUND A 2" IRON PIPE UP 6" PER BEARING TREE BOOK C, PAGE 182, COLUMBIA COUNTY SURVEY RECORDS. REFERENCES FOUND: AN 18" FIR STUMP N 03° E 10.0' TO CENTER, WITH A HEALED BLAZE.

A 21" FIR STUMP N 85° E 17.6' TO CENTER, WITH A HEALED BLAZE. A 16" FIR STUMP LEANING TO THE NORTHWEST S 54° E 19.3' TO CENTER NARRATIVE: OF RECONSTRUCTED UPRIGHT LOCATION, WITH A HEALED BLAZE. A 30" FIR STUMP, S 88° W 12.8' TO CENTER, WITH A HEALED BLAZE. --THIS SURVEY WAS ACCOMPLISHED AT THE REQUEST OF HANCOCK A 3" x 4" WOOD POST BEARS N 45° E 2.5'. TIMBER RESOURCE GROUP TO MARK AND MONUMENT THE BOUNDARY AN EAST-WEST LOGGING ROAD IS SOUTH 25' TO CENTERLINE. LINES AS SHOWN. REFERENCES SET: A 13" FIR S 65° E 35.35' TO SPIKE. — THE BASIS OF BEARINGS IS FROM CROWN ZELLERBACH RECORD 5526—01 A 12" FIR S 51° E 7.94' TO SPIKE. BETWEEN THE 1/4 CORNER COMMON TO SECTIONS 25 AND 26, AND THE A 13" FIR N 09° W 2.18' TO SPIKE. SECTION CORNER COMMON TO SECTIONS 23, 24, 25, AND 26. A 9" FIR S 37° W 11.05' TO SPIKE. --ALL REFERENCES WERE MEASURED WITH A HAND COMPASS SET AT DECLINATION 21° EAST AND A STEEL TAPE. UNLESS OTHERWISE 26 | 25 NOTED, ALL NEW BEARING TREES WERE MEASURED TO THE HEAD OF A 3" TRACK SPIKE SET IN THE BASE BLAZE OF 4 BLAZES UP THE FACE. BEARING TREE TAGS WERE PLACED AT SHOULDER HEIGHT ABOVE THE --THE BOUNDARY LINES SHOWN IN BOLD WERE MARKED WITH RED AND WHITE RIBBON ON LINE. TREES WITHIN 10' OF A BOUNDARY LINE WERE MARKED WITH A SINGLE BLAZE AT CHEST HEIGHT FACING TOWARDS THE BOUNDARY LINE. ON HANCOCK TIMBER RESOURCE GROUP PROPERTY, BOUNDARY REFERENCE TAGS WERE PLACED IN A SLICE AT THE LOWEST PART OF THE ROOT CROWN ON TREES WITHIN FOUR FEET OF LINE, FACING TOWARDS THE BOUNDARY LINE, AT APPROXIMATELY 50' INTERVALS. NORTH 1/16 CORNER SET A 5/8" IRON ROD WITH A Y.P.C. MARKED "KEENON LAND SERVICES INC." UP 4" AT THE BASE OF A 34" CEDAR TO THE NORTHEAST. REFERENCES SET: A 26" FIR N 65" W 50.94' TO SPIKE. AN 8" CEDAR S 10" W 45.97' TO SPIKE. A 1/2" X 6' FIBERGLASS FENCE POST SOUTH 2'. AN OLD 4" x 4" WOOD POST S 45° W 1.5'. A 1" IRON PIPE WITH A PLUMBERS CAP PER CROWN ZELLERBACH BEARING TREE PECORDS BEARS S 04°51'46" E 31.06'. 1/4 CORNER 1/4 CORNER COMMON TO SECTIONS 25 AND 30
FOUND A 1" STAINLESS STEEL PIPE UP 20" PER BEARING TREE
BOOK C, PAGE 270, COLUMBIA COUNTY SURVEY RECORDS. REFERENCES FOUND: 1/4 CORNER A 10" FIR S 57° E 4.6' TO CENTER, WITH A HEALED BLAZE.

A DOWNED A ROTTING 10" FIR WITH A HEALED BLAZE S 89° W 15'
TO CENTER OF STANDING LOCATION. 1/4 CORNER COMMON TO SECTIONS 25 AND 26 FOUND A 2" IRON PIPE PER CROWN ZELLERBACH BEARING TREE RECORDS CENTER OF SECTION A METAL FENCE POST WITH A LONGVIEW FIBRE METAL LOCATION FOUND A 1" STAINLESS STEEL PIPE UP 18 PER BEARING TREE BOOK C, PAGE 251, COLUMBIA COUNTY SURVEY RECORDS. REFERENCES FOUND: TAG SOUTH 1'. A 40" FIR SNAG N 74° E 18.3' TO FACE OF A HEALED BLAZE, WITH A AN EAST-WEST LOGGING ROAD IS NORTH 35' TO CENTERLINE. REFERENCES SET: A 21" FIR N 51° E 29.84' TO SPIKE. METAL LOCATION TAG. A 17" FIR S 29° E 12.1' TO CENTER, WITH A HEALED BLAZE. A 12" FIR S 40° W 9.12' TO SPIKE IN LOWEST OF 4 HEALED BLAZES, WITH A 14" FIR N 62° E 17.2' TO CENTER, WITH A HEALED BLAZE. A METAL LOCATION TAG. A 19" FIR S 04° E 44.30' TO SPIKE. A 50" DOUBLE FIR STUMP S 82° E 30.2' TO FACE OF BLAZE A 20" FIR N 34° W 22.92' TO SPIKE IN LOWEST OF 4 HEALED BLAZES. I A 7" FIR N 82° W 44.34' TO SPIKE. ATTACHED A NEW METAL LOCATION TAG. A 60" FIR SNAG N 09° W 27.50' TO FACE OF BLAZE SCRIBED "BT 1/4 CS". I A METAL FENCE POST WITH LONGVIEW FIBRE COMPANY LOCATION TAG WEST 1'. ATTACHED A NEW METAL LOCATION TAG. A 4" x 4" WOOD POST N 45° W 2.5'. I SET 1/2" X 6' FIBERGLASS FENCE POST SOUTH 1'. 26 / 25 25 S 89°49'53" W 2517.82' S 89°46'51" W 2575.43' 1302.02 1215.80' 3(S 89°56' E 1216.0') FOUND A 1" STAINLESS STEEL PIPE UP 20" PER BEARING TREE BOOK C, T5N, PAGE 251, COLUMBIA COUNTY SURVEY RECORDS S 00°11'39" E 1.35' FROM E-W CENTERLINE OF SECTION. NOT HELD. REFERENCES FOUND: A 25" CEDAR N 24° W 8.7' TO CENTER, WITH A HEALED BLAZE. A METAL FENCE POST WITH LONGVIEW FIBRE COMPANY LOCATION TAG NORTH 1'.
A 4" x 4" WOOD POST N 45° W 2'.

LEGEND

= MONUMENT FOUND AS NOTED

O = SET A 5/8" x 30" IRON ROD WITH A Y.P.C. MARKED "KEENON LAND SERVICES INC."

() = RECORD SURVEY DATA

CS = RECORD SURVEY No.

Y.P.C. = YELLOW PLASTIC CAP

REFERENCE SURVEYS

1 = BERNDT'S CREEK SUBDIVISION 2 = CROWN ZELLERBACH RECORD 5526-01

3 = CS No. L-527

4 = CS No. L842 5 = CS No. 3903 PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 30, 1976
LESLIE G. KEENON

1080

RENEWAL DATE 6/30/01

RAWN BY: VSS

REGISTERED

LAND
NONE
HE ST.

1224 ALDER ST.
VERNONIA, OR 97064
(503) 429-6115
FIELD: VSS/MM/JB

SURVEY FOR

HANCOCK TIMBER RESOURCE GROUP IN THE N 1/2 OF SECTION 25 T5N, R5W, W.M.

COLUMBIA COUNTY, OREGON SCALE 1" = 400' JAN. 14, 2000 COLUMBIA COUNTY
SURVEYORS OFFICE
RECEIVED____

ACCEPTED_____CHECK #_____

REVISED: 2/24/00

EQUIPMENT: GTS300/TDS48 JOB No.00-017

PROJECT No. 00-017