Fd E-W fence 16 ft. South

Prop. Con.

Set 1" IP W/ yellow

Pla. cap marked

01 Art & Veda Johnson

DB 104, Pg. 230

Art & Veda Johnson

DB 106, Pp 129 N 25°48 #3" W 3.63

Scribed 20" Fir N 20°W 16.3

20" Fir N 76°W 20.32

1026.00 (Deed Held)

1177. 1177. 1177.

1" IRON Pipe Fd. Section Cor. 12 13 1026.00 (Deed Held)

N 88° 22' E (Deed Held)

Side. N 88° 22' E (Deed Held)

2673.76

Fd 24" Fir S62°41'50" W 60.53 (fore Grown over, not chopped out) Fd. 18" Fir Stamp N 62°39'36" W 19.95 (NO scribs visibal) Fd 16" Fir N 21°55'10" E 12.75 (fore grown over, not chopped out)

Fd leaning dead cedar free approx. 556°E 12'

Set I" Iron Pipe W/ Yellow Pla.

Fd 34" IPN65°31'31" E 2.35
Fd 13" Hem NISE 3.63 from Fd Pipe
Fd 29" Fir 3 4 E 7.83
Fd 20" Fir 842W 19.75 " "

Scribed CS BT Esetyellow tog on 13" Fin NB4°W 20.30

"FIT Stamp N 52°39'38"W 19.95 Lines Flagged
FIT N 21°55'10" E 12.75 & Blazed

(N89°45'E 2686.2 C.S. 470) (2692.7 C.S. 2555)

(N89°17'E 2698.0 C.S. 1025 & CS 2593)

NARRATIVE:

Beginning on July 20, 1982, with a Franke Theodolite and a Mac 1-H E.D.M. we ran a random traverse line from the S. /4 corner of Section 12 to the S.W. corner of Section 12; thence to the E. Vaconner of Section 14; thence back to the s. 1/4 corner of Section 12. The unadjusted closure of this troverse was I foot in 31,800 feet. From this traverse we tied in the corners and Bearing Trees shown hereon and calculated offsets to the true lines of the westerly 1026 feet of the south line of Section 12 and the northerly 1312.17 feet of the east line of section 14. We flagged and blazed these lines and set the corners shown. The field survey was completed on August 11, 1982.

> Philip Dewey Land Surveyor Courthouse St. Helens, Oregon 97051

Scale: 1"= 200 ft.

Basis of bearing is Deed Book 106, Page 129

Calong the S.line of Section 12)

See Flel. Bk. 137, Pg. 6-13 See Work Map # 502

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
PHILIP DEWEY

Survey for Longview Fibre Co.

on the S. line of the SW/4 of the SW/4

of Section 12, T. 4N, R. 5 W., W.M.

and the E. line of the NE/4 of the NE 1/4

of Section 14, T. 4 N., R. 5 W., W.M.

Columbia County, Oregon

August 17, 1982

Fd /2" IP flush with ground o Fd tall IP along side Fd Rotted 50" Firstum P 589°30'18" F 9.35 Fd 24" Fir N40°01' 14" E 19.70 Fd 24" Fir \$61°06' 49" W 17.55