1/4 CORNER BETWEEN SECTIONS 13 AND 24

FOUND A 1" IRON PIPE UP 1.2' ORIGIN UNKNOWN, NOTED IN PAGE 10 OF CROWN ZELLERBACH BEARING TREE NOTES.
A 4" x 4" WOOD POST WITH A LOCATION TAG IS NORTHWEST 1'.

REFERENCES SET:

A 16" FIR S 31° E 41.70' TO SPIKE SET IN LOWEST OF FOUR BLAZES, WITH A METAL LOCATION TAG.
AN 11" FIR S 81° W 17.38' TO SPIKE SET IN LOWEST OF FOUR BLAZES,

WITH A METAL LOCATION TAG.


THERE IS NO SIGN OF ORIGINAL G.L.O. BEARING REFERENCE, OR TREE AT

SECTION CORNER COMMON TO SECTIONS 13 AND 24, T 5N R 5W, AND SECTIONS 18 AND 19, T 5N R 4W

FOUND A 1" GALVANIZED IRON PIPE WITH A Y.P.C. MARKED "KEENON LAND SERVICES INC." INSIDE A 2" IRON PIPE. REFERENCES FOUND: AN18" HEMLOCK STUMP N 34° W 47.65' TO SPIKE SET IN FACE.

AN 11" FIR N 71° E 19.40' TO SPIKE IN LOWEST OF 4 BLAZES. A 12" FIR S 65° E 5.46' TO SPIKE IN LOWEST OF 4 BLAZES.
A 21" FIR S 70° W 40.45' TO SPIKE IN LOWEST OF 4 BLAZES.
A WHITE 4" x 4" WOOD POST N 45° E 1.5'.

AN OLD BARBED WIRE FENCE LAYING ON GROUND RUNS NORTH AND



LEGEND

REFERENCE SURVEYS

1 = UNRECORDED HANCOCK T.R.G. SURVEY

= MONUMENT FOUND AS NOTED

O = SET A 5/8" x 30" IRON ROD WITH A Y.P.C. MARKED "KEENON LAND SERVICES INC."

() = RECORD SURVEY DATA

[] = RECORD DEED DATA

CS No. = RECORD SURVEY No.

Y.P.C. = YELLOW PLASTIC CAP

= CONTROL POINT No.

CURVE AND LINE TABLE

CURVE	RADIUS	LENGTH	TANGENT	CHORD	BEARING	DELTA
C1	390.00'	154.82'	78.44'	153.80'	S 09°41'02" E	22°44'40"
C2	420.00'	349.42'	185.54'	339.43'	N 02°46'40" E	47°40'04"
СЗ	305.00'	200.63	104.09'	197.03'	S 07°46'03" W	37*41'20"
LINE	DIRECTION	DISTANCE				
IJ	S 26°36'42" W	115.35'				

LAND REGISTERED **PROFESSIONAL** LAND SURVEYOR OREGON JULY 30, 1976 LESLIE G. KEENON 1080

RENEWAL DATE 6/30/01

RAWN BY: VSS

1224 ALDER ST. VERNONIA, OR 97064 (503) 429-6115 FIELD: MM/JB

NARRATIVE:

THIS SURVEY WAS ACCOMPLISHED TO ADJUST THE PROPERTY LINES SHOWN AT THE REQUEST OF

THE BASIS OF BEARINGS ARE BETWEEN FOUND MONUMENT 63 AND 59 PER AN UNRECORDED 1998 HANCOCK T.R.G. SURVEY.

I HELD THE FOUND MONUMENTS SHOWN, AND ESTABLISHED THE NEW PROPERTY LINE PER BOB

PROPERTY LINE ADJUSTMENT FOR

BOB GREGG IN THE NE 1/4 OF SECTION 24, T5N, R5W, W.M. COLUMBIA COUNTY, OREGON SCALE 1'' = 200'APRIL 5, 2000

COLUMBIA COUNTY SURVEYORS OFFICE RECEIVED_ ACCEPTED_ CHECK #_

EQUIPMENT: GTS300/TDS48 JOB No. 00-063 PROJECT No. 00-063 REVISED: