

CS# 6890

SHEET 1 OF 2



# RECORD OF SURVEY

IN THE SE 1/4 OF SECTION 19,
THE NW 1/4, NE 1/4 AND SE 1/4
OF SECTION 20, THE NW 1/4,
NE 1/4 AND SE 1/4 OF
SECTION 28, T4N, R3W, W.M.
COLUMBIA COUNTY, OREGON



#### LEGEND:

- INDICATES MONUMENT FOUND (UNLESS NOTED OTHERWISE)
- ( ) INDICATES RECORD INFORMATION PER SURVEY REFERENCE NUMBER

INDICATES LINE MARKED WITH 1/2" x 72" FIBER GLASS RODS WITH RED RIBBON. TREES ALONG LINE BLAZED AND PAINTED WITH RED PAINT.

CS COUNTY SURVEY

BLM BUREAU OF LAND MANAGMENT

GPS GLOBAL POSITIONING SYSTEM

RTK REAL TIME KINEMATIC



SCALE: 1"=1000'

JOB NO. 20-143

DATE: 3-22-2022

CALC BY: GAB

DRAWN BY: TJC

CHECKED BY: EVB

SHEET \_1\_ OF \_2

PO BOX 414
AMBOY, WA 98601
360-600-0846
ebrownsurveying@gmail.com

CS# 6890

- FOUND AND HELD BLM 3" BRASS CAP AS SHOWN ON CS 3435 **EXISTING REFERENCES:** 15" FIR, N45"W, 26.65' TO SC 10" FIR STUMP, N65"W, 10.95' TO SC **NEW REFERENCES:** 13" FIR, S40°E, 3.85' 7" FIR, S80°W, 11.25'
- FOUND AND HELD CZ 3" BRASS CAP AS SHOWN ON CS 3435 **EXISTING REFERENCES:** 23" FIR, S53°E, 29.50' TO SC 12" FIR, N64"W, 21.2' TO SC SET FIBERGLASS POST SOUTH, 0.1'
- FOUND AND HELD CZ 3" BRASS CAP AS SHOWN ON CS 3435 **EXISTING REFERENCES:** 51" FIR WITH HEALED BLAZE, SO3"E, 161.4' TO SC 22" FIR GROWING ON TOP OF 7' STUMP WITH VISIBLE SCRIBING, S89°W, 53.4' TO SC 37" FIR WITH HEALED BLAZE, N29"W, 50.3' TO SC **NEW REFERENCES:** 16" FIR, S59"W, 42.23" SET FIBERGLASS POST SOUTH, 0.2'
- FOUND AND HELD BLM 3" BRASS CAP AS SHOWN ON SURVEY REFERENCE NO. 4 **EXISTING REFERENCE:** 25" FIR WITH HEALED BLAZE, N32"W, 24.8' TO SC **NEW REFERENCES:** 31" FIR, N52°E, 19.85' 20" FIR, N84°E, 31.75' SET FIBERGLASS POST EAST, 0.1'
- FOUND AND HELD BLM 3" BRASS CAP AT WITNESS CORNER AS SHOWN ON SURVEY REFERENCE NO. 4 **EXISTING REFERENCE:** 34" FIR, S74°E, 4.7' TO SC **NEW REFERENCES:** 26" FIR, S08"W, 34.40" 28" FIR, S74"W, 26.75' 24" ALDER, N72°W, 14.10'
- FOUND AND HELD BLM 3" BRASS CAP AS SHOWN ON SURVEY REFERENCE NO. 4 **EXISTING REFERENCE:** 17" FIR STUMP WITH HEALED BLAZE, \$26°W, 78.5' TO SC **NEW REFERENCES:** 4" FIR STOB, N31°E, 1.6' 16" HEMLOCK, N81°E, 11.45' 16" HEMLOCK, NO9"W, 19.85'
- FOUND AND HELD BLM 3" BRASS CAP AS SHOWN ON SURVEY REFERENCE NO. 4 **EXISTING REFERENCES:** 27" FIR, S53°E, 34.3' TO SC 40" FIR, S63"W, 21.1' TO FACE SET FIBERGLASS POST SOUTH, 0.2'
- FOUND AND HELD 2 1/2" BRASS CAP AS SHOWN ON CS 3435 **EXISTING REFERENCES:** 42" FIR WITH HEALED BLAZE, N68°E, 23.1' TO RRS IN FACE 30" FIR WITH HEALED BLAZE, S36"E, 20.5' TO SC 19" ALDER, S37°E, 8.0' TO RRS AT FACE 45" FIR STUMP, S75"W, 4.6" 28" FIR WITH HEALED BLAZE, N26"W, 23.2' METAL "T" POST EAST, 0.5'
- FOUND AND HELD CZ 3" BRASS CAP AS SHOWN ON CS 3435 **EXISTING REFERENCES:** 25" FIR GROWING ON TOP OF 6' STUMP, S46°E, 6.9' TO SC 22" FIR WITH HEALED BLAZE, N72"W, 14.2' TO SC **NEW REFERENCES:** 38" FIR, N84°E, 21.94' TO SC SET FIBERGLASS POST EAST, 0.2'

- FOUND AND HELD BLM 3" BRASS CAP AS SHOWN ON CS 2348 **EXISTING REFERENCES:** 30" FIR WITH HEALED BLAZE, N33°E, 20.5' TO SC 17" FIR WITH HEALED BLAZE, S41°E, 13.9' TO SC 31" FIR WITH HEALED BLAZE, S50°W, 3.0' TO SC 8" ALDER WITH VISIBLE SCRIBING, N47'W, 29.90' TO SC
- FOUND AND HELD BLM 3" BRASS CAP AS SHOWN ON CS 2348 **EXISTING REFERENCES:** 15" FIR WITH HEALED BLAZE, N33°E, 10.40' TO SC 14" FIR WITH HEALED BLAZE, N85°E, 19.70' TO SC SET FIBERGLASS POST SOUTH, 0.1'
- FOUND AND HELD BLM 3" BRASS CAP AS SHOWN ON CS 2348 **EXISTING REFERENCES:** 9" FIR WITH HEALED BLAZE, S43°E, 15.98' TO SC 17" FIR GROWING ON TOP OF 4' STUMP WITH HEALED BLAZE, S36°W, 7.70' TO FACE 12" FIR WITH HEALED BLAZE, S71°W, 17.40' TO SC SET FIBERGLASS POST SOUTH, 0.3'
- FOUND AND HELD BLM 3" BRASS CAP AS SHOWN ON CS 3077 **EXISTING REFERENCES:** METAL "T" POST WITH SURVEY MARKER SIGN, S62°E, 2.0' 29" FIR WITH HEALED BLAZE, N45"W. 30.50' TO SC
- FOUND AND HELD BLM 3" BRASS CAP AS SHOWN ON CS 3077 **EXISTING REFERENCES:** 13" ROTTED FIR STUMP WITH VISIBLE SCRIBING, NOO'E, 4.2' TO SC METAL "T" POST, N70°E, 2.4' FIBERGLASS POST S16'E, 0.2' **NEW REFERENCES:** 12" FIR, S48°E, 4.80 TO SC 14" FIR, S72"W, 6.10' TO SC
- FOUND AND HELD BLM 3" BRASS CAP AS SHOWN ON CS 2348 **EXISTING REFERENCES:** 14" FIR SNAG, S72"E, 13.9' TO FACE 25" FIR, WEST, 8.0' TO SC FIBERGLASS POST NORTH, 1.9'
- CALCULATED POSITION OF BLM BRASS CAP AS SHOWN ON CS 3077
- CALCULATED POSITION OF BLM BRASS CAP AS SHOWN ON SURVEY REFERENCE NO. 4
- CALCULATED POSITION OF THE NORTHWEST CORNER OF SECTION 28 BY BEARING-BEARING INTERSECTION HOLDING MONUMENTS 3 AND 4 ALONG THE NORTH LINE AND MONUMENTS 5 AND 6 ALONG THE WEST LINE. POSITION FALLS IN GUNNERS LAKE.

## REFERENCE TREE NOTE NEW REFERENCE TREES WERE MEASURED TO A 6" NAIL SET IN SIDE


CENTER OF TREE, ALSO PLACED A BEARING TREE SIGN AND 4 NOTCHES FACING TOWARD THE CORNER. BEARINGS NOTED WERE TAKEN WITH A HAND HELD COMPASS WITH A DECLINATION SET TO 16' EAST

#### SURVEY REFERENCE

- 1) CS 2348
- 2) CS 3077
- 3) CS 3435 4) BLM SURVEY (1986), GROUP NO. 1092
- 5) CS 5831

# RECORD OF SURVEY

IN THE SE 1/4 OF SECTION 19, THE NW 1/4, NE 1/4 AND SE 1/4 OF SECTION 20, THE NW 1/4, NE 1/4 AND SE 1/4 OF SECTION 28, T4N, R3W, W.M. COLUMBIA COUNTY, OREGON



### LEGEND:

INDICATES MONUMENT FOUND (UNLESS NOTED OTHERWISE)

REGISTERED

**PROFESSIONAL** 

LAND SURVEYOR

OREGON NOVEMBER 13, 2012

EDWARD V. BROWN


87015PLS

Renews 12-31-2023

4-12-2022

Ellem

- INDICATES RECORD INFORMATION PER SURVEY REFERENCE NUMBER
- CS COUNTY SURVEY
- BLM BUREAU OF LAND MANAGMENT
- SC SIDE CENTER
- CZ CROWN ZELLERBACH
- RRS RAILROAD SPIKE



NOT TO SCALE

NA SCALE: JOB NO. <u>20-143</u> DATE: 3-22-2022 CALC BY: GAB

DRAWN BY: TJC CHECKED BY: EVB SHEET 2 OF 2

SURVEYING PLLC

PO BOX 414 AMBOY, WA 98601 360-600-0846 ebrownsurveying@qmail.com