




SURVEY for  
CROWN ZELLERBACH  
in the S 1/2, SEC 26, 15N, R4W, W.M.  
COLUMBIA COUNTY, OREGON  
JAN 10, 1986 SCALE 1"=200'



THE 1/4 CORNER OF S23 & S26 DESTROYED BY EXCAVATION WORK  
AT THE PROPER LOCATION I SET A 2" I.P. WITH BRASS CAP, FROM WHICH  
A 13" D.FIR SOUTH, 7.2' HEALED BLAZE MACHINE SCARS NOTED (1963)  
A 24" CEDAR STUMP S74W, 35' (FITS 1898 RESTORATION)  
I MARKED  
A 19" D.FIR S27W, 48.07' TO CENTER OF TREE  
47.32' TO 'B' IN SCRIBED "1/4 S26 T5N R4W BT"  
A 17" D.FIR S85W 52.50' TO CENTER OF TREE  
51.82' TO 'B' IN SCRIBED "1/4 S26 T5N R4W BT"  
ALSO SET A WHITE FIBREGLASS POST 1.0' NORTH

PROPERTY CORNER

S 89° 54' 56" E - 1313.36'

PROPERTY CORNER

FOUND A 1"x48" I.P. 15' OUT WHICH  
I REPLACED WITH A 2" I.P. AND BRASS CAP  
A 22" W.FIR S50E, 15.52' TO CENTER OF TREE  
13.32' TO THE 'B' IN SCRIBED "PROP COR S26 BT"  
A 10" D.FIR S35W, 14.17' TO CENTER OF TREE  
13.76' TO THE 'B' IN SCRIBED "PROP COR S26 BT"  
ALSO A WHITE FIBREGLASS POST 1.0' SOUTH

FOUND A 3"x4" CEDAR POST AS  
NOTED IN 1951. 1" IRON PIPE NOW MISSING  
AT THE PROPER POSITION FROM THE REFERENCE  
TREE, I SET A 2" IRON PIPE WHICH IS  
CONCRETE FILLED, HAVING A 3" BRASS CAP FIXED ON TOP  
A 21" D.FIR N26E 4.55' TO CENTER OF TREE  
2.82' TO THE SCRIBED 'B' IN THE "PROP COR S26 BT"  
A 17" D.FIR N76W 12.92' TO THE CENTER OF TREE  
12.16' TO THE SCRIBED 'B' IN THE "PROP COR S26 BT"  
ALSO A WHITE FIBREGLASS POST SET 1.0' SOUTH

NARRATIVE:  
THE BOUNDARY SURVEYED WERE AT THE REQUEST OF  
CROWN ZELLERBACH CORP OF VERNONIA. MONUMENT RECOVERED  
AS INDICATED, FROM THE 1937 SURVEY BY C.O. MARSTON WHICH  
WAS FOR THE A. PARKER-CLARK & WILSON COMPANY LAND  
EXCHANGE. MONUMENTS FROM THE 1937 SURVEY HAVE BEEN  
PERPETUATED BY THE OWNERS. NOTE THE LAND CORNER  
RECORDED FOR EACH OF THESE MONUMENTS. THE 1/4 CORNER  
WAS REMONUMENTED AND NOT MEASURED. BOUNDARY LINES  
ARE BLAZED AND FLAGGED BETWEEN MONUMENTS.  
BASIS OF BEARINGS IS THE SURVEY OF RECORD CS# 3280.

FOUND A 1"x48" I.P. 18' OUT WHICH  
I REPLACED WITH A 2" I.P. AND BRASS CAP  
A 7" CEDAR N25W - 11.62' TO CENTER OF TREE  
11.29' TO SCRIBED 'B' IN "PROP COR S26 BT"  
A 24" CEDAR S50W - 3.57' TO CENTER OF TREE  
2.70' TO 'B' IN SCRIBED "PROP COR S35 BT"  
A 4x4 WHITE POST FOUND S50E - 2.0'  
SET A WHITE FIBREGLASS POST 1.0' EAST

PROPERTY CORNER

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR  
  
OREGON  
JULY 30, 1976  
LESLIE G. KEENON  
P.L.S. 1080

COUNTY SURVEYOR  
RECEIVED 1-29-86  
FILED 1-31-86

L. JERRY KEENON  
1311 E. ALDER ST.  
VERNONIA, OREGON  
97064  
PH - 429-6115