

NARRATIVE:

-- THE PURPOSE OF THIS SURVEY WAS TO MONUMENT THOSE TRACTS AS SHOWN AT THE REQUEST OF RON DODGE, DONNIE NORMAND AND JIM

-- THE BEARINGS ARE GEODETIC AND WERE BASED ON GPS OBSERVATIONS TAKEN AT COLUMBIA 02, HAVING A OF LATITUDE 45°51'25.28" NORTH, LONGITUDE 123°10'24.80" WEST. THE CONVERGENCE ANGLE (FROM OREGON STATE PLANE COORDINATE SYSTEM NORTH ZONE) AT SAID POINT IS -01°53'45.78". DISTANCES SHOWN ARE GROUND DISTANCES.

BLOCK 2, VERNONIA:
--I HELD MONUMENTS 869 AND 870 FOR THE CENTERLINES OF BRIDGE
STREET & MADISON STREET AND BRIDGE STREET & JEFFERSON STREET. I HELD MONUMENT NO. 1377 FOR THE CENTERLINE OF JEFFERSON STREET AND THE NORTH LINE OF VERNONIA. I COMPUTED THE CENTER LINE INTERSECTION OF JEFFERSON STREET AND SHADY LANE ON THE NORTHERLY EXTENSION OF JEFFERSON STREET 25' FROM MONUMENT NO. 1377. FOR MADISON AVE I HELD THE NORTHERLY EXTENSION OF MADISON STREET LYING SOUTH OF BRIDGE STREET AND THE PLATTED DISTANCE FOR THE NORTH LINE OF VERNONIA. I PROPORTIONED THE LOTS BETWEEN THE BLOCK CORNER.

BLOCK 3, VERNONIA: --I HELD MONUMENTS 870 AND 872 FOR THE CENTER LINE OF BRIDGE STREET. I COMPUTED THE NORTHEAST CORNER AT THE PLATTED DISTANCE (250.00') FROM THE SOUTHEAST CORNER. I HELD THE NORTH LINE PARALLEL WITH THE SOUTH LINE OF BLOCK 3 AND COMPUTED THE NORTHWEST CORNER OF LOT 10 AT THE INTERSECTION WITH THE EAST LINE OF CENTRAL ADDITION.

--THE DODGE TRACTS ARE LOT 1 AND THE NORTH HALF OF LOT 2, BLOCK 2. THE WESTERLY PORTION IS THE WEST 32.00 FEET OF LOT 1 AND THE NORTH HALF OF LOT 2.

--I ESTABLISHED THE SOUTHWEST CORNER AT THE DEEDED DISTANCE [100.00'] FROM THE NORTHWEST CORNER OF LOT 10 BLOCK 3 VERNONIA, ALONG THE EAST LINE OF CENTRAL ADDITION. I ESTABLISHED THE SOUTHEAST CORNER AT THE DEEDED DISTANCE FROM THE NORTHEAST CORNER OF BLOCK 3, ALONG THE NORTHERLY EXTENSION OF MADISON STREET. I HELD MONUMENT NO. 866 FOR THE NORTHEAST CORNER. I HELD THE NORTH LINE PARALLEL WITH NORTH LINE OF BLOCK 3, VERNONIA AND ESTABLISHED THE NORTHWEST CORNER AT THE INTERSECTION WITH THE EAST LINE OF CENTRAL ADDITION.

--FOR THE EASTERLY LINE OF THE WELLER TRACT I HELD MONUMENT NO. 344 AND 615 AND ESTABLISHED THE ANGLE POINT BETWEEN THEM USING THE BLM BROKEN BOUNDARY METHOD OF ADJUSTMENT USING RECORD DATA PER CS NO. 3136.


CENTRAL ADDITION:


--I HELD MONUMENT NO. 1380 FOR THE SOUTHEAST CORNER OF LOT 8 AND MONUMENT NO. 433 FOR THE NORTHEAST CORNER OF LOT 1 AND PROPORTIONED THE LOT CORNERS BETWEEN THEM. I COMPUTED THE NORTHWEST CORNER OF LOT 1 HOLDING RECORD DATA PER CS NO. 4774 AND I HELD MONUMENT NO. 610 FOR THE SOUTHWEST CORNER OF LOT 6 AND PROPORTIONED THE LOT CORNERS BETWEEN THEM.

DETAIL A

NO SCALE

DETAIL B NO SCALE





MONUMENT NOTES:

FOUND A 3/4" IRON PIPE WITH A 2 1/2" BRASS CAP PER CS 4369.

SW CORNER LOT 8, BLOCK 1, CENTRAL ADDITION TO VERNONIA FOUND A 5/8" IRON ROD WITH A Y.P.C. MARKED "KEENON LAND SERVICES INC" PER CS NO. 4774. (HELD)

FOUND A 1" IRON PIPE PER CS NO. 3136. (HELD)

NE CORNER OF BLOCK 1, CENTRAL ADDITION FOUND A 1" IRON BAR (HELD)

SW CORNER LOT 6, BLOCK 1, CENTRAL ADDITION TO VERNONIA FOUND A 5/8" IRON ROD WITH A Y.P.C. MARKED "KEENON LAND SERVICES INC" PER CS NO. 4894. (HELD

SW CORNER LOT 9, BLOCK 1, CENTRAL ADDITION TO VERNONIA FOUND A 5/8" IRON ROD WITH A Y.P.C. MARKED "KEENON LAND SERVICES INC" PER CS NO. 4774. (HELD)

FOUND A BENT 1/2" IRON ROD PER CS NO. 3136, N 00°43" E 0.60'. (HELD FOR EASTING)

FOUND A 1" ALUMINUM PIPE PER CS NO. 3136. (HELD)

FOUND A BENT 1/2" IRON ROD, CS NO 3136 NOTES SETTING A 1" IRON PIPE.

FOUND A 5/8" IRON ROD WITH A 1 1/2" BRASS CAP STAMPED "ODOT" IN MONUMENT BOX PER CS NO. 5648, (HELD)

FOUND A 5/8" IRON ROD WITH A 1 1/2" BRASS CAP STAMPED "ODOT" IN MONUMENT BOX PER CS NO. 5648, (HELD)

FOUND A 5/8" IRON ROD WITH A 1 1/2" BRASS CAP STAMPED "ODOT" IN MONUMENT BOX PER CS NO. 5648, (HELD)

FOUND A 1/2" IRON PIPE DOWN 0.7' AS NOTED ON CS NO. 4573. (HELD FOR THE CENTERLINE OF JEFFERSON STREET AND THE NORTH LINE OF THE PLAT

[1379] SW CORNER LOT 11, BLOCK 1, CENTRAL ADDITION TO VERNONIA FOUND A 5/8" IRON ROD WITH A Y.P.C. MARKED "KEENON LAND SERVICES INC" PER CS NO. 4774. (HELD)

SE CORNER LOT 8, BLOCK 1, CENTRAL ADDITION TO VERNONIA FOUND A 5/8" IRON ROD WITH A Y.P.C. MARKED "KEENON LAND SERVICES INC" PER CS NO. 4894. (HELD)

REFERENCES:

1 = CS NO. 129

2 = CS NO. 2889

3 = CS NO. 31364 = CS NO. 3806

5 = CS NO. 4260

6 = CS NO. 4573 7 = CS NO. 4774

8 = CS NO. 4894

9 = CS NO. 5250

10 = CS NO. 5648

11 = CS NO. 599012 = CS NO. L-438

13 = CS NO. L-150114 = CS NO. L-1845

15 = PLAT OF VERNONIA DV J/11616 = PARTITION PLAT 2001-17

17 = PLAT OF CENTRAL ADDITION 2/25

1 = BOOK 52 PAGE 1272 = DOC. NO. 93-4247

3 = DOC. NO. 03-070734 = DOC. NO. 2015-001301

5 = DOC. NO. 2015 - 0106326 = DOC. NO. 2005-008596

7 = DOC. NO. 88-03440

PROFESSIONAL LAND SURVEYOR OREGON JANUARY 19, 1993 DONALD D WALLACE JR 2601 RENEWAL DATE 6/30/18

DRAWN BY: DDW

REGISTERED

K.L.S. SURVEYING INC. 1224 ALDER STREET VERNONIA, OR 97064 (503)429-6115 FIELD: MDM/MB

SURVEY FOR

DODGE, NORMAND & WALTERS IN THE NW 1/4 OF SECTION 4, T4N, R4W, W.M. COLUMBIA COUNTY, OREGON

SCALE 1" = 50'SEPTEMBER 1, 2016

EQUIPMENT: GTS300/TDS48 JOB No. 12-171

PROJECT No. VERNONIA

Alumbia County Surveyo, Received 9-7-70/6 Filed 10-70 - 7016 CS# 6210

SHEET 2 OF

REVISED: 10/03/2016