

18 54

2604.18' 2618') 2620.6')

2

(38)

CROOKED CREEK

02°01'57" 1(N 01°23' 3(N 01°32' 1

3(N

19

SECTION CORNER COMMON TO SECTIONS 13 AND 24, T 5N R 5W, AND SECTIONS 18 AND 19, T 5N R 4W
FOUND A 1" GALVANIZED IRON PIPE WITH A Y.P.C. MARKED "KEENON LAND SERVICES INC." INSIDE A 2" IRON PIPE.

> FOUND AN UNRECORDED BOUNDARY MARKER A 1 1/8" AXLE UP 6", N 87°58'03" E 14.18' FROM SECTION LINE. A WEST-SOUTH FENCE

CORNER IS SOUTHWEST 0.5'.

AN18" HEMLOCK STUMP N 34° W 47.65' TO SPIKE SET IN FACE.

AN 11" FIR N 71° E 19.40' TO SPIKE IN LOWEST OF 4 BLAZES.
A 12" FIR S 65° E 5.46' TO SPIKE IN LOWEST OF 4 BLAZES.
A 21" FIR S 70° W 40.45' TO SPIKE IN LOWEST OF 4 BLAZES.
AN OLD A WHITE 4" x 4" PAINTED WOOD POST N 45° E 1.5'.

REFERENCES FOUND:

NARRATIVE:

--THIS SURVEY WAS ACCOMPLISHED AT THE REQUEST OF HANCOCK TIMBER RESOURCES GROUP TO MARK THE BOUNDARY LINES SHOWN.

-- THE BASIS OF BEARINGS IS PER AN UNRECORDED CROWN ZELLERBACH MAP 55254-04 BETWEEN FOUND MONUMENTS 1 AND 21 .

-- I HELD THE FOUND MONUMENTS FOR THE BOUNDARY LINES AS SHOWN.

--ALL REFERENCES WERE MEASURED WITH A HAND COMPASS SET AT DECLINATION 21° EAST AND A STEEL TAPE. ALL NEW BEARING TREES
WERE MEASURED TO THE HEAD OF A 3" TRACK SPIKE SET IN THE BASE
BLAZE OF 4 BLAZES UP THE FACE. BEARING TREE TAGS WERE PLACED AT SHOULDER HEIGHT ABOVE THE BLAZES.

--THE LINES WERE MARKED WITH RED AND WHITE RIBBON, METAL BOUNDARY REFERENCE TAGS PLACED IN A SLICE AT LOWEST PART OF ROOT CROWN, AND QUARTER BLAZES AT CHEST HEIGHT.

LEGEND

MONUMENT FOUND AS NOTED

() = RECORD SURVEY DATA

CS = RECORD SURVEY No.

Y.P.C. = YELLOW PLASTIC CAP

---x = FENCE

X = MONUMENT POINT NUMBER

A 10" HEMLOCK N 52° W 7.36' TO SPIKE. A 13" FIR S 47° W 22.03' TO SPIKE.

A FIBERGLASS FENCE POST NORTH 1'.

OLD FENCES RUN NORTH AND EAST.

REFERENCE SURVEYS

1 = MAP 5524-01 CROWN ZELLERBACH RECORDS

2 = MAP 5524-02 CROWN ZELLERBACH RECORDS

3 = MAP 5524-03 CROWN ZELLERBACH RECORDS

4 = MAP 5524-04 CROWN ZELLERBACH RECORDS

FOUND A 1" GALVANIZED IRON PIPE WITH A A BABBIT CAP PER CROWN ZELLERBACH BT 33, BOOK PAGE 23, UP 12". 00°34'04" W 4(345') 1(S 88°46' E 2582.6') 3(S 88°46' E 2580.7') 4(EAST 2631') S 90°00'00" E 2624.32' z 1 21 CROOKED CREEK C 1/4 CORNER FOUND A 1" GALVANIZED IRON PIPE WITH A BABBIT CAP PER CROWN ZELLERBACH BT BOOK PAGE 23 UP 12". 1/4 CORNER COMMON TO SECTIONS 19 AND 24 FOUND A 3/4" IRON PIPE PER CROWN ZELLERBACK BT BOOK PAGES 10 & 25 FLUSH WITH THE GROUND. REFERENCES FOUND: A ROTTED STUMP N 05° E 12.7'. REFERENCES ADDED:

c plumbia County Survey CS# 59/4

REGISTERED **PROFESSIONAL** LAND SURVEYOR OREGON JULY 30, 1976 LESLIE G. KEENON 1080 RENEWAL DATE 6/30/99 DRAWN BY: VSS

LAND KEENON I

1224 ALDER ST. VERNONIA, OR 97064 (503) 429-6115 FIELD: VSS/MM/RH

SURVEY FOR

REFERENCES ADDED:

A 14" FIR N 88° W 25.02' TO SPIKE. A 13" FIR S 25° E 11.46' TO SPIKE.

A FIBERGLASS FENCE POST NORTH 1'.

PROJECT No. 99-062

HANCOCK TIMBER RESOURCES GROUP IN THE SE 1/4 OF SECTION 24, T5N, R5W, W.M. COLUMBIA COUNTY, OREGON SCALE 1" = 200' MAY 20, 1999

EQUIPMENT: GTS300/TDS48 JOB No. 99-062

COLUMBIA COUNTY SURVEYORS OFFICE RECEIVED

ACCEPTED. CHECK