



REFERENCES:

RECORD SURVEYS:
 1 = CS NO. 1821
 2 = CS NO. 2401
 3 = CS NO. 2707
 4 = CS NO. 4585
 5 = CS NO. 5209
 6 = ODOT STRIP MAP NO. 4B-23-4

MONUMENT NOTES:

- 17 FOUND A 5/8\" IRON ROD WITH Y.P.C. MARKED \"KEENON LAND SERVICES INC\" PER CS NO. 4585 (HELD)
- 18 FOUND A 5/8\" IRON ROD WITH Y.P.C. MARKED \"KEENON LAND SERVICES INC\" PER CS NO. 5209 (HELD)
- 23 FOUND A 5/8\" IRON ROD WITH Y.P.C. MARKED \"KEENON LAND SERVICES INC\" PER CS NO. 5209 LIES AT HIGHWAY STATION 626+54.85 39.83' LEFT
- 200 1/4 CORNER COMMON TO SECTIONS 22 & 23 FOUND A 1\" IRON PIPE AS NOTED ON CS NO. 3539 (HELD)
- 201 SECTION CORNER COMMON TO SECTIONS 22, 23, 26 & 27 COMPUTED THE LOCATION OF THE 3/4\" IRON BAR AS NOTED ON CS NO. 4585 FROM LOCAL CONTROL (HELD)

LEGEND:

- = FOUND MONUMENT AS NOTED
 ○ = SET A 5/8\" X 30\" IRON ROD WITH A YELLOW PLASTIC CAP MARKED \"KLS SURVEYING INC\"
 △ = COMPUTED LOCATION
 1() = RECORD SURVEY DATA
 CS NO. = RECORD SURVEY, COLUMBIA COUNTY SURVEY RECORDS
 Y.P.C. = YELLOW PLASTIC CAP
 999 = MONUMENT NUMBER

NARRATIVE:

--THE PURPOSE OF THIS SURVEY WAS TO MONUMENT AND MARK THE WEST RIGHT OF WAY LINE OF NEHALEM HIGHWAY (STATE HIGHWAY NO. 47) BETWEEN THE SOUTH BANK OF THE NEHALEM RIVER AND THE SECTION LINE COMMON TO SECTIONS 22 & 27 AT THE REQUEST OF THE WEYERHAEUSER COMPANY.

--BEARINGS ARE GEODETIC BASED ON GPS OBSERVATIONS AT A POINT LYING S 54°00'29\" E 663.54' FROM THE 1/4 CORNER COMMON TO SECTIONS 22 & 23, HAVING A LATITUDE OF 45° 54'00.8\" N AND A LONGITUDE 123°09'11.4\" W. THE CONVERGENCE ANGLE FROM OREGON STATE PLANE NORTH ZONE IS -1°52'53.7\". DISTANCES ARE GROUND DISTANCES.

--FOR CONTROL I HELD THE MONUMENTS AS NOTED.

NEHALEM HIGHWAY:
 --I HELD THE CENTERLINE ALIGNMENT PER ODOT STRIP MAP NO. 4B-23-4 BEGINNING AT HWY STATION 586+50 AT THE EASTERLY END OF THE CONCRETE BRIDGE OVER THE EAST FORK OF THE NEHALEM RIVER. I ROTATED THE CENTERLINE ALIGNMENT -0°12'30\" INTO A COMPUTED POINT EQUIDISTANT TO MONUMENT NO. 17 & NO. 18. THIS FITS THE AS-TRAVELED CENTERLINE.

--FOR THE WESTERLY RIGHT OF WAY I HELD RIGHT OF WAY WIDTHS PER ODOT STRIP MAP NO. 4B-23-4 & ASSOCIATED RIGHT OF WAY DEEDS.

SECTION LINE COMMON TO SECTIONS 22 & 27:
 --I HELD THE COMPUTED SECTION CORNER AND MONUMENT NO. 17 & NO. 18 PER CS NO. 4585.

| | | | | | |
|--|--|---|----------------|--|------------------|
| REGISTERED PROFESSIONAL LAND SURVEYOR OREGON JANUARY 19, 1993 DONALD D WALLACE, JR. 2601 RENEWAL DATE 6/30/12 | K.L.S. SURVEYING INC. 1224 ALDER STREET VERNONIA, OR 97064 (503) 429-6115 | RECORD OF SURVEY FOR THE WEYERHAEUSER COMPANY IN THE SE 1/4 OF SECTION 22, T5N, R4W, W.M., COLUMBIA COUNTY, OREGON SCALE 1\" = 200' FEBRUARY 27, 2012 | | Received 4/2/12 Filed 5/30/12 CS# 5858 | |
| DRAWN BY: BTF | FIELD: SWM/MDM | EQUIPMENT: 300/RECON | JOB No. 12-020 | PROJECT No. 12-020 | REVISED: 2/27/12 |