SECTION 28, T. SN. RHW. WM. COLUMBIA. COUNTY, OREGON SEC. COR FOUND I" I.P. SET W /16 CORNER By C-Z FOUND 1" I.P. WITH LEAD CAP SET BY C-2 SURVEY 1958 1/4 CORNER SECS 21628 FOUND I" I.P. WITH LEAD CAP N89°09'50"E 1273.96' N89º13.43"E 1274.56 SET BY C-Z SURVEY 1958 29 28 (N89'09'50"E 1274.16") * (N89°09'50"E /274.16')" 1/4 CORNER SECS. 28429 FOUND ORIGINAL CORNER 12"Hem. 540W 35 LKS. now 36" STUMP Old axe WORK remaining around rotted out face. 12 Hem. WEST 3 LKS. NOW Just fotted roots remaining C14 CORNER CW116 CORNER SET IR P/C SET IR Pla SET IRPIC AT CORNER POINT 12" Hemlock SGIW 6.2' 12"FIR 569W 14.6" CE'//6 CORNER MARKED NEW BTS 12" Hemlock N52W11.8' SET IRPIC 7"FIR S54E 0.8" 10"/lem. 58E 66.6" 11"FIR 543W6.4" 22" Hcm. 521W 64,0' 8" FIR NG8 E 2.9" OID FENCE CORNER N42W 15.0' N89º12'48"E W 1/4 CORNER SECS. 27628 N89º 12.48"E 1287.32 FOUND 1" I.P. W/ coupling 1287.32 1307.37 AND REMAINS OF 2 BES 1307.37 N89º12'48"E MARKED IN 1898 BTBKAP6 293 CREEK SW 1/16 CORNER SET IR PIC 7"CEDAR NGTE 420" 7" FIR N36 E 45.2" N89º21'11"E N89ºZI'11"E 1297.27 1297.27 ROAD 1/4 CORNER 28 & 33 MISSING COMPUTED PROPORTIONATE CORNER POSITION NOT SET SECTION CORNER OLD RAIL FENCE CORNER TO E-W-S FOUND 3/4" I.P. IN FENCE SEC. CORNER FOUND 5/8" IRON ROD N19W 21.0' CORNER TO E-W-N S. END POST OF FENCE RUNNING N. N3/033'W 31.7' THEN N. 9.5' THEN CORNERS TO N.4E. BT BK. B PG.95 IN FENCE CORNER TO N-E-W AND REMAINS 3 BTS. ORIG. B.T. B.F. A P6.293 28 29 1307.21 1307.21. 2614.43' 32 33 28 /27 (WEST 39.75 CHAINS) N89°29.26"E 33 34 (WEST 39.75 CHAINS)

JULY 31, 1986 SCALE / "=400" SURVEY PURPOSE

SURVEY FOR!

AND CAVENHAM FOREST INDUSTRIES

TO SUBDIVIDE SECTION ESTABLISH CORNERS AND MARK LINES AS SHOWN

NARRATIVE

HELD TO CORNERS SHOWN AS FOUND I WAS UNABLE TO PROVE OR DIS PROVE THE N.W. SECTION CORNER TO BE AN ORIGINAL CORNER SO ACCEPTED CORNER SET BY C-Z AS BEST AVAILABLE EVIDENCE I WAS UNABLE TO FIND ANY EVIDENCE OF ORIGINAL 1/4 28633, SO COMPUTED A PROPORTIONAL POSITION. SUBDIVIDED THE SECTION IN ACCORDANCE WITH "MANUAL OF SURVEYING INSTRUCTIONS 1973". BEARINGS BASED ON C-Z SURUEY BETWEEN 1/4 CORNER + W1/16 CORNER TO SECTIONS 21628 ALL NEW B.T.S SCRIBED ACCORDING TO "MANUAL" BEARINGS TO BITS WITH MAGNETIC COMPASS DEC'L 22° E. DISTANCES MEASURED TO BT. FACES. ALL NEW B.T.S POSTED WITH YELLOW ALUMINUM B.T. TAGS.

LEGEND

= FOUND CORNER

O = ESTABLISHED CORNER BY THIS SURVEY IRPIC = SET 5/8" x 30" IRON ROD WITH YELLOW PLASTIC CAP MARKED "MORRIS PLS40/

BT. = BEARING TREE

C-Z = CROWN - ZELLER BACH CORP.

LILL . MARKED TRUE LINE WITH FLUOR ESCENT PINK PLASTIC RIBBON, PAINTED TREE BLAZES AND ALUMINUM TAGS

) = ORIGINAL SURVEY RECORD

)2: SURVEY NO. 2365 RECORD

)3 = BK. A PG 293 1898 RECORD

)4 : C.Z 1958 SURVEY RECORD

COUNTY SURVEYOR RECEIVED_ FRED 9-2-86 9.11

SURVEYED BY:

REGISTERED **PROFESSIONAL** LAND SURVEYOR OREGON MAY 10, 1957 RICHARD A. MORRIS 401

16775 CHEHALEM WAY HILLS BORD, OR, 97/23 PHONE 628-2353