Stone 1/4 Cor. 9 5/8" 1. R. O. 14 ft. E 16 4"XII" Stone 9" Deep

28

O

## RECORD OF SURVEY FOR KEITH CLARK

IN THE S.E. 1/4, SECTION 9 TAN, RAW W.M. COLUMBIA COUNTY, OREGON Scale: 1"=100' 31 MAY, 1973 48"DF Stump 533°30W 3 9 (1/4 Cor. 16"RC Stump N 18°30'E 44.2ft 1924 L.J. Van Orshaven survey 2642.27 585°58'36"E Fcl. Cedar Stake 1" I.P. With Cap 1177.41 Stone 1/4 Cor. C.Z. 1959 Set 5/8" 1.R. 0.3'W 52" DF Bears \$79°30'E A Stone 54.0ft. 24" DF Bears 537° 15'W 1594.61 25.5 ft. Blazed 18"DF Quad 5.80 Acres 1-10.0 ft. Blazed 22" DF Quad 2-13.5 ft. Blazed 28"RC Quad 3-34.5 ft. Blazed 20" DF Quad A= = 04°53'33" 585°58'36"E 3-35.4ft. from 1/4 Cor. Stone 1173.88 N83º/9'57W 8°CL 1= 14º/3' B= A=09°19'27" LC=113.19 R= 716.30 5T=89.33 L=/77.73 R. 696.30 LC=177.28 9.148 Acres 574°00'30"E Δ=06°34'22" 16=129.10 3 102°34'34"--3 5°66 Δ=9°09' 588°28'45″E 1091.11 R= 1146.00 51.70 L= 183.01 LC=182.82 5.175 Acres 588° 28'45"E 998.02 5.00 Acres 588°28'45"E 897.52 5.00 Acres 588° 28'45"E 58/° 27' 23"E - R. 798-60. 769.72 7.126 Acres (8.061) Acres ACres 935 O. 2 7° C L Δ=50°43' R=818.60 51 = 387.97 L= 724,60 LC=701.18 R=224.60 ∆:49°58'29" LC=189.75 575° 51' 30"W 1 N50°52'151/2"E N88°28'45"W / 28°CR 5:74°20'15" REGISTERED R= 204.60 PROFESSIONAL LAND SURVEYOR 57=155.14 L=265.46 3690559.19 LC=247.22 57=155.12 LEGEND · Monuments Found as Noted 0 5/8" x 30" Iron Rod Set Beith M. Clar 588°28'45"E CIKEGON KEITH M CLARK Basis of Bearing - L.J. Van Orshaven 1924 Survey (North Line S.E. 1/4 Section 9)

2810

 $\omega$