

30 29
31 32

M

Exemption 2
Jamez track
25 Acres

Road

Exemption 1
A.B. County

65 Acres

Road

1/4 Cor.

Exemption 1
Albert Woods
5 acres

Crack

39.78
238.68
238.68
238.68
2625.48

39.86
239.16
239.16
2630.76



The NW $\frac{1}{4}$ of Sec. 32, - 5-4.

#1 Exempting therefrom tract decided to Robert Woods Aug 23, 1884, - IX-83

#2 Exempting tract decided to John C. Hall Feb. 10, 1909, - 11-265

#3 Exempting tract decided to A. B. Counts Feb. 10, 1909, - 11-178

Exempt #1 Beginning at the S.E. corner of the NW $\frac{1}{4}$ of Sec. 32, - 5-4, thence north to rock creek, thence west along bank of said creek to where the creek leaves the bluff, thence following the top of the bluff to the west line of the east $\frac{1}{2}$ of the NW $\frac{1}{4}$, thence south to corner of said 80; thence east to place of beginning, containing 5 acres, more or less.

Exemption #2 - Beginning at the NE. corner of the NW $\frac{1}{4}$ and running south along the center line of Sec. 32, to the county road as it now is following the county road west 54 rods to a stone set on north side of county road - thence N. 80° W. and intersect with the center line running north & south of the NW $\frac{1}{4}$ of Sec. 32; thence north to north line of Sec. 32; thence east on said north line to place of beginning & containing 25 acres, more or less.

Exemption #3 - Beginning at the NW. corner of Sec. 32 and running south on Sec. line to quarter post between 31 & 32; thence east on quarter line, sixty-five rods thence north & parallel with section line, across corner

rock creek, south to the north line of Sec. 32;
thence West 65 rods to the place of beginning
and containing 65 acres, more or less.

Sec. 32 - 5 - 9
By Walker in March 1889

10" Fir - S. 65° W. - 24 1/2 Ks.
12" " - N. 77 1/2° E - 61 Ks

N. 85° 21' W - 38.56
19.28 19.28

N. 0° 43' E - 39.50

Co. Road

N. 1 measured

19.48 19.48

N. 89° 43' E
Var 2° 30' E

N. 0° 30' E - 39.76

S. 0° 25' W
39.86
26.50

measured with deflection
to top of small rock

30.22

39.48

31 32

32 33

By Prescott, cedar post frame
held B.T.
22" cedar - S. 13° W - 15.3
22" Fir - S. 85° 40' E - 162.6

By Watts in 1904
40" Fir - S. 71° E - 86 1/2 Ks
48" cedar - N. 25° E - 94 1/2 Ks

By Watts in 1904
Set cedar post from which

20" Fir - S. 7° E - 35 Ks
16" Fir - S. 71° 30' W - 54 1/2 Ks
20" Hemlock - N. 24° 30' E - 57 1/2 Ks

