



---

## Topic 7. Support Vector Machines

# Support Vector Machines (SVM)

- Approach for classification developed in computer science
- One of the best “out of the box” classifiers
- Recall classifiers covered in Chapter 4: logistic regression, LDA, QDA, KNN




# Outline

- **Maximal Margin Classifier**: classes are separable by a linear boundary
- **Support Vector Classifier**: extend to cases where classes are not separable
- **Support Vector Machine**: extend to non-linear class boundaries

# Maximal Margin Classifier

# Hyperplane

- In a  $p$ -dimensional space, an affine *hyperplane* is a flat affine subspace of dimension  $p - 1$ . For example, in two dimensions, a hyperplane is a line.



# Classification Problem

## ➤ Feature space

- Space formed by the predictors
- Also referred to as the state space, input space
- $p$ -dimensional ( $p$  predictors),  $n$ -points ( $n$  observations)

## ➤ Training data

- Inputs determine its location in the feature space

$$x_1 = \begin{pmatrix} x_{11} \\ \vdots \\ x_{1p} \end{pmatrix}, \dots, x_n = \begin{pmatrix} x_{n1} \\ \vdots \\ x_{np} \end{pmatrix}$$


- Outputs  $y_1, \dots, y_n$  determine the **color** (i.e., **classes**)

## ➤ Classification: Find the hyperplane such that a test point

$$x^* = (x_1^* \quad \dots \quad x_p^*)^T$$


is assigned the correct class.

# Classifier as Feature Space Coloring



# Separating Hyperplane

- **Separating hyperplane**: separates the training observations perfectly according to their class labels
  - **Blue**: class 1 ( $y = 1$ )
  - **Purple**: class  $-1$  ( $y = -1$ )
  - $f(x) = \beta_0 + \beta_1 x_1 + \beta_2 x_2 + \dots + \beta_p x_p$
  - **class 1**:  $f(x) > 0$
  - **class  $-1$** :  $f(x) < 0$
- Property:  $y_i f(x_i) > 0$ , for all training points  $x_1, x_2, \dots, x_n$






# Prediction

- Given a test point  $x^*$ , we will assign it to  
class 1 ( $y^* = 1$ ), if  $f(x^*) > 0$   
class -1 ( $y^* = -1$ ), if  $f(x^*) < 0$
- If  $y^* f(x^*)$  is far from zero, that means the test point lies far from the hyperplane, and so we can be confident about our class assignment for it.
- If  $y^* f(x^*)$  is close to zero, that means the test point is located near the hyperplane, and so we are less certain about the class assignment for it.


# How to Do It Right?

- There may be an infinite number of hyperplanes that separates the training observations perfectly.
- We need to decide which hyperplane to use.




# Margin

- Suppose we have a separating hyperplane
- Find perpendicular distance from every point to the hyperplane
- Margin: The smallest of such distances,  $M$   
i.e., minimum distance from the observations to the hyperplane



# Maximal Margin Classifier

- Best separating hyperplane
- Maximize min-distance (max margin)
- Represent the mid-line of the widest “slab” inserted between the two classes



# Support Vectors

- **Support vectors**: the 3 training points equidistant from the maximal margin hyperplane
  - “**vectors**”: each point is a vector in  $p$ -dimensional space
  - “**support**”: they support the maximal margin hyperplane: if they were moved slightly then the maximal margin hyperplane would move as well.
- The maximal margin hyperplane depends directly on the support vectors, but not on the other observations: a movement of any of those observations would not affect the separating hyperplane.

# Optimization Formulation

$$\text{maximize } M$$

$$\beta_0, \beta_1, \dots, \beta_p$$


$$\text{subject to } \sum_{j=1}^p \beta_j^2 = 1,$$

$$y_i(\beta_0 + \beta_1 x_{i1} + \beta_2 x_{i2} + \dots + \beta_p x_{ip}) \geq M \quad \forall i = 1, \dots, n$$

**Question:** for each point to be on the correct side of the hyperplane, we only need  $y_i f(x_i) > 0$ . Why here it is required that  $y_i f(x_i) > M$  ( $M > 0$ )?

# Non-separable Case

- No solution if the observation classes are mixed (*non-separable case*)
- We can extend the concept of a separating hyperplane to develop a hyperplane that almost separate the classes, using the idea of “**soft margin**”
- This generalization to the non-separable case is known as the **support vector classifier**




# Support Vector Classifier





# Motivation

- Maximal margin classifier only works for separable cases
- Need to extend it to the non-separable case



# Motivation

- In the separable case, the separating hyperplane is sensitive to individual observations.
- The addition of a single observation may lead to dramatic change in the maximal margin hyperplane.
- Reason: margin is tiny (recall that  $yf(x)$  is a measure of our confidence of correct classification)



# Idea of Support Vector Classifier

- Consider a hyperplane that does not perfectly separate the two classes, in the interest of
  - Greater robustness to individual observations, and
  - Better classification of most of the training observations
- It could be worthwhile to misclassify a few training points in order to do a better job in classifying the remaining points.
- Soft margin classifier: the margin is “soft” because it can be violated by some of the training points.

# Relax the Constraint of Perfect Separation

- Support vector classifier

$$\underset{\beta_0, \beta_1, \dots, \beta_p, \epsilon_1, \dots, \epsilon_n}{\text{maximize}} \quad M$$

$$\text{subject to} \quad \sum_{j=1}^p \beta_j^2 = 1,$$

$$y_i(\beta_0 + \beta_1 x_{i1} + \beta_2 x_{i2} + \dots + \beta_p x_{ip}) \geq M(1 - \epsilon_i),$$


$$\epsilon_i \geq 0, \quad \sum_{i=1}^n \epsilon_i \leq C,$$

# Slack Variables and Tuning Parameter

- For a sample  $i$ ,
- $\epsilon_i = 0$  margin not violated (on the correct side of the margin)
  - $\epsilon_i > 0$  margin violated (on the wrong side of the margin)
  - $\epsilon_i > 1$  hyperplane boundary crossed (on the wrong side of the hyperplane, or leakage)


$C$ : tuning parameter, a budget for the amount that the margin can be violated

# Effect of $\epsilon$



**3,4,5,6:** on the correct side of the margin  
**2:** on the margin  
**1:** on the wrong side of the margin

**7,10:** on the correct side of the margin  
**9:** on the margin  
**8:** on the wrong side of the margin



**11,12:** on the wrong side of the margin and the wrong side of the hyperplane

# Effect of $C$ — Bias-Variance Trade-off


## ➤ Small $C$

- Narrow margins
- Rarely violated
- Fitting data well
- Low bias but high variance

## ➤ Large $C$


- Wide margins
- Allow more violations
- Fitting data less hard
- Low variance but high bias

$$C = 25$$







$C = 15$



$C = 10$



$$C=5$$



# Properties of the Solution to the Relaxed Formulation

- For the support vector classifier formulation, we have  $n$  constraints



$$y_i(\beta_0 + \beta_1 x_{i1} + \beta_2 x_{i2} + \dots + \beta_p x_{ip}) \geq M(1 - \epsilon_i)$$

- **Support vectors:** Points that lie on the margin or on the wrong side of the margin for their class (including those on the wrong side of the hyperplane)
- Observations that lie strictly on the correct side of the margin do not affect the support vector classifier.

# Support Vector Machine

# Motivation

- What would you use to classify?
- Linear classifier performs poorly.



# Accommodating Nonlinearity


- Recall Chapter 3: linear regression may suffer when there is nonlinear relationship between predictors and the response. The solution is to add *transformations* (e.g., quadratic and cubic terms) of predictors into the model. Similar idea can be applied here.
- Instead of fitting a support vector classifier using the  $p$  features  $X_1, X_2, \dots, X_p$ , we can enlarge the feature space by using  $X_1, X_1^2, X_2, X_2^2, \dots, X_p, X_p^2$ .

# Modified Optimization Formulation

$$\underset{\beta_0, \beta_{11}, \beta_{12}, \dots, \beta_{p1}, \beta_{p2}, \epsilon_1, \dots, \epsilon_n}{\text{maximize}} \quad M$$

$$\text{subject to } y_i \left( \beta_0 + \sum_{j=1}^p \beta_{j1} x_{ij} + \sum_{j=1}^p \beta_{j2} x_{ij}^2 \right) \geq M(1 - \epsilon_i)$$

$$\sum_{i=1}^n \epsilon_i \leq C, \quad \epsilon_i \geq 0, \quad \sum_{j=1}^p \sum_{k=1}^2 \beta_{jk}^2 = 1.$$





# However...

- Including quadratic terms is only one way to enlarge the feature space in order to accommodate nonlinearity.
- There are many possible ways to enlarge the feature space. Unless we are careful, we could end up with a huge number of features. Then computations would become unmanageable.
- The support vector machine allows us to enlarge the feature space in a way that leads to efficient computations.

# Properties of Optimal Hyperplane

- Let us define an inner product (dot product) of two vectors:

$$\langle a, b \rangle = \sum_{i=1}^r a_i b_i$$

For real vectors, it is simply  $a^T b$

- The optimal linear hyperplane  $f(x) = 0$  can be written as

$$f(x) = \beta_0 + \sum_{i=1}^n \alpha_i \langle x, x_i \rangle$$

It turns out that  $\alpha_i \neq 0$  only for support vectors


$$f(x) = \beta_0 + \sum_{i \in \mathcal{S}} \alpha_i \langle x, x_i \rangle$$

- **Decision rule is based on the inner product.**

# Support Vector Machine (SVM)

- Let us generalize the support vector classifier

$$f(x) = \beta_0 + \sum_{i \in \mathcal{S}} \alpha_i \langle x, x_i \rangle$$


$$f(x) = \beta_0 + \sum_{i \in \mathcal{S}} \alpha_i K(x, x_i)$$

$K$  is called the *kernel* function

# Choices of Kernel Function

- Linear kernel (i.e., support vector classifier)

$$K(x_i, x_{i'}) = \sum_{j=1}^p x_{ij} x_{i'j}$$

- Polynomial kernel

$$K(x_i, x_{i'}) = \left(1 + \sum_{j=1}^p x_{ij} x_{i'j}\right)^d$$

tuning parameter:  $d$


- Radial kernel

$$K(x_i, x_{i'}) = \exp\left(-\gamma \sum_{j=1}^p (x_{ij} - x_{i'j})^2\right)$$


tuning parameter:  $\gamma$

# SVM Boundaries

Degree 3 polynomial kernel



Radial kernel



# Summary

- Maximal Margin Classifier  
linear boundary  
separable cases
- Support Vector Classifier  
linear boundary  
separable or non-separable cases  
(A special case of SVM when linear kernel is used.)
- Support Vector Machine  
linear or nonlinear boundary  
separable or non-separable cases