

Data Dictionary

TABLE BUSINESS NAME	TAB LE TECHNICAL NAME	COLUMN BUSINESS NAME	COLUMN BUSINESS DEFINITION	COLUMN TECHNICAL NAME	COLUMN DATA TYPE	TOTAL COLUMN LENGTH	# OF PLACES TO RIGHT OF DECIMAL	MANDATORY/ OPTIONAL (Is Value Required)	N=NULL NN=Not Null ND=Not Null W /Default	Primary Key (PK) Foreign Key (FK)	COLUMN IS AUTO-INCREMENTED (Identity)
COUNTRY	ctry	ISO Alpha2 Country Code	ISO Alpha2 Country Code Sample Values: IN UK US	iso_alpha2_ctry_cd	character	2		MANDATORY	NN	(PK)	NO
COUNTRY	ctry	ISO Alpha2 Country Name		iso_alpha2_ctry_nm	varchar	100		MANDATORY	NN		NO
DATA OPERATOR	da_opr	Data Operator Identifier	Description : Unique ID for identifying an operator. Sample Values : 1 equals 2 greater than 3 less than 4 includes 5 excludes	da_opr_id	smallint			MANDATORY	NN	(PK)	NO
DATA OPERATOR	da_opr	Data Operator Description	Description : Description of operator that will be shown on displays. Sample Values : Equals, Less Than, Greater Than, Value of etc.	da_opr_ds	varchar	20		MANDATORY	NN		NO
DATA OPERATOR	da_opr	Data Point Type Identifier	Identifier for the data point type.	da_pt_type_id	numeric	2		MANDATORY	NN	(FK)	NO
DATA POINT	da_pt	Lookback Applicability Indicator	Description : Description: Indicates whether a data point can be looked back on, in terms of filtering date range. Sample Values : Y, N	lookback_applicability_in	boolean			MANDATORY	ND		NO
DATA POINT	da_pt	Last Update User Identifier	Specifies the person (his/her ads id) who last updated this record in the table.	lst_upd_usr_id	varchar	34		OPTIONAL	N		NO
DATA POINT	da_pt	Data Point Description	Description : Description associated with a data-point that describes its purpose. Sample Values : Center Code, Product Code, etc.	da_pt_ds	varchar	500		MANDATORY	NN		NO
DATA POINT	da_pt	Last Update Timestamp	Specifies the date and time the last update was made to the record in the table.	lst_upd_ts	timestamp	6		OPTIONAL	N		NO
DATA POINT	da_pt	Override Applicability Indicator	Description : Indicates whether a data-point can be used as an element weight override. Sample Values : 1 = Override Applicable, 0 = Not Applicable	ovrrd_applicability_in	boolean			MANDATORY	ND		NO
DATA POINT	da_pt	Data Point Identifier	Description : Unique ID for identifying a data-point.. Sample Values : 1, 2, 3, 4, etc.	da_pt_id	integer			MANDATORY	NN	(PK)	NO
DATA POINT	da_pt	Data Point Group Identifier		da_pt_grp_id	numeric	3		OPTIONAL	N	(FK)	NO
DATA POINT	da_pt	Create User Identifier	Specifies the person (his/her ads id) who inserted / created this record in the table.	creat_user_id	varchar	34		MANDATORY	NN		NO
DATA POINT	da_pt	Minimum Maximum Multiplier Evaluation Code	Description: Code that defines whether ruleset should be evaluated based on maximum or minimum ruleset multiplier value. If Max, start with highest multiplier value, else start with lowest multiplier value. Sample Values: Min, Max	min_max_mult_eval_cd	character	3		MANDATORY	ND		NO
DATA POINT	da_pt	Data Point Type Identifier	Identifier for the data point type.	da_pt_type_id	numeric	2		MANDATORY	NN	(FK)	NO
DATA POINT	da_pt	Create Timestamp	Specifies the date and time when the record in the table was inserted / created.	creat_ts	timestamp	6		MANDATORY	NN		NO

DATA POINT	da_pt	Data Point Evaluation Function Identifier		da_pt_eval_func_id	numeric	3		OPTIONAL	N	(FK)	NO
DATA POINT	da_pt	Source Data Point Name	Attribute name sourced from DAM (e.g., accountBusinessUnit).	srce_da_pt_nm	varchar	30		OPTIONAL	N		NO
DATA POINT GROUP	da_pt_grp	Data Point Group Identifier		da_pt_grp_id	numeric	3		MANDATORY	NN	(PK)	NO
DATA POINT GROUP	da_pt_grp	Data Point Group Name	Grouping data points based on characteristics (e.g., TRANS, ALERT, DEMOG).	da_pt_grp_nm	varchar	10		MANDATORY	NN		NO
DATA POINT TYPE	da_pt_type	Data Point Type Identifier	Identifier for the data point type.	da_pt_type_id	numeric	2		MANDATORY	NN	(PK)	NO
DATA POINT TYPE	da_pt_type	Data Point Type Name	Name of the data point type (e.g., Lookup, Specific, Boolean).	da_pt_type_nm	varchar	20		MANDATORY	NN		NO
EVALUATION FUNCTION	eval_func	Data Point Evaluation Function Name		da_pt_eval_func_nm	varchar	10		MANDATORY	NN		NO
EVALUATION FUNCTION	eval_func	Data Point Evaluation Function Identifier		da_pt_eval_func_id	numeric	3		MANDATORY	NN	(PK)	NO
MULTIPLIER OPTION	mult_optn	Multiplier Option Identifier	Multiplier Option Code 1,2 and 3 corresponds to User Input, File & Assessment respectively Sample Values: Multiplier Option Identifier Multiplier Option Name 1 User Input 2 File 3 Assessment	mult_optn_id	smallint			MANDATORY	NN	(PK)	NO
MULTIPLIER OPTION	mult_optn	Multiplier Option Name	Multiplier Option Code 1,2 and 3 corresponds to User Input, File & Assessment respectively	mult_optn_nm	varchar	20		OPTIONAL	N		NO
RISK ASSESSMENT	risk_assess	Risk Assessment Name	Description : Name of the assessment. Sample Values : Customer Risk Rating	risk_assess_nm	varchar	75		MANDATORY	NN		NO
RISK ASSESSMENT	risk_assess	Last Update User Identifier	Specifies the person (his/her ads id) who last updated this record in the table.	lst_upd_usr_id	varchar	34		OPTIONAL	N		NO
RISK ASSESSMENT	risk_assess	ISO Alpha2 Country Code	ISO Alpha2 Country Code Sample Values: IN UK US	iso_alpha2_ctry_cd	character	2		MANDATORY	ND	(FK)	NO
RISK ASSESSMENT	risk_assess	Create Timestamp	Specifies the date and time when the record in the table was inserted / created.	creat_ts	timestamp	6		MANDATORY	NN		NO
RISK ASSESSMENT	risk_assess	Risk Assessment Description	Description : Business description detailing the purpose of an assessment. Sample Values : Assessment used to calculate the risk rating associated with every customer account.	risk_assess_ds	varchar	500		MANDATORY	NN		NO
RISK ASSESSMENT	risk_assess	Create User Identifier	Specifies the person (his/her ads id) who inserted / created this record in the table.	creat_user_id	varchar	34		MANDATORY	NN		NO
RISK ASSESSMENT	risk_assess	History Timestamp	History Timestamp is the timestamp when this Risk Assessment will be copied into a new version and the current version would become inactive.	hist_ts	timestamp	6		OPTIONAL	N		NO
RISK ASSESSMENT	risk_assess	Risk Assessment Identifier	Description : Unique ID for identifying an assessment. Sample Values : 1, 2, 3, 4, etc.	risk_assess_id	integer			MANDATORY	NN	(PK)	NO

RISK ASSESSMENT	risk_assess	Active Indicator	All the versions are active until if it is moved to Production and it cannot be made Active if made Inactive	act_in	boolean			MANDATORY	NN		NO
RISK ASSESSMENT	risk_assess	Parent Risk Assessment Identifier	Description : References the parent assessment if this is a copied or versioned assessment(If this is a versioned row ,this references the original assessment) Sample Values : 1,2,3,4 etc	srce_risk_assess_id	integer			OPTIONAL	N	(FK)	NO
RISK ASSESSMENT	risk_assess	Risk Assessment Version Number	Description : Incremental number which indicates which release/version Sample Values : 1, 2, 3, 4, etc.	risk_assess_vsn_no	integer			MANDATORY	NN	(PK)	NO
RISK ASSESSMENT	risk_assess	Last Update Timestamp	Specifies the date and time the last update was made to the record in the table.	lst_upd_tst	timestamp	6		OPTIONAL	N		NO
RISK ASSESSMENT	risk_assess	Merge Production Risk Assessment Identifier	Referenced the production assessment where it is merged after moving to production. Sample Value:	merge_prod_risk_assess_id	integer			OPTIONAL	N	(FK)	NO
RISK ASSESSMENT	risk_assess	Risk Assessment Verion Number	Description : Incremental number which indicates which release/version but that of Parent Risk Assessment Verion Number (References the parent assessment if this is a copied or versioned assessment and if this is a versioned row ,this references the original assessment) Sample Values : 1, 2, 3, 4, etc.	srce_risk_assess_vsn_no	integer			OPTIONAL	N	(FK)	NO
RISK ASSESSMENT	risk_assess	Merge Production Risk Assessment Version Number	Description : Incremental number which indicates which release/version Sample Values : 1, 2, 3, 4, etc.	merge_prod_risk_assess_vsn_no	integer			OPTIONAL	N	(FK)	NO
RISK ASSESSMENT CONFIGURATION EVENT	risk_assess_config_event	Event Status Name	Status of the event weather it is acknowledged or not. Sample Values: Blank/Acknowledged	event_status_nm	varchar	15		OPTIONAL	N		NO
RISK ASSESSMENT CONFIGURATION EVENT	risk_assess_config_event	Risk Assessment Status Code	Description : Status of the assessment for which event is published Sample Values : 1, 2, 3, 4, etc. for SandboxTesting-in-Progress/ Sandbox Complete	risk_assess_status_cd	smallint			MANDATORY	NN	(FK)	NO
RISK ASSESSMENT CONFIGURATION EVENT	risk_assess_config_event	Risk Assessment Identifier	Description : Unique ID for identifying an assessment. Sample Values : 1, 2, 3, 4, etc.	risk_assess_id	integer			MANDATORY	NN	(FK)	NO
RISK ASSESSMENT CONFIGURATION EVENT	risk_assess_config_event	Event Name	Event Name Sample Values: SandboxPublish, SandboxCancellation, SandboxProductionMerge	event_nm	varchar	50		MANDATORY	NN		NO
RISK ASSESSMENT CONFIGURATION EVENT	risk_assess_config_event	Risk Assessment Configuration Event Identifier	GUID / unique identifier for event Sample Value: b12ea181-55ad-492e-b44e-ccedb34e705b	risk_assess_config_event_id	integer			MANDATORY	NN	(PK)	NO
RISK ASSESSMENT CONFIGURATION EVENT	risk_assess_config_event	Risk Assessment Version Number	Description : Incremental number which indicates which release/version Sample Values : 1, 2, 3, 4, etc.	risk_assess_vsn_no	integer			MANDATORY	NN	(FK)	NO
RISK ASSESSMENT CATEGORY	risk_assess_catgy	Create Timestamp	Specifies the date and time when the record in the table was inserted / created.	creat_tst	timestamp	6		MANDATORY	NN		NO
RISK ASSESSMENT CATEGORY	risk_assess_catgy	Last Update Timestamp	Specifies the date and time the last update was made to the record in the table.	lst_upd_tst	timestamp	6		OPTIONAL	N		NO
RISK ASSESSMENT CATEGORY	risk_assess_catgy	Risk Category Identifier	A unique identfier for a risk category	risk_catgy_id	integer			MANDATORY	NN	(PK)	NO

RISK ASSESSMENT CATEGORY	risk_assess_ctgy	Risk Assessment Identifier	Description : Unique ID for identifying an assessment. Sample Values : 1, 2, 3, 4, etc.	risk_assess_id	integer			MANDATORY	NN	(PK) (FK)	NO
RISK ASSESSMENT CATEGORY	risk_assess_ctgy	Risk Assessment Category Description		risk_assess_ctgy_ds	varchar	500		MANDATORY	NN		NO
RISK ASSESSMENT CATEGORY	risk_assess_ctgy	Risk Assessment Version Number	Description : Incremental number which indicates which release/version Sample Values : 1, 2, 3, 4, etc.	risk_assess_vsn_no	integer			MANDATORY	NN	(PK) (FK)	NO
RISK ASSESSMENT CATEGORY	risk_assess_ctgy	Risk Category Name	This attribute contains the business definition of the risk category.	risk_ctgy_nm	varchar	30		MANDATORY	NN		NO
RISK ASSESSMENT CATEGORY	risk_assess_ctgy	Create User Identifier	Specifies the person (his/her ads id) who inserted / created this record in the table.	creat_user_id	varchar	34		MANDATORY	NN		NO
RISK ASSESSMENT CATEGORY	risk_assess_ctgy	Last Update User Identifier	Specifies the person (his/her ads id) who last updated this record in the table.	lst_upd_dt_user_id	varchar	34		OPTIONAL	N		NO
RISK ASSESSMENT CATEGORY ELEMENT	risk_assess_ctgy_elem	Create Timestamp	Specifies the date and time when the record in the table was inserted / created.	creat_ts	timestamp	6		MANDATORY	NN		NO
RISK ASSESSMENT CATEGORY ELEMENT	risk_assess_ctgy_elem	Risk Assessment Element Description	Description : Business description detailing the purpose of a category. Sample Values : This category contains risk elements that represent a geographical factor of a customer account.	risk_assess_elem_ds	varchar	500		MANDATORY	NN		NO
RISK ASSESSMENT CATEGORY ELEMENT	risk_assess_ctgy_elem	Last Update User Identifier	Specifies the person (his/her ads id) who last updated this record in the table.	lst_upd_dt_user_id	varchar	34		OPTIONAL	N		NO
RISK ASSESSMENT CATEGORY ELEMENT	risk_assess_ctgy_elem	Prohibited Indicator	It will have the maximum risk score of 10, if marked as prohibited	prohibited_in	boolean			MANDATORY	ND		NO
RISK ASSESSMENT CATEGORY ELEMENT	risk_assess_ctgy_elem	ISO Alpha2 Country Code	ISO Alpha2 Country Code Sample Values: IN UK US	iso_alpha2_ctry_cd	character	2		MANDATORY	NN	(PK) (FK)	NO
RISK ASSESSMENT CATEGORY ELEMENT	risk_assess_ctgy_elem	Last Update Timestamp	Specifies the date and time the last update was made to the record in the table.	lst_upd_dt_ts	timestamp	6		OPTIONAL	N		NO
RISK ASSESSMENT CATEGORY ELEMENT	risk_assess_ctgy_elem	Create User Identifier	Specifies the person (his/her ads id) who inserted / created this record in the table.	creat_user_id	varchar	34		MANDATORY	NN		NO
RISK ASSESSMENT CATEGORY ELEMENT	risk_assess_ctgy_elem	Risk Element Identifier	Description : Unique ID for identifying an element. Sample Values : 1, 2, 3, 4, etc.	risk_elem_id	integer			MANDATORY	NN	(PK)	NO
RISK ASSESSMENT CATEGORY ELEMENT	risk_assess_ctgy_elem	Risk Assessment Identifier	Description : Unique ID for identifying an assessment. Sample Values : 1, 2, 3, 4, etc.	risk_assess_id	integer			MANDATORY	NN	(PK) (FK)	NO

RISK ASSESSMENT CATEGORY ELEMENT	risk_assessment_category_element	Time based Indicator	Few elements are to be evaluated wrt time Example, Length of Relationship, Customer Age etc	tm_base_in	boolean			MANDATORY	ND		NO
RISK ASSESSMENT CATEGORY ELEMENT	risk_assessment_category_element	Risk Element Name	Description : Name of the element. Sample Values : PEP Present, Cross-border Transaction Amount, etc.	risk_element_nm	varchar	75		MANDATORY	NN		NO
RISK ASSESSMENT CATEGORY ELEMENT	risk_assessment_category_element	Minimum Maximum Multiplier Evaluation Code	Description: Code that defines whether ruleset should be evaluated based on maximum or minimum ruleset multiplier value. If Max, start with highest multiplier value, else start with lowest multiplier value. Sample Values: Min, Max	min_max_multiplier_eval_cd	character	3		MANDATORY	ND		NO
RISK ASSESSMENT CATEGORY ELEMENT	risk_assessment_category_element	Time Based Run Interval Day Count	Time interval for evaluating rules particularly for time-based elements. The unit is time interval in days.	tm_base_run_interval_day_ct	numeric	3		OPTIONAL	N		NO
RISK ASSESSMENT CATEGORY ELEMENT	risk_assessment_category_element	Risk Category Identifier	A unique identifier for a risk category	risk_category_id	integer			MANDATORY	NN	(FK)	NO
RISK ASSESSMENT CATEGORY ELEMENT	risk_assessment_category_element	Risk Assessment Version Number	Description : Incremental number which indicates which release/version Sample Values : 1, 2, 3, 4, etc.	risk_assessment_version_no	integer			MANDATORY	NN	(PK) (FK)	NO
RISK ASSESSMENT STATUS	risk_assessment_status	Risk Assessment Status Description	Description : Description of approval status that will be shown on displays. Sample Values : Not Submitted, Submitted/Pending Approval, Approved, etc.	risk_assessment_status_ds	varchar	50		MANDATORY	NN		NO
RISK ASSESSMENT STATUS	risk_assessment_status	Risk Assessment Status Code	Description : Unique ID for identifying approval status. Sample Values : 1, 2, 3, 4, etc.	risk_assessment_status_cd	smallint			MANDATORY	NN	(PK)	YES
RISK ASSESSMENT STATUS TRACKER	risk_assessment_status_tracker	Risk Assessment Version Number	Description : Incremental number which indicates which release/version Sample Values : 1, 2, 3, 4, etc.	risk_assessment_version_no	integer			MANDATORY	NN	(PK) (FK)	NO
RISK ASSESSMENT STATUS TRACKER	risk_assessment_status_tracker	Create User Identifier	Specifies the person (his/her ads id) who inserted / created this record in the table.	create_user_id	varchar	34		MANDATORY	NN		NO
RISK ASSESSMENT STATUS TRACKER	risk_assessment_status_tracker	Create Timestamp	Specifies the date and time when the record in the table was inserted / created.	create_ts	timestamp	6		MANDATORY	NN		NO
RISK ASSESSMENT STATUS TRACKER	risk_assessment_status_tracker	Status Comment Text		status_comment_tx	varchar	1000		OPTIONAL	N		NO
RISK ASSESSMENT STATUS TRACKER	risk_assessment_status_tracker	Risk Assessment Status Code	Description : Unique ID for identifying approval status. Sample Values : 1, 2, 3, 4, etc. for SANDBOX DRAFT, SANDBOX TESTING IN PROGRESS, PENDING APPROVAL1, PENDING APPROVAL2, COMPLETE, CANCELLATION	risk_assessment_status_cd	smallint			MANDATORY	NN	(PK) (FK)	NO
RISK ASSESSMENT STATUS TRACKER	risk_assessment_status_tracker	Risk Assessment Identifier	Description : Unique ID for identifying an assessment. Sample Values : 1, 2, 3, 4, etc.	risk_assessment_id	integer			MANDATORY	NN	(PK) (FK)	NO

RISK METHOD	risk_mthd	Risk Method Code	Risk Method / Applicability This Code represents the relationship that AMEX has with the card holder or merchants for e.g. A consumer card holder is an Individual relationship, A merchant is an Entity relationship and an FXIP(Foreign exchange) relationship is of type intermediary (any third party). In CADENCE it is driven based on the product type that account has Sample Values: Compliance Risk Method Code Compliance Risk Method Description XX ALL M Intermediary I Individual E Entity	risk_mthd_cd	character	3		MANDATORY	NN	(PK)	NO
RISK METHOD	risk_mthd	Risk Method Name	Risk Method / Applicability This Code represents the relationship that AMEX has with the card holder or merchants for e.g. A consumer card holder is an Individual relationship, A merchant is an Entity relationship and an FXIP(Foreign exchange) relationship is of type intermediary (any third party). In CADENCE it is driven based on the product type that account has Sample Values: Compliance Risk Method Code Compliance Risk Method Description XX ALL M Intermediary I Individual E Entity	risk_mthd_nm	varchar	20		MANDATORY	NN		NO
RISK RULE	risk_rule	Last Update User Identifier	Specifies the person (his/her ads id) who last updated this record in the table.	lst_upd_usr_id	varchar	34		OPTIONAL	N		NO
RISK RULE	risk_rule	Last Update Timestamp	Specifies the date and time the last update was made to the record in the table.	lst_upd_dt_ts	timestamp	6		OPTIONAL	N		NO
RISK RULE	risk_rule	Data Point Value Data	Description : Value associated with data-point that will be evaluated by rule engine. Sample Values : Center Code (US, FR, UK), Product Code, etc.	da_pt_val_da	json			OPTIONAL	N		NO
RISK RULE	risk_rule	Data Point Value	Description : Value associated with data-point that will be evaluated by rule engine. Sample Values : Center Code (US, FR, UK), Product Code, etc.	da_pt_val	varchar	500		OPTIONAL	N		NO
RISK RULE	risk_rule	Create Timestamp	Specifies the date and time when the record in the table was inserted / created.	creat_ts	timestamp	6		MANDATORY	NN		NO
RISK RULE	risk_rule	Data Operator Identifier	Description : Unique ID for identifying an operator. Sample Values : 1 equals 2 greater than 3 less than 4 includes 5 excludes	da_opr_id	smallint			MANDATORY	NN	(FK)	NO
RISK RULE	risk_rule	Rule Sequence Number		rule_seq_no	integer			MANDATORY	NN		NO
RISK RULE	risk_rule	Rule Set Identifier	Description : Unique ID for identifying a rule set. Sample Values : 1, 2, 3, 4, etc.	rule_set_id	integer			MANDATORY	NN	(PK) (FK)	NO
RISK RULE	risk_rule	ISO Alpha2 Country Code	ISO Alpha2 Country Code Sample Values: IN UK US	iso_alpha2_pty_cd	character	2		MANDATORY	NN	(PK) (FK)	NO
RISK RULE	risk_rule	Data Point Identifier	Description : Unique ID for identifying a data-point.. Sample Values : 1, 2, 3, 4, etc.	da_pt_id	integer			MANDATORY	NN	(FK)	NO

RISK RULE	risk_rule	Data Point Value File Name	Data Point Value File Name contains the Data Point Value which can be used on UI to display/download the file with its original name	da_pt_val_fi_nm	varchar	150		OPTIONAL	N		NO
RISK RULE	risk_rule	Risk Assessment Identifier	Description : Unique ID for identifying an assessment. Sample Values : 1, 2, 3, 4, etc.	risk_assess_id	integer			MANDATORY	NN	(PK) (FK)	NO
RISK RULE	risk_rule	Rule Identifier	Description : Unique ID for identifying a rule. Sample Values : 1, 2, 3, 4, etc.	rule_id	integer			MANDATORY	NN	(PK)	NO
RISK RULE	risk_rule	Create User Identifier	Specifies the person (his/her ads id) who inserted / created this record in the table.	creat_user_id	varchar	34		MANDATORY	NN		NO
RISK RULE	risk_rule	Risk Element Identifier	Description : Unique ID for identifying an element. Sample Values : 1, 2, 3, 4, etc.	risk_element_id	integer			MANDATORY	NN	(PK) (FK)	NO
RISK RULE	risk_rule	Risk Assessment Version Number	Description : Incremental number which indicates which release/version Sample Values : 1, 2, 3, 4, etc.	risk_assess_vsn_no	integer			MANDATORY	NN	(PK) (FK)	NO
RISK SCORE THRESHOLD CONFIGURATION	risk_score_thld_config	Risk Score Threshold Configuration Identifier	Description : Unique ID for identifying an assessment. Sample Values : 1, 2, 3, 4, etc.	risk_score_thld_config_id	uuid			MANDATORY	NN	(PK)	NO
RISK SCORE THRESHOLD CONFIGURATION	risk_score_thld_config	Latest Threshold Risk Rating Indicator		latest_thld_risk_rating_in	boolean			MANDATORY	ND		NO
RISK SCORE THRESHOLD CONFIGURATION	risk_score_thld_config	Risk Assessment Production Status Indicator	Description : Unique ID for identifying approval status. Sample Values : 1 (Production)/ 0 (Sandbox).	risk_assess_prod_status_in	boolean			MANDATORY	ND		NO
RISK SCORE THRESHOLD CONFIGURATION	risk_score_thld_config	Risk Assessment Score Number	Based on the Risk Rating, the Rsk score will be assigned for the customers run against this Assessment + Version Sample Values: If Risk Rating is less than 1000, the risk score will be 1 (0 - 999) If Risk Rating is less than 2000, the risk score will be 2 (1000 - 1999)	risk_assess_score_no	numeric	5		MANDATORY	NN		NO
RISK SCORE THRESHOLD CONFIGURATION	risk_score_thld_config	Create User Identifier	Specifies the person (his/her ads id) who inserted / created this record in the table.	creat_user_id	varchar	34		MANDATORY	NN		NO
RISK SCORE THRESHOLD CONFIGURATION	risk_score_thld_config	Create Timestamp	Specifies the date and time when the record in the table was inserted / created.	creat_ts	timestamp	6		MANDATORY	NN		NO
RISK SCORE THRESHOLD CONFIGURATION	risk_score_thld_config	Last Update Timestamp	Specifies the date and time the last update was made to the record in the table.	lst_update_ts	timestamp	6		OPTIONAL	N		NO
RISK SCORE THRESHOLD CONFIGURATION	risk_score_thld_config	Last Update User Identifier	Specifies the person (his/her ads id) who last updated this record in the table.	lst_update_user_id	varchar	34		OPTIONAL	N		NO
RISK SCORE THRESHOLD CONFIGURATION	risk_score_thld_config	Lowest Threshold Risk Rating Number	The lowest threshold risk rating number for the risk assessment, to be able to assign a score Sample Values: If Risk Rating is less than 1000, the risk score will be 1 If Risk Rating is less than 2000, the risk score will be 2	low_thld_risk_rating_no	numeric	5		MANDATORY	NN		NO
RISK SCORE THRESHOLD CONFIGURATION (OLD)	risk_score_thld_config(old)	Create User Identifier	Specifies the person (his/her ads id) who inserted / created this record in the table.	creat_user_id	varchar	34		MANDATORY	NN		NO

RISK SCORE THRESHOLD CONFIGURATION (OLD)	risk_score_threshold_config (old)	Last Update User Identifier	Specifies the person (his/her ads id) who last updated this record in the table.	lst_updated_user_id	varchar	34		OPTIONAL	N		NO
RISK SCORE THRESHOLD CONFIGURATION (OLD)	risk_score_threshold_config (old)	Lowest Threshold Risk Rating Number	The lowest threshold risk rating number for the risk assessment, to be able to assign a score Sample Values: If Risk Rating is less than 1000, the risk score will be 1 If Risk Rating is less than 2000, the risk score will be 2	lowest_threshold_rating_no	numeric	5		MANDATORY	NN		NO
RISK SCORE THRESHOLD CONFIGURATION (OLD)	risk_score_threshold_config (old)	Risk Assessment Identifier	Description : Unique ID for identifying an assessment. Sample Values : 1, 2, 3, 4, etc.	risk_assessment_id	integer			MANDATORY	NN	(PK) (FK)	NO
RISK SCORE THRESHOLD CONFIGURATION (OLD)	risk_score_threshold_config (old)	Create Timestamp	Specifies the date and time when the record in the table was inserted / created.	create_timestamp	timestamp	6		MANDATORY	NN		NO
RISK SCORE THRESHOLD CONFIGURATION (OLD)	risk_score_threshold_config (old)	Last Update Timestamp	Specifies the date and time the last update was made to the record in the table.	last_updated_timestamp	timestamp	6		OPTIONAL	N		NO
RISK SCORE THRESHOLD CONFIGURATION (OLD)	risk_score_threshold_config (old)	Risk Assessment Score Number	Based on the Risk Rating, the Rsk score will be assigned for the customers run against this Assessment + Version Sample Values: If Risk Rating is less than 1000, the risk score will be 1 (0 - 999) If Risk Rating is less than 2000, the risk score will be 2 (1000 - 1999)	risk_assessment_score_no	numeric	5		MANDATORY	NN	(PK)	NO
RISK SCORE THRESHOLD CONFIGURATION (OLD)	risk_score_threshold_config (old)	Risk Assessment Version Number	Description : Incremental number which indicates which release/version Sample Values : 1, 2, 3, 4, etc.	risk_assessment_version_no	integer			MANDATORY	NN	(PK) (FK)	NO
RULE SET	rule_set	Create User Identifier	Specifies the person (his/her ads id) who inserted / created this record in the table.	create_user_id	varchar	34		MANDATORY	NN		NO
RULE SET	rule_set	Last Update Timestamp	Specifies the date and time the last update was made to the record in the table.	last_updated_timestamp	timestamp	6		OPTIONAL	N		NO
RULE SET	rule_set	Rule Set Identifier	Description : Unique ID for identifying a rule set. Sample Values : 1, 2, 3, 4, etc.	rule_set_id	integer			MANDATORY	NN	(PK)	NO
RULE SET	rule_set	Last Update User Identifier	Specifies the person (his/her ads id) who last updated this record in the table.	last_updated_user_id	varchar	34		OPTIONAL	N		NO
RULE SET	rule_set	Rule Set Description	Description : Business description detailing the purpose of a rule set. Sample Values : Collection of rules used to determine if...	rule_set_desc	varchar	500		MANDATORY	NN		NO
RULE SET	rule_set	ISO Alpha2 Country Code	ISO Alpha2 Country Code Sample Values: IN UK US	iso_alpha2_country_cd	character	2		MANDATORY	NN	(PK) (FK)	NO
RULE SET	rule_set	Ruleset Multiplier Number	Description : Numeric multiplier value that will be multiplied with element weight value to derive a score. Sample Values : 1, 50, 100, etc.	ruleset_multiplier_no	numeric	7	3	OPTIONAL	N		NO
RULE SET	rule_set	Default Multiplier Number	Description : Default numerical multiplier value for an element - used when no value is available for the element (if it is a mandatory element) Sample Values : 1, 50, 100, etc. Mandatory elements - Product, Address, Industry, Occupation, Channel..to have come from the source say CRPS	default_multiplier_no	numeric	7	3	MANDATORY	NN		NO

RULE SET	rule_set	Default Weightage Number	Description : Default numerical weight value for an element - used when no value is available for the element. Sample Values : 1, 50, 100, etc.	dflt_wt_no	smallint			MANDATORY	NN		NO
RULE SET	rule_set	Multiplier Option Identifier	Multiplier Option Code 1,2 and 3 corresponds to User Input, File & Assessment respectively Sample Values: Multiplier Option Identifier Multiplier Option Name 1 User Input 2 File 3 Assessment	mult_optn_id	smallint			OPTIONAL	N	(FK)	NO
RULE SET	rule_set	Create Timestamp	Specifies the date and time when the record in the table was inserted / created.	create_ts	timestamp	6		MANDATORY	NN		NO
RULE SET	rule_set	Multiplier Data Point Identifier	Description : Unique ID for identifying a data-point.. Sample Values : 1, 2, 3, 4, etc.	mult_data_pt_id	integer			OPTIONAL	N	(FK)	NO
RULE SET	rule_set	Risk Element Identifier	Description : Unique ID for identifying an element. Sample Values : 1, 2, 3, 4, etc.	risk_element_id	integer			MANDATORY	NN	(PK) (FK)	NO
RULE SET	rule_set	Risk Assessment Version Number	Description : Incremental number which indicates which release/version Sample Values : 1, 2, 3, 4, etc.	risk_assess_vsn_no	integer			MANDATORY	NN	(PK) (FK)	NO
RULE SET	rule_set	Rule Set Condition Text		rule_set_cond_tx	varchar	500		OPTIONAL	N		NO
RULE SET	rule_set	Risk Assessment Identifier	Description : Unique ID for identifying an assessment. Sample Values : 1, 2, 3, 4, etc.	risk_assess_id	integer			MANDATORY	NN	(PK) (FK)	NO
RULESET RISK METHOD	ruleset_risk_mthd	ISO Alpha2 Country Code	ISO Alpha2 Country Code Sample Values: IN UK US	iso_alpha2_pty_cd	character	2		MANDATORY	NN	(PK) (FK)	NO
RULESET RISK METHOD	ruleset_risk_mthd	Last Update Timestamp	Specifies the date and time the last update was made to the record in the table.	last_update_ts	timestamp	6		OPTIONAL	N		NO
RULESET RISK METHOD	ruleset_risk_mthd	Create User Identifier	Specifies the person (his/her ads id) who inserted / created this record in the table.	create_user_id	varchar	34		MANDATORY	NN		NO
RULESET RISK METHOD	ruleset_risk_mthd	Rule Set Identifier	Description : Unique ID for identifying a rule set. Sample Values : 1, 2, 3, 4, etc.	rule_set_id	integer			MANDATORY	NN	(PK) (FK)	NO
RULESET RISK METHOD	ruleset_risk_mthd	Risk Element Identifier	Description : Unique ID for identifying an element. Sample Values : 1, 2, 3, 4, etc.	risk_element_id	integer			MANDATORY	NN	(PK) (FK)	NO
RULESET RISK METHOD	ruleset_risk_mthd	Create Timestamp	Specifies the date and time when the record in the table was inserted / created.	create_ts	timestamp	6		MANDATORY	NN		NO
RULESET RISK METHOD	ruleset_risk_mthd	Risk Method Code	Risk Method / Applicability This Code represents the relationship that AMEX has with the card holder or merchants for e.g. A consumer card holder is an Individual relationship, A merchant is an Entity relationship and an FXIP(Foreign exchange) relationship is of type intermediary (any third party). In CADENCE it is driven based on the product type that account has Sample Values: Compliance Risk Method Code Compliance Risk Method Description XX ALL M Intermediary I Individual E Entity	risk_mthd_cd	character	3		MANDATORY	NN	(PK) (FK)	NO

RULESET RISK METHOD	rules et_ri sk_ mthd	Last Update User Identifier	Specifies the person (his/her ads id) who last updated this record in the table.	lst_up dt_us er_id	var char	34		OPTIONAL	N		NO
RULESET RISK METHOD	rules et_ri sk_ mthd	Risk Assessme nt Identifier	Description : Unique ID for identifying an assessment. Sample Values : 1, 2, 3, 4, etc.	risk_a ssess _id	inte ger			MANDAT ORY	NN	(PK) (FK)	NO
RULESET RISK METHOD	rules et_ri sk_ mthd	Risk Assessme nt Version Number	Description : Incremental number which indicates which release/version Sample Values : 1, 2, 3, 4, etc.	risk_a ssess _vsn_ no	inte ger			MANDAT ORY	NN	(PK) (FK)	NO
TIME BASED ELEMENT EXECUTI ON LOG	tm_b ase_ elem _exe c_log	ISO Alpha2 Country Code	ISO Alpha2 Country Code Sample Values: IN UK US	iso_al pha2_ ctry_cd	cha racter	2		MANDAT ORY	NN	(PK) (FK)	NO
TIME BASED ELEMENT EXECUTI ON LOG	tm_b ase_ elem _exe c_log	Last Assessme nt Date	Date when rules under time-based elements were last run.	lst_as sess_ dt	date			MANDAT ORY	NN	(PK)	NO
TIME BASED ELEMENT EXECUTI ON LOG	tm_b ase_ elem _exe c_log	Next Assessme nt Date	Date when rules under time-based elements will be run next.	next_ asses s_dt	date			OPTIONAL	N		NO
TIME BASED ELEMENT EXECUTI ON LOG	tm_b ase_ elem _exe c_log	Risk Element Identifier	Description : Unique ID for identifying an element. Sample Values : 1, 2, 3, 4, etc.	risk_e lem_id	inte ger			MANDAT ORY	NN	(PK) (FK)	NO
TIME BASED ELEMENT EXECUTI ON LOG	tm_b ase_ elem _exe c_log	Risk Assessme nt Identifier	Description : Unique ID for identifying an assessment. Sample Values : 1, 2, 3, 4, etc.	risk_a ssess _id	inte ger			MANDAT ORY	NN	(PK) (FK)	NO
TIME BASED ELEMENT EXECUTI ON LOG	tm_b ase_ elem _exe c_log	Risk Assessme nt Version Number	Description : Incremental number which indicates which release/version Sample Values : 1, 2, 3, 4, etc.	risk_a ssess _vsn_ no	inte ger			MANDAT ORY	NN	(PK) (FK)	NO
USER	user	User Last Name	Last Name of the authorized users (Marketing Compliance Officers (MCOs) and Business users for configuring and viewing the rules).	user_l st_nm	var char	60		MANDAT ORY	NN		NO
USER	user	Employee Contractor Number	Employee Contractor Number is the unique identifier of an AMEX employee or contractor (Marketing Compliance Officers (MCOs) and Business users for configuring and viewing the rules). The 11 digit number used to uniquely represent an employee / contractor.	emp_ cntrct _no	var char	11		MANDAT ORY	NN	(PK)	NO
USER	user	Active Directory Service Identifier	Active Directory Services (ADS) Identifier - This is the unique identifier of the AMEX authorized users (Marketing Compliance Officers (MCOs) and Business users for configuring and viewing the rules). as stored in LDAP Amex Enterprise Directory	ads_id	var char	50		MANDAT ORY	NN		NO
USER	user	Electronic Mail AddressText	Electronic Mail Address Identifier - the email address of the authorized users (Marketing Compliance Officers (MCOs) and Business users for configuring and viewing the rules).	email _ad_tx	var char	255		MANDAT ORY	NN		NO
USER	user	User First Name	First Name of the authorized users (Marketing Compliance Officers (MCOs) and Business users for configuring and viewing the rules).	user_f irst_nm	var char	60		MANDAT ORY	NN		NO
USER	user	User Full Name	Full Name of the authorized users (Marketing Compliance Officers (MCOs) and Business users for configuring and viewing the rules).	user_f ull_nm	var char	180		MANDAT ORY	NN		NO